ORDER

8130.2D

Change 2 Incorporated

Initiated by: AIR-200

AIRWORTHINESS CERTIFICATION OF AIRCRAFT AND RELATED PRODUCTS



September 30, 1999

DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION

RECORD OF CHANGES

DIRECTIVE NO.

8130.2D

					T .	1			<u> </u>
CHANGE TO BASIC	SUF	PPLEME	NTS	OPTIONAL	CHANGE TO BASIC	SUF	PLEME	NTS	OPTIONAL
				- /4 - 7 /0 O	BAGIC				
Chg. 1				2/15/00					
Chg. 2				12/18/00					



U.S. DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION

8130.2D CHG 1

2/15/00

SUBJ: AIRWORTHINESS CERTIFICATION OF AIRCRAFT AND RELATED PRODUCTS

- 1. PURPOSE. This change is issued to incorporate revised operating limitations.
- 2. <u>DISTRIBUTION</u>. This change is distributed to the Washington headquarters branch levels of the Aircraft Certification Service, Flight Standards Service, and the Regulatory Support Division; to the Aviation System Standards Office; to the branch level in the Aircraft Certification Directorates and Regional Flight Standards Divisions; to all Aircraft Certification Offices; to all Manufacturing Inspection District and Satellite Offices; to all Flight Standards District Offices; to the Aircraft Certification Branch and Flight Standards Branch at the FAA Academy; to the Brussels Aircraft Certification Staff and Flight Standards Staff; to applicable Representatives of the Administrator; and to all International Field Offices.
- 3. <u>DISPOSITION OF TRANSMITTAL</u>. After filing the attached pages, this change transmittal shall be retained.

PAGE CONTROL CHART

REMOVE PAGES	DATED	INSERT PAGES	DATED
111 thru 115 (and 116)	9/30/99	111 thru 115 (and 116)	2/15/00
127	9/30/99	127	2/15/00
128	9/30/99	128	9/30/99

/s/

Frank P. Paskiewicz Manager, Production and Airworthiness Certification Division



12/18/00

SUBJ: AIRWORTHINESS CERTIFICATION OF AIRCRAFT AND RELATED PRODUCTS

- **1. PURPOSE.** This change incorporates revised guidance for the issuance of a U.S. Standard Airworthiness Certificate for new aircraft manufactured outside the United States along with general updates from field comments. Also included in this change are comments submitted from previous revisions that were not incorporated.
- **2. DISTRIBUTION.** This change is distributed to the Washington headquarters branch levels of the Aircraft Certification Service, Flight Standards Service, and the Regulatory Support Division; to the Aviation System Standards Office; to the branch level in the Aircraft Certification Directorates and Regional Flight Standards Divisions; to all Aircraft Certification Offices; to all Manufacturing Inspection District and Satellite Offices; to all Flight Standards District Offices; to the Aircraft Certification Branch and Flight Standards Branch at the FAA Academy; to the Brussels Aircraft Certification Division and Flight Standards Staff; to applicable Representatives of the Administrator; and to all International Field Offices.
- **3. EXPLANATION OF CHANGES.** Included in this change are:
- **a.** Incorporation of appendix 1, Issuance of U.S. Standard Airworthiness Certificates for New Aircraft Manufactured Outside the United States.
 - **b.** Clarification of existing information, including previously submitted field comments.
 - **c.** Removal of the, Jet Flow Forms reference at the bottom of each effected form.
- **4. DISPOSITION OF TRANSMITTAL.** After filing the attached pages, this change transmittal shall be retained.

PAGE CONTROL CHART

Remove Pages	Dated	Insert Pages	Dated	
vii	9/30/99	vii	12/18/00	
viii	9/30/99	viii	9/30/99	
xi	9/30/99	xi	9/30/99	
xii	9/30/99	xii	12/18/00	
3 and 4	9/30/99	3 and 4	12/18/00	
5	9/30/99	5	12/18/00	

AVR-20 (ALL); AEU-100/200; A-FDR-1D

8130.2D CHG 2 12/18/00

PAGE CONTROL CHART

Remove Pages	Dated	Insert Pages	Dated
6	9/30/99	6	9/30/99
13 thru 14	9/30/99	13 thru 14	12/18/00
23	9/30/99	23	12/18/00
24	9/30/00	24	9/30/99
29	9/30/99	29	9/30/99
30	9/30/99	30	12/18/00
49	9/30/99	49	9/30/99
50	9/30/99	50	12/18/00
51 thru 54	9/30/99	51 thru 54	12/18/00
67 thru 76	9/30/99	67 thru 76	12/18/00
93 thru 98	9/30/00	93 thru 98	12/18/00
101	9/30/99	101	12/18/00
102	9/30/99	102	9/30/99
105	9/30/00	105	12/18/00
106	9/30/00	106	9/30/99
109	9/30/99	109	9/30/99
110	9/30/99	110	12/18/00
111 and 112	2/15/00	111 and 112	12/18/00
123	9/30/99	123	12/18/00
124	9/30/99	124	12/18/00
127	2/15/00	127	12/18/00
128	9/30/99	128	12/18/00
135	9/30/99	135	9/30/99
136	9/30/99	136	12/18/00
141 (and 142)	9/30/99	141 (and 142)	12/18/00
157 thru 167	9/30/99	157 thru 167	12/18/00
168	9/30/99	168	9/30/99
169 thru 171	9/30/99	169 thru 171	12/18/00
172	9/30/99	172	9/30/99
181	9/30/99	181	9/30/99
182 thru 184	9/30/99	182 thru 184	12/18/00
187	9/30/99	187	9/30/99
188 and 189	9/30/99	188 and 189	12/18/00
190 and 191	9/30/99	190 and 191	9/30/99
192	9/30/99	192	12/18/00
195 thru 198	9/30/99	195 thru 198	12/18/00
201	9/30/99	201	12/18/00
202	9/30/99	202	9/30/99
209 thru 212	9/30/99	209 thru 212	12/18/00

12/18/00 8130.2D CHG 2

PAGE CONTROL CHART

Remove Pages	Dated	Insert Pages	Dated
249	9/30/99	249	12/18/00
250	9/30/99	250	9/30/99
253 (and 254)	9/30/99	253 (and 254)	12/18/00
		Appendix 1, 1 thru 8	12/18/00

/S/ Frank P. Paskiewicz Manager, Production and Airworthiness

Division

FOREWORD

This order establishes procedures for accomplishing original and recurrent airworthiness certification of aircraft and related products. The procedures contained in this order apply to both Aircraft Certification Manufacturing and Flight Standards Airworthiness Aviation Safety Inspectors, and to private persons/organizations delegated authority to issue airworthiness certificates and related approvals.

This order has been extensively rewritten to include current guidance for specific types of airworthiness certification approvals. Therefore, this edition of Federal Aviation Administration (FAA) Order 8130.2D, Airworthiness Certification of Aircraft and Related Products, replaces the guidance and procedures found in Order 8130.2C. Other relevant material has been incorporated, and sample documents, e.g., forms, letters, etc., are included at the end of most sections. These documents are intended as guides and do not represent a total requirement for every certification action of that section.

Changes and improvements suggested by agency Directives Management Officers have been incorporated. In addition, suggestions for improvement of this directive may be submitted using FAA Form 1320-19, Directive Feedback Information.

/S/ Frank P. Paskiewicz Manager, Production and Airworthiness Certification Division

TABLE OF CONTENTS

CHAPTER 1. INTRODUCTION

Paragra	uph	Page
1.	Purpose	1
2.	Distribution	1
3.	Cancellation	1
4.	Authority to Change this Order	1
5.	Deviations	1
6.	Forms	1
7.	Acronyms	1
8.	Definitions	3
9.	Interpretation of the Term "Airworthy" for U.S. Type Certificated Aircraft	4
10.	Information Currency	4
11.	Reserved	4
PTER 2	2. GENERAL POLICIES AND PROCEDURES	
SECTION	ON 1. GENERAL INFORMATION	
12.	Representatives of the FAA Authorized to Issue Airworthiness Certificates	_
10	and Related Approvals	
13.	Responsibilities of FAA Inspectors and Designees	
14.	Possession and Display of Airworthiness Certificates	
15.	Aircraft Registration	6
16.	Aircraft Nationality, Registration Marks, and Reservation of Special	
	Registration Numbers	7
17.	Display of Nationality and Registration Marks on Antique and Antique	
	Replica Aircraft	
18.	Original and Replacement Identification Plates	
19.	Public Aircraft	
20.	Aircraft Being Removed from a Continuous Maintenance System	10
21.	Operation of Civil Aircraft with Door Open or Removed for Parachuting,	
	Skydiving, or Other Special Operations	
22.	Banner Towing	12
23.	Reserved	12
SECTION	ON 2. AIRWORTHINESS CERTIFICATES AND CERTIFICATIONS	
24.	General	
25.	Classification and Category of Airworthiness Certificates	
26.	Replacement, Exchange, or Amendment of Airworthiness Certificates	13
27.	Surrendered Airworthiness Certificate.	15
28.	Aircraft Model Change	15
29.	Safeguarding FAA Airworthiness Certificates	16

Paragrapi	<i>h</i>	Page
30.	Recording of Conformity Inspections	16
31.	Airworthiness Certification of Manned Free Balloons	16
32.	Reserved	17
SECTION	N 3. INITIAL OR SUBSEQUENT ISSUANCE OF AIRWORTHINESS	
CERTIFI	CATES (ORIGINAL/RECURRENT) OR RELATED APPROVALS	
33.	General	19
34.	Airworthiness Certification.	19
35.	Exceptions	21
36.	Recording of Conformity Inspections	21
3739.	Reserved	21
Figure 2-1	. Sample AC Form 8050-64, Assignment of Special	
	Registration Numbers (face side, reverse is blank) (1 page)	22
Figure 2-2	. Sample Response Letter Regarding Identification Plates (1 page)	23
Figure 2-3	. Sample Limitations for the Operation of an Aircraft With a Door	
	Removed (2 pages)	24
Figure 2-4	. Sample Conformity Inspection Record, FAA Form 8100-1	
<u> </u>	(face side only) (1 page)	26
	N 1. GENERAL INFORMATION	2.5
40.	General	
41.	Standard Airworthiness Certificate	
42.	Application for Airworthiness Certificate	
43.	Statement of Conformity	
44.	Use of Parts Catalogs and Maintenance Manuals	
45.	Basic Eligibility Requirements	
46.	Certification Procedures	
4748.	Reserved	31
SECTION	N 2. NEW AIRCRAFT	
49.	General	33
50.	Use of Designees	33
51.	Certification Procedures	33
52.	Aircraft Manufactured Without an FAA Production Approval (TC Only)	33
53.	Aircraft Manufactured Under an APIS	
54.	Aircraft Manufactured Under a PC	34
55.	Aircraft Manufactured Under a DOA	34
56.	Airworthiness Certification of Very Light Aircraft	35
57.	Aircraft Manufactured in a Bilateral Country	

	3. OTHER AIRCRAFT	Page
58.	General	37
59.	Certification Procedures	
60.	Conformity Determination - Other Aircraft	
61.	Flight Testing.	
62.	Issuance of Standard Airworthiness Certificates § 21.183(d) - Other Aircraft	
63.	Aircraft Built from Spare and Surplus Parts	
64.	Screening of Surplus Military Aircraft	
65.	Conformity Certificate - Military Aircraft	
66.	Issuance of Standard Airworthiness Certificates - Surplus Military Aircraft	
67.	Certification Requirements (Applicant)	
68.	Certification Procedures	
69.	Additional Examples.	49
7085.	Reserved	49
Figure 3-1.	Sample FAA Form 8100-2, Standard Airworthiness Certificate, New	
C	Aircraft and Spare and Surplus Parts (1 page)	50
Figure 3-2.	Sample FAA Form 8130-6, Application for Airworthiness Certificate,	
C	VLA Under § 21.183(a) (1 page)	51
Figure 3-3.	Sample FAA Form 8100-2, Standard Airworthiness Certificate, VLA	
C	Under § 21.183(a) (1 page)	52
Figure 3-4.	Sample FAA Form 8130-6, Application for Airworthiness Certificate,	
	JAR/VLA Under § 21.183(c) (1 page)	53
Figure 3-5.	Sample FAA Form 8100-2, Standard Airworthiness Certificate,	
_	JAR/VLA Under § 21.183(c) (1 page)	54
Figure 3-6.	Sample FAA Form 8130-11, Checklist and Inspection Record, Aircraft	
_	Built from Spare and Surplus Parts (8 pages)	55
Figure 3-7.	Sample FAA Form 8130-9, Statement of Conformity, Aircraft Built	
	from Spare and Surplus Parts (1 page)	63
Figure 3-8.	Sample FAA Form 8130-10, Surplus Military Aircraft Inspection	
	Record, No Reasonable Potential for Standard Certification (1 page)	64
Figure 3-9.	Sample FAA Form 8130-10, Surplus Military Aircraft Inspection Record,	
	Reasonable Potential for Standard Certification (1 page)	65
Figure 3-10.	Sample FAA Form 8130-2, Conformity Certificate, Military Aircraft (1 page)	66
Figure 3-11.	Sample FAA Form 8100-2, Standard Airworthiness Certificate,	
	Surplus Military Aircraft (1 page)	67
Figure 3-12.	Sample FAA Form 8130-6, Application for Airworthiness Certificate, Used	
_	Aircraft, No Previous U.S. Airworthiness Certificate (2 pages)	68
Figure 3-13.	Sample FAA Form 8130-6, Application for Airworthiness Certificate,	
_	New Aircraft Produced Under an APIS or PC (2 pages)	70
Figure 3-14.	Sample FAA Form 8130-6, Application for Airworthiness Certificate,	
-	Surplus Military Aircraft (2 pages)	72
Figure 3-15.	Sample FAA Form 8130-6, Application for Airworthiness Certificate,	
_	Aircraft Built from Spare and Surplus Parts (2 pages)	74

Paragraph		Page
PTER 4. S	SPECIAL AIRWORTHINESS CERTIFICATION	
SECTION	1. GENERAL INFORMATION	
86.	General	77
87.	Application for Airworthiness Certificate	77
88.	Certification Procedures	77
89.	Special Airworthiness Certificates	79
SECTION	2. RESTRICTED AIRWORTHINESS CERTIFICATION	
90.	General	81
91.	Certification Procedures	81
92.	Eligibility	81
93.	Special Purpose Operations	82
94.	Statement of Conformity.	82
95.	Operating Limitations	82
96.	Agricultural Aircraft	83
97.	Airworthiness Certificate	
98.	Display of Marks (Restricted)	84
99100.	Reserved	84
SECTION	3. MULTIPLE AIRWORTHINESS CERTIFICATES	
101.	General	85
102.	Certification Procedures	85
103.	Eligibility	85
104.	Special Purpose Operations	86
105.	Airworthiness Certificates	86
106.	Operating Limitations	86
107.	Operating with Multiple Airworthiness Certificates, Standard and Restricted	86
108.	Display of Marks (Restricted or Limited)	87
109111.	Reserved	87
SECTION	4. LIMITED AIRWORTHINESS CERTIFICATION	
112.	General	89
113.	Certification Procedures	
114.	Eligibility	89
115.	Operating Limitations	
116.	Display of Marks (Limited)	
117.	Aircraft Issued Limited Category Type Certificates	90

12/18/00 8130.2D CHG 2

Para	agraph	Page
	CTION 5. PRIMARY CATEGORY AIRCRAFT AIRWORTHINESS RTIFICATIONS	
118.	General	91
119.	Certification Procedures	92
120.	Reserved	92
SEC	CTION 6. GENERAL EXPERIMENTAL AIRWORTHINESS CERTIFICATIONS	
121.	General	93
122.	Eligibility	94
123.	Demilitarization of Former Military Aircraft	95
124.	Aircraft Equipped with Ejection Seats or Jettisonable Stores	96
125.	Flight Test Areas	97
126.	Operating Outside Flight Test Areas	98
	CTION 7. EXPERIMENTAL AMATEUR-BUILT AIRWORTHINESS RTIFICATIONS General	00
127. 128.		
120.		
130.		
130.		
131.	5 1 8 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
133.		
134.	e	
135.		
	CTION 8. CERTIFICATION AND OPERATION OF AIRCRAFT UNDER THE PERIMENTAL PURPOSE(S) OF EXHIBITION AND AIR RACING	
136.		
137.	•	
138.	\mathcal{C}	
139.	1	
140.	1	
141.		
142.	6 - F	
143.	. Reserved	131

Paragraph		Page
EXPERIM COMPLIA	9. CERTIFICATION AND OPERATION OF AIRCRAFT UNDER THE ENTAL PURPOSE(S) OF RESEARCH AND DEVELOPMENT, SHOW NCE WITH REGULATIONS, CREW TRAINING, MARKET SURVEYS, RATING KIT-BUILT AIRCRAFT	
144.	General	133
145.	Special Certification Requirements	
146.	PC/APIS Holder's Experimental Operating Procedure	134
147.	Issuance of Experimental Research and Development, Show Compliance with Regulations, Crew Training, Market Surveys, and Operating Kit-Built Aircraft	
	Operating Limitations	136
148149.	Reserved	141
SECTION	10. PROVISIONAL AIRWORTHINESS CERTIFICATION	
150.	General	143
151.	Eligibility	
152.	Special Purpose Operations	
153.	Statement of Conformity	
154.	Certification Procedures	
155.	Special Airworthiness Certificate, FAA Form 8130-7	
156.	Operating Limitations	
157170.	Reserved	
SECTION	11. SPECIAL FLIGHT PERMITS	
171.	General	145
172.	Purposes	146
173.	Application and Issuance (General)	147
174.	Aircraft Inspections	147
175.	Special Operating Limitations	148
176.	Special Flight Permits for Operation of Overweight Aircraft	149
177.	Special Flight Permit for Production Flight Testing	
178.	Special Flight Permit for Conducting Customer Demonstration Flights	153
179.	Special Flight Permit for Certain Large Aircraft to Which Part 125 is Not Applicable (Seating Capacity of 20 or More or Maximum Payload	
	Capacity of 6000 Pounds or More)	
180183.	Reserved	
Figure 4-1.	Sample FAA Form 8130-7, Special Airworthiness Certificate (1 page)	157
Figure 4-2.	Sample FAA Form 8130-7, Special Airworthiness Certificate for	
	Restricted Category Aircraft Certificated Under § 21.25(b)(7) (1 page)	158
Figure 4-3.	Sample FAA Form 8130-6, Airworthiness Application for Primary Category	
	Aircraft Certificated Under § 21.184(a) (2 pages)	159

	Figure 4-4.	Sample FAA Form 8130-7, Special Airworthiness Certificate for Primary	1.7.1	
	T' 4.5	Category Aircraft Certificated Under § 21.184(a) (1 page)	161	
	Figure 4-5.	Sample FAA Form 8130-6, Airworthiness Application for Primary Category	160	
	Figure 4-6.	Aircraft Certificated Under § 21.184(b) (2 pages)	102	
	rigule 4-0.	Category Aircraft Certificated Under § 21.184(b) (1 page)	16/	
	Figure 4-7.	Sample FAA Form 8130-6, Airworthiness Application for Primary Category	104	
	riguic + 7.	Aircraft Certificated Under § 21.184(c) (2 pages)	165	
	Figure 4-8.	Sample FAA Form 8130-7, Special Airworthiness Certificate for Primary	100	
	118010 . 01	Category Aircraft Certificated Under § 21.184(c) (1 page)	167	
	Figure 4-9.	Sample Operating Limitations For Primary Category Aircraft		
	U	Certificated Under § 21.184(c) (1 page)	168	
	Figure 4-10.	Sample FAA Form 8130-6, Airworthiness Application for Primary Category		
	C	Aircraft Certificated Under § 21.191(h) (2 pages)	169	
	Figure 4-11.	Sample FAA Form 8130-7, Special Airworthiness Certificate, for Primary		
		Category Aircraft Certificated Under § 21.191(h) (1 page)	171	
	Figure 4-12.	Operating Limitations for Primary Category Aircraft Certificated		
		Under § 21.191(h) (1 page)	172	
	Figure 4-13.	Sample Program Letter (1 page)	173	
	Figure 4-14.	Sample FAA Form 8130-12, Eligibility Statement, Amateur-Built		
		Aircraft (1 page)	174	
	Figure 4-15.	Sample FAA Form 8000-38, Fabrication/Assembly Operation		
		Checklist (5 pages)	175	
	Figure 4-16.	Sample Letter to Kit Manufacturer When Kit is Determined Eligible		
		(1 page)	180	
	Figure 4-17.	Sample Letter to Kit Manufacturer when Kit is Determined Not Eligible		
		(1 page)		
		Sample Unlimited FAA Form 8130-7 (1 page)		
	_	Sample FAA Form 8130-7, Special Flight Permit (1 page)		
	Figure 4-20.	Sample FAA Form 337, Major Repair and Alteration (1 page)	184	
СНА	CHAPTER 5. EXPORT APPROVAL PROCEDURES			
	SECTION 1	. GENERAL INFORMATION		
	184.	General	185	
	185187.	Reserved	186	
	SECTION 2. EXPORT APPROVALS			
	188.	Section 21.323, Eligibility	187	
	189.	Section 21.325, Engrointy Section 21.325, Export Airworthiness Approvals		
	190.	Section 21.327, Application		
	170.	occion 21.527, rippioution	.00	

	Paragrapn		Page
	191.	Issuance of FAA Form 8130-4, Export Certificate of Airworthiness, for	
		Class I Products (§ 21.329)	188
	192.	Issuance of FAA Form 8130-3, Airworthiness Approval Tag, for Class II	
		Products (§ 21.331)	189
	193.	Issuance of FAA Form 8130-3, Airworthiness Approval Tag, for Class III	
		Products (§ 21.333)	
	194.	Responsibilities of Exporters (§ 21.335)	
	195.	Special Export Airworthiness Approval for Aircraft (§ 21.339)	189
	196.	Reserved	
	197.	Determination of "New" and "Used" Products	190
	198.	Preparation of Export C of A	191
	199.	Approval of Modifications	193
	200.	Export Certificate of Airworthiness Number Assignment Card	193
	201.	Routing and Processing of Export Files	194
	202.	Issuance of Export C of A for Aircraft Type Certificated in Multiple	
		Categories	194
	203.	Issuance of Export C of A for Restricted Category Aircraft	
	204.	Controversial Information.	
	205207.	Reserved	194
	Figure 5-1.	Sample FAA Form 8130-4, Export Certificate of Airworthiness (1 page)	195
	Figure 5-2.	Sample FAA Form 8130-1, Application for Export Airworthiness Approval	
	C	(2 pages)	196
	Figure 5-3.	Sample AC Form 8050-72, Export Certificate Number Assignment Card	
	C	, ,	
CH	APTER 6. IN	MPORT PROCEDURES	
	SECTION	1. GENERAL INFORMATION	
	208.	General	199
		Reserved	
	SECTION	2. IMPORT AIRCRAFT	
	211.	Requirements for U.S. Airworthiness Certification.	201
	212.	Application	
	213.	Airworthiness Determination.	
	214.	Airworthiness Certification of Aircraft with Mandatory Continuing	
	21	Airworthiness Information (MCAI)	203
	215.	Certification Procedures.	
	216217.	Reserved	
	210. 217.	10301 700	201
		3. AIRCRAFT ENGINES, PROPELLERS, MATERIALS,	
	PARTS, AN	ND APPLIANCES	
	218.	Airworthiness Determination.	205
v			

	Paragraph		Page
	219.	Identification and Marking	205
	220.	Return to Service	
	221.	Special Maintenance Records Consideration	206
	222223.	Reserved	
	IAPTER 7. S.	PECIAL FLIGHT AUTHORIZATIONS FOR NON-U.S. REGISTERED C	IVIL
			•00
	224.	General	
	225.	Eligibility	
	226.	Blanket Special Flight Authorizations	
	227.	Application	
	228.	Issuance	
	229.	Duration	
	230.	Operating Limitations	213
	231.	Special Flight Authorizations for Operation of Canadian-Registered	
		Amateur-Built Aircraft in the United States	
	232235.	Reserved	218
	Figure 7-1.	Sample Special Flight Authorization for the Flight of an Aircraft to a	
		Place Where Repairs or Alterations are to be Made (2 pages)	219
	Figure 7-2.	Sample Special Flight Authorization for the Flight of an Aircraft to a	
		New Country of Registry (2 pages)	
	Figure 7-3.	Sample Special Authorization for the Purpose of Flight Testing (2 pages)	223
	Figure 7-4.	Sample "Blanket" Special Flight Authorization for Customer Crew	
		Training (2 pages)	225
	Figure 7-5.	Sample Special Flight Authorization for Export Delivery (2 pages)	227
	Figure 7-6.	Sample "Blanket" Special Flight Authorization for Delivering Aircraft	
	_	for the Purpose of Export Delivery (2 pages)	229
	Figure 7-7.	Sample Special Flight Authorization for the Purpose of Demonstration	
	C	(2 pages)	231
	Figure 7-8.	Sample Special Flight Authorization for Canadian-Registered Amateur-Built	
	C	Aircraft (2 pages)	233
	Figure 7-9.	Sample "Blanket" Special Flight Authorization for Glider Meet (2 pages)	
CH	APTER 8. P	ROCESSING FORMS, REPORTS, AND CERTIFICATION FILES	
	236.	General	237
	237.	Application for Airworthiness Certificate	
	238.	Completion of FAA Form 8100-2	
	239.	Completion of FAA Form 8130-7	
	240.	Reserved	
	241.	Completion of FAA Form 8130-4	
	242.	Completion of FAA Form 8130-1	
	243.	Examination, Review, and Routing of Certification Files	
		, ,	

8130.2D CHG 2 12/18/00

Parag	graph	Page
2442	250. Reserved	252
Figure	e 8-1. Forms Listing and Availability	253
NEW AIRO	Purpose	
2.	Applicability	
3.	Procedure	
1	Administrative Requirements	8

CHAPTER 1. INTRODUCTION

- **1. PURPOSE.** This order establishes procedures for accomplishing original and recurrent airworthiness certification of aircraft and related products. The procedures contained in this order apply to both Manufacturing and Flight Standards Airworthiness Aviation Safety Inspectors and private persons or organizations delegated authority to issue airworthiness certificates and related approvals.
- **2. DISTRIBUTION.** This order is distributed to the Washington headquarters branch levels of the Aircraft Certification Service, Flight Standards Service, and the Regulatory Support Division; to the Aviation System Standards Office; to the branch level in the Aircraft Certification Directorates and Regional Flight Standards Divisions; to all Aircraft Certification Offices; to all Manufacturing Inspection District and Satellite Offices; to all Flight Standards District Offices; to the Aircraft Certification Branch and Flight Standards Branch at the FAA Academy; to the Brussels Aircraft Certification Staff and Flight Standards Staff; to applicable Representatives of the Administrator; and to all International Field Offices.
- **3. CANCELLATION.** FAA Order 8130.2C, Airworthiness Certification of Aircraft and Related Products, dated June 13, 1994 and FAA Order 8130.27, Certification and Operation of Aircraft Under the Experimental Purpose(s) of Research and Development, Exhibition, and/or Air Racing; and Issuance of Special Flight Authorization for Non-U.S. Aircraft, dated January 11, 1996, are cancelled.
- **4. AUTHORITY TO CHANGE THIS ORDER.** The issuance, revision, or cancellation of the material in this order is the responsibility of the Aircraft Certification Service, Production and Airworthiness Certification Division, AIR-200. All changes, as required, will be accomplished by this division to carry out the agency's responsibility to provide for original and recurrent airworthiness certifications and related approvals for eligible aeronautical products.
- **5. DEVIATIONS.** Adherence to the procedures in this order is necessary for uniform administration of this directive material. Any deviations from this guidance material must be coordinated and approved by AIR-200. If a deviation becomes necessary, the FAA employee involved should be guided by sound judgment, ascertaining that all deviations are substantiated, documented, and concurred with by the appropriate supervisor and AIR-200. FAA employees are NOT federally protected for the work they perform if that work is done outside the scope of national policy.
- **6. FORMS.** Examples of forms applicable to specific applications are found at the end of the section or chapter as referenced in the text.
- **7. ACRONYMS.** The following acronyms are used in this order:

AC Advisory Circular

ACO Aircraft Certification Office AD Airworthiness Directive

APIS Approved Production Inspection System

ASI Aviation Safety Inspector BAA Bilateral Airworthiness Agreement

Par 1 Page 1

BASA Bilateral Aviation Safety Agreement

CAA Civil Aviation Authority
CAR Civil Air Regulation

CFR Code of Federal Regulations

14 CFR Title 14 Code of Federal Regulations

CG Center of Gravity

CHDO Certificate Holding District Office

CM Certificate Management

CMO Certificate Management Office CMU Certificate Management Unit

C of A Certificate of Airworthiness (Export)

CO Certificating Office

DAR Designated Airworthiness Representative

DAS Designated Alteration Station

DMIR Designated Manufacturing Inspection Representative

DOA Delegation Option Authorization

DOD Department of Defense

DOT Department of Transportation
EAA Experimental Aircraft Association
FAA Federal Aviation Administration
FSDO Flight Standards District Office
GPO Government Printing Office

ICAO International Civil Aviation Organization ICAW Instructions for Continued Airworthiness

ID Identification

IFO International Field OfficeIFR Instrument Flight RulesJAR Joint Aviation Requirements

MIDO Manufacturing Inspection District Office

MIO Manufacturing Inspection Office

MISO Manufacturing Inspection Satellite Office

ODAR Organizational Designated Airworthiness Representative

PAH Production Approval Holder

PC Production Certificate
PCA Primary Category Aircraft

PI Principal Inspector

PMA Parts Manufacturer Approval SFA Special Flight Authorization

SFAR Special Federal Aviation Regulation **STC** Supplemental Type Certificate

Title 49, U.S. Code, Subtitle VII, Aviation Programs (Replaces the Federal

Aviation Act of 1958, as amended)

TC Type Certificate/Type Certification

TCDS Type Certificate Data Sheet

Page 2 Par 7

12/18/00 8130.2D CHG 2

TPA	Turbine-Powered Aircraft
TSO	Technical Standard Order
U.S.	United States
VFR	Visual Flight Rules
VLA	Very Light Aircraft

8. DEFINITIONS. Some of the definitions included in 14 CFR part 1, Definitions and Abbreviations, and other publications are listed below:

- **a. Aircraft Category.** The term "category," as used with respect to the certification of aircraft, means a grouping of aircraft based upon its intended use or operating limitations, e.g., Normal, Utility, Acrobatic, Primary, etc. For purposes of this order, gliders and balloons will be referred to as categories in lieu of classifications.
- **b.** Aircraft Classification. The term "classification," as used with respect to the certification of aircraft means a broad grouping of aircraft having similar characteristics of propulsion, flight, or landing, e.g., airplane, rotorcraft, glider, and balloon.
- c. Bilateral Agreement. An executive agreement between the United States government and the government of another country to facilitate the airworthiness approval or acceptance of civil aeronautical products exported from one country (contracting state) to the other. There are two types of bilateral agreements related to airworthiness: bilateral airworthiness agreements (BAA) and bilateral aviation safety agreements (BASA). These agreements are not trade agreements, but rather technical cooperation agreements. These agreements are intended to provide a framework for the airworthiness authority of the importing country to give maximum practicable credit to airworthiness certification functions performed by the airworthiness authority of the exporting country using its own certification system.
- **d.** Category of Special Airworthiness Certificates. The term "category" is also used to identify the six specific certification processes and certificates issued as special airworthiness certificates.
- **e.** Certification Office. The FAA Certification Office at which the applicant applies for airworthiness certification or related approval (i.e., MIDO, MISO, FSDO, IFO, CMO, CMU, and the Brussels Aircraft Certification Division).
 - **f.** Classification of Airworthiness Certificates. The term "classification" is also used to distinguish between the two certification processes and certificates, i.e., standard and special.
 - **g. Exception.** Case to which a rule, general principle, etc., does not apply.
 - **h.** Exemption. To free from a rule or obligation that others must observe; excuse; release.
 - **i. Manufacturer.** Any PAH or DOA.

Par 7 Page 3

8130.2D CHG 2 12/18/00

9. INTERPRETATION OF THE TERM "AIRWORTHY" FOR U.S. TYPE CERTIFICATED

AIRCRAFT. The term "airworthy" is not defined in Title 49 or the regulations; however, a clear understanding of its meaning is essential for use in the agency's Airworthiness Certification program. Below is an analogy of the conditions necessary for the issuance of an airworthiness certificate. A review of case law relating to airworthiness reveals two conditions that must be met for an aircraft to be considered "airworthy." Title 49 Section 44704(c) and 14 CFR part 21, Certification Procedures for Products and Parts (part 21), § 21.183(a), (b), and (c), all relate to the two conditions necessary for issuance of an airworthiness certificate. The statutory language establishes the two conditions as:

- **a.** The aircraft must conform to its TC. Conformity to type design is considered attained when the aircraft configuration and the components installed are consistent with the drawings, specifications, and other data that are part of the TC, and would include any STC and field approved alterations incorporated into the aircraft.
- **b.** The aircraft must be in a condition for safe operation. This refers to the condition of the aircraft relative to wear and deterioration, e.g., skin corrosion, window delamination/crazing, fluid leaks, tire wear, etc.

NOTE: If one or both of these conditions were not met, the aircraft would be considered unairworthy. Aircraft which have not been issued a TC must meet the requirements of paragraph 9b above.

10. INFORMATION CURRENCY. Any deficiencies found, clarifications needed, or improvements suggested regarding the content of this order will be forwarded (written or electronically) to the Aircraft Certification Service, the Automated Systems Branch, AIR-520, Attention: Directives Management Officer, for consideration. FAA Form 1320-19, Directive Feedback Information, is located on the last page of this order for your convenience or you may obtain it from the AIR-200 Web Site at: http://www.faa.gov/avr/air200/200home.htm. A copy may be forwarded to the Production and Airworthiness Division, AIR-200, Attention: Comments to Order 8130.2. If an interpretation is urgently needed, you may contact AIR-100, AIR-200, or for Flight Standards concerns, AFS-300. Always use Form 1320-19 to follow up each verbal conversation.

11. RESERVED.

Page 4 Par 9

12/18/00 8130.2D CHG 2

CHAPTER 2. GENERAL POLICIES AND PROCEDURES

SECTION 1. GENERAL INFORMATION

12. REPRESENTATIVES OF THE FAA AUTHORIZED TO ISSUE AIRWORTHINESS CERTIFICATES AND RELATED APPROVALS.

- **a.** Consistent with applicable Aircraft Certification Service policies and instructions, a Manufacturing ASI or Flight Standards Airworthiness ASI is authorized to issue airworthiness certificates and related approvals covered in this order.
- **b.** The FAA is authorized under 14 CFR part 183, Representatives of the Administrator (part 183), to designate private persons or organizations to act as representatives of the Administrator to issue airworthiness certificates and related approvals. A DMIR, DAR, and ODAR may issue standard and special airworthiness certificates, airworthiness approvals, export approvals, and may perform certain other examinations, inspections, and testing services relative to certification functions in the areas of manufacturing and maintenance. The designee's Certificate of Authority shall specify the type and limitation of authority granted.

NOTE: The authority of a DMIR or manufacturing ODAR must be specifically linked to a PAH or PAH's approved supplier.

- **c.** The FAA is authorized under part 21, subpart J, Delegation Option Authorization Procedures, and subpart M, Designated Alteration Station Authorization Procedures to delegate to organizations for the purpose of issuing airworthiness certificates and related approvals. A DOA may issue airworthiness certificates, airworthiness approvals, conformity certifications, and export approvals. A DAS may issue experimental certificates and amend standard airworthiness certificates under the conditions prescribed in part 21.
- **d.** The use of electronic signatures on airworthiness certificates, including export certificates of airworthiness, is not permitted.

13. RESPONSIBILITIES OF FAA INSPECTORS AND DESIGNEES.

- **a.** The procedures in this order cover original airworthiness certification for which Manufacturing Inspectors are primarily responsible, and recurrent airworthiness certification for which Flight Standards Airworthiness Inspectors are primarily responsible. Manufacturing and Flight Standards ASI's may assist each other by mutual agreement.
- **b.** The FAA designees, within the limits of their authority, are authorized to issue original or recurrent airworthiness certificates and related approvals. They are responsible for determining that the products or parts submitted to them conform to the approved type design, are in a condition for safe

Par 12 Page 5

operation, and meet any other specified requirements. They are also responsible for the completeness, accuracy, and processing of all official documents and paperwork as provided for in this order. All actions taken by the designees on behalf of the FAA are subject to the monitoring, review, and approval of the supervising FAA inspector.

- **c.** FAA inspectors are responsible for training and supervising designees assigned to them regarding airworthiness certification procedures and all related documentation. The supervising FAA inspector should also assure that designees have been provided (or have access to) the appropriate regulations, instructions, and forms necessary for the performance of their designated duties.
- **d.** FAA inspectors will supervise and maintain surveillance over the certification activities accomplished by designees to ensure that all certifications and approvals comply with the applicable rules, policies, and procedures.

NOTE: Within the text of this order the term "FAA" refers to the FAA inspector and/or authorized designee.

14. POSSESSION AND DISPLAY OF AIRWORTHINESS CERTIFICATES. Any airworthiness certificate issued to a U.S.-registered civil aircraft must be displayed at the cabin or cockpit entrance so that the certificate is legible to passengers or crew (14 CFR part 91, General Operating and Flight Rules (part 91), § 91.203(b)).

15. AIRCRAFT REGISTRATION.

- **a. Registration.** The procedures for aircraft registration and issuance of registration numbers are contained in 14 CFR part 47, Aircraft Registration (part 47). The registration of aircraft is not a function of airworthiness certification; however, U.S. registration is a prerequisite for issuance of an airworthiness certificate. The FAA must ensure that an aircraft presented for airworthiness certification is properly registered (Title 49, § 44704(c), and § 21.173).
- **b. Proof of Ownership.** The applicant for registration of an aircraft must submit proof of ownership to the FAA Aircraft Registration Branch (AFS-750) that meets the requirements prescribed in part 47. The Aeronautical Center Form 8050-2, Aircraft Bill of Sale, or its equivalent may be used as proof of ownership. If the applicant did not purchase the aircraft from the last registered owner, the applicant must submit a complete chain of ownership from the last registered owner to the applicant. The purchaser under a contract of conditional sale is considered the owner for the purpose of registration. The contract of conditional sale may be submitted as proof of ownership in lieu of a bill of sale.
- c. Aircraft Operation Outside the United States Pending U.S. Registration. For aircraft operations to or from the U.S., including operations conducted wholly outside the U.S., a current airworthiness certificate and Aircraft Registration Certificate, Aeronautical Center Form 8050-3, must be carried in the aircraft. Pending receipt of Form 8050-3, AFS-750 will, upon request, transmit a telex/facsimile confirmation of registration to the party whose name appears on the application as owner or authorized agent. The telex/facsimile may be used as a temporary Certificate of Aircraft Registration pending receipt of the original certificate.

Page 6 Par 13

16. AIRCRAFT NATIONALITY, REGISTRATION MARKS, AND RESERVATION OF SPECIAL REGISTRATION NUMBERS.

a. All U.S. civil aircraft registration numbers are prefixed by an "N." The registration number, apart from the "N" prefix, is made up of one to five symbols, the last two of which may be alphabetical. This alphabetical suffix must be preceded by at least one numerical symbol. The lowest possible number is N1. A zero never precedes the first number. For example:

N1 through N99999, all symbols are numeric N1A through N9999Z, single alphabetical suffix N1AA through N999ZZ, double alphabetical suffix

NOTE: To avoid confusion with the numbers zero and one, the letters "O" and "I" are never used as alphabetical suffixes.

b. Individuals may reserve a registration number of their choice, if available, for one year by sending a written request and the appropriate fee for each number to be reserved to the following address:

FAA Aircraft Registration Branch, AFS-750 Mike Monroney Aeronautical Center Post Office Box 25504 Oklahoma City, Oklahoma 73125-0504

c. The applicant should list five numbers in case the first choice is not available. Reservations may be renewed from year-to-year by paying the appropriate fee before the end of the renewal period. If the renewal payment is not received prior to the end of the one-year period, reservation of the special registration number will expire.

NOTE: Once AFS-750 has been notified that the numbers have been permanently affixed to the aircraft and the airworthiness certificate has been issued, no subsequent fees apply.

- **d.** When aircraft owners apply for a special registration number, they must do so in writing, describing the aircraft to AFS-750. Permission to place the special number on the aircraft will be given on Aeronautical Center Form 8050-64, Assignment of Special Registration Numbers. The owner must complete, sign, and return the original form to AFS-750 within 5 days after the special registration number is affixed to the aircraft. The duplicate of Form 8050-64, together with the airworthiness certificate, would be presented to the FAA representative who will issue a revised airworthiness certificate showing the new registration number. The old registration certificate and the duplicate Form 8050-64 must be carried in the aircraft until the new registration certificate is received (§ 47.15(f), see figure 2-1).
- **e.** Any changes in the current assignment of nationality and registration numbers will be processed as a request for assignment of special registration numbers.

Par 16 Page 7

17. DISPLAY OF NATIONALITY AND REGISTRATION MARKS ON ANTIQUE AND ANTIQUE REPLICA AIRCRAFT.

- **a.** 14 CFR part 45, Identification and Registration Marking (part 45), § 45.22(b)(1)(ii) provides, in pertinent part, that small U.S.-registered aircraft at least 30 years old, or aircraft which have been issued an experimental certificate for the purpose of exhibition or operating an amateur-built aircraft, and which have the same exterior configuration as a 30-year old aircraft, may display marks consisting of the Roman capital letter "N" followed by: the U.S. registration number; or, the symbol APPROPRIATE TO THE AIRWORTHINESS CERTIFICATE OF THE AIRCRAFT (i.e., "C," standard; "R," restricted; "L," limited; or "X," experimental) followed by the U.S. registration number. The symbol used must be appropriate for the airworthiness certificate of the aircraft being certificated, NOT the aircraft being replicated.
 - EXAMPLE 1. A Great Lakes 2T-1A aircraft manufactured in 1929 is registered in the United States and has been issued nationality and registration marks N1234. The aircraft has been issued a standard airworthiness certificate. The owner/operator may display the marks NC1234 if so desired.
 - EXAMPLE 2. An aircraft which has the same exterior configuration as the Great Lakes 2T-1A is registered in the United States and has been issued nationality and registration marks N5678. An experimental airworthiness certificate has been issued under § 21.191(d) or § 21.191(g). The owner/operator may display the marks NX5678 if so desired.
- **b.** When aircraft are marked as described in 45.22(b)(1)(ii), the airworthiness and registration certificates will NOT include the inserted symbol. In example 1 above, the aircraft could be marked NC1234, but the registration and airworthiness certificates would reflect only the N1234.
- **c.** In making a query of the Civil Aviation Registry computer database, the inserted symbol must be OMITTED, in order to obtain accurate information concerning the aircraft.
- **d.** In addition, § 45.23(b) provides that when the appropriate symbol is used with the nationality and registration marks in accordance with § 45.22(b)(1)(ii), the words "limited," "restricted," or "experimental" are not required to be displayed on the aircraft.
- **18. ORIGINAL AND REPLACEMENT IDENTIFICATION PLATES.** Each aircraft presented for airworthiness certification must meet the requirements of § 21.182.
- **a.** Each aircraft, aircraft engine, propeller, propeller blade, and propeller hub manufactured under a TC or PC must be identified with the information specified in § 45.13. Manned free balloons are required to comply with § 45.11(c).
- **b.** When FAA personnel receive inquiries regarding replacement, removal, or destruction of identification plates, the sample letter in figure 2-2 may be used as a guide for responding.

Page 8 Par 17

c. When a new identification plate is required, the owner or the owner's authorized representative contacts the appropriate Certification Office. The FAA determines if the request is valid and provides a letter to the applicant with the FAA's finding. If the FAA determines the request is valid, the applicant includes the FAA letter with his/her request for the replacement data plate from the appropriate manufacturer.

- **d.** Upon notification by the applicant, which must include the FAA's letter, the product manufacturer may then issue the replacement identification plate.
- **e.** The old identification plate, when available, should be voluntarily surrendered by the owner with a written statement to the FAA office who authorized the replacement. The FAA office shall make a copy of the plate and then physically destroy it. The FAA office shall then submit a letter to AFS-750 stating the surrendered plate has been destroyed. AFS-750 will include the letter in the permanent aircraft records file.

NOTE: When the identification plate is surrendered the identification plate is no longer considered personal property.

19. PUBLIC AIRCRAFT.

- **a.** Public aircraft are defined in Title 49, section 40102(a)(37).
- **b.** "Public Aircraft" is a STATUS that is NOT granted by the FAA. There is no requirement to make a declaration in writing of this status nor is there any responsibility to carry any proof of this status. The burden of proof is on the operator to establish to the FAA's satisfaction that it is a public aircraft if its status is questioned.
- **c.** A U.S.-registered public aircraft operating within the territorial limits of the U.S. is not required to have an airworthiness certificate. However, any U.S.-registered public aircraft engaged in international air navigation is required to have a valid certificate of airworthiness, in accordance with the ICAO agreements.
- **d.** Safety is enhanced through the operation of aircraft certificated according to part 21 and the FAA encourages those who operate public aircraft to obtain the appropriate airworthiness certification, if possible. An application for an airworthiness certificate for a public aircraft will be processed in accordance with the applicable procedures in this order. The airworthiness certificate, when issued, is effective only if all terms and conditions of the certificate are complied with. If 14 CFR part 43, Maintenance, Preventive Maintenance, Rebuilding, and Alteration (part 43), part 45, and part 91 are NOT complied with, FAA Form 8100-2, Standard Airworthiness Certificate, shall be surrendered.
- **e.** Public aircraft must be registered in accordance with part 47 and must display nationality and registration marks in accordance with part 45. Any deviations from these requirements must be processed in accordance with the procedures in 14 CFR part 11, General Rulemaking Procedures, applicable to petitions for exemptions.

Par 18 Page 9

f. Aircraft operated by the FAA will be certificated in accordance with part 21, subpart H, Airworthiness Certificates, except for those aircraft authorized by the Director, Office of Aviation System Standards, or the Director's designee, to be operated as public aircraft. Certificated aircraft will display an appropriate airworthiness certificate.

- **g.** Non-certificated FAA aircraft will display a public aircraft document in lieu of the airworthiness certificate. All requests for the public aircraft document will be processed through the Director, Aviation Systems Standards, Oklahoma City, Oklahoma (AVN-100). The letter of request will contain as a minimum:
 - (1) Nationality and Registration Marks.
 - (2) Manufacturer and Model.
 - (3) Aircraft Serial Number.
 - (4) Location (base of operation/airport) of the aircraft.
 - (5) Registered owner and operator of the aircraft.
- **h.** The signed public aircraft document will be displayed in the aircraft at all times in lieu of the airworthiness certificate. For procedures applicable to public aircraft operated by the FAA, refer to FAA Order 4100.24, General Maintenance Manual.

20. AIRCRAFT BEING REMOVED FROM A CONTINUOUS MAINTENANCE SYSTEM.

- **a.** No change in the airworthiness certificate is required if the aircraft has a current airworthiness certificate, Form 8100-2.
- **b.** Operators of aircraft previously operated under 14 CFR part 121, Operating Requirements: Domestic, Flag, and Supplemental Operations (part 121), or part 91, Subpart D, Special Flight Operations, and intending to operate them under part 91, must select, identify, establish, and use an inspection program as prescribed in § 91.409(e), (f), (g), and (h).
- **c.** It is also important for the operator to know the current status of the aircraft relative to applicable requirements, for example: (1) weight and balance data, (2) flight manual appropriate to the operation, and (3) compliance with AD's. Some carriers have exemptions or adjusted AD compliance times.

21. OPERATION OF CIVIL AIRCRAFT WITH DOOR OPEN OR REMOVED FOR PARACHUTING, SKYDIVING, OR OTHER SPECIAL OPERATIONS.

a. Advisory Circular 105-2, Sport Parachute Jumping, lists aircraft that the FAA has determined can be safely flown with one door open or removed if operated in accordance with specified operating limitations.

Page 10 Par 19

b. Owners or operators using aircraft listed in appendix 2 of AC 105-2 interested in obtaining authorization with operating limitations for operation of such aircraft for parachuting or other special operations should forward a written request to the FSDO having jurisdiction over the area in which the operations are to be conducted. The request should contain the following information:

- (1) Name and address of the registered aircraft owner.
- (2) Make, model, serial, and registration number of the aircraft.
- (3) Location where aircraft is normally based.
- (4) Reason for the aircraft to be operated with a door removed.
 - **c.** There are two avenues for operation with the door removed:
- (1) If identified in AC 105-2 to operate with the door removed and no STC is installed, operating limitations will be issued by the FAA.
- (2) Aircraft other than those listed in AC 105-2 will be modified in accordance with STC procedures in part 21, subpart E, Supplemental Type Certificates. If altered in accordance with an STC, no other limitations are required.
- **d.** Sample operating limitations outlined in figure 2-3 may be issued by inspectors for any aircraft listed in AC 105-2. The inspector will note on the operating limitations the aircraft make, model, registration and serial number, type of operation authorized, date of issuance, inspector's name, and district office number. On an aircraft that requires removal or opening of a particular door, the inspector shall specify in the limitations which door may be removed or opened.

NOTE: A copy of the limitations will be forwarded to AFS-750.

- **e.** Removal or installation of a cabin door for the specified aircraft is considered maintenance and as such must be accomplished by persons authorized under § 43.3.
- **f.** If operations of rotorcraft with the doors opened or removed obstructs the nationality and registration marks from view, the operator must notify the appropriate managing office in writing detailing the nature of the proposed operation and the proposed dates of operation with doors removed. The managing office will then instruct the operator to affix temporary nationality and registration marks on an authorized surface required by § 45.27(a). The size of the marks must comply with § 45.29(b) unless no authorized surface is large enough for display of marks meeting the size requirements of this section. The rotorcraft would then be marked on the largest authorized surface with marks as large as practicable as allowed by § 45.29(f). Any remnants of the permanent nationality and registration marks must be obliterated so as not to confuse identification of the rotorcraft with temporary markings. The temporary markings must be able to endure flight operations in various weather conditions. Flight operations must be authorized in writing by the managing office for a specified time and purpose. The managing office will verify the temporary markings for compliance to the CFR and return of the rotorcraft to its permanent marking scheme.

Par 21 Page 11

g. Under part 43, appendix A, paragraph (c)(15), a pilot may be authorized to remove or reinstall passenger seats if specifically listed by name in the operating limitations for the aircraft. The issuing inspector may require the pilot to demonstrate ability in this preventative maintenance function.

- **h.** Removal or installation of control sticks and wheels will be done in accordance with applicable sections of part 43.
- **22. BANNER TOWING.** An aircraft that is in full compliance with its type design and has an FAA-approved banner tow installation may be operated under a standard airworthiness certificate for banner towing purposes. An aircraft that has a standard airworthiness certificate and is modified for a special purpose operation must be operated under a multiple airworthiness certificate (standard/restricted) when the following conditions occur:
 - **a.** The special purpose modification does not meet the type design.
 - **b.** The special purpose modification is not approved for standard category use.
 - **c.** The aircraft will be operated outside the normal category operating limitations.

23. RESERVED.

Page 12 Par 21

12/18/00 8130.2D CHG 2

SECTION 2. AIRWORTHINESS CERTIFICATES AND CERTIFICATIONS

24. GENERAL. FAA Form 8100-2, Standard Airworthiness Certificate, and FAA Form 8130-7, Special Airworthiness Certificate, will be referred to as being either a standard or a special classification within the text of this order.

25. CLASSIFICATION AND CATEGORY OF AIRWORTHINESS CERTIFICATES.

- **a. Standard Classification.** Form 8100-2 may be issued for an aircraft that fully complies with all the requirements applicable to Normal, Utility, Aerobatic, Commuter and Transport category, Manned Free Balloons, or for any other special classes of aircraft designated by the Administrator.
- **b. Special Classification.** Form 8130-7 may be issued for an aircraft that does not meet the requirements for a standard airworthiness certificate. The certificate may be issued for an aircraft that meets the following:
 - (1) **Primary.** Aircraft that satisfies the requirements of § 21.184.
 - (2) **Restricted.** Aircraft that satisfies the requirements of § 21.185.
 - (3) **Limited.** Aircraft that satisfies the requirements of § 21.189.
- **(4) Provisional.** Aircraft that satisfies the applicable requirements of part 21, subpart C, Provisional Type Certificates, and subpart I, Provisional Airworthiness Certificates.
- (5) **Experimental.** For any category aircraft, including amateur-built (§§ 21.191, 21.193, and 21.195).
- **(6) Special Flight Permits.** Form 8130-7 may be issued for an aircraft that does not currently meet applicable airworthiness requirements, but is capable of safe flight, and meets the requirements of §§ 21.197 and 21.199.

26. REPLACEMENT, EXCHANGE, OR AMENDMENT OF AIRWORTHINESS CERTIFICATES.

a. Replacement.

- (1) The FAA may issue a replacement airworthiness certificate when a certificate is declared lost, has been mutilated, or is no longer legible. The replacement airworthiness certificate shall carry the original issue date of the certificate being replaced, preceded by a capital "R" in the date block of the certificate. Additionally, replacement certificates will be issued when the aircraft registration number has been changed. In this case a new application for airworthiness certification is not required.
- (2) Request for a replacement certificate will be made to the applicable certification office. The registered owner or certificate operator will certify this by submitting a signed statement containing the

Par 24 Page 13

8130.2D CHG 2 12/18/00

registration number (N number), serial number, make, and model of the aircraft, and a reason the replacement certificate is needed. Replacement of airworthiness certificates shall not be accomplished by verbal agreement with the assigned inspectors or through procedures contained in air carrier's manuals that allow the continued operation of an aircraft without an airworthiness certificate. Such actions are contrary to §§ 91.203(b), 121.153(a)(1), and 14 CFR part 135, Operating Requirements: Commuter and On Demand Operations and Rules Governing Persons on Board Such Aircraft (part 135), § 135.25(a).

- (3) A replacement airworthiness certificate may be issued without supporting documentation from AFS-750 if the date of issuance and the airworthiness classification and/or category of the lost or mutilated certificate can be positively established from the aircraft records, or from the remains of the certificate. If there is insufficient data upon which to base issuance of the replacement certificate, the FAA inspector will request copies of the appropriate data (such as the application form or previously issued airworthiness certificate) from AFS-750.
- (4) Before issuing a replacement certificate, the FAA shall review the aircraft records, and if necessary, inspect the aircraft to ensure the applicant's request is justified, and the aircraft is eligible for the airworthiness certificate requested.
 - (5) A copy of the replacement certificate must be forwarded to AFS-750.

b. Amendment.

- (1) Either a standard or special airworthiness certificate may be amended under the following situations:
- (a) Modification, i.e., STC or amended TC, that changes the category of the aircraft specified in Block #4 of the standard airworthiness certificate.
- **(b)** A change to the "Exceptions" specified in Block #5 of the standard airworthiness certificate.
- (c) A change in the aircraft model specified in Block #2 of the standard airworthiness certificate.
- (d) A change in the operating limitations for an aircraft with a special airworthiness certificate.
 - (2) A DAS may amend a standard airworthiness certificate under § 21.451(b)(3).
- (3) When a certificate is amended, the issuance date will be the current date; also the capital letter "A" will be typed in front of the date.
- (4) Any amendment of an airworthiness certificate will require submission of FAA Form 8130-6, Application for Airworthiness Certificate. An appropriate record entry, in accordance with chapter 8 of this order, will be made in the aircraft records documenting the issuance of the amended certificate.

Page 14 Par 26

- (5) Paragraph 28 of this order details further information on aircraft model changes.
- **c. Exchange.** It is highly desirable that all aircraft currently certificated in the standard category carry Form 8100-2 to be consistent with the regulations. Owners and operators of general aviation and air carrier aircraft that still have FAA Form 1362A, Certificate of Airworthiness, should be encouraged to exchange such forms for the standard airworthiness certificate, Form 8100-2. In exchanging these certificates, the operating certificate number will NOT be entered on the revised form. Form 1362A will be attached to and forwarded with a copy of the revised certificate to AFS-750 in order to establish an official record of the exchange action. The foregoing exchange procedure also applies to Form 8130-7, in lieu of FAA Form 1362B, Certificate of Airworthiness. The new airworthiness certificate will reflect the date as indicated on Form 1362A or Form 1362B preceded by a capital "E" in the date block of the certificate.

27. SURRENDERED AIRWORTHINESS CERTIFICATE.

- **a.** Airworthiness certificates voluntarily surrendered by written authorization of an aircraft owner or authorized representative, should state why the certificate is being surrendered. The authorization and certificate must be forwarded to AFS-750 for retention in the permanent airworthiness files for that aircraft.
- **b.** When a U.S.-owned aircraft is sold to a purchaser in another country or is leased for operations and registered in another country and is removed from the U.S. registry, the airworthiness certificate is no longer effective and therefore must be surrendered to the FAA by the aircraft owner or operator as specified in § 21.335(e). The exporting FAA representative should request a copy of the de-registration and surrendered airworthiness certificate from the exporter to complete the FAA representative's file.

28. AIRCRAFT MODEL CHANGE.

- **a.** When an aircraft has been modified to conform to another model of the same make, the aircraft registration, airworthiness certificate, and the aircraft identification plate must reflect the new model designation. Data submitted for conversion must give instructions for identification plate alteration or exchange in order to be approved.
- **b.** A new fireproof plate with the new model designation will be attached as close as physically possible to the original identification plate without obscuring it.
- **c.** In order to maintain an accurate and continuous operating history for the aircraft, the original identification plate should not be altered in any manner.
- **d.** The normal procedures, including any applicable inspections, apply for processing a Form 8130-6. The amended airworthiness certificate will be identified with a capital "A" preceding the current date of the certificate being issued. If ownership of the aircraft has not changed, an application for aircraft registration, reflecting the new model designation, need not be submitted. AFS-750 will issue an amended registration certificate.

Par 26 Page 15

29. SAFEGUARDING FAA AIRWORTHINESS CERTIFICATES. Airworthiness certificates are official forms and must be safeguarded by those FAA representatives who are charged with the responsibility for their issuance. Airworthiness certificates may not be produced in a computerized electronic format. Every measure must be taken to assure these certificates are not obtained by unauthorized persons and at no time may a blank certificate be given to any unauthorized individual. Airworthiness certificates should be secured in a locked container when left unattended.

- **30. RECORDING OF CONFORMITY INSPECTIONS.** FAA Form 8100-1, Conformity Inspection Record, should be used to document conformity inspections during type, production, and airworthiness certification programs. These forms may also be used as worksheets during any production surveillance activity to supplement official surveillance records and any inspections deemed appropriate during airworthiness certification (figure 2-4).
- **a. Preparation.** Form 8100-1 will be prepared in accordance with the instructions shown on the back of the form.
- **b. Retention.** Form 8100-1 should be retained until it has been determined that it would serve no useful purpose.
- **31. AIRWORTHINESS CERTIFICATION OF MANNED FREE BALLOONS.** Manned free balloons are type certificated as complete aircraft consisting of three major components: the envelope, the burner and fuel system, and the basket. The burner and fuel system and basket are also known as the "bottom-end" components. Airworthiness certificates will not be issued for any individual component. The following are situations that may be encountered in certificating balloons in the Standard Category.
- **a.** An applicant for a special airworthiness certificate must present a complete system (three major components) for the purpose of making a "condition for safe operation" determination of airworthiness.
- **b.** Many balloon TCDS require each individual balloon envelope to be assigned an individual aircraft serial number, aircraft data plate, and aircraft registration number. As such, the balloon manufacturer obtains a registration number from the aircraft registry, assigns the N-number to the aircraft, and reports the aircraft model and serial number to the FAA registry. When an eligible envelope is mated with the necessary components to make a complete aircraft as described in the applicable TCDS, it is eligible for a standard airworthiness certificate.
- c. A new airworthiness certificate is not required when the aircraft is disassembled and a different burner basket combination is installed, as allowed for by the type certificate. Reassembly of the envelope and bottomend components into a complete aircraft may be done by qualified persons as a preventive maintenance entry under part 43, appendix A, paragraph (c)(27). The aircraft records must properly reflect the installation of the bottom-end components and record the new empty weight. The bottom-end components must be in a current "Annual or 100-hour" inspection status. In this case, individual records of the bottom-end components must be maintained, and the date of the next required inspection due is determined based upon the time the component parts are due for inspection.

Page 16 Par 29

d. If an envelope is provided only as a replacement part, without obtaining a new aircraft serial number, new registration number, or new aircraft identification data plate, then the installation of the replacement envelope is a maintenance item under the provisions of part 43. This requires appropriate documentation of the work performed and return to service entry in the aircraft records by a person authorized to perform the maintenance. In this case, the aircraft identification data plate, aircraft serial number, and aircraft registration number would be carried over from the previous aircraft envelope.

e. For model changes, see paragraph 28 of this order.

32. RESERVED.

Page 17 (and 18)

SECTION 3. INITIAL OR SUBSEQUENT ISSUANCE OF AIRWORTHINESS CERTIFICATES (ORIGINAL/RECURRENT) OR RELATED APPROVALS

- **33. GENERAL.** This section clarifies the terms "original" and "recurrent" as related to the issuance of airworthiness certificates or approvals. Also identified in this section are the FAA offices responsible for performing such functions including, as appropriate, the cross-utilization of FAA inspection personnel.
- **a.** There are a variety of airworthiness functions performed by FAA inspection personnel. Many of these functions must be accomplished by or coordinated with ASI's from Manufacturing or Flight Standards having expertise in that particular specialty. These ASI's may include the Principal Manufacturing Inspector for a major airplane manufacturer or the Principal Flight Standards Airworthiness or Avionics Inspector assigned to an air carrier with aircraft of the same type and complexity as the one for which certification is requested. There are a number of airworthiness functions that can be accomplished by cross-utilization of FAA inspection personnel. Cross-utilization of FAA inspection personnel should be employed whenever possible in accordance with the guidance contained in this section.
- **b.** The terms "original" and "recurrent" distinguish between those functions for which FAA Manufacturing Inspectors have primary responsibility and those for which Flight Standards Airworthiness Inspectors have primary responsibility.
- **c.** The Manufacturing ASI has primarily responsibility for the issuance of original airworthiness certificates and approvals. The Flight Standards Airworthiness ASI has primarily responsibility for the issuance of recurrent airworthiness certificates and approvals.

34. AIRWORTHINESS CERTIFICATION.

- **a. Original Certification.** The term "original certification" applies to the issuance of standard or special airworthiness certificates and approvals including FAA Form 8130-4, Export Certificate of Airworthiness, for aircraft holding a U.S. type design for:
- (1) Aircraft or related products (new or used) that have not left the original product manufacturer's quality control system.
- (2) Aircraft or related products for which an airworthiness certificate or approval has never been issued. Examples include:
 - (a) Surplus military aircraft.
 - **(b)** Aircraft built from spare and surplus parts.
- (c) U.S.-manufactured aircraft returning from another country without having been issued a U.S. airworthiness certificate or U.S. export airworthiness approval.

Par 33 Page 19

- (d) Provisional airworthiness certificates and amendments thereto.
- (e) Limited airworthiness certificates.
- **(f)** Experimental airworthiness certificates.
- (g) Aircraft manufactured to other than U.S. requirements imported to the United States.

NOTE: Aircraft manufactured to other than a § 21.29 TC, when imported to the United States, require a statement from either the CAA of the country of manufacture or the CAA of the exporting country with a bilateral agreement. The latter requires agreements with third party provisions that the aircraft, when modified to FAA-approved data, will meet § 21.29 and will be in a condition for safe operation.

- (3) Aircraft that have been previously issued an airworthiness certificate and presented for certification in another category or classification; e.g., aircraft converted from standard to restricted for the first time or from a special airworthiness certificate to standard for the first time.
- (4) Aircraft that have undergone changes to the type design and require flight test, e.g., under an experimental certificate for the purpose of showing compliance with regulations including, as applicable, the issuance or re-issuance of a standard airworthiness certificate.
- (5) Prototype or test articles to be used for design evaluation for TC or STC purposes. This would include parts or installation approvals.
- **(6)** Issuance of special flight permits for aircraft that have not previously been issued an airworthiness certificate.
- **b. Recurrent Certification.** The term "recurrent certification" applies to the issuance of standard or special airworthiness certificates or approvals for:
- (1) Aircraft that have been previously issued an airworthiness certificate except those listed in paragraphs 34a(3) through (5) of this order.
- (2) Issuance of special flight permits for aircraft that have previously been issued an airworthiness certificate.
- (3) Export certification or approval of aeronautical products which have previously been issued an airworthiness certificate or approval, e.g., PMA or TSO authorization parts that have left the production approval holder's FAA-approved inspection/quality system and are presented for export.
- (4) Issuance of airworthiness certificates for aircraft with certificates that have expired, been surrendered, or revoked.
 - (5) Changes to operating limitations.

Page 20 Par 34

(6) Issuance of experimental certificates for aircraft with expired experimental certificates issued for research and development or exhibition.

- (7) U.S.-manufactured aircraft returning to the United States which were previously issued an airworthiness certificate or an Export C of A in the United States.
- (8) Aircraft manufactured to a U.S. TC accompanied by an Export C of A from the country of manufacture with which the United States has a bilateral agreement that provides for its acceptance. The certification must contain a statement from that CAA stating that the aircraft conforms to its U.S. type design and is in a condition for safe operation.

35. EXCEPTIONS.

- **a.** Any requests, original or recurrent, for a special airworthiness certificate for amateur-built, exhibition, market survey, crew training, or air racing aircraft may be handled by either Manufacturing or Flight Standards Airworthiness Inspectors or their authorized designee. If the responsible office cannot support the certification request, an appropriate delegation will be coordinated with the alternate office.
- **b.** Any requests, original or recurrent, for an experimental certificate for showing compliance with the regulations shall be the primary responsibility of the Manufacturing Inspector or authorized designee. In remote areas or under special circumstances, a Flight Standards Airworthiness Inspector may be delegated the authority by the Aircraft Certification Service if it is established that the person has had experience in type certification programs of a TYPE AND COMPLEXITY comparable to the certificate requested.
- **36. RECORDING OF CONFORMITY INSPECTIONS.** All inspections conducted by an FAA inspector or designee to determine conformity to an approved type design prior to the issuance of an airworthiness certificate should be recorded on Form 8100-1.

37.-39. RESERVED.

Par 34 Page 21

FIGURE 2-1. SAMPLE AC FORM 8050-64, ASSIGNMENT OF SPECIAL REGISTRATION NUMBERS (FACE SIDE, REVERSE IS BLANK)

3	ASSIGNMENT OF SPECIAL REG	ISTRATION I	NUMBERS	Special Registration Number N 54321						
US Department of Transportation	Aircraft Make and Model Lockheed L-100, 382G	Present Registration Number								
Federal Aviation Administration	Serial Number 78361C	_N 12345								
		Issue Date October 31, 19XX								
	ABC Cargo, Inc.	This is your authority to change the United States registration number on the above described aircraft to the special registration number shown.								
į į	P.O. Box 390 Nashington National Airport Nashington, D.C. 20001	Carry duplicate of this form in the aircraft together with the old registration certificate as interim authority to operate the aircraft pending receipt of revised certificate of registration. Obtain a revised certificate of airworthiness from your nearest Flight Standards field office.								
	The latest FAA Form 8130-6, Application For Airworthiness on file is dated May 21, The airworthiness classification and category									
	THE ORIGINAL of this form to the FAA Aircraft Registry, with hen be issued. Unless this authority is used and this office so not	hin 5 days after placir								
CERTIFICATION: 1 ce	ertify that the special registration number was placed on the airc	craft described above	October 30, 19	XX						
Signature of Owner:			RETURN FORM TO:	-						
Title of Owner: Ch	ief, Aircraft Services		FAA Aircraft Registry							
Date Placed on Aircr	P.O. Box 25504 Oklahoma City. Oklahoma									
	BELOW THIS POINT FOR F.	AA USE ONLY								
1. FP NAME 2. NF										
ADDRESS										
ç	FC	ZIP	EMP CODE	DATE						

12/18/00 8130.2D CHG2

FIGURE 2-2. SAMPLE RESPONSE LETTER REGARDING IDENTIFICATION PLATES



March 3, 2000

Mr. William Blue 220 West Broad Street Boston, Massachusetts 26204

Dear Sir:

This is in response to your letter dated February 14, 2000, concerning disposition of the identification plate from Cessna Model 305A, Registration No. N5297G, Serial No. 305A-12345.

The aircraft will be scrapped as a result of an accident. It is requested that the aircraft registration, airworthiness certificate, identification plate, and a copy of this letter be forwarded to the address listed below.

Federal Aviation Administration Aircraft Registration Branch, AFS-750 Mike Monroney Aeronautical Center P.O. Box 25504 Oklahoma City, Oklahoma 73125-0750

Sincerely,

John J. Doe, Manager Burlington Manufacturing Inspection District Office

FIGURE 2-3. SAMPLE LIMITATIONS FOR THE OPERATION OF AN AIRCRAFT WITH A DOOR REMOVED

U.S. Department of Transportation		
Federal Aviation Administration		
Make		
Model	Serial No	
Registration No		

AIRCRAFT OPERATING LIMITATIONS

The aircraft described above may be flown with not more than one cabin door removed for the purpose of (<u>see note below</u>), provided the aircraft is operated in accordance with the applicable Federal Aviation Regulations and the following limitations:

Note: Show specific operations; e.g., intentional parachute jumping, skydiving, etc.

1. Maximum speed not to exceed any of the following:

The approved maneuvering speed.

70 percent maximum level flight speed.

70 percent maximum structural cruising speed.

- 2. Aerobatic maneuvers are not permitted.
- 3. Maximum yaw angle 10 degrees; maximum bank angle 15 degrees.
- 4. An FAA-approved safety belt shall be provided and worn by each occupant during takeoff and landing and at all other times when required by the pilot-in-command.
- 5. All occupants shall wear parachutes when intentional parachute jumping and skydiving operations are conducted.
- 6. Smoking is not permitted.
- 7. When operations other than intentional parachute jumping and skydiving are conducted, a suitable guardrail or equivalent safety device shall be provided for the doorway.
- 8. All loose articles shall be tied down or stowed.
- 9. No baggage shall be carried.
- 10. Parachutist's static lines shall be kept free of pilot's controls and control surfaces.

FIGURE 2-3. SAMPLE LIMITATIONS FOR THE OPERATION OF AN AIRCRAFT WITH A DOOR REMOVED (CONTINUED)

11. Operations limited to VFR conditions.
12. Cabin door hold-open clips installed on wing brace struts and/or under surface of wing shall be removed prior to conducting parachute jumping or sky diving operations.
13. When intentional parachute jumping, skydiving, or other specified operations are being conducted, the pilot at the controls shall hold at least a private pilot certificate rating.
14. This aircraft shall not be operated in solo flight by the holder of a student pilot certificate.
15. Operation of this aircraft with a door removed for any purpose other than that for which it is certificated is prohibited.
16. The following placard shall be placed on the instrument panel in full view of the pilot:
For flight with door removed, see aircraft operating limitations dated
17. A copy of these limitations shall be carried in the aircraft when flight operations are conducted with the door removed.
18. These operating limitations are a part of the airworthiness certificate.
FAA Inspector Date
Office No.

FIGURE 2-4. SAMPLE CONFORMITY INSPECTION RECORD, FAA FORM 8100-1 (FACE SIDE ONLY)

	Conformity Inspection Record	1. Project Number, TIA/Request Date:	A/Request Date:			2. SHEET of	Sheets
3. Appl	2		4. Begining Date:	ng Date:		5. Ending Date:	
6. Model:	el:	7.	7. Inspected By:				
8. Item No.	9. Nomenclature of Item Inspected	 Drawing, Document, Specification, etc. 	, 11. Revision and Date	12. No. of Items Determined	s Determined	13. Comments	
FAA Forn	FAA Form 8100-1 (5-82) Supersedes Previous Edition						

CHAPTER 3. STANDARD AIRWORTHINESS CERTIFICATION

SECTION 1. GENERAL INFORMATION

- **40. GENERAL.** In no case may any aircraft be operated unless there is an appropriate airworthiness certificate issued to and valid for that aircraft. This chapter provides policy and guidance material associated with airworthiness certification and issuance of Form 8100-2.
- **a.** Section 21.183(a) prescribes the basic requirements for issuance of standard airworthiness certificates for aircraft manufactured under a PC.
- **b.** Section 21.183(b) prescribes the basic requirements for issuance of standard airworthiness certificates for aircraft manufactured under a TC only.
- c. Section 21.183(c) prescribes the basic requirements for issuance of the standard airworthiness certificates for an import aircraft type certificated in accordance with § 21.29. The CAA certifications should be made by issuance of an Export C of A that contains the certification statement noted on the corresponding FAA TCDS or a certification statement that the aircraft meets its FAA-approved type design and is in a condition for safe operation.
- **d.** Section 21.183(d) prescribes the basic requirements for issuing standard airworthiness certificates not covered in paragraphs 40 a, b, or c above.

NOTE: NO FAA Field Office or FAA representative is authorized to WAIVE regulatory requirements.

e. The FAA has full responsibility for ensuring that each aircraft, at the time an airworthiness certificate is issued, conforms to the type design and is in a condition for safe operation. Therefore, sufficient FAA inspections of each aircraft must be conducted by the certificating inspector or authorized designee.

41. STANDARD AIRWORTHINESS CERTIFICATE.

- **a.** Form 8100-2 (GPO pad only) is used for all original and recurrent certification of aircraft in the STANDARD CATEGORY ONLY and for replacement of Form 1362A still in effect. See chapter 8 of this order for instructions on completing Form 8100-2 (figure 3-1).
- **b.** A standard airworthiness certificate remains valid as long as maintenance, preventive maintenance, and alterations are performed in accordance with parts 21, 43, and 91.
- **42. APPLICATION FOR AIRWORTHINESS CERTIFICATE.** Form 8130-6 is required whenever an airworthiness certificate is issued or amended. The application for a U.S. airworthiness certificate must be made by the registered owner or an agent who has a notarized letter of authorization from the

Par 40 Page 27

registered owner. The applicant must complete and sign the appropriate sections of Form 8130-6 prior to submitting it to the FAA. (Sample forms are contained at the end of each applicable section.) Instructions for completing Form 8130-6 are contained in chapter 8 of this order. AC 21-2, Application for U.S. Airworthiness Certificates, can also be used as a reference.

43. STATEMENT OF CONFORMITY.

- **a.** FAA Form 8130-9, Statement of Conformity, should be submitted to the FAA as required by §§ 21.53 and 21.130 under the following circumstances:
- (1) By the applicant at the time the aircraft or parts thereof are submitted for FAA tests during the type certification program.
 - (2) By the applicant for each aircraft, aircraft engine, or propeller submitted for type certification.
- (3) By a TC holder or licensee manufacturing products under a TC only: (a) with the initial transfer of ownership of each product; (b) upon application for the original issue of an airworthiness certificate; or (c) an Export Airworthiness Approval.

NOTE: For the purpose of this order, Type Certification programs include any tasks associated with the issuance of a TC, STC, or approval of FAA Form 337, Major Repair and Alteration.

b. The FAA should review Form 8130-9 for completion and ensure that all the entries are typewritten or printed legibly in permanent ink. The form must also be signed in permanent ink by an authorized person who holds a responsible position in the manufacturing organization. If the certifier is also an FAA designee, the designee title should not be used. If the inspection and certification is delegated to a supplier by the applicant, a copy of the letter of delegation must be submitted to the FAA at the time of conformity.

44. USE OF PARTS CATALOGS AND MAINTENANCE MANUALS.

- **a.** When an aircraft is submitted for airworthiness certification, a determination must be made that the aircraft is in conformance with its type design. This does not imply that every part or component must be subjected to a conformity inspection. Conformity inspections should only be conducted when, in the FAA's judgment, conformity to the type design for a particular part or component cannot be substantiated by any other means.
- **b.** Conformity to the type design can only be established when a determination has been made that the materials, processes, dimensions, etc., conform to FAA-approved design data.
- **c.** While parts catalogs or maintenance manuals cannot be used to conduct conformity inspections, they should be used (when applicable) as an aid in establishing the configuration of a particular aircraft and determining the aircraft has been properly maintained.

Page 28 Par 42

d. MIDO's and MISO's having CM responsibility for a particular manufacturer have access to and can provide pertinent information, technical data, etc., as necessary for the certification effort. It is the applicant's responsibility to provide the type design data for those parts and components for which a conformity determination must be made.

- **45. BASIC ELIGIBILITY REQUIREMENTS.** Before a standard airworthiness certificate can be issued, the applicant must show that:
 - **a.** The aircraft conforms to its approved type design and is in a condition for safe operation.
- **b.** Any alterations were accomplished in accordance with an approved STC or other FAA-approved data.
 - **c.** All applicable AD's have been complied with.
- **d.** If altered while in another category, the aircraft continues to meet, or has been returned to, its approved type design configuration and is in a condition for safe operation.
- **46. CERTIFICATION PROCEDURES.** The procedures described herein are consistent with any other specific procedures prescribed in paragraphs dealing with individual airworthiness categories.
- **a.** Obtain from the applicant a properly executed Form 8130-6, and any other documents required for certification. The applicant must have the form completed and the appropriate sections signed prior to submitting it to the FAA. The application for a U.S. airworthiness certificate must be made by the registered owner or an agent who has a notarized letter of authorization from the registered owner.
- **b.** Contact AFS-750 to determine that an application for airworthiness certification has not previously been denied. If it was denied, the reasons stated in the denial letter must be rectified prior to issuing an airworthiness certificate.
- **c.** Arrange with the applicant to make available for inspection and review the aircraft, aircraft records, and any other data necessary to establish conformity to its type design.
 - **d.** Determine that the aircraft is properly registered in accordance with part 47.
- e. As applicable, ensure compliance with the noise standards of §§ 21.93(b), 21.183(e), 14 CFR part 36, Noise Standards: Aircraft Type and Airworthiness Certification (part 36), or part 91. Also ensure compliance with the fuel venting and exhaust emission requirements of 14 CFR part 34, Fuel Venting and Exhaust Emission Requirements for Turbine Engine Powered Airplanes (part 34), and the applicable passenger emergency exit requirements of § 21.183(f) and SFAR 41.
 - **f.** Review records and documentation to the extent necessary to establish that:

Par 44 Page 29

8130.2D CHG 2 12/18/00

(1) All of the required records and documentation are provided for the aircraft, i.e., an up-to-date approved flight manual, a current weight and balance report, equipment list, maintenance records, FAA-accepted ICAW and/or FAA-accepted maintenance manual(s) (MM), and any other manuals required by §§ 21.31, 21.50, 14 CFR part 23, Airworthiness Standards: Normal, Utility, Acrobatic, and Commuter Category Airplanes (part 23), § 23.1529, 14 CFR part 25, Airworthiness Standards: Transport Category Airplanes (part 25), § 25.1529, 14 CFR part 27, Airworthiness Standards: Normal Category Rotorcraft (part 27), § 27.1529, 14 CFR part 29, Airworthiness Standards: Transport Category Rotorcraft (part 29), § 29.1529, 14 CFR part 33, Airworthiness Standards: Aircraft Engines (part 33), § 33.4, and 14 CFR part 35, Airworthiness Standards: Propellers (part 35), § 35.4. These documents must be in the English language.

- (2) The aircraft is eligible by make, model, and serial number, using the TCDS, aircraft specifications, and/or applicable aircraft listing.
- (3) The inspection records and technical data reflect that the aircraft conforms to the type design, and all required inspections and tests have been satisfactorily completed, and the records are complete and reflect no unapproved design changes.
- (4) The aircraft has been flight tested in accordance with paragraph 61 of this order, if required. If it has not been flight tested, issue the appropriate special airworthiness certificate prescribed in chapter 4. The flight test must be recorded in the aircraft records in accordance with § 91.417(a)(2)(i) as time in service as defined in part 1. Aircraft assembled by a person other than the manufacturer (e.g., a dealer or distributor) must have been assembled and, when applicable, flight tested in accordance with the manufacturer's FAA-approved procedures.
- (5) Large airplanes, turbojet, or turbopropeller multi-engine airplanes comply with the inspection program requirements of part 91, subpart E, Maintenance, Preventive Maintenance, and Alterations, or other CFR referenced therein. A supplemental structural inspection program is also required for certain large transport category airplanes. Reference AC 91-56, Supplemental Structural Inspection Program for Large Transport Category Airplanes.
- (6) The TC holder or STC holder has furnished one set of FAA-accepted ICAW or one complete set of FAA-accepted Maintenance Manuals (MM's) to the owner of the aircraft when the first standard airworthiness certificate is issued, or has procedures in place that will positively ensure that FAA-accepted ICAW/MM are provided upon delivery of the aircraft, as required by §§ 21.17(a) and (b), 21.31, and 21.50. The ICAW/MM are also required for all TC and STC products. If no FAA-accepted ICAW/MM are available, the FAA inspector having certificate management responsibility over the manufacturer will contact the ACO and Aircraft Evaluation Group (AEG) to determine the status of the ICAW/MM. The FAA inspector is responsible for ensuring that the manufacturer and company designees are made aware of the status of the ICAW/MM. No deliveries will be allowed prior to the ICAW/MM approval.

NOTE: For additional information relative to import products, reference AC 21-23, Airworthiness Certification of Civil Aircraft, Engines, Propellers, and Related Products Imported to the United States.

Page 30 Par 46

- **g.** Inspect the aircraft for the following:
- (1) The nationality and registration marks and identification plate are displayed and marked in accordance with part 45. The information therein agrees with the application for airworthiness certification.
- (2) All equipment, both required and optional, is properly installed and listed in the aircraft equipment list.
- (3) Instruments and placards are correctly located, installed, and properly marked in the English language.
 - (4) All applicable AD's have been accomplished and appropriately recorded.
 - (5) The aircraft conforms to its approved U.S. TC and is in a condition for safe operation.
 - **(6)** All aircraft systems have been satisfactorily checked for proper operation.
- (7) Operation of the engine(s) and propeller(s) have been checked in accordance with the aircraft manufacturer's instructions.
- **h.** If it is determined that the aircraft meets the requirements for the certification requested, the FAA inspector or authorized designee should:
 - (1) Make an aircraft log book entry per paragraph 237a(8)(d) of this order.
 - (2) Issue Form 8100-2 per paragraph 238 of this order.
- (3) Complete Sections V and VIII of Form 8130-6, as appropriate, in accordance with the instructions contained in paragraph 237a(5) and 237a(8) of this order.
 - (4) Examine, review, and route the certification file per paragraph 243 of this order.
- **i.** If the aircraft does not meet the requirements for the certification requested and the airworthiness certificate is denied, a letter should be written to the applicant stating the reason(s) for denying the certificate. A copy of the denial letter should be attached to the application and forwarded to AFS-750 to be made a part of the aircraft record.

47.-48. RESERVED.

Par 46 Page 31 (and 32)

SECTION 2. NEW AIRCRAFT

- **49. GENERAL.** In addition to the instructions contained in Section 1 of this chapter, this section provides further guidance material associated with the airworthiness certification of new aircraft being produced under a TC only, APIS, PC, DOA, or BAA.
- **50. USE OF DESIGNEES.** With the exception of paragraph 55 of this order, designees authorized under § 183.33 may perform the necessary inspections leading to the issuance of airworthiness certificates for completed products and parts thereof. A designee authorized under § 183.31 may be appointed to inspect and issue airworthiness certificates for aircraft manufactured under an APIS or PC, including parts thereof. The designees are under the direct supervision of the MIDO having CM responsibility over the manufacturer.
- **51. CERTIFICATION PROCEDURES.** The FAA inspector or authorized designee should follow the appropriate procedures in Section 1 of this chapter in conjunction with any applicable steps listed in this order.

52. AIRCRAFT MANUFACTURED WITHOUT AN FAA PRODUCTION APPROVAL (TC ONLY).

- **a.** THE FAA HAS FULL RESPONSIBILITY FOR ENSURING THAT EACH AIRCRAFT, FOR WHICH AN AIRWORTHINESS CERTIFICATE IS ISSUED, CONFORMS TO THE TYPE DESIGN AND IS IN A CONDITION FOR SAFE OPERATION. Sufficient inspections of each aircraft must be conducted by FAA inspectors or authorized designees.
- **b.** Under the provisions of §§ 21.183(b) and 21.123(c), Form 8100-2 may be issued for aircraft produced by a manufacturer who does not have a FAA production approval, for a period of 6 months after the TC has been issued. An extension of the 6-month period may be authorized by the manager of the Directorate in which the manufacturer is located.
- (1) Before any extension of the six month requirement of § 21.123(c) is authorized, it should be positively determined that the FAA responsibility will be satisfied. All inspections conducted or witnessed by the FAA should be documented on Form 8100-1, and all nonconformity's should be corrected and documented before issuing an airworthiness certificate.
- (2) The appropriate MIDO should establish and retain an FAA inspection record file for each aircraft manufactured without an FAA-approved inspection system to substantiate the basis for issuance of the airworthiness certificate. Nonconformity's involving material review actions should be resolved through the certificating ACO prior to certification.
- (3) Form 8130-9 must be submitted by the applicant with each application for an original airworthiness certificate (§ 21.183(b)).

Par 49 Page 33

53. AIRCRAFT MANUFACTURED UNDER AN APIS.

a. Aircraft manufactured under an APIS will be inspected and certificated in a manner similar to that noted in paragraph 52 of this order, except that under an APIS, a designee may be appointed to inspect and issue airworthiness certificates for completed aircraft. Each aircraft must be inspected and certificated by an FAA inspector if a designee has not been appointed under an APIS.

- **b.** The extent of each inspection conducted is dependent upon many factors requiring good judgment. All parts, assemblies, and completed aircraft should be given a thorough inspection during the initial stages of production under an APIS. The FAA may reduce its inspections after it has determined that the APIS is capable of producing reasonable duplicates. In all cases, the basis for any reduced inspections must be substantiated, documented, and concurred with by the managing office.
- **c.** FAA inspections should be adjusted for any significant changes in manufacturing systems, procedures, and personnel, or when major changes have been introduced into the aircraft.
- **d.** Form 8130-9 must be submitted by the applicant with each application for an original airworthiness certificate (§ 21.183(b)).

54. AIRCRAFT MANUFACTURED UNDER A PC.

- **a.** FAA inspections may be reduced to a minimum when aircraft are manufactured under the terms of a PC. The manufacturer must have demonstrated to the satisfaction of the FAA that it has the facilities, equipment, personnel, systems, and procedures that will ensure continuous conformity with the approved type design.
- **b.** Aircraft manufactured under the terms of a PC are eligible for the issuance of an airworthiness certificate without further showing (§ 21.183(a)). The submission of Form 8130-9 is not required, nor is it mandatory for the FAA to inspect each aircraft to determine conformity with the approved type design. The inspection frequency may be adjusted by the geographic MIDO having CM responsibility over the certificate holder.

55. AIRCRAFT MANUFACTURED UNDER A DOA.

- **a.** The procedures for issuing airworthiness certificates are similar to those outlined in paragraph 54 of this order, except the manufacturer is delegated the related FAA duties. By prior arrangement with the manufacturer and in accordance with current program guidelines established by each Directorate, the MIDO will conduct inspections of aircraft currently being certificated under these procedures. The inspections are to determine that the manufacturer is performing its duties in accordance with the applicable regulations. The FAA should periodically select an aircraft for inspection that has been certificated by the manufacturer.
- **b.** If an aircraft is found to be unairworthy or not in conformity with the approved type design data, the manufacturer will be notified as required by FAA Order 2150.3, Compliance and Enforcement Program.

Page 34 Par 53

56. AIRWORTHINESS CERTIFICATION OF VERY LIGHT AIRCRAFT.

a. A VLA is considered to be a special class of aircraft under § 21.17(b). A VLA is defined as an airplane with a single engine (spark or compression-ignition), not more than two seats, a maximum certified takeoff weight of not more than 750 kg. (approximately 1654 pounds), and a stall speed of not more than 45 knots calibrated airspeed in the landing configuration. The operation of these airplanes is limited to Normal Category maneuvers and to DAY-VFR only under part 91.

- **b.** All VLA are eligible to receive a Form 8100-2 under § 21.183(a) or (b) if the airplane has a type certificate and is manufactured under an FAA PC or APIS. Since the VLA is type certificated as a special class of aircraft under § 21.17(b), the category in block 4 on Form 8100-2 will be identified as VLA-Special Class.
- c. The import airworthiness certification requirements of § 21.183(c) are applicable to VLA designed to meet the criteria of JAR-VLA. The FAA type certification basis for import VLA with JAR 22 engines and propellers installed will be shown on the TCDS. The category in block 4 on Form 8100-2 will be identified as VLA-Special Class for imported VLA. (see figures 3-2 through 3-5 for samples of airworthiness applications and certifications for VLA aircraft.)

57. AIRCRAFT MANUFACTURED IN A BILATERAL COUNTRY.

- **a.** New aircraft manufactured in a bilateral country will be inspected and certificated in a manner similar to that noted in paragraph 52 of this order, except that under a bilateral agreement, the CAA of the country of manufacture must certify that the aircraft has been examined, tested, and found to meet its U.S. type design (see paragraph 197 of this order for a definition of a "new" product). A FAA inspector or authorized designee must inspect the aircraft to determine airworthiness eligibility using the current TCDS prior to the issuance the § 21.183(c) airworthiness certificate for the completed aircraft.
- **b.** The extent of each inspection conducted is dependent upon many factors requiring good judgment. All parts, assemblies, and completed aircraft should be given a thorough inspection upon delivery of the aircraft to the U.S. owner/operator.
- **c.** The certified statement from the country of manufacture must be submitted by the applicant with each application for the first U.S. airworthiness certificate to be issued for a particular aircraft. See paragraph 34b(8) of this order and §§ 21.183(c) and 21.185(c).

Page 35 (and 36)

SECTION 3. OTHER AIRCRAFT

58. GENERAL.

- **a.** Section 21.183(d) is generally applicable to used aircraft. Its provisions are also applied to airworthiness certification of aircraft built from spare and surplus parts and U.S.-manufactured civil aircraft that were exported and later returned to the United States for FAA certification. In addition to the provisions contained in section 1 of this chapter, this section provides further guidance material and procedures associated with airworthiness certification of these aircraft.
- **b.** Obtaining an airworthiness certificate may not, by itself, be sufficient to meet all the regulatory requirements for operating an aircraft in the United States. Operations under parts 121 or 135 may require additional inspections, tests, or the installation of additional instruments and/or equipment prior to operation.
- **59. CERTIFICATION PROCEDURES.** The FAA inspector should follow the appropriate procedures listed in paragraph 46 of this order, along with the guidance and procedures contained in paragraphs 60 through 63 of this order.

60. CONFORMITY DETERMINATION - OTHER AIRCRAFT.

- **a.** Under § 21.183(d), an applicant is entitled to a standard airworthiness certificate for aircraft that are either used (to include § 21.29 aircraft), surplus military, or built from surplus and/or spare parts. The applicant must present acceptable evidence to substantiate conformance to the FAA-approved type design, including any modifications, e.g., an STC, Form 337, etc., and that the aircraft has been inspected in accordance with the performance rules for 100 hour inspections as set forth in § 43.15 and found to be airworthy by one of the following:
 - (1) The manufacturer.
- (2) The holder of an appropriately rated repair station certificate issued under 14 CFR part 145, Repair Stations (part 145).
- (3) The holder of a mechanic certificate issued under 14 CFR part 65, Certification: Airmen Other Than Flight Crewmembers (part 65).
- (4) The holder of a certificate issued under part 121, and having a maintenance and inspection organization appropriately rated for the type of aircraft involved.
- **b.** Under the provisions of § 21.183(d), it is the applicant's responsibility to present, with the application, evidence that substantiates conformity with the FAA-approved type design. The applicant should provide any inspection and maintenance records, service history, and any other records substantiating eligibility of the parts being used. The FAA is required to make a "finding of conformity" per § 21.183(d)(3). This shall consist of a review of the applicant's evidence showing how conformity

Par 58 Page 37

was determined. Sufficient conformity checks shall be made on the aircraft and the applicant's evidence for the inspector to find the aircraft to be in conformity. If conformity cannot be determined, the inspection should be stopped until such time as the applicant presents new evidence showing such determination has been made.

- **c.** Compliance with the inspection requirement can be demonstrated by one of the following methods:
- (1) The applicant may have the aircraft inspected in accordance with the performance rules for 100 hour inspections set forth in § 43.15(c)(1); or
- (2) The FAA certificating inspector may accept a recent 100 hour inspection, whether performed in the United States or any other country in which the aircraft was previously located while the aircraft was on the U.S. registry, when:
- (a) The inspection was performed within 30 days before the date of application for a standard airworthiness certificate.
- **(b)** The inspection was accomplished by an operator appropriately certificated by the CAA of a country with which the United States has a bilateral maintenance agreement and meets the requirements as defined in § 21.183(d)(2). Reference AC 21-23, appendix 4, Summary of Importing Bilateral Agreements.
 - NOTE: § 21.183(d)(2) exempts an "experimentally certificated aircraft" that previously had been issued a different airworthiness certificate under this section being returned to the standard airworthiness category, from the 100-hour inspection set forth in § 43.15.
- **d.** The process by which an applicant can meet these requirements depends upon the aircraft involved and its history. This order is intended to address the most common situations encountered in certificating aircraft under § 21.183(d). Unique situations should be discussed in advance with the Production and Airworthiness Certification Division, AIR-200.
- **e.** If the application is for an original airworthiness certificate, the maintenance rules of part 43 are not applicable. An example of this situation is when a new aircraft is delivered WITHOUT an Export C of A and later returns to the United States for certification. Approval of major and minor changes to type design, that include repairs, would come under the applicable provisions of part 21, §§ 21.95 and 21.97. All changes in type design and their approval will be appropriately documented and made part of the original airworthiness certification file. This approval shall be documented in an attachment to Form 8130-6.
- **61. FLIGHT TESTING.** The FAA may require flight tests to determine that the aircraft is in a condition for safe operation. The applicant must consult with the FAA to establish a flight test procedure and flight check-off form. The FAA should confirm that the aircraft has been flight tested by the applicant's pilot in accordance with that procedure. Flight tests will not be conducted by the FAA

Page 38 Par 60

until an entry has been placed in the aircraft records to show that these tests have been satisfactorily completed by the applicant. The appropriate airworthiness certificate for this purpose is a special airworthiness certificate, for show compliance with the CFR.

62. ISSUANCE OF STANDARD AIRWORTHINESS CERTIFICATES § 21.183(d) - OTHER AIRCRAFT. Prior to issuance of a standard airworthiness certificate the applicant must show that the aircraft meets the FAA-approved type design for that aircraft. This includes aircraft type certificated under § 21.29.

- **a.** Upon initial contact by persons desiring a standard airworthiness certificate for a U.S. type certificated aircraft located in a country other than the United States, the FAA should:
- (1) Determine if the certification program can be accomplished in the desired location without placing an undue burden on FAA resources. If the determination results in a finding that the desired location places an undue burden on FAA resources and certification cannot be performed by an FAA inspector, then advise the applicant that the use of an appropriate FAA designee is permissible.
- (2) If it is appropriate to relocate the aircraft for the necessary airworthiness inspection, advise the applicant that a special flight permit for U.S.-registered aircraft (§ 21.197), or SFA for non-U.S. registered aircraft may be issued under § 91.715. To ferry an aircraft to a location near the office or a mutually acceptable location, refer to chapter 7 of this order.

NOTE: Special Flight Permits/Special Flight Authorizations are not recognized by ICAO.

(3) Discuss with the applicant any anticipated issues, the applicable certification procedures in section 1 of this chapter, as well as the specific requirements listed herein and any proposed certification time schedules.

b. Bilateral Agreements (BAA or BASA).

- (1) A bilateral agreement provides for close cooperation between the contracting states in the resolution of safety issues that might arise from in-service operation of any product exported or imported and approved or accepted under the terms of the agreement. When a safety concern arises, the FAA will work with and through the CAA of the other country to the maximum extent practicable (e.g., exchange of information and technical opinions) to determine the appropriate corrective action required of operators or owners of affected U.S.- registered aircraft. The CAA's are expected to keep the FAA informed of corrective actions that they believe are required for safety on U.S.-registered aircraft.
- (2) Service documents (e.g., service bulletins, structural repair manuals, etc.) approved by the airworthiness authority of the country where an affected product is manufactured are considered to be FAA-approved data unless otherwise noted, if the United States has a bilateral agreement with that country. However, service bulletins or other similar instructions classified as "mandatory" by the CAA are not mandatory in the U.S. regulatory system unless required by an AD. Thus, owners or operators of affected U.S.-registered aircraft are not required under U.S. law to comply with service documents or

Par 61 Page 39

directives issued by the airworthiness authorities of other countries unless an FAA AD is issued under 14 CFR part 39, Airworthiness Directives (part 39). However, for U.S. type certificated products not currently on the U.S. Register, FAA Directorate Standards Staff have instituted alternate procedures involving the processing of foreign Mandatory Continuing Airworthiness Information (MCAI), that may affect the way the airworthiness certification requirements are met. The MCAI process is described in detail in paragraph 214 of this order.

c. Third Party Agreements (reference AC 21.23, paragraph 31c(4)).

- (1) The United States has bilateral agreements for reciprocal acceptance of export certificates of airworthiness with a number of countries that contain a "third party country" provision (reference AC 21-2, Export Airworthiness Approval Procedures), through which the CAA of one country may certify products that are manufactured in another participating country. This provision was primarily intended to provide the CAA of the exporting country (other than the country of manufacture) authority to certify to a third (importing) country that a product to be exported is in conformance with the type design of the third country and further that the product is in a condition for safe operation. For example, an aircraft manufactured in England is exported to France and operated under French registry. It is then sold to a buyer in the United States under this provision. If the French DGAC issues a certification to the effect that the aircraft meets its U.S. type design and is in a condition for safe operation, the FAA would honor the certification (bilateral agreements with both England and France have "Third Party" provisions).
- (2) In view of the fact that the United States has bilateral agreements with third party countries that attest to their competence in making conformity and airworthiness determinations, the FAA will also accept certifications of those aircraft that have been manufactured in the United States when the CAA of these countries are willing to issue such certificates. Accordingly, a prospective buyer of a U.S.-manufactured aircraft located in a country other than the United States may request from the CAA of the bilateral third party country a certification to the effect that the particular U.S.-manufactured aircraft has remained in or has been returned to its type design configuration and is in a condition for safe operation. When applicable, the certification should also contain information concerning any areas where the aircraft does not conform to its type design. This certification will be honored by the FAA as fulfilling the applicant's responsibility, but will not eliminate the inspection requirements mandated by § 21.183(d).
- (3) Applicants should be cautioned that it may be impractical to obtain a U.S. airworthiness certificate for an aircraft operated under the registry of another country subsequent to the issuance of an Export C of A by the CAA of the country of manufacture. Applicants should be able to identify repairs and modifications, and document the equipment installed and any maintenance accomplished on the aircraft from the time the Export C of A was issued and the date of application for the U.S. airworthiness certificate. The applicant must show that the aircraft has remained in or has been returned to its FAA-approved type design and is in a condition for safe operation. This may involve extensive inspections accomplished by designees, the CAA of the country of manufacture, the aircraft manufacturer, repair stations, etc., before a U.S. airworthiness certificate can be issued.

Page 40 Par 62

(4) In cases where an aircraft manufactured outside the United States was originally exported to another country, and the CAA of the country of manufacture has issued an Export C of A attesting conformance to a design other than that approved by the FAA, such certificates may be useful to the applicant to establish a baseline for showing conformity to the FAA-approved design after modification. In these cases, or when the Export C of A may not be available, it would be helpful if the applicant obtained a statement from the CAA of the country of manufacture. The statement must certify that when originally exported from that country, the aircraft met its FAA-approved design, or it must identify otherwise any differences between the configuration identified in the original export certification and the FAA-approved design. The applicant must obtain the necessary technical data needed to convert the aircraft to its FAA-approved design configuration. This method may involve extensive inspections to be accomplished by designees, the CAA of the country of manufacture, the aircraft manufacturer, persons authorized under part 43, etc., before the applicant can show conformity to the FAA-approved design. Attempts to obtain a U.S. airworthiness certificate via this method may prove to be impracticable for the applicant; in some instances, the applicant may ultimately be unable to obtain the desired U.S. airworthiness certificate.

- (5) The FAA will not normally issue a U.S. airworthiness certificate for an aircraft manufactured outside the United States when no export certification is available. To be acceptable, aircraft manufactured outside the United States must be controlled under bilateral agreement procedures with assurance of conformity and condition provided by the CAA in the country of manufacture. Without assurance in the form of an export certificate or a certifying statement from the CAA of the country of manufacture, there is no practical way for an applicant to show, or for the FAA to find, conformance with the FAA-approved design and that the aircraft is in a condition for safe operation.
- (6) Inspections by the FAA should be conducted to determine that no changes or modifications have been made, and that the condition of the aircraft has not deteriorated subsequent to export certification by the CAA. Flight testing in accordance with chapter 4 and/or paragraph 61 of this order may be required prior to issuance of a U.S. airworthiness certificate if the aircraft has been disassembled and reassembled subsequent to export certification by the CAA.
- (7) It should be noted that other CAA's will most likely charge a fee for their services. The applicant must be prepared to pay any such fee if the services of a CAA are requested. Any certification, inspection, or information documents provided to the applicant by the CAA must be in the English language.
- **d.** Certification Procedures. In addition to the certification requirements of section 1 of this chapter, the applicant shall:

Par 62 Page 41

(1) For U.S.-manufactured, U.S. Type Certificated Aircraft.

(a) Provide the original or an acceptable copy of the U.S. Export C of A obtained when the aircraft was originally exported from the United States. This will provide a baseline for the inspection to determine if the aircraft meets its FAA TC. This is used to determine if there were any deviations to the type design as annotated on the Export C of A when originally exported. For example, equipment inconsistent with the CFR may have been incorporated to comply with the importing country's additional design requirements. All deviations must be resolved before a standard airworthiness certificate can be issued.

- **(b)** Show that any aircraft component overhauled or repaired while the aircraft was operating under non-U.S. registry was accomplished in accordance with methods acceptable to the FAA and it conforms to its type design. When this cannot be shown, the component must be removed.
- (c) Show that any major alterations, modifications, or repairs performed while the aircraft was under non-U.S. registry were accomplished in compliance with FAA-approved data and the aircraft conforms to its type design. The use of an FAA Designated Engineering Representative (DER) to expedite the design approval process should be encouraged for any alteration or repair that may have been incorporated without FAA approval. Persons authorized under § 43.7 must record in the maintenance records that the major alterations, modifications, or repairs, conform to FAA-approved data.
 - (d) Obtain FAA approval or resolve any other deviation to the type design.
- (e) Show that any maintenance performed while the aircraft was under non-U.S. registry was performed in accordance with methods acceptable to the FAA, and the aircraft conforms to its approved type design or properly altered condition.
- **(f)** The applicant for an airworthiness certificate whose aircraft has been maintained, modified, or repaired while under foreign registry must ensure that all records required by § 91.417(b) are translated into the English language.

(2) For Non-U.S.-manufactured, U.S. Type Certificated Aircraft.

- (a) Furnish a certifying statement from the CAA of the country of manufacture, or a certifying statement from the CAA with whom the U.S. has a "third party" bilateral agreement, attesting to conformity of the aircraft to its type design and that it is in a condition for safe operation.
- **(b)** Obtain FAA approval for any non-FAA-approved modifications, alterations, or repairs incorporated in the aircraft.
- (c) Obtain FAA approval or resolve any other deviations to the type design (e.g., those annotated on the CAA Export C of A).

Page 42 Par 62

63. AIRCRAFT BUILT FROM SPARE AND SURPLUS PARTS.

a. General. This section provides guidance and instructions on issuing a standard airworthiness certificate for an aircraft assembled from spare and surplus parts when the aircraft has a TC issued under §§ 21.21, 21.27, or 21.29.

NOTE: Building aircraft from spare or surplus parts does not include the repair of wrecked aircraft. However, it would not preclude the use of parts obtained from a wrecked aircraft. Parts removed from wrecked aircraft must be inspected and tested to assure they are acceptable for installation and meet the requirements of the type design.

- (1) Prior to purchasing or building an aircraft assembled from spare or surplus parts, prospective purchasers or assemblers should be advised that it may be difficult or impossible to satisfy all the requirements for an airworthiness certificate due to difficulty in establishing conformity to a TCDS for such aircraft. Prospective applicants should be encouraged to review the TCDS or aircraft specifications and any other records that will be used to substantiate conformity to the type design. An FAA inspector or authorized designee must determine whether any changes to the aircraft will be required before airworthiness certification.
- (2) The procedures described in this order require the applicant to fully establish conformity of the aircraft to its original type design and determine that it is in a condition for safe operation. A new ID plate is required to be affixed to the aircraft.

NOTE: Figure 3-6 is a reproducible sample of FAA Form 8130-11, Checklist and Inspection Record for Aircraft Built from Spare and Surplus Parts.

- **b.** Conformity. In addition to the requirements of section 1 of this chapter, use the following guidance to establish that the aircraft conforms to its type design as modified by any amendment to the TC:
- (1) The aircraft must be assembled from approved materials, parts, and assemblies that conform to the FAA-approved type design for that particular model. Appropriate documents substantiating approval status of these parts, to include the manufacturer's documents indicating the parts were produced under an FAA PC, must be made available by the applicant to substantiate that such items are approved.
- (2) The applicant must obtain a STC under § 21.113 for any major changes to the approved type design.
- (3) The applicant must have records establishing that parts fabricated by the applicant or by a third party having no form of FAA production approval are in conformity with the FAA-approved type design. These parts will be subject to FAA inspection for conformity to the design data. The applicant must provide the necessary FAA-approved type design data applicable to the aircraft model being

Par 63 Page 43

certificated. When the approval status or currency of the data is in question, the inspector should refer to the appropriate ACO for verification. The applicant should obtain verification that the data is approved and current prior to determination of conformity.

- (4) Parts and assemblies with established service life limits must be proven airworthy and be accompanied by appropriate historical records to substantiate time in service. Any evidence that such parts or assemblies have exceeded their service life should be referred to the appropriate ACO for evaluation or replaced with serviceable parts. Such evidence, together with other maintenance records, should be returned to the applicant and made part of the aircraft historical records. Life limited items not having historical records substantiating their eligibility cannot be accepted for certification on aircraft.
- (5) The serial number of the aircraft need not appear on the aircraft specification, TCDS, or aircraft listing to be eligible for original airworthiness certification. The aircraft serial number is primarily for the purpose of individual identification of an aircraft. Under Title 49, Section 44704, it need only be shown that the aircraft conforms to its FAA-approved TC and is in a condition for safe operation to be eligible for an airworthiness certificate.
- (6) A new identification plate that meets the requirements of §§ 45.11 and 45.13 must be approved by the FAA before installation on the aircraft. The serial number selected by the builder should be clearly distinguishable from the TC holder's serial numbers, i.e., the use of the builder's name or initials together with a number. The model designation should be that of the aircraft type design to which conformity is determined.
- (7) The applicant must provide an assembly and maintenance manual, or its equivalent, for use as a guide by the FAA during all phases of the aircraft inspection.
- (8) The applicant must weigh the aircraft to determine empty weight and center of gravity. A weight and balance report must be submitted at the time of airworthiness certification. The weighing should be witnessed or verified by the FAA inspector.
- (9) The aircraft should be flight tested by the applicant in accordance with an FAA-approved production flight test procedure and flight check-off format as prescribed by § 21.127. The flight test procedure must be approved by an FAA Flight Test Engineer or DER.
- (10) The applicant must present a FAA Form 8130-9, Statement of Conformity, certifying that the completed aircraft conforms with the applicable TC, except for any major deviations which must be described on the Statement of Conformity and approved by FAA engineering (figure 3-7).
- (a) When submitting Form 8130-9 for an aircraft built from spare and surplus parts, "X" out the words in Section IV, Item B, "Produced under TC only" (figure 3-7).
- **(b)** Enter below Section IV, Item B: Type Certificate, Specification or Listing number as applicable.

Page 44 Par 63

(11) Supporting documents such as manufacturers' invoices, suppliers' affidavits, packing lists, parts lists, and other acceptable records submitted by the applicant should be listed on Form 8100-1 which becomes part of the Checklist and Inspection Record. The basis for determining conformity with the TC will be established and become a matter of record for future reference.

- **64. SCREENING OF SURPLUS MILITARY AIRCRAFT.** This paragraph provides guidance and instructions on establishing the basic eligibility of surplus military aircraft for airworthiness certification under the provisions of § 21.183(d) when an FAA TC has been issued under the provisions of §§ 21.21, 21.27, and 21.29.
- **a. Initial Screening Inspection.** Initial screening inspection will determine whether the aircraft has reasonable potential for airworthiness certification. Inspections may be performed on some, but not all, surplus military aircraft prior to their being offered for sale to the public. Aircraft determined to have "no potential" for airworthiness certification during the initial screening inspection may later be presented for re-screening if adequate cause is demonstrated by the owner, e.g., because of an initial lack of military service historical/modification records. The inspector performing the initial inspection or re-inspection shall submit FAA Form 8130-10, Surplus Military Aircraft Inspection Record (figures 3-8 and 3-9) for each inspection to the appropriate MIO. Aircraft may be considered potentially certifiable when the manufacturer's identification plate is installed and when the aircraft military records are adequate to determine the historical background of the aircraft. As a minimum, the initial screening inspection must consist of:
- (1) Examination of the aircraft identification plate(s) to determine military model number, serial number, date of manufacture, and any other pertinent data.
- (2) Review of military maintenance manuals and modification records affecting the subject aircraft regarding its current status of mandatory maintenance; i.e., equivalent to FAA AD's. The records may be considered adequate for potential certification purposes when it is determined that:
- (a) Major repairs/modifications and military safety-of-flight items have been properly documented in accordance with prescribed military directives.
 - **(b)** Historical records document all known replacement of parts/assemblies.
- (c) Historical records document a current list of life-limited parts/assemblies and their current status on the subject aircraft.
- (d) The following table provides EXAMPLES of typical records to review during the screening inspection process.

Par 63 Page 45

Table 1

TYPICAL RECORDS TO REVIEW WHEN PERFORMING SCREENING INSPECTION ON SURPLUS (ARMY) MILITARY AIRCRAFT
DOD FORMS RECORD DESCRIPTION
DA FORM 2408-13 AIRCRAFT STATUS INFORMATION
DA FORM 2408-5 EQUIPMENT MODIFICATION
DA FORM 2408-15 AIRCRAFT HISTORICAL RECORD
DA FORM 2408-16 AIRCRAFT COMPONENT HISTORICAL RECORD

- (e) Historical records have been documented to reflect maximum weight limits, airspeeds, and operating regimes that have been exceeded as described in the applicable military flight manuals, technical directives, and aircraft specifications. If any of these limits have been exceeded, this information should be recorded on Form 8130-10. The inspector will not make any determination as to what, if any, adverse effect may have resulted from exceeding the described limits. If these limits are exceeded, the MIDO will contact the cognizant FAA engineering office for their appraisal.
- (3) Examination of the aircraft to determine its degree of completeness, state of preservation, repair, and general condition. This examination is not necessarily all inclusive, is for information only, and does not guarantee approval of an airworthiness certificate.
- (4) The condition of the aircraft and its historical records, as found during the initial screening inspection, shall be noted on Form 8130-10 for each aircraft. This information will be used for future reference. Upon completion of the above, the inspector who has conducted the initial screening inspection shall render an opinion as to whether or not the aircraft has reasonable potential for an airworthiness certificate.
- **b. Aircraft Condition.** The condition of the aircraft and its historical records, as found during the initial inspection, shall be noted on the inspection records for each aircraft. This information will be used for future reference. Upon completion of the above, the person who has conducted the initial screening inspection shall render an opinion as to whether or not the aircraft has a "...reasonable potential for standard certification."
- **c. Screening Report.** All inspection findings shall be recorded on Form 8130-10. The original form and appropriate attachments will be forwarded to the appropriate MIO within five working days after completion of the inspection (figures 3-8 and 3-9).

65. CONFORMITY CERTIFICATE - MILITARY AIRCRAFT.

a. Contractual agreements between segments of the military services and a manufacturer may require the manufacturer to provide an FAA Form 8130-2, Conformity Certificate - Military Aircraft, for each aircraft procured. Such aircraft must be type certificated and, in most cases, be manufactured under the terms of a PC (figure 3-10).

Page 46 Par 64

b. By mutual agreement between the FAA and the military services, the FAA may have certain other responsibilities related to the issuance of Form 8130-2. Except as provided in this paragraph, and in any specific requirements in the memorandum of understanding, the normal inspection and surveillance procedures relating to production under a TC or under a PC should be met.

- **c.** The completed original Form 8130-2 should be given to the authorized military representative. The cognizant MIDO, or FSDO when delegated, shall forward a copy, including those issued by DOA manufacturers, to the appropriate MIO for indefinite retention. The copies may be forwarded either separately or all in one package at the end of the military contract or at the discretion of the directorate.
 - NOTE: If such military aircraft are eventually sold as surplus and presented for civil certification, it is the applicant's responsibility to furnish Form 8130-2 with the application when the form is necessary as a part of the airworthiness determination. If the applicant cannot obtain the original or a legible copy of the completed conformity certificate, the FAA inspector or authorized designee may request a copy through their supervising office from the cognizant military office.
- **66. ISSUANCE OF STANDARD AIRWORTHINESS CERTIFICATES SURPLUS MILITARY AIRCRAFT.** Form 8100-2 (figure 3-11) may be issued when the applicant shows, and the FAA finds, that the aircraft conforms to the FAA-approved type design (including applicable modifications incorporated by an amendment to the TC or STC) and that the aircraft is in a condition for safe operation. A standard airworthiness certificate may be issued for a surplus military aircraft under § 21.183(d) when an FAA TC has been issued under §§ 21.21, 21.27, or 21.29. A copy of Form 8130-2, which should have been issued to the military service at the time the aircraft was accepted, shall be made available to the FAA representative or authorized designee by the applicant. This document is necessary to establish basic conformity, including documenting any deviations which may have been in existence at the time of manufacture. This procedure applies to a complete aircraft operated by and released as a complete aircraft from the military service. Adequate military maintenance records must be made available to assist in determining conformity.
- **67. CERTIFICATION REQUIREMENTS (APPLICANT).** The following are typical steps that may be taken by an applicant to show compliance with the airworthiness certification requirements of § 21.183(d):
- **a.** Proof of ownership in the form of a DOD Bill of Sale, which is considered to be recordable evidence and proof of ownership, or a DOD Form 1427, Notice of Award, Statement, and Release Document (DD 1427), considered to be proof of ownership only. The DD 1427 is not a bill of sale and cannot be used for registering the aircraft. When an aircraft is sold for recovery of parts or reduction to scrap, a bill of sale is not issued.
- **b.** Compliance and conformity to the TC, taking into account any STC's or any amendments to the TC. The applicant must present evidence that the aircraft conforms to the type design. The type design data used to determine conformity should be shown in the applicant's records. The following are typical records that could be used:

Par 65 Page 47

(1) Records maintained by the military, the manufacturer, or any other prior owner pertaining to the manufacturing, inspection, maintenance, and operation of the aircraft. Military records may be used to determine continuous conformity while the aircraft was in military service.

- (2) Form 8130-2 or prior airworthiness certificate issued by the FAA, if any.
- (3) Records such as the TCDS or aircraft specifications which establish, by manufacturer's serial number, that the complete aircraft was produced under an FAA PC or APIS and the extent it was so produced.
- (4) Where components and parts have been replaced since original manufacture, the applicant must show that they are airworthy and eligible for installation.
- (5) Records of any components and parts that have been fabricated or assembled by the applicant which establish that they conform to the type design.
- (6) Records of engines, gear box assemblies, landing gears, instruments, or other components or parts which establish that they originally conformed to the type design and have been maintained in accordance with applicable FAA requirements. Military maintenance and/or FAA-approved repair station records may be used for this purpose.
- (7) Where military records are being used to substantiate any portion(s) of conformity to FAA-approved type design, the applicant must show that the records for that specific aircraft, component, or part are complete and accurate.
- (8) An approved flight test procedure and flight check-off form has been established (when a flight test is deemed necessary) and each aircraft is flight tested by the applicant's pilot in accordance with that procedure. The FAA production flight test will not be conducted until an entry has been placed in the aircraft records to show that these tests have been satisfactorily completed by the applicant.
- (9) The civil and military model designation is reflected on the identification plate (§ 45.13) and all airworthiness documentation, including airworthiness certificates, (excluding registration) reflects the civil and military model designation and serial number. The military designation and serial number should be placed in parentheses in the same blocks as the civil model designation and serial number.
 - **c.** Form 8130-9 with an outline explaining determination of conformity.
 - **d.** A current weight and balance report from an actual weighing of the aircraft.
 - e. Records that indicate that all applicable AD's have been complied with.
 - **f.** The applicant must present records of inspection required by § 21.183(d)(2).

Page 48 Par 67

68. CERTIFICATION PROCEDURES. The following would be some of the typical steps taken by the FAA inspector toward certification of the aircraft in conjunction with those specified in paragraph 46 of this order.

- **a.** Ensure that the application is complete and correct.
- **b.** Inspect the aircraft and review records to determine:
- (1) Compliance and conformity to the TC, taking into account any STC's or any amendments to the TC.
 - (2) Compliance with applicable AD's.
- (3) Currency of weight and balance from actual weighing; it is recommended that the inspector observe the actual weighing.
- (4) Which inspections and tests, including flight tests, are required to find that the aircraft is in a condition for safe operation. The FAA production flight test requirements will be coordinated with FAA flight test personnel.
- (5) An approved flight test procedure and flight check-off form has been established (when a flight test is deemed necessary) and that each aircraft is flight tested by the applicant's pilot in accordance with that procedure. The FAA production flight tests will not be conducted until an entry has been placed in the aircraft records to show that these tests have been satisfactorily completed by the applicant.
 - (6) Compliance with the registration and marking requirements of parts 47 and 45.
- (7) The civil model designation is reflected on the identification plate and all the airworthiness documentation, including registration and airworthiness certificates, reflect the civil and military model designation and serial number. The military designation and serial number should be placed in parentheses in the same blocks as the civil model and serial number.
- **69. EXAMPLES OF FORMS.** Figures 3-1 through 3-15 provide examples of forms used in the certification process.

70.-85. RESERVED.

Par 68 Page 49

8130.2D CHG 2 12/18/00

FIGURE 3-1. SAMPLE FAA FORM 8100-2, STANDARD AIRWORTHINESS CERTIFICATE, NEW AIRCRAFT (FACE SIDE)

UNITED STATES OF AMERICA

DEPARTMENT OF TRANSPORTATION-FEDERAL AVIATION ADMINISTRATION

STANDARD AIRWORTHINESS CERTIFICATE

1 NATIONALITY AND REGISTRATION MARKS	2 MANUFACTURER AND MODEL	3 AIRCRAFT SERIAL NUMBER	. 4 CATEGORY						
N12345	Transport								
5 AUTHORITY AND BASIS FOR ISSUANCE This airworthiness certificate is issued pursuant to the Federal Aviation Act of 1958 and certifies that, as of the date of issuance, the aircraft to which issued has been inspected and found to conform to the type certificate therefor, to be in condition for safe operation, and has been shown to meet the requirements of the applicable comprehensive and detailed airworthiness code as provide by Annex 8 to the Convention of International Civil Aviation, except as noted herein. Exceptions:									
	None								
6 TERMS AND CONDITIONS									
airworthiness certificate is	d, suspended, revoked, or a termination date is otherwise established effective as long as the maintenance, preventative maintenance, and 43, and 91 of the Federal Aviation Regulations, as appropriate, and the	alterations are performed in							
DATE OF ISSUANCE	FAA REPRESENTATIVE		DESIGNATION NUMBER						
1/20/00	E.R. White E.R. V	Vhite	NE-XX						
Any alteration, reproduction, or misuse of this certificate may be punishable by a time not exceeding \$1,000, or imprisonment not exceeding 3 years or both. THIS CERTIFICATE MUST BE DISPLAYED IN THE AIRCRAFT IN ACCORDANCE WITH APPLICABLE FEDERAL AWAITION REQUIATIONS.									

FAA Form 8100-2 (8-82)

SAMPLE FAA FORM 8100-2, STANDARD AIRWORTHINESS CERTIFICATE, SPARE AND SURPLUS PARTS (FACE SIDE)

UNITED STATES OF AMERICA

DEPARTMENT OF TRANSPORTATION-FEDERAL AVIATION ADMINISTRATION

STANDARD AIRWORTHINESS CERTIFICATE

1 NATIONALITY AND REGISTRATION MARKS	2 MANUFACTURER AND MODEL	3 AIRCRAFT SERIAL NUMBER	4 CATEGORY						
N54321	Jackson 47G-4	3191HG	Normal						
the aircraft to which issued h operation, and has been show	NOE sissued pursuant to the Federal Aviation Act of 1998 and certifies that, sibeen inspected, and found to conform to the type certificate therefo in to meet the requirements of the applicable comprehensive and detain wention of International Civil Aviation, except as noted herein.	r, to be in condition for safe	,						
	None								
6 TERMS AND CONDITIONS									
airworthiness certificate is ef	suspended, revoked, or a termination date is otherwise established by i ective as long as the maintenance, preventative maintenance, and alte i, and 91 of the Federal Aviation Regulations, as appropriate, and the a	rations are performed in							
DATE OF ISSUANCE	FAA REPRESENTATIVE	DE	SIGNATION NUMBER						
1/20/00	E.J. Smith E.J. Smith	th	SW-XX						
Any alteration, reproduction, or misuse of this certificate may be purishable by a fine not exceeding \$1,000, or imprisonment not exceeding \$1,000									

FAA Form 8100-2 (8-82)

Page 50

12/18/00 8130.2D CHG 2

FIGURE 3-2. SAMPLE FAA FORM 8130-6, APPLICATION FOR AIRWORTHINESS CERTIFICATE, VLA UNDER § 21.183(a)

												_										Form O.M.E	Approved 3. No. 2120-0018
U.S. D of Tran Federa	al A	ortatio viatio	n n		Al	PLICA RWO CERT	RTHII TFIC	NES	s					INSTRUCTIONS - Pri use only. Submit origi space is required, use Il and VI or VII as applie	inal o an a	nly to ttach	an auth	noriz	ed FAA Rep	rese	as; t	hese ive.	are for FAA If additional
				ON MAR	RK	2. AIRCE	RAFT BU	ILDER'	SNAME	E (M	ake)	- 1		AIRCRAFT MODEL DESIG	NATI	ON	4. YR. MF	R.	FAA CODING	3			
FS .		18C				Lite-I						-	_	F-1-A			93	4					
1 to = 1	L	F01)	ERIALN		Rotax						- 1	91	ENGINE MODEL DE SIGNA									
- 30	One Wood Built Good-1 IMPORT							icable)															
	AF	PLIC	ATION	SHERE	BY MADE FOR: (Check	k a pplicabl	le items)																
	Α	1	X	STAND	ARD AIRWORTH INESS	CERTIFI	CATE (In	dicate d	category	1)	NOI	RMAL	L	UTILITY ACRO	OBAT	IC	TRANS	SPOF	T G	LIDEF	R		BALLOON
	В			SPECIA	L AIR WORTHINESS CI	ERTIFICA	TE (Chec	ck appro	opriate i	items)												
				2	LIMITED																		
_				5	PROVISIONAL (Indi	cate class)			1		LASS											
STE			Į.		· ·					2		LASS											
O.			RESTRICTED (Indicate operation(s) to							TURE AND PEST CONTRO (Wildlife conservation)	OL	5	-	RIAL	LING	3 6			AL ADVERTISING THER CONTROL				
2				3	be conducted)				ŀ	7	_		_			0	-			0		WEA	THER CONTROL
Ē			ŀ							1	_		_	E OF CARGO CH AND DEVELOPMENT		2	_		Specify)	3		EVUI	BITION
E				4	EXPERIM ENTAL (In	ndicate ope	eration(s)			4	_	ACIN		NI THE BEVELOR MEIT		2 AMATEUR BUILT 5 CREW TRAINING					_	SURVEY	
II. CERTIFICATION REQUESTEC					to be conducted)					0	т) SH	OW	/ COMPLIANCE WITH FAR	2	-							
=			Ī							1				LIGHT FOR REPAIRS, ALT		TIONS	, MAINT	ENAN	ICE OR STO	RAGE			
					SPECIAL FLIGHT PI					2			_	E FROM AREA OF IMPEN									
				8	complete Section V	or VII as	m			3	O	PERA	ATIC	ON IN EXCESS OF MAXIM	UM C	_	-						
					applicable on reverse	e side)				4	-			NG OR EXPORT		5	PR	ODU	CTION FLIGH	IT TE	STIN	IG	
l +	С	6	\vdash	MI II TIE	DI E AID WODTHINESS	CEPTIEIC	ATE (Ch	ock ABI	OVE *P	6				ER DEMONSTRATION FLI and "Standard" or "Limited,"			No.1						
	÷		ETED		IER (As shown on certifi					031110	лей Оре	i a boi	17 0	and Standard of Elimited,			ER, CHE	- L II	EDE		_	Т	
l t	N/	ME				cate or arr	crait regis	strauuri				1	ADI	DRESS			-		EKE				
	L	te-F	ligh	Corp).								18	301 Airport Rd. W	ichi	ta, I	KS 672	209					
	В.				ICATION BASIS (Check							ated)	1	1									
	×	Re	CRAF vision N	o.) A2	FICATION OR TYPE CI WI Rev. 1	ERTIFICA	TE DATA	SHEE	T (Give	No. a	and		\times	AIRWORTHINESS DIRE	ECTIV	ES(C	Check if al	lapp	licable AD's o	omp li	ed w	ith and	give
ō.		AIE	CDAE	FLICTIA	IG (Give page num ber(s)	11						-		SUPPLEMEN TAL TYPE	CEB	TIEIC	ATE // int	no consi	or of on ab C7	C inc	orno	e odoeñ	
-ICA		N.		шотп	o (Give page number (s)	,								N/A	OLK	11110	AIL (LIST	nam	AN OF BELLION	C IIIC	upu	i atou)	
RT	C.	_		OPERA	TION AND MAINTENAN	CE RECO	RDS					-+											
SCE	J	СН	ECKIF	RECOR	RDSIN	TOTAL	AIRFRAN	1E HOU	IRS										NLY (Enter h	ours fi	low n	since	last certificate
OWNER'S CERTIFICATION	$^{\wedge}$	FA	MPLIA R 91.17	CE WI	тн	2.0									3	-0-	ed or rene	wed)					
≡ 0	Ad	ministr	ation in	accorda	I hereby certify that I a nce with Section 501 of t the airworthiness certif	he Federa	al Aviatio	wner (d n Act d	orhisag f 1958, a	gent) and a	of the ai pplicab	rcraf le Fe	ft d	lescribed above; that the air ral Aviation Regulations; an	ircraft nd tha	is reg	gistered v aircraftha	vith t	ne Federal Av en inspected	iation and is	i S		
1	D/	TE O	APPL	CATIO	V	NAME A	ND TITL	E (Prin	t or type	1)						SIGN	IATURE						
	0	1/27	/200)		K.H.	Good,	, Dire	ectór	Q.A	Α.			KA Good									
	A.	THE /	IRCR/	FT DES	CRIBED ABOVE HAS B	EEN INSF	PECTED	AND F	OUND A	AIR W	ORTH	BY:	(C	mplete this section only if FAR part 21 . 183(d) applies).									
NOI YOU	2		FAR Certi	part 121 ficate N	or 127 CERTIFICATE I	HOLDER	(Give	3		CER [*] Certif	TIFICAT i cate N	ED N	иЕС	CHANIC (Give		6	0	CERT No.)	IFICATED RE	PAIR	STA	TION	(Give Certificate
IV. INSPECTION AGENCY VERFICATION	5		AIRC	RAFT	MANUFACTURER (Give	name or f	irm)	•															
≥ 5	DA	TE	L			TITLE										SIGI	NATURE						
\vdash	_					<u> </u>						_	Т	Terre oee									
	A.				ele blocks in items A and described in Section I or		s requirer	ments fo	or:			4	+	AMENDMENT OR MO				DEN	IT AIDWODT	HINE	99.0	EDTIE	ICATE
ų z					al flight permit under Se							Ż	F	AMENDMENT OR MO	ا ۱۰ ا		FAA D	_		NES	JU U	-IX HIP	IO/ II E
V. FAA RESENTATIVE RTIFICATION			ond uct		gra pormit unuel 36	- 3-011 VII						É		CERTIFICATE HOLDER UN	IDER:		FAR 6	5	FAR 121, 1		135		FAR 145
V. F.	DA	TE			DISTRICT OFFICE		DES	SIGNEE	'S SIGN	NATL	IRE ANI	ONO).			FAA	NSPEC	TOR	SSIGNATUR	E			
REPR							4								1	A	J. Koo	1					
	0	1/28	/200)	CE43												J. Koo						
	_					E1 00 : :									\perp	1							
FAAI	-0	m 8	130-6	(11-88) SUPERSEDES PR	EVIOUS	EDITIO	iN															
	\dagger	A	. Opera	ting Limi	tations and Markings in	Complian	ce with F	AR				Т		G. Statement of Conform	ity, F	AA Fo	rm 8130-	9 (At	ach when req	uired)	,		
VIII. AIRWORTHNESS DOCUMENTATION (FAA use only)	<u>.</u>	9	.31 as	applica	ble							_		H. Foreign Airworthiness (Attach when required)		ficatio	n for Impo	ort Aiı	craft				
NTAI	ľ	_			ting Limitations Attache s, Photographs, etc. (At		roguirod	n				+		I. Previous Airworthiness		fi cate	Issuedin	Acco	rdance with				
RWC UME	1	_			nt and Balance Information							一;	X	FAR 21.191(b)			CAR				Orie	inal Att	achadi
II. Al	ľ	<u>`</u>			and Alteration, FAA For				9d)			\dashv	_	J. Current Airworthiness	Certif	icate		Acco	dance with	(origi	ıraı Att	auritiu)
>	1	ا آ	This is	.,								\dashv	X	21 101(-)									

8130.2D CHG 2 12/18/00

FIGURE 3-3. SAMPLE FAA FORM 8100-2, STANDARD AIRWORTHINESS CERTIFICATE, VLA UNDER § 21.183(a)

UNITED STATES OF AMERICA DEPARTMENT OF TRANSPORTATION-FEDERAL AVIATION ADMINISTRATION

STANDARD AIRWORTHINESS CERTIFICATE

1 NATIONALITY AND	2 MANUFACTURER AND MODEL	3 AIRCRAFT SERIAL	4 CATEGORY
REGISTRATION MARKS		NUMBER	VLA Special
N18CE	Lite-Flight LF-1-A	LF010	Class

5 AUTHORITY AND BASIS FOR ISSUANCE

This airworthiness certificate is issued pursuant to the Federal Aviation Act of 1958 and certifies that, as of the date of issuance, the aircraft to which issued has been inspected and found to conform to the type certificate therefor, to be in condition for safe operation, and has been shown to meet the requirements of the applicable comprehensive and detailed airworthiness code as provide by Annex 8 to the Convention of International Civil Aviation, except as noted herein. Exceptions:

None

6 TERMS AND CONDITIONS

Unless sooner surrendered, suspended, revoked, or a termination date is otherwise established by the Administrator, this airworthiness certificate is effective as long as the maintenance, preventative maintenance, and alterations are performed in accordance with Parts 21, 43, and 91 of the Federal Aviation Regulations, as appropriate, and the aircraft is registered in the United States.

DATE OF ISSUANCE FAA REPRESENTATIVE DESIGNATION NUMBER

08/10/00 A.J. Kool A.J. Kool CE43

Any alteration, reproduction, or misuse of this certificate may be punishable by a fine not exceeding \$1,000, or imprisonment not exceeding \$3 years or both. THIS CERTIFICATE MUST BE DISPLAYED IN THE AIRCRAFT IN ACCORDANCE WITH APPLICABLE FEDERAL AVIATION REGULATIONS.

FAA Form 8100-2 (8-82)

12/18/00 8130.2D CHG 2

FIGURE 3-4. SAMPLE FAA FORM 8130-6, APPLICATION FOR AIRWORTHINESS CERTIFICATE, JAR/VLA UNDER § 21.183(c)

																					rm Approved VI.B. No. 2120-0018
U.S. D of Trai Feder Admir	nsp al/	ortatio Aviatio	n n			Al	RW	OR'	TION FOR THINESS FICATE				INSTRUCTIONS - Pr use only. Submit orig space is required, use Il and VI or VII as appl	inal o an a	nly to ttachm	an authori	zed FAA	Repr	esen	; the	se are for FAA . If additional
			TR ATI	ON M	٩RK		2. AIR	CRA	T BUILDER'S NAM	ΛΕ (Make	e)	3	3. AIRCRAFT MODEL DESIG	GNAT	- 1	YR. MFR.	FAA CC	DING			
Fõ							AK-1A			989											
I. ARCRAFT DESCRIPTION	5. AIRCRAFT SERIAL NO. 6. ENGINE BUILDER'S NAME (Make) AK901 Rotax							7. ENGINE MODEL DE SIGN 1912	ATION	1											
- Bi	8.	NUME	BER OF	ENGI	NES	1	9. PR	OPEL	LER BUILDER'S N	AME (Ma	ake)	1	0. PROPELLER MODEL DE	SIGN	ATION	_1	1. AIRCR	AFT IS	(Che	ck if a	pplicable)
		ne					God					1	1-GP-008				MP0	RT			
		PLIC	1 \ 7			Y MADE FOR: (Check														_	
	Α	1	$\perp \!$			RD AIRWORTH INESS					NORM	ΛAL	UTILITY ACR	OBAT	IC	TRANSPO	RT	GLI	DER		BALLOON
	В			SPEC	IAL A	AIR WORTHINESS CI	ERTIFIC	CATE	(Check appropriate	items)											
				2		LIMITED															
				5		PROVISIONAL (Indi	cate cla	iss)		1	CLA										
II. CERTIFICATION REQUESTED				_		,				2	CLA							_			
l g						RESTRICTED (India	ate ope	ration	(s) to	1			LTURE AND PEST CONTR	OL	2	AERIA		-	3	_	ERIAL ADVERTISING
2				3		be c onducted)			,	4	_		(Wildlife conservation)		5		DLLING		6	W	EATHER CONTROL
Ď				4	_					7	_		GE OF CARGO		0		(Specify)			-	
I S				4		EXPERIM ENTAL (In	dicate d	perat	ion(s)	4	RAC		RCH AND DEVELOPMENT		5		TRAININ	\rightarrow	3	_	KT. SURVEY
H H				4		to be conducted)				0	_		W COMPLIANCE WITH FA		, I	CREW	I KAININ	6	_	IVI	KI. SURVET
E			ł	\dashv						1			FLIGHT FOR REPAIRS, ALT		TIONS.	MAINTENA	NCE OR	STORA	AGE		
						SPECIAL FLIGHT PI	ERMIT	(Indi c	ate	2			ATE FROM AREA OF IMPEN								
				8		operation to be cond				3	OPE	RAT	TION IN EXCESS OF MAXIN	иuм с	ERTIF	ICATED TA	KE-OFF V	/EIGH	г		
						complete Section Vi applicable on reverse		as		4	4 DELI				PROD	DUCTION FLIGHT TESTING					
												STOP	IER DEMONSTRATION FLIGHTS								
	С	6		MULT	IPLE	AIR WORTHINESS (CERTIF	ICAT	E (Check ABOVE "F	Restricte	d Opera	tion"	and "Standard" or "Limited,	" as a	pplicabl	e.)					
					/NE	R (As shown on certifi	cate of a	aircra	ft registration)			_		IF	DEALE	R, CHECK	HERE -		_		
	N/	ME R. A	pplic	ant								Į AI	DDRESS 4 David Road. Wi	chit	a. KS	67209					
	_											-	· Daviditoda. Wi		.,	0,20,					
1 1	В.					ATION BASIS (Check						6a) 	✓ AIRWORTHINESS DIR	FCTIV	/ES/Ch	eck if all an	nlicah le A	D's cor	molier	d with:	and give
_	AIRCRAFT SPECIFICATION OR TYPE CERTIFICATE DATA SHEET (Give No. and Revision No.) A 2EU Rev. 1					/	latest AD No.) 92-25			out ii uii up	pirocab to 7 t	D 0 00i	- Pilot	2 ** 1011	and give						
OWNER'S CERTIFICATION	AIRCRAFT LISTING (Give page num ber(s)) N/A						>	SUPPLEMENTAL TYPE CERTIFICATE (List number of each STC incorporated) A89NE													
ERT	C.	AIRC	CRAFT	OPER	ATIC	ON AND MAINTENAN	CERE	CORE	S												
NER'S C	CHECK IF RECORDS IN COMPLIANCE WITH FAR 91.173.							3	issued -0-	RIMENTAL for renewed	ONLY (Er	nter hou	rs flo	wnsin	ce last certificate						
≡ ov	D. CERTIFICATION - I hereby certify that I am the registered owner (or his agent) of the aircr Administration in accordance with Section 501 of the Federal Aviation Act of 1958, and applicable I airworthy and eligible for the airworthiness certificate requested.							raft Fed	alt described above; that the aircraft is registered with the Federal Aviation ederal Aviation Regulations; and that the aircraft has been inspected and is												
			F APPL /199		NC		J.B.	E AND	TITLE (Print or typing ht	oe)			SIGNATURE $J.B.\ Wright$								
	Α.	THE	NRCR/	FT DI	ESC	RIBED ABOVE HAS B	EEN IN	ISPEC	TED AND FOUND	AIR WO	RTHYB	BY: (: (Complete this section only if FAR part 21.183(d) applies).								
NO NO	2			part 1 ficate		r 127 CERTIFICATE I	HOLDER (Give 3 CERTIFICATED Certificate No.)				D ME	MECHANIC (Give 6 CERTIFICATED REPAIR STATION (Giv. No.)				ON (Give Certificate					
IV. INSPECTION AGENCY VERFICATION	5		AIRO	RAFT	MA	NUFACTURER (Give	name	or firm)												
≥ >	DA	ATE	1				TITLE	:							SIGN	ATURE					
\vdash	_											-	× d =								
	_					blocks in items A and scribed in Section I or		ote ra	ouirements for		-	+	THE CERTIFICATE R								
w_											-	4	AMENDMENT OR MO	JUIFIC	SATION			ORTH	NES	SCER	TIFICATE
A E E			onduct		ciai	flight permit under Se	ction vi	II			ľ	7	CERTIFICATE HOLDER UN	NDED	.	FAR 65	FAR -	121 12	7 or 1	125	FAR 145
V. FAA PRESENTATIVE ERTIFICATION	DA	ATE			1	DISTRICT OFFICE			DESIGNEE'S SIG	NATUR	E AND N	NO.	CERTIFICATE HOLDER OF	VDER		INSPECTO				130	TAIL 190
CER																					
~	0	1/27	/200	0	1	NW78		4						1		Mende Mende					
FAAI	Fo	rm 8	130-6	(11-8	38) \$	SUPERSEDES PR	EVIOL	JS EI	DITION												
A. Operating Limitations and Markings in Compliance with FAR						with FAR			ī	G. Statement of Conform	nitv F	AA For	n 813n.a //	Attach who	n reassi	red)					
VIII. AIRWORTHINE SS DOCUMENTATION (FAA use only)	P	× 🤅	1.31 as	applic	able	una markingo III	Southin					F		-				. roqui)		
E E	ìŀ	В	. Curre	nt Ope	ratin	g Limitations Attache	d					∜	H. Foreign Airworthiness (Attach when required	erti f)	ncation	ı ur import A	arcraft				
ORT ENT/	1	-				Photographs, etc. (At		en rec	quired)			†	I. Previous Airwor thiness	s Certi	ficate Is	sued in Acc	cor dance v	rith			
JRW SUMI	į þ	_			_	and Balance Information						1	FAR			CAR			(0	riginal	l Attached)
∏. A DOC	ځځ	-1-										t	J. Current Airworthiness	Certif	li cate Is		or dance w	ith		gu	
>	E. Major Repair and Alteration, FAA Form 337 (Attach when required) F. This inspection Recorded in Aircraft Records				オ᠈	EAR 21 183(c)						(C	ony of	tached)							

8130.2D CHG 2 12/18/00

FIGURE 3-5. SAMPLE FAA FORM 8100-2, STANDARD AIRWORTHINESS CERTIFICATE, JAR/VLA UNDER § 21.183(c)

UNITED STATES OF AMERICA DEPARTMENT OF TRANSPORTATION-FEDERAL AVIATION ADMINISTRATION

STANDARD AIRWORTHINESS CERTIFICATE

1 NATIONALITY AND	2 MANUFACTURER AND MODEL	3 AIRCRAFT SERIAL	4 CATEGORY
REGISTRATION MARKS		NUMBER	VLA Special
N569K	Aero-K AK-1A	AK901	Class

5 AUTHORITY AND BASIS FOR ISSUANCE

This airworthiness certificate is issued pursuant to the Federal Aviation Act of 1958 and certifies that, as of the date of issuance, the aircraft to which issued has been inspected and found to conform to the type certificate therefor, to be in condition for safe operation, and has been shown to meet the requirements of the applicable comprehensive and detailed airworthiness code as provide by Annex 8 to the Convention of International Civil Aviation, except as noted herein. Exceptions:

None

6 TERMS AND CONDITIONS

Unless sooner surrendered, suspended, revoked, or a termination date is otherwise established by the Administrator, this airworthiness certificate is effective as long as the maintenance, preventative maintenance, and alterations are performed in accordance with Parts 21, 43, and 91 of the Federal Aviation Regulations, as appropriate, and the aircraft is registered in the United States.

DATE OF ISSUANCE FAA REPRESENTATIVE DESIGNATION NUMBER 01/20/00 Tom Kick $Tom\ Kick$ NW78

Any alteration, repoduction, or misuse of this certificate may be punishable by a fine not exceeding \$1,000, or imprisomment not exceeding 3 years or both. THIS CERTIFICATE MUST BE DISPLAYED IN THE AIRCRAFT IN ACCORDANCE WITH APPLICABLE FEDERAL AVIATION REGULATIONS.

FAA Form 8100-2 (8-82)

FIGURE 3-6. SAMPLE FAA FORM 8130-11, CHECKLIST AND INSPECTION RECORD, AIR-CRAFT BUILT FROM SPARE AND SURPLUS PARTS

Project No.:
Date:
Ref. FAA Form 8130-6,
Dated:

Date: Ref. FAA Form 8130-6, Dated:	
CHECKLIST AND INSPECTION RECORD	
Subject: Original Airworthiness Certificate of Aircraft Built from Spare and Surplus Parts.	
A. Builder's Name and Address:	
B. Aircraft Type: Airplane, Rotorcraft, Other (specify)	
C. Type Certificate No and Model to Which Conformity Shown.	
D. Name and Address of Type Certificate Holder:	
E. Builder's Assigned Serial Number:	
F. Registration No.:	
G. Identification Plate Location:	
H. Aircraft Inspected By:	
(Signature FAA Inspector)	
(District Office No. and Location)	
FAA Form 8130-11 (7-77) Page 1	

FIGURE 3-6. SAMPLE FAA FORM 8130-11, CHECKLIST AND INSPECTION RECORD, AIR-CRAFT BUILT FROM SPARE AND SURPLUS PARTS (CONTINUED)

INSPECTION DATA

Period of Inspection: From To

Conducted At:

Circle as appropriate. Explain "No" items under "Remarks"

Yes No

Yes No

Yes No

Yes No

Yes No

- 1. Did the applicant submit a properly executed Application for Airworthiness Certificate, FAA Form 8130-6?
- 2. Did the applicant submit a completed Statement Yes No of Conformity, FAA Form 8130-9?
- 3. Did the applicant submit acceptable evidence in the form of inspection records, technical data, and any other data as required to establish conformity with the approved type design?
- 4. Is the aircraft eligible for a standard airworthiness certificate, by make and model, as established by the applicable type data sheet, aircraft specification, or aircraft listing?
- 5. Is the aircraft properly registered in accordance with FAR 47 and is the identification number properly displayed in accordance with FAR 45?
- 6. Is a fireproof identification plate containing the information required by FAR 45 installed in a location as prescribed FAR 45?
- 7. Is the serial number assigned by the builder Yes No one which cannot be confused with the type certificate holder's serial number?
- 8. Do the inspection records submitted by the applicant show that the aircraft has satisfactorily completed all required inspections and tests?
- 9. Has the aircraft been flight tested in accordance with the type certificate holder's FAA-approved procedures?

FAA Form 8130-11 (7-77) Page 2 Local Reproduction Authorized

FIGURE 3-6. SAMPLE FAA FORM 8130-11, CHECKLIST AND INSPECTION RECORD, AIR-CRAFT BUILT FROM SPARE AND SURPLUS PARTS (CONTINUED)

10.	Has the flight test been appropriately recorded in the aircraft records?	Yes	No
11.	Have all records and documentation been provided for the aircraft, as required by the applicable airworthiness part of the CFR?	Yes	No
12.	Are all substitutions of materials, parts, components, assemblies, etc., and all changes to the type design appropriately FAA-approved?	Yes	No
13.	Have internal inspections of gearboxes, rotor components, and other similar components been conducted to determine that all parts are within type design tolerances?	Yes	No
14.	Are all parts and assemblies with service life limits within such limits? (Show under "remarks" on the record of service life limit components how the time in service was proved.)	Yes	No
15.	Are all required items of equipment installed and are they functioning properly?	Yes	No
16.	Are all required placards and instrument markings installed?	Yes	No
17.	Have all applicable airworthiness directives been complied with?	Yes	No
18.	Based upon inspection and the evidence submitted by the applicant, has the aircraft been found to conform to the type design?	Yes	No
19.	Based upon inspection, has the aircraft been found in condition for safe operation?	Yes	No

FIGURE 3-6. SAMPLE FAA FORM 8130-11, CHECKLIST AND INSPECTION RECORD, AIR-CRAFT BUILT FROM SPARE AND SURPLUS PARTS (CONTINUED)

Remarks

FAA Form 8130-11 (7-77) Page 4 Local Reproduction Authorized

FIGURE 3-6. SAMPLE FAA FORM 8130-11, CHECKLIST AND INSPECTION RECORD, AIR-CRAFT BUILT FROM SPARE AND SURPLUS PARTS (CONTINUED)

CONFORMITY RECORD

List and identify below, documents submitted by the applicant and used by the inspector in determining conformity with the FAA approved type design. This should include reference to Conformity Inspection Records, FAA Form 8100-1, by date or serial number; the Statement of Conformity, FAA Form 8130-9; submitted by the applicant; supplemental type certificates, if applicable; airworthiness directives; and any other data submitted as evidence that the aircraft conforms to the type design, in accordance with FAR § 21.183(d)(1).

FAA Form 8130-11 (7-77) Page 5 Local Reproduction Authorized

FIGURE 3-6. SAMPLE FAA FORM 8130-11, CHECKLIST AND INSPECTION RECORD, AIR-CRAFT BUILT FROM SPARE AND SURPLUS PARTS (CONTINUED)

WEIGHT AND BALANCE

As part of the original airworthiness inspection, the aircraft should be weighed to determine that ranges of weight and center of gravity are within the limits originally approved, as specified in the appropriate aircraft specification or type certificate data sheet.

The Weight and Balance Report should include the following:

- 1. Leveling Means.
- 2. Location of Datum.
- 3. Most Forward C.G. Loading.
- 4. Most Rearward C.G. Loading.
- 5. If ballast is used, the amount and location should be given.

EQUIPMENT LIST

All items of equipment which are replaceable on the aircraft shall be listed with the weights and moment arms.

Note: A verified copy of the applicant's Weight and Balance Report and Equipment List containing the above information may be substituted for this page.

FIGURE 3-6. SAMPLE FAA FORM 8130-11, CHECKLIST AND INSPECTION RECORD, AIR-CRAFT BUILT FROM SPARE AND SURPLUS PARTS (CONTINUED)

RECORD OF SERVICE LIFE COMPONENTS INSTALLED

	Component	Part or Assembly Number	Serial Number	Total Time on Part	Service Time Remaining Before Retirement
1.	•				
2.					
3.					
4.					
5.					
6.					
7.					
8.					
9.					
10.					
11.					
12.					
13.					
14.					
REMARK	<u>(S</u> :				

FAA Form 8130-11 (7-77) Page 7 Local Reproduction Authorized

FIGURE 3-6. SAMPLE FAA FORM 8130-11, CHECKLIST AND INSPECTION RECORD, AIR-CRAFT BUILT FROM SPARE AND SURPLUS PARTS (CONTINUED)

FLIGHT TEST REPORT

Refer to, or attach a copy of, the approved flight test check-off form completed by the FAA flight test representative.

FAA Form 8130-11 (7-77) Page 8 Local Reproduction Authorized

FIGURE 3-7. SAMPLE FAA FORM 8130-9, STATEMENT OF CONFORMITY, AIRCRAFT BUILT FROM SPARE AND SURPLUS PARTS

	Not Subject to OMB Cle	erence
UNITED STATES DEPARTMENT OF TI FEDERAL AVIATION	RANSPORTATION	
STATEMENT OF	CONFORMITY	
SECTION I -	AIRCRAFT	
I. MAKE	2. MODEL	
Jackson	47G-4	
serial no. 321	4. REGISTRATION NO. N54321	
. MAKE	2. MODEL	
SERIAL NO.		
SECTION III - F		
I. MAKE	2. HUB MODEL	
1 SLADE MODEL	4. HUB SERIAL NO.	
S. BLAGE SERIAL NOS. SECTION IV — C	ERTIFICATION	
hereby certify that:		
A. I have compiled with Section 21.33(a).		
is in a condition for safe operation, and was flight checks C. The engine or propeller described above, presented herew	ith for type centification, conforms to the type design there	
	ype certificate only (FAR 21 Subpart F), conforms to its ty- ngine or, if applicable, the variable pitch propeller was sub-	pe bjected
by the manufacturer to a final operational check on	(Data)	
Deviations: NONE		
SIGNATURE OF CERTIFIER // TITLE		
Henry L. Jackson	Owner	
ORGANIZATION	DATE	
•	Fahren 12	1071

FAA Form 8130-9 (9-78) USE PREVIOUS EDITION

FIGURE 3-8. SAMPLE FAA FORM 8130-10, SURPLUS MILITARY AIRCRAFT INSPECTION RECORD, NO REASONABLE POTENTIAL FOR STANDARD CERTIFICATION

	Not Subject to OMB Clea	rance
UNITED STATES O	FAMERICA	
DEPARTMENT OF TRA	ANSPORTATION	1
FEDERAL AVIATION AS		1
STATEMENT OF C	ONFORMITY	- 1
SECTION I - A		
	2. MODEL	
1. MAKE Jackson	47G-4	- 1
3. SERIAL NO. 321 SECTION II -		
1. MAKE	2. MODEL	\dashv
1. MARE		1
3. SERIAL NO.		
SECTION III - PR	OPELL ER	
1. MAKE	2. HUE MODEL	1
1. SLADE MODEL	4. HUS SERIAL NO.	1
S. BLADE SERIAL NOS.		
SECTION IV - CE	RTI FICATION	
I hereby certify that:		
' '		İ
A. I have complied with Section 21.33(a).		- 1
区 B. The sircreft described above, protocotypates xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx	twosly (FAR 21 Subpart F), conforms to its type certificate	.
is in a condition for safe operation, and was flight checked	on February 12, 19XX	
	(Date)	Ì
		- 1
C. The engine or propeller described above, presented herewith	h for type certification, conforms to the type design therefo)T.
		I
D. The engine or propeller described above produced under type certificate and is in a condition for safe operation. The eng	e certificate only (FAR 21 Support F), conforms to its type	ected
by the manufacturer to a final operational check on	me of, it applicable, the variable picture properties was every	
(Deta)	1
Deviations: NONE		
į		
SIGNATURE OF CERTIFIER // TITLE		
Henry L. Jackson	Owner	
ORGANIZATION	DATE	
-	February 13.	19XX

FAA Form 8130-9 (9-76) USE PREVIOUS EDITION

FIGURE 3-9. SAMPLE FAA FORM 8130-10, SURPLUS MILITARY AIRCRAFT INSPECTION RECORD, REASONABLE POTENTIAL FOR STANDARD CERTIFICATION

SURPLUS MILITARY	AIRCRAFT	INSPECTION	RECO	ORD	SUSPE	NSE DAT	E	
	itial Screenin							
	Se	etion A - DESC	CRIPTIC	ON OF AIR	CRAFT			
1. MANUFACTURER		2. MOI				3. :	SERIAL	NUMBER
	A. CIVIL		B. MIL	YRATI	A. CIV			S. MILITARY
Hiller	UH-231	D	OH	-23D		1160		59-2680
4. DATE OF MANUFACTURE	5. TOTAL	TIME ON ACFT	r.	6. FAA	T.C. DATA SH	EET		7. P.C. NO.
January 22, 19XX	7640:50			4H1	0		60	7
	:	Section B — LO	CATIO	OF AIRC	RAFT			
1. LOCATION MASDC/ILMP Davis-Moth Tucson, Ar	an AFS	2. CONTAC					TELEPHO	ONE (Incl. area code)
rucson, ar	120114	Section C - IR			ESTER		02 / 3	,-4321
1. DATE 2. N	AME				Chief, A	ircraf	t la	MILITARY BRANCH
September 15, XX R.					sal Branc			USAF
5. ADDRESS						6.	TELEPH	ONE (incl. area code)
(Same as Locat	ion)							
		Section D — FA	AA INSI	PECTION R	ESULTS			
1A. AIRCRAFT HISTORICAL RE	CORDS	B. AIRCRA		DIFICATIO	N RECORDS	c	_	DS CONSIDERED -
FROM TO		FROM		То			=	DEGUATE IADEQUATE FOR
December 15. XX March	23, XX	May 10,	XX	Nov	ember 16,	XX.		W CERTIFICATION
	Record the fol	lowing paly; if/I	C:Die	#Sheet/Spe	ification Limit	: exceeded	L" - A-Y	SEARCH IN THE SECOND
				ENGTH OF		(1) T.C.		(2) MILITARY ACTUA
(1) T.C. DATA	(2) MILITARY	ACTUAL	(3) -	ENGTH OF		(1) 1.6.	0414	(2) MICHARY ACTOR
3. CONDITION OF AIRCRAFT	Date plate affixe	rd: 🗶 YES	□ *	101				
Good Condition								
A DISBOSITION /"Y" and								
A. X AIRCRAFT HAS REAS	4. DISPOSITION ("X" one) A. \(\subseteq \) AIRCRAFT HAS NO REASONABLE POTENTIAL B. \(\subseteq \) AIRCRAFT HAS NO REASONABLE POTENTIAL FOR POR STANDARD CERTIFICATION FOR STANDARD CERTIFICATION							
	TIPICATION							>M
FAA INSPECTOR (Typed and sign	ned) ,	OFFICE			TELEPHONE (FTS)	1	NSPECTION DATE
James a.	ned) ,		•		TELEPHONE (NSPECTION DATE
	ned) ,	NM-XX	etion E	- ACTION	964-770			NSPECTION DATE
James A. Street	Stead -	NM-X2 Sa /R	etion E		964-7709	3	S	NSPECTION DATE
Janes a.	Stead -	NM-X2 Sa /R	etion E	- ACTION	964-7709	3	S	NSPECTION DATE SEPTEMBER 12. 19X
James A. Street	Stead -	NM-X2 Sa /R	etion E	- ACTION for AFS-18	964-7709	3	SON OF	NSPECTION DATE SEPTEMBER 12. 19X

FAA Form 8130-10 (1-74)

Page 65

FIGURE 3-10. SAMPLE FAA FORM 8130-2, CONFORMITY CERTIFICATE - MILITARY AIRCRAFT

DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION CONFORMITY CERTIFICATE—MILITARY AIRCRAFT (Instructions on Reverse)

A. This certifies that the aircraft described below has been manufactured in conformity with data forming the basis for Type Certificate No. 1H6 , and any revision or modification thereof approved by the FEDERAL AVIATION ADMINISTRATION as of October 17, 19XX with the exception of the following deviations:

Auto Electric Automatic Stabilizer, Model 330D ABC Radio Receiver, Model 50 External Fuel Tank, Safeaire Dwg. 59-2642

(NOTE: When there are no deviations from the approved type design write "None.")

	B.	DESCRIPTIO	N OF AIRCRAFT	r
MANUFACTURER	MODEL	MANI	FACTURER'S SERIAL	NO. MILITARY SERIAL NO.
Safeaire	B- 50	2	6442	59-26791
	C	DESCRIPTIO	N OF ENGINES	
MANUFACTURER	MODEL	MANL	FACTURER'S SERIAL	NO. MILITARY SERIAL NO.
1. Clunker 2.	R-1840-3	14235		59-3164
3.				
4.				
5.				
6.				
D. CONTRACT NO. 646-21-4641		AF-9	CATION MARKINGS D	ISPLAYED
F. CONTRACTOR'S GROUND I	NSPECTION AND FLIGHT TEST		G. FAA GROUND IN	ISPECTION AND FLIGHT TEST
Date completed APPROVED BY Doctober 17 19XX	- Mark. Smil	*	October 25 19XX	R.G. Wright
	Smith, Chief Eng		-	R.E. Wright (SIGMATURE OF FAA REPRESENTATIVE) (DMIR NO.)

FAA FORM 8130-2 (10-67) FORMERLY FAA FORM 970 Use reverse for remarks.

12/18/00 8130.2D CHG 2

FIGURE 3-11. SAMPLE FAA FORM 8100-2, STANDARD AIRWORTHINESS CERTIFICATE, SURPLUS MILITARY AIRCRAFT

UNITED STATES OF AMERICA DEPARTMENT OF TRANSPORTATION-FEDERAL AVIATION ADMINISTRATION

STANDARD AIRWORTHINESS CERTIFICATE

1 NATIONALITY AND REGISTRATION MARKS	2 MANUFACTURER AND MODEL	3 AIRCRAFT SERIAL NUMBER	4 CATEGORY Normal
N34561	Hughes 369A	1441	

5 AUTHORITY AND BASIS FOR ISSUANCE

This airworthiness certificate is issued pursuant to the Federal Aviation Act of 1958 and certifies that, as of the date of issuance, the aircraft to which issued has been inspected and found to conform to the type certificate therefor, to be in condition for safe operation, and has been shown to meet the requirements of the applicable comprehensive and detailed airworthiness code as provide by Annex 8 to the Convention of International Civil Aviation, except as noted herein. Exceptions:

None

6 TERMS AND CONDITIONS

Unless sooner surrendered, suspended, revoked, or a termination date is otherwise established by the Administrator, this airworthiness certificate is effective as long as the maintenance, preventative maintenance, and alterations are performed in accordance with Parts 21, 43, and 91 of the Federal Aviation Regulations, as appropriate, and the aircraft is registered in the United States

DATE OF ISSUANCE	FAA REPRESENTATIVE	DESIGNATION NUMBER		
01/20/00	B. Potrer B. Porter	SW-XX		

Any alteration, reproduction, or misuse of this certificate may be punishable by a fine not exceeding \$1,000, or imprisonment not exceeding 3 years or both. THIS CERTIFICATE MUST BE DISPLAYED IN THE AIRCRAFT IN ACCORDANCE WITH APPLICABLE FEDERAL AVIATION REGULATIONS.

FAA Form 8100-2 (8-82)

8130.2D CHG 2 12/18/00

FIGURE 3-12. SAMPLE FAA FORM 8130-6, APPLICATION FOR AIRWORTHINESS CERTIFICATE, USED AIRCRAFT, NO PREVIOUS U.S. AIRWORTHINESS CERTIFICATE (FACE SIDE)

_																									provea No. 2120-0018
of T Fed	Deparansport	ortatio viatio	n n			Al	RW	ATIO ORTH TIFIC	INES					u:	NSTRUCTION se only. Subpace is required and VI or VI	omit origi ired, use	inal or an att	nly to achn	an autho	rized F	FAA Re	prese	ntative	. If a	dditional
	1			ATION I	/ARK			CRAFT B	UILDER	'S NAN	ЛЕ (Ма	ake)			RCRAFT MOD	ELDESIG	SNATIC	- 1	4. YR. MFR	. FA	A CODIN	G			
FO	_	123	_	SERIA	u NO			iglas Sine buii	DEDIC	NIANAT	(8.4-1-	- 1			-6A IGINE MODEL	DECION	ATION		1952	-					
I. AIRCRAFT DESCRIPTION		321		SERI	AL INO	-		t & W			(IVI alke	9)		CB		DESIGNA	ATION								
I. A	_			OF EN	SINES			PELLER			AMF ((Make)	+	10. P	ROPELLER M	ODEL DE	SIGNA	TION		11. AIF	RCRAFT	IS (CF	neck if:	nnlica	ide)
	4			O. L.	J 120			nilton				maio,	- 1		E60-300	002202	0.0.47				MPORT	10 (0)	noon in c	рриос	20)
	AF	PLIC	ATIC	N IS H	REB	Y MADE FOR: (Check																			
	Α	1	$ \rangle$	STA	NDAF	RD AIRWORTH INESS	CERTII	FICATE (Indicate	catego	ry)	NO	RMAL		UTILITY	ACR	OBATIO	βX	TRANSP	ORT	0	SLIDER	₹	В	ALLOON
	В			SPE	CIAL	AIR WORTHINESS CE	RTIFIC	ATE (Ch	eck appi	opriate	items	;)													
				2		LIMITED																			
۾ ا				5		PROVISIONAL (India	cate clas	ss)			2		LASS												
CERTIFICATION REQUESTED											1	·			RE AND PES	T CONTR	ΩI	2	AERI	ΔΙ		3	IΔ	=RIAI	ADVER TISING
Eau				3		RESTRICTED (Indic	ate oper	ration(s) t	,		4				ildlife conserv			5		OLLIN	IG	6	_		ER CONTROL
N N						be conducted)					7	С	ARRI	AGE	OF CARGO			0	ОТНЕ	R (Spe	cify)				
CATI											1	R	ESEA	RCH	AND DEVELO	OPMENT		2	_	TEUR E		3	E	KHIBIT	ION
I				4		EXPERIMENTAL (In to be conducted)	dicate o	perati on(s	5)		4	R	ACIN	G				5	CRE	N TRA	INING		N	KT. SL	IRVEY
CEF											0	_			OMPLIANCE HT FOR REP						00.070	D.105			
=						SPECIAL FLIGHT PE	RMIT /	(Indicate			2				FROM AREA			_		IANCE	OR STO	KAGE			
				8		operation to be cond	lucted, ti	hen			3				IN EXCESS (AKE-O	FF WEIG	нт			
						complete Section VI applicable on reverse		is			4	D	ELIVE	RING	OR EXPORT	7		5	PROI	DUCTIO	ON FLIGI	HT TES	STING		
		6										_			DEMONSTR										
	С			-		AIR WORTHINESS (Restric	ted Op	eration	" and	"Standard" or	"Limited,"							- 1		
						R (As shown on certific	cate of a	ircraft reç	istration)			- 1,	/DDE	FSS				R, CHEC	HERE					
	Ť	ger	Αv	iatio	n C	orp.							1	234	Jane Ave	. Jacks	on, l	MS	78965						
	В.					ATION BASIS (Check							cated)												
8	×	Re	visio	AFT SP n No.)	ECIFI 53A	CATION OR TYPE CE Rev. 26	ERTIFIC	CATE DAT	A SHE	T (Giv	e No. a	and	,	_	AIRWORTHIN latest AD No.)										e
IFICATI		AIF	RCR	AFT LIS	TING	(Give page num ber(s)))						;	A	SA2-414							FC inc	orpor at	ed)	
ER	c.	AIR	CRA	T OPE	RATIO	ON AND MAINTENAN	CE REC	ORDS																	
OWNER'S CERTIFICATION	×	, cc	MPL	IF REG IANCE .173.	WITH	S IN	12,3	LAIRFRA 147.0	ME HO	JRS							3		RIMENTA d or renew		Y (Enter h	ours fl	ow n sir	ce las	certi ficate
° =	Ad	minist	ration	in acco	rdanc	I hereby certify that I a e with Section 501 of t e ai rworthin ess certif	he Fede	ral Aviati	owner (on Act o	orhisa of 1958	agent) , and a	of the a applicab	ircraft ble Fe	des deral	cribed above; Aviation Regu	that the ai	ircraft i	is regi the a	istered wit ircraft has	h the F been ii	ederal A	viation and is			
		TE 0 2/21		PLICAT	ION		NAME Johr	AND TIT 1 Doe,	LE (<i>Prir</i> Presi	tor typ dent	e)								ature n Doe						
	Α.	THE	AIRC	RAFT	DESC	RIBED ABOVE HAS B	EEN IN	SPECTED	AND F	OUND	AIR W	/ORTH	Y BY:	(Com	plete this sect	ion only if	FAR p	art 21	. 183(d) app	olies).					
NO LO	2			AR part ertificat		r 127 CERTIFICATE H	HOLDER	R (Give	3			TIFICA ficate N		IECH	ANIC (Give			6	CE No		CATED R	EPAIR	STATI	ON (Gi	ve Certificate
IV. INSPECTION AGENCY	5		A	RCRAF	T MA	NUFACTURER (Give	name o	r firm)																	
		TE					TITLE											SIGN	IATURE						
						blocks in items A and									THE CERTII	FICATE R	EQUES	STED							
	\perp					scribed in Section I or		ets requir	ements t	or:			4		AMENDMEN		DIFIC	ATION				HINES	SCER	TIFICA	TE
4TVE	В.	Insper	ction	for a spucted by	ecial	flight permit under Sea	ction VII								INSPECTOR			+	FAA DE					1	
V. FAA	E DA	TE.				DISTRICT OFFICE		DI	SIGNE	e's sig	SNATU	JRE AN	D NO.	CEI	RTIFICATE HO	JLDER UN	IDER:	FAA	FAR 65		AR 121, IGNATUR		135	FA	R 145
V. FAA	3																1.								
~		1/12	/20	00		CE45		4									1		nes Jon mes Jor						

FAA Form 8130-6 (11-88) SUPERSEDES PREVIOUS EDITION

12/18/00 8130.2D CHG 2

FIGURE 3-12. SAMPLE FAA FORM 8130-6, APPLICATION FOR AIRWORTHINESS CERTIFICATE, USED AIRCRAFT, NO PREVIOUS U.S. AIRWORTHINESS CERTIFICATE (CONTINUED) (REVERSE SIDE)

	Α.Ι	MANUFACTURE	₹									
	NA	ME			ADI	DRESS						
VI. PRODUCTION FLIGHT TE STING	В. І	PRODUCTION B	ASIS (Check applicat	ble item)								
UC.				(Give production certificate number)								
3OD HTT			RTIFICATE ONLY	(1.1)								
I. P				SPE CTION SYSTEM								
> L	C. (R EQUIRED FOR OPERATING NEEDS								
	_	TE OF APPLICAT		NAME AND TITLE (Print or type)			SIGNATURE					
	Δ	DESCRIPTION OF	- AIRCRAFT									
		GISTERED OWN			ADI	DRESS						
	KE	GISTERED OWN	EK		ADI	DREGG						
	DII	ILDER (Make)				DEL						
	ВО	ILDER (Make)			IVIC	DEL						
	051					OUOTE ATION MADIC						
	SEI	RIAL NUMBER			KE	GISTRATION MARK						
	_			CUSTOMER DEMONS	TDATI	ON FLIGHTS (Check if a	policable)					
	FR.	DESCRIPTION O	F FLIGHT	COSTOWER DEWONS	TO	DIVITUORITS [CHECKTIZ	і філсавіе)					
	FK	OW			110							
	VIA				-	PARTURE DATE		DURATION				
_	VIA				DEI	PARTURE DATE		DURATION				
FEST												
Ē	C. (E AIRCRAFT AND ITS EQUIPMENT								
DI.		PILOT	CO-PIL									
NO.	D.	THE AIRCRAFT I	OOES NOT MEET TI	HE APPLICABLE AIRWORTHINESS REQUIREMEN	TS AS	FOLLOWS:						
CT												
nac												
PRC												
HAN												
RT												
뿓												
o s:												
SOS												
UR												
Ħ												
VII. S PECIAL FLIGHT PERMIT PURPOSES OTHER THAN PRODUCTION FLIGHT TEST												
토	E. 1	THE FOLLOW ING	RESTRICTIONS A	RE CONSIDERED NECESSARY FOR SAFE OPER.	ATION:	(Use attachment if neces sary)						
<u> </u>												
H.												
EC												
S.												
₹												
	- (DEDITIES ATION	166			ib-d-b		land Ariaban Administration in				
	acc	ordance with Title	49 of the United Sta	am the registered owner (or his agent) of the aircra ates Code 44101 et seq. and applicable Federal Aviati	n Reg	ulations; and that the aircraft has	gistered with the red s been inspected and	is air worthy for the flight				
	des	cribed.										
	DA	TE		NAME AND TITLE (Print or type)			SIGNATURE					
	$\overline{}$	A. Operating Lim	itations and Marking	s in Compliance with FAR	X	G. Statement of Conformity, FA	A Form 8130-9 (Atta	ch when required)				
SS	X	91.31 as applica	ible	· •		H. Foreign Airworthiness Certif						
VIII. AIRWORTHINESS DOCUMENTATION (FAA useonly)		B. Current Oper	ating Limitations Atta	ac hed	1	(Attach when required)	icadorror importArro	or car.				
ORT ENT,				:. (Attach when required)	+	I. Previous Airworthiness Certif	i cate Issued in Accor	dance with				
UME VA u	X			mation Available in Aircraft	\exists	FAR	CAR					
E S E	$\stackrel{\sim}{}$			Form 337 (Attach when required)	+	J. Current Airworthiness Certifi		(Original Attached)				
> 1	X		n Recorded in Aircra		ΗX	EAR 21 183(d)		(Copy attached)				

8130.2D CHG 2 12/18/00

FIGURE 3-13. SAMPLE FAA FORM 8130-6, APPLICATION FOR AIRWORTHINESS CERTIFICATE, NEW AIRCRAFT PRODUCED UNDER AN APIS OR PC (FACE SIDE)

																							F (Form O.M.I	Approved 3. No. 2120-001
U.S. E of Tra Feder Admi	nspor al Av	tation iation	ı			IRW	CATION ORTHII TIFIC	NES					us sp	se only. Su	omit origi ired, use	inal o	only attac	to an	authori	zed F	AA Re	eprese	as; t entat	hese ive.	are for FAA If additional ete Sections
	1. R			ION MA	RK	2. AIR	CRAFT BU	ILDER'	'S NAME	E (Make))			CRAFT MOE	EL DE SIG	GNAT	ION	4. YI	R. MFR. 68	FAA	CODIN	NG			
I. AIRCRAFT DES CRIPTION	5. Al	RCR	AFT:	SER IAL	NO.	6. ENG	GINE BUILD			Make)		7.	EN	GINE MODEL	DESIGNA	IOITA	N	1							
ESCF		714					t & Wh							D-9											
- 0	8. N	UMBE	R O	F ENGIN	IES	9. PRO	OPELLER E	BUILDE	R'S NAM	ME (Mak	ke)). PF J/A	ROPELLER M	ODEL DE	SIGN	ITA	ON	F		CRAFT	ris (C	heck	if appi	icable)
	APF	LICA	TION	IS HER	EBY MADE FOR: (Chec		able items)					114	1/1:	1											
	Α	1	X	STANI	DARD AIRWORTHINES	S CERTII	FICATE (In	dicate o	category)	NORN	ЛAL		UTILITY	ACR	OBAT	TIC	$X _{T}$	RANSPO	RT		GLIDEI	۲		BALLOON
	В			SPECI	AL AIR WORTHINESS C	ERTIFIC	CATE (Chec	ck appro	opriate it	items)															
				2	LIMITED																				
a				5	PROVISIONAL (Ind	icate clas	ss)		H	2	-	SSI SSII													
II CERTIFICATION REQUESTED										1	-			RE AND PES	T CONTR	OL	2	2	AERIA	L		3		AER	AL ADVER TISING
REGL				3	RESTRICTED (Indi-	cate oper	ration(s) to		Ī	4	FOF	REST	(W	'ildlife conserv	ation)			5	PATRO	OLLING	3	6		WEA	THER CONTROL
NO.					,					7	-			OF CARGO			(_	OTHER						
ICA					EXPERIM ENTAL (I	ndicate o	neration(s)		- 1	1 4	-		СН	AND DEVEL	OPMENT		2	_	AMATI			3		_	BITION
ERTIF				4	to be conducted)		, , , ,		H	0	+ -	CING	N C	OMPLIANCE	WITH EAR	D		<u> </u>	CREW	IRAII	NING	Ш		MKI	. SURVEY
= 5										1			_	HT FOR REF			TIO	NS, MA	INTEN	ANCE	OR ST	ORAGE			
					SPECIAL FLIGHT F				Ī	2	EVA	CUAT	TEF	FROM AREA	OF IMPEN	NDIN	G D/	ANGER							
				8	operation to be con- complete Section V	Tor VII a	hen is			3	OPE	RATIO	ION	IN EXCESS	OF MAXIM	MUM (CER	TIFICA	TED TA	KE-OF	F WEI	GHT			
					applicable on revers	e side)				4				OR EXPOR				5	PROD	UCTIC	N FLIG	HT TE	STIN	IG	
	С	6		MULT	PLE AIR WORTHINESS	CERTIE	ICATE (Ch	ock ARI	OVE "P.	6 estricted	-			DEMONSTR				cable)							
			STER	_	NER (As shown on certif					20117 01000	Орога		aria.	otariara o	Dimicou,				CHECK	HERE				Т	
	NAN	ΛE			nes, Inc.			,				ADI 11	DR 11	ESS Airport V	Vav St						010				
			IRCRAFT CERTIFICATION BASIS (Check applicable blocks and complete items as indicate											F	, ,			,							
z	×	AIR	CRAF	T SPEC	CIFICATION OR TYPE CO	ERTIFIC	CATE DATA	SHEE	T (Give	No. and		×	(AIRWORTHIN latest AD No.)	93-03	ECTI	VES	(Chec	k if all ap	plicab	le AD's	compli	ed w	ith and	1 give
OWNER'S CERTIFICATION		AIR		T LISTI	NG (Give page num ber(s	;))								SUPPLEMEN N/A	TALTYPE	CER	RTIF	ICATE	(List nur	nber o	each S	STC inc	orpo	r ated)	
CERI	C.	_			TION AND MAINTENAM																				
WNER'S	×	CO	СК I ИРЦ/ 91.1	F RECC NCE W 73.	RDS IN ITH	8.45	L AIRFRAN	1E HOU	IRS							3			renewed		(Enter	hours f	low n	since	last certificate
=	Adm	inistra	tion i	n accord	I hereby certify that I ance with Section 501 of it the airworthiness certification.	the Fede	eral Aviatio																		
	02	/23/	200	_		-	and titu n Doe, '										J	gnati ohn i	Doe						
	A. T	HE A	RCR	AFT DE	SCRIBED ABOVE HAS I	BEEN IN:	SPECTED	AND F	OUND A	AIR WOR	THYE	3Y: (C	Comp	plete this sect	ion only if	FAR	part	21 . 18:	(d) appl	ies).					
ICY ATION	2		Cer	tificate N	- ,			3		CERTIFI Certificat			CHA	ANIC (Give				6	CER No.)	TIFIC	ATED F	REPAIR	STA	TION	(Give Certificate
IV. INSPECTION AGENCY VERIFICATION	5		AIR	CRAFT	MANUFACTURER (Giv	e name o	or firm)																		
	DAT	Έ				TITLE											S	IGNATI	JRE						
					ble blocks in items A an			·			I			THE CERTI											
w					t described in Section I o			nents to	UI:		\dashv	4	_	AMENDME		DIFI	CAT	<u> </u>			RWOR	THINE	SS C	ERTIF	ICATE
ATIVE	B. Inspection for a special flight permit under Section VII was conducted by:							H	_		NINSPECTOR RTIFICATE HO		אחביי	,. l	_	AA DESI AR 65		AR 121,	127	125		FAR 145			
V. FAA REPRESENTATIVE CERTIFICATION	DAT				DISTRICT OFFICE		DES	SIGNEE	SSIGN	NATURE	AND		UER	VIIIOATE HO	JEDER UN	*DEK			PECTO				135		I AIN INO
CER							4 G	E Sm	;+l,								,								
_	03	/15/	200	0	WE40 4346	DMIR	R 12:	34																	

FAA Form 8130-6 (11-88) SUPERSEDES PREVIOUS EDITION

12/18/00 8130.2D CHG 2

FIGURE 3-13. SAMPLE FAA FORM 8130-6, APPLICATION FOR AIRWORTHINESS CERTIFICATE, NEW AIRCRAFT PRODUCED UNDER AN APIS OR PC (CONTINUED) (REVERSE SIDE)

	A.	MANU	JFACTURER						
	N.A	ME			ADI	DRESS			
Z 0									
ΗĒ	В.	PROD	OUCTION BASIS (Check applicable)						
E E			PRODUCTION CERTIFICATE	(Give production certificate number)					
VI. PRODUCTION FLIGHT TE STING			TYPE CERTIFICATE ONLY						
1. P			APPROVED PRODUCTION INS	SPECTION SYSTEM					
	c.	GIVE	QUANTITY OF CERTIFICATES F	REQUIRED FOR OPERATING NEEDS -					
	-		- APPLICATION	NAME AND TITLE (Print or type)			SIGNATURE		
	"	(IE OI	AFFEIGATION				SIGNATURE		
-									
	⊢		RIPTION OF AIRCRAFT						
	RE	GIST	ERED OWNER		ADI	DRESS			
	BU	IILDEF	R (Make)		МО	DEL			
	SE	RIAL	NUMBER		RE	GISTRATION MARK			
	-	DESC	RIPTION OF FLIGHT	CUSTOMER DEMONSTI	RATIO	ON FLIGHTS (Check if a	annlicable)		
		OM	KIFTION OF FLIGHT		то				
	' '	Oivi			10				
	L							T	
	VIA	A			DE	PARTURE DATE		DURATION	
EST									
1	c.	CREV	V REQUIRED TO OPERATE THE	AIRCRAFT AND ITS EQUIPMENT					
펼			PILOT CO-PIL	OT FLIGHT ENGINEER OTHER (Spi	ecify)				
트	D.	THE /	AIRCRAFT DOES NOT MEET TH	E APPLICABLE AIRWORTHINESS REQUIREMENT	S AS	FOLLOWS:			
ē									
2									
8									
<u> </u>									
¥									
E E									
里									
0									
SE									
8									
E E									
¥									
VI. SPECIAL FLIGHT PERMIT PURPOSES OTHER THAN PRODUCTION FLIGHT TEST	_								
Ë	E. '	THEF	OLLOWING RESTRICTIONS AR	RE CONSIDERED NECESSARY FOR SAFE OPERAT	ION:	(Use attachment if neces sary)			
9									
<u> </u>									
_გ									
SPE									
=									
-									
	F.	CERT	IFICATION - I hereby certify that I : ce with Title 49 of the United Sta	am the registered owner (or his agent) of the aircraft tes Code 44101 <u>et seq</u> . and applicable Federal Aviatior	descr Rea	ibed above; that the aircraft is re ulations: and that the aircraft ha:	gistered with the Fed s been inspected and	deral Aviation A d is airworthy fr	dmini stration in or the flight
		scribe		<u></u>					
	-	TE		NAME AND TITLE (Print or type)			DIOLIATURE		
	"	VIE.		Transfer Tree (rinkor yps)			SIGNATURE		
<u> </u>	⊢					1			
	\times	A. C	Operating Limitations and Markings	s in Compliance with FAR		G. Statement of Conformity, FA	AA Form 8130-9 (Atta	ach when requir	red)
NO ~	ĽÌ	91.3	1 as applicable			H. Foreign Airworthiness Certif	ication for Import Air	craft	
VIII. AIRWORTHI NESS DOCUMENTATION (FAA use only)		В. С	Current Operating Limitations Atta	ched		(Attach when required)	•		
ORT ENT,		-	Data, Drawings, Photographs, etc.		H	I. Previous Airworthiness Certif	i cate Issued in Accor	dance with	
RW. UME	X	+	Current Weight and Balance Inform		1				(Onininal Award 17
A O A	$\stackrel{\frown}{}$	1			-	J. Current Airworthiness Certifi	CAR_	donos with	(Original Attached)
ǰ	L	-	Major Repair and Alteration, FAA F		X			uance with	
1	IΧ	F. T	his inspection Recorded in Aircra	ft Records	ľÌ	FAR 21.183 (a) or (b)		(Copy attached)

8130.2D CHG 2 12/18/00

FIGURE 3-14. SAMPLE FAA FORM 8130-6, APPLICATION FOR AIRWORTHINESS CERTIFICATE, SURPLUS MILITARY AIRCRAFT (FACE SIDE)

																								Fo.	m Approv	ed 120-0018
U.S. E of Tra Feder Admi	nspor al Av	tation iation	ı			PLIC IRWC	DRT	HIN	ES					u s	NSTRUCTIO ise only. Sub pace is requi	mit orig red, use	ginal c e an a	only attac	to an a	authori	zed FAA	Repre	esen	tative	. If additi	onal
	1. R	EGIST		TION MAI	RK			T BU IL	DER'S	S NAME	(Make)			RCRAFT MOD	ELDESI	GNATI	ION		.MFR.	FAACO	DING				
I. AIRCRAFT DES CRIPTION		456		SER IAL N	10.	Hugl 6. ENG		BUII DE	R'S N	IAME (Make)		_	369 LEN	9A NGINE MODEL	DESIGN	AOITAL	V	196	6						
CRIF	13					Allis				(.					0-C10B											
I. A	8. N	UMBE	R O	F ENGIN	ES	9. PRO N/A	PELL	ER BU	ILDEF	R'S NAI	ME (Ma	ke)		10. P	PROPELLER MO	ODEL DE	ESIGN	IATIO	ON	1	1. AIRC RA		(Che	ck if a	pplicable)	
	APF	LICA	TION	I IS HERI	BY MADE FOR: (Chec	k applicat	bl e ite	ms)													_					
	Α	1	X	STAND	ARD AIRWORTH INES	CERTIF	ICAT	E (Indi	icate c	ategory)	NOR	MAL		UTILITY	ACR	ROBAT	TIC	TR	ANSPO	RT	GLI	DER		BALLC	ON
	В			SPECIA	L AIR WORTHINESS C	ERTIFICA	ATE (Check	appro	priate i	tems)															
				2	LIMITED																					
۵				5	PROVISIONAL (Ind	icate clas	s)			-	1	-	ASSI													
II. CERTIFICATION REQUESTED											2	_	ASSII		JRE AND PEST	CONTR	201	1 2	,	AFRIAI			3	LA	FRIAL ADVI	ED TISING
Egu				3	RESTRICTED (India	cate opera	ation(s) to		ŀ	4	1			Vildlife conserva		(OL	5		PATRO			+	- 1	EATHER C	
N.					be conducted)					ŀ	7	+		_	OF CARGO			0	,		(Specify)					
ATIC											1	RE	SEAR	СН	AND DEVELO	PMENT		2	$\overline{}$		UR BUILT	r [:	3	E	KHIBITION	
Ĭ				4	EXPERIMENTAL (II to be conducted)	ndicate op	oerati d	on(s)			4	RA	CING	;				5	5	CREW	TRAINING	3		М	KT. SURVE	Υ
CER					· ·						0			-	COMPLIANCE											
=											1	_			GHT FOR REPA					INTENA	NCE OR	STORA	GE			
				8	SPECIAL FLIGHT P operation to be con-	ducted, th	hen	te		ŀ	2				FROM AREA O					TED TAI	KE-OFF W	/FIGHT				
			complete Section VI or VII as applicable on reverse side)									+-			G OR EXPORT	1 WIFFORIII	VIOIVI C	5	$\overline{}$		JCTION F			TING		
					,,,	,				ı	6				R DEMONSTRA	TION FL	JGHTS	S .		TROD	JOHOIVI	LIGITI	ILO	11140		
	С	6		MULTII	PLE AIR WORTHINESS	CERTIFIC	CATE	(Chec	k ABO	VE "R e	estricted								cable.)							
	Α.	REGI	STER	ED OWI	NER (As shown on certif	icate of ai	ircraft	registr	ration)								IF	DEA	ALER, C	HECK	HERE -		_			
	He	lico	pte	er Ope	ratiors, Inc.								2	34	SESS S Perimite	er Driv	ve, S	tac	ckton,	, Cali	f. 9404	4				
_	В.				FICATION BASIS <i>(Checi</i> IFICATION OR TYPE C BWE Rev. 2								ted)	<	AIRWORTHIN latest AD No.)	ESS DIR 93-20	RECTIV	VES	(Check	if all ap	plicable Al	D's cor	nplied	d w ith	and give	
OWNER'S CERTIFICATION		AIR		T LISTIN	NG (Give page num ber(s))								- 1	SUPPLEMENT N/A	AL TYPE	E CER	TIFI	ICATE (List nun	nber of eac	ch ST C	inco	rpor at	ed)	
E E	С.	AIRCI	RAFT	OPERA	TION AND MAINTENAN	ICE REC	ORDS	3					-													
WNER'S C	×	CON	CK I //PLI/ ! 91.1	F RECOI ANCE WI 173.	RDS IN TH	TOTAL 2852	AIRF 2.0	RAME	HOUI	RS							3	iss N	KPERIM sued or r	ENTAL renewed	ONLY (En	iter hou	rs flo	w n sir	ce last certi	ficate
0 =	Adm	inistra	ition i	n accorda	I hereby certify that I nce with Section 501 of the airworthiness certi	the Feder	ral Av	iation																		
		E OF /12/		LI CATIO	N	Jame	and es J.	Jone	(Print	or type) Jener	al M	gr.						1	GNATUI ames		s					
	Α.Τ	HE AI	RCR	AFT DE	SCRIBED ABOVE HAS E	BEEN INS	SPECT	TED A	ND FC	OUND A	NR WOF	RTHY	BY: (0	Can	nplete this secti	on only if	f FAR _j	part	21 . 183(d) appli	ies).					
NO NO H	2			R part 12 tificate N	or 127 CERTIFICATE 0.)	HOLDER	(Give	9	3		CERTIF Certifica			ЕСН	IANIC (Give				6	CER No.)	TIFICATE	D REP	AIR S	TATI	ON (Give C	ertificate
IV. INSPECTION AGENCY VERIFICATION	5	×	AIR	CRAFT	MANUFACTURER (Give	e name or	r firm)			•									•	•						
	04.	e /26/	200	00		Man	age	r, Qu	ıalit	y Ass	suran	ce						1	GNATU <i>ichar</i>		rtin					
					ole blocks in items A and										THE CERTIF											
l					described in Section I o		ts req	jui reme	nts fo	r:			4		AMENDMEN	T OR MO	ODIFIC	CATI				ORTHI	NESS	CER	TIFICATE	
ATIVE				or a speci	al flight permit under Se	ction VII						-			A INSPECTOR			+		A DESI		04.45			T-10 ··	_
SBNT,	DAT				DISTRICT OFFICE			DESIG	GNEE'	SSIGN	IATURE	AND		CE	RTIFICATE HO	LDER UI	NDER			R 65 PECTOR	FAR 1		or 1	35	FAR 14	5
V. FAA REPRESENTATIVE CERTIFICATION	"							-	_			_										_				
~	11.	/13/	200	00	NM-XX		4										1		B <i>en P</i> Ben P							

FAA Form 8130-6 (11-88) SUPERSEDES PREVIOUS EDITION

12/18/00 8130.2D CHG 2

FIGURE 3-14. SAMPLE FAA FORM 8130-6, APPLICATION FOR AIRWORTHINESS CERTIFICATE, SURPLUS MILITARY AIRCRAFT (CONTINUED) (REVERSE SIDE)

	А	. MANI	UFACTURER							
	N	IAME			AE	DDRI	ESS			
8 <u>8</u>	F		DUCTION BASIS (Check applica							
VI. PRODUCTION FLIGHT TE STING	P	. PROL		(Give production certificate number)						
l d E		-	TYPE CERTIFICATE ONLY	(Give production certificate number)						
문 호		-	APPROVED PRODUCTION IN	HODE OTION CVOTEM						
> =	H									
	-			R EQUIRED F OR OPERATING NEEDS NAME AND TITLE (Print or type)			_			
	D	ATE O	F APPLICATION	NAME AND THE (PHILOT type)				SIGNATURE		
	А	. DESC	CRIPTION OF AIRCRAFT							
	R	EGIST	ERED OWNER		AE	DDRI	ESS			
	В	UILDEI	R (Make)		М	IODE	EL			
	SI	ERIAL	NUMBER		RE	EGIS	TRATION MARK			
	В	. DESC	CRIPTION OF FLIGHT	CUSTOMER DE	MONSTRAT	TION	FLIGHTS (Check if a	pplicable)		
		ROM			TC	0				
	VI	ΊΑ			DE	EPAF	RTURE DATE		DURATION	
ES.	H									
토	С	. CRE	W REQUIRED TO OPERATE TH	IE AIRCRAFT AND ITS EQUIPMENT ILOT FLIGHT ENGINEER OTH	HER (Specify					
밀	Ŀ			THE APPLICABLE AIRWORTHINESS REQUIR						
VII. S PECIAL FLIGHT PERMIT PURPOSES OTHER THAN PRODUCTION FLIGHT TEST										
VII. S PECIAL FLIGHT				RE CONSIDERED NECESSARY FOR SAFE	S. <u>-</u> 1311.01	(0	,			
	de	CERT ccordar escribe	nce with Title 49 of the United St	I am the registered owner (or his agent) of the lates Code 44101 et seg. and applicable Federa NAME AND TITLE (Print or type)	aircraft desc al Aviation Re	cribe egula	ed above; that the air craft is req tions; and that the aircraft has	gistered with the Fed been inspected and SIGNATURE	eral Aviation Aviation for air worthy for	dministration in r the flight
	╄	_			k	71				
VIII. AIR WORTHINESS DOCUMENTATION (FAA use only)	$\mid \times \mid$	91.3	Operating Limitations and Markin 31 as applicable	gs in Compliance with FAR	×	+	 Statement of Conformity, FA Foreign Airworthiness Certifi 			ed)
THIN Only)	Г	В. 0	Current Operating Limitations At	tached		1	(Attach when required)		-	
/OR ENT	Г	C. [Data, Drawings, Photographs, et	c. (Attach when required)		I.	Previous Airworthiness Certifi	cate Issued in Accor	dance with	
NA L	\times	D. 0	Current Weight and Balance Infor	rmation Available in Aircraft			FAR	CAR		_ (Original Attached)
M. F. P.	F	-1		A Form 337 (Attach when required)	\ .		Current Airworthiness Certifi		dance with	•
>	×	_	This inspection Recorded in Aircr		$\longrightarrow \hspace{-0.1cm} \mid \hspace{-0.1cm} $	$\langle $	FAR 21 183(d)			(Copy attached)

8130.2D CHG 2 12/18/00

FIGURE 3-15. SAMPLE FAA FORM 8130-6, APPLICATION FOR AIRWORTHINESS CERTIFICATE, AIRCRAFT BUILT FROM SPARE AND SURPLUS PARTS (FACE SIDE)

																					F	orm D.M.E	Approved 3. No. 2120-0018
U.S. I of Tra Fede Admi	ınspor ral Av	tation iation				PLIC IRWO CERT	RTH	INES	SS				:	INSTRUCTION use only. Subn space is require II and VI or VII a	nitorigin ed, use a	nal oi an at	nly to tachm	an author	ized FAA R	teprese	ntati	ive.	If additional
	1. R			TION MA	RK	2. AIRC		BUILDEF	R'S NAMI	E (Mak	:e)			AIRCRAFT MODE	L DE SIG	NATIO	- 1	YR. MFR.	FAA CODI	ING			
한				SER IAL	NO.			I DFR'S	NAME ((Make)				NGINE MODEL D	FSIGNA	TION		908					
I. AIRCRAFT DES CRIPTION	ı	91 I					mmii		,	,				0540-B1B									
ES P	8. N	UMBE	R O	F ENGIN	NES	9. PRO	PELLER	BUILDI	ER'S NA	ME (M	ake)	$^{+}$	10.	PROPELLER MO	DEL DES	SIGNA	ATION		11. AIRC RAF	TIS (CI	heck	if appl	icable)
	1					N/A							N/	/A					IMPORT				
	APF	LICA	TION	IS HER	EBY MADE FOR: (Chec	k applicat	bl e items	s)															
	Α	1	X	STANI	DARD AIRWORTHINES	CERTIF	ICATE ((Indicate	category	v) X	NOR	RMAL	-	UTILITY	ACRO	DBATI	С	TRANSPO	DRT	GLIDEF	2		BALLOON
	В			SPECI	AL AIR WORTHINESS C	ERTIFIC <i>A</i>	ATE (CI	neck app	ropriate	items)													
				2	LIMITED																		
l e				5	PROVISIONAL (Ind	cate class	s)			1 2		ASS											
II. CERTIFICATION REQUESTED				\vdash						1	-	ASS		TURE AND PEST	CONTRO	N .	2	AERIA		3	_	ΛEDI	IAL ADVERTISING
l g				3	RESTRICTED (India	cate opera	ation(s)	to		4				Wildlife conservati		<i></i>	5		OLLING	6			THER CONTROL
N N					be c and ucted)					7	_		_	E OF CARGO			0	OTHE	R (Specify)		_		
) ¥										1			_	H AND DEVELOR	MENT		2	_	EUR BUILT	3		EXHI	IBITION
≝				4	EXPERIMENTAL (II to be conducted)	ndicate op	erati on(s)		4	R/	ACINO	G				5	CREV	/ TRAINING			MKT	. SURVEY
CER					,					0	_			COMPLIANCE W									
=										1	_			IGHT FOR REPAI					ANCE OR ST	ORAGE			
					SPECIAL FLIGHT P operation to be con-					2				E FROM AREA OF									
				8	complete Section V applicable on revers	or VII as				3				ON IN EXCESS OF	MAXIMI	ом с	5				07111		
					адриса де оттечето	e side)				6				NG OR EXPORT ER DEMONSTRAT	ION ELIC	SHTS		PROL	UCTION FLI	GHT TE	STIN	G	
	С	6		MULT	IPLE AIR WORTHINESS	CERTIFIC	CATE (C	Check AE	BOVE "R									9.)					
	Α.	REGI	STER	ED OW	NER (As shown on certif	icate of ail	rcraft re	gistratio	n)							IF C	EALE	R, CHECK	HERE -		-		
	NAM He	nry	L. J	Jacks	on									oress unicipal Air	port, F	Han	ger 5	, Cranb	erry, Nev	w Jerso	ey 3	3303	33
	В.				FICATION BASIS (Checi							ated)		LIDILLODTUNE	00 DID 5	OT11	50/0					-41	
N N	X				CIFICATION OR TYPE C H3 Rev. 8		ATE DA	IA SHE	EI (Give	No. an	a	,	\times	AIRWORTHINE latest AD No.)									1 give
OWNER'S CERTIFICATION		N/		FT LISTI	NG (Give page num ber(s))							\times	SH165EA				TE (List nu	mber of each	STC inc	orpor	ated)	
E E	С.	_			ATION AND MAINTENAN																		
WNER'S	X	CON	IPLIA 91.1	F RECC ANCE W 173.	IRDS IN ITH	11.3	.AIRFRA	AME HO	URS							3	issued N/A	or renewe	d)	rnours 11	ow n	since	last certificate
0	Adm	inistra	ition i	n accord	I hereby certify that I ance with Section 501 of or the airworthiness certi	he Feder	al Aviat	lowner (or his aç of 1958,	gent) of and app	the ai	rcraft e Fed	t de dera	escribed above; the al Aviation Regula	at the air ations; an	rcraft nd tha	is regis t the ai	stered with rcraft has l	the Federal been inspecte	Aviation ed and is			
		E OF /23/		LICATIO	N	NAME A Henr	and th	TLE (<i>Prii</i> Iasksc	nt or type on, Ov	e) vner								TURE ry L. Ja	ckson				
	A.T	HE AI	RCR	AFT DE	SCRIBED ABOVE HAS E	EEN INS	PECTE	D AND F	OUND /	AIR WO	RTHY	BY: ((Ca	omplete this section	n only if F	-AR p	art 21.	183(d) app	lies).				
NOIF:	2	FAR part 121 or 127 CERTIFICATE HOLDER (Give Certificate No.) CERTIFICATE HOLDER (Give 3 CERTIFICATE HOLDER)											MEC	CHANIC (Give			6	CEF No.)	RTIFICATED	REPAIR	STA	TION	(Give Certificate
IV. INSPECTION AGENCY VERIFICATION	5	X	AIR Be	CRAFT ell He	MANUFACTURER (Giv	e name or	firm)	•									•						
=	DAT 07.	E /05/	200	00		TITLE Man	ager,	Quali	ity As:	suran	ice							ATURE	nes				
		Chec	k ALI	L appli ca	able blocks in items A and	1B)								THE CERTIFIC	CATERE	QUE	STED						
	A.1	ind th	at the	e ai rcraf	t described in Section I o	r VII meet	ts requir	rements	for:			4	Ĺ	AMENDMENT	OR MOI	DIFIC	ATION	OF CURR	ENT AIRWOR	RTHINES	SS CI	ERTIF	ICATE
₽ N					cial flight permit under Se	ction VII						X	FA	AA INSPECTOR				FAA DES	IGNEE				
V. FAA REPRESENTATIVE CERTIFICATION	-		nduc	ted by:	DISTRICT OFFICE		T-	FOICH	FIG OIC:	NAT''	- A			ERTIFICATE HOL	DER UN	DER:		FAR 65	FAR 121		135		FAR 145
PRES	DAT	_			DISTRICT OFFICE			ESIGNE	E'S SIGN	NAIUR	E AND	NO.					FAAI	NSPECTO	R 'S SIGNATI	UKE			
E	12.	/23/	200	00	NE-XX		4									1		Smith . Smith					

FAA Form 8130-6 (11-88) SUPERSEDES PREVIOUS EDITION

12/18/00 8130.2D CHG 2

FIGURE 3-15. SAMPLE FAA FORM 8130-6, APPLICATION FOR AIRWORTHINESS CERTIFICATE, AIRCRAFT BUILT FROM SPARE AND SURPLUS PARTS (CONTINUED) (REVERSE SIDE)

	1	A. MAN	UFACTURER						
	1	NAME			AD	DRESS			
Z 9	H								
	F	B. PRO	DUCTION BASIS (Check applica						
ᇐ			-	(Give production certificate number)					
VI. PRODUCTION FLIGHT TESTING			TYPE CERTIFICATE ONLY						
₹ 5			APPROVED PRODUCTION IN	ISPECTION SYSTEM					
	[. GIVE	QUANTITY OF CERTIFICATES	R EQUIRED FOR OPERATING NEEDS -					
	1	DATE C	F APPLICATION	NAME AND TITLE (Print or type)			SIGNATURE		
	١,	N DEC	CRIPTION OF AIRCRAFT	1					
	\vdash				T				
	ľ	REGIST	ERED OWNER		AD	DRESS			
	L								
	E	BUILDE	R (Make)		MC	DDEL			
	L								
	[5	SERIAL	NUMBER		RE	GISTRATION MARK			
	ħ	B DESC	CRIPTION OF FLIGHT	CUSTOMER DEMONST	RATIO	ON FLIGHTS Check if	applicable)		
		ROM	oral flore of Filloria		то				
	I.								
	H	/IA			-	PARTURE DATE		DURATION	
	Ι,	/IA			DE	PARTURE DATE		DURATION	
EST	L								
ΙĖ		C. CRE	W REQUIRED TO OPERATE TH	E AIRCRAFT AND ITS EQUIPMENT					
호			PILOT CO-PI	LOT FLIGHT ENGINEER OTHER (Sp	ecify)				
료	1	D. THE	AIRCRAFT DOES NOT MEET T	HE APPLICABLE AIRWORTHINESS REQUIREMENT	SAS	FOLLOWS:			
은									
2									
Š									
Ē									
₹									
1 K									
1 2									
So									
SE									
A P									
₹.									
VI SPECIAL FLIGHT PERMIT PURPOSES OTHER THAN PRODUCTION FLIGHT TEST									
H.	H		FOLLOWING DESTRUCTIONS A	DE ACUAD EDED NECESOADY FOR ALE OPENA	TION	/// * /			
노	ľ	. IHE	FOLLOWING RESTRICTIONS A	RE CONSIDERED NECESSARY FOR SAFE OPERAT	HON:	(Use attachment if necessary)			
9									
l F									
2									
SP									
Ĭ.									
	H								
	F	CERT	TIFICATION - I hereby certify that I	l am the registered ow ner (or his agent) of the aircraft ates Code 44101 et seq. and applicable Federal Aviation	desci	ribed above; that the aircraft is re	egistered with the Fer	deral Aviation Ad	dmini stration in
		describe		ates code 44101 et seq. and applicable i ederal Avialion	iiikog	juliations, and that the arrorant he	3 Deen mape cle d an	2 is all worthy to	in the lingue
	\perp			NAME AND TITLE (Print or type)					
	10	DATE		NAME AND TITLE (Print or type)			SIGNATURE		
	K	/ A.	Operating Limitations and Marking	gs in Compliance with FAR	X	G. Statement of Conformity, F.	AA Form 8130-9 (Atta	ach when require	ed)
VIII. AIRWORTHI NESS DOCUMENTATION (FAA use only)	ľ	91.	31 as applicable			H. Foreign Airworthiness Certi			
E C E	H	R	Current Operating Limitations Att	ached	1	(Attach when required)	ilication import Air	urall	
ATA Por	\vdash				-	I. Previous Airworthiness Certi	ficate lecued in Associ	rdance with	
WO ME	F	_	Data, Drawings, Photographs, etc		4			GUIDO WILLI	
AR DC	\mathbb{Z}	-1-	Current Weight and Balance Infor			FAR	CAR		_ (Original Attached)
	Γ	E.	Major Repair and Alteration, FAA	Form 337 (Attach when required)		J. Current Airworthiness Certif	cate Issued in Accor	dance with	
Γ	12	Z = -	This inequation Recorded in Aircr	aft Pacorde	7/	EAR 21 183(d)			(Conv. attached)

CHAPTER 4. SPECIAL AIRWORTHINESS CERTIFICATION

SECTION 1. GENERAL INFORMATION

- **86. GENERAL.** The procedures in this chapter provide guidance material associated with airworthiness certification and the issuance of Form 8130-7. Part 21, subparts H and I, prescribe the procedural requirements for airworthiness certification for restricted, limited, provisional, multiple, experimental categories, and primary category aircraft. Procedures are also provided for issuance of special flight permits.
- **87. APPLICATION FOR AIRWORTHINESS CERTIFICATE.** Form 8130-6 is required whenever an airworthiness certificate is issued or amended. This includes changes to operating limitations that may have been prescribed. The applicant must complete the appropriate sections and sign the application; also, a program letter must be submitted to the FAA with any other document(s) required for the requested certification. The program letter must be reviewed to ensure all the requirements of § 21.193(d) have been met.
- **88. CERTIFICATION PROCEDURES.** The following procedures are generally common for issuance of Form 8130-7, consistent with any other specific procedures that may be prescribed in other paragraphs dealing with individual airworthiness categories. In no case may any aircraft be operated unless there is an appropriate and valid airworthiness certificate issued for that aircraft. The FAA representative shall conduct any inspections necessary to verify the certification procedures listed below, including any other inspections found appropriate for that certification. For amateur-built aircraft, refer to paragraph 128 of this order.
 - **a. Record Inspection.** The FAA representative shall:
- (1) Obtain from the applicant a properly executed Form 8130-6 and any other documents required for the certification.
- (2) Obtain from the applicant a program letter identifying the aircraft, the purpose of the certificate, the area over which the operations are to be conducted, the duration of the program, etc.
- (3) Review the documentation provided by the applicant to determine that the registration requirements of part 47 have been met, and assure the aircraft is marked in accordance with part 45.
- **(4)** Check with AFS-750 to determine if a denial letter exists for the particular aircraft. This may assist the inspector in determining aircraft eligibility.
- (5) Review the aircraft records to determine that any required maintenance, inspections, etc., have been accomplished. Records should be complete and reflect no unapproved design changes.

Par 86 Page 77

(6) Arrange to review any inspection or technical data needed to establish conformity to type design.

- (7) Review the applicant's weight and balance data for accuracy and currency for the aircraft submitted.
- (8) Determine that the aircraft has been flight tested, if required. If it has not been flight tested, issue an appropriate Form 8130-7, experimental certificate, for showing compliance with the airworthiness regulations (§§ 21.189(a)(2), 21.185(d) and 91.319(b)). The flight test must be recorded in the aircraft records certifying the requirements of § 91.319(b) have been met. Flight test time is included as "time in service," as defined by part 1.
 - (9) Determine that all relevant AD's have been complied with.

NOTE: Each AD contains an applicability statement specifying the product to which it applies. Airworthiness Directives, unless specifically limited, apply to the make and model set forth in the applicability statement regardless of category. The TC and airworthiness certification categories are used to identify the product affected. For further guidance see AC 39-7, Airworthiness Directives for General Aviation Aircraft.

- (10) Establish that all required documentation and records have been provided for the aircraft; i.e., an up-to-date approved flight manual, equipment list, and maintenance records and manuals as required by certain airworthiness parts of the CFR.
- **b. Aircraft Inspection.** The FAA shall arrange with the applicant to make the aircraft available for inspection to determine that:
- (1) The aircraft is eligible by make and model using the TCDS, aircraft specification, or aircraft listing, as applicable.
 - (2) The identification plate meets the requirements of § 45.11, as applicable.
- (3) The information on the identification plate is correct, matches the information on Form 8130-6, and is in accordance with § 45.13, as applicable.
 - (4) The aircraft nationality and registration marks are in accordance with part 45, subpart C, Nationality and Registration Marks.

NOTE: Reference § 21.182 (a) and (b) (2). This requires each aircraft to be identified as described in § 45.11. In addition, if the aircraft was previously registered in the United States, it is acceptable to continue use of the duplicate pink copy of the Aeronautical Center Form 8050-1 as temporary authority to operate. However, it must be first verified that AFS-750 has received the Aircraft Registration Application as temporary authority to operate.

- (5) The flight control system operates properly.
- (6) The engine(s), propeller(s), and associated instruments operate per the manufacturer's instructions.
- (7) The pitot static system and associated instruments operate properly.
- (8) The instruments are marked in accordance with the approved flight manual or any other data used for aircraft involved in a type certification program.
 - (9) All modifications have been inspected, recorded, and are in a condition for safe operation.
 - (10) An emergency locator transmitter (ELT) is installed, as required (§ 91.207).

c. Certificate Issuance.

- (1) If the aircraft meets the requirements for the certification requested, the FAA shall:
 - (a) Make an aircraft log book entry.
 - **(b)** Issue Form 8130-7.
- (c) Complete Sections V and VIII of Form 8130-6, as appropriate, in accordance with the instructions contained in chapter 8.
- (d) Examine, review, and route the certification file in accordance with the instructions contained in chapter 8.
- (2) If the aircraft does not meet the requirements for the certification requested and the airworthiness certificate is denied, the FAA shall:
 - (a) Write a letter to the applicant stating the reason(s) for denying the airworthiness certificate.
- **(b)** Attach a copy of the denial letter to Form 8130-6 and forward to AFS-750 to be made part of the aircraft record.

89. SPECIAL AIRWORTHINESS CERTIFICATES.

- **a.** Form 8130-7 (GPO pad only) is used for all aircraft that are certificated in categories other than STANDARD.
- **b.** An experimental certificate for research and development, showing compliance with regulations, crew training, or market surveys is effective for one year or less after the date of issuance.

Par 88 Page 79

c. Duration of amateur-built, exhibition, and air racing experimental certificates will be unlimited unless the Administrator finds good cause that a specific period should be established. Any other operating limitations deemed necessary will be attached to this form; see paragraphs 134 and 142 of this order.

- **d.** However, original experimental certificates issued for the purpose of exhibition and air racing are effective for a period of time necessary to complete the flight testing required by § 91.319(b). If the testing is not completed within the terms of the certificate, the aircraft must be submitted for re-inspection to the FAA and a new certificate issued.
- **e.** When an exhibition or air racing aircraft has successfully completed its flight testing, the applicant can apply for a special airworthiness certificate of unlimited duration. The certificate will show the word "unlimited" in the expiry block of the certificate and the operating limitations will be revised to reflect those applicable limitations. A certificate of unlimited duration should not be issued until the aircraft has successfully completed its flight testing. This paragraph does not imply that unlimited expiry is granted automatically; each case must be evaluated to ensure the request is warranted and the applicant has provided evidence of compliance to § 91.319(b)(1) and (2).
- **f.** Operating limitations generally applicable to non-standard aircraft are imprinted on the reverse side of the form (figure 4-1). The FAA may also prescribe additional operating limitations as deemed necessary for the special purpose involved. The additional limitations will be enumerated on a separate sheet, dated, signed, and attached to Form 8130-7. Refer to applicable sections of this chapter for information regarding additional operating limitations which may be prescribed for the particular certification action.
 - g. The first page of the operating limitations should be typed on FAA letterhead paper.

NOTE: FAA letterhead paper may be provided to designees for the specific purpose of issuing aircraft operating limitations. It is imperative that the designee understand that the FAA supplied letterhead paper is for issuing operating limitations only and will be signed using the designee's name (typed and signed) and title as a designee.

Page 80 Par 89

SECTION 2. RESTRICTED AIRWORTHINESS CERTIFICATION

90. GENERAL. The procedures in this section provide guidance for the issuance of Form 8130-7 for aircraft type certificated in the restricted category in accordance with §§ 21.25, 21.29, or CAR 8.

- **a.** Aircraft type certificated in the restricted category for agricultural operations in accordance with the provisions of CAR 8.10(b) may continue to be operated under the provisions of the original certification. The type certification basis for aircraft in the restricted category is determined in accordance with § 21.25, except as specified in subparagraph 92a(2) of this order.
- **b.** Non-U.S.-manufactured aircraft that are type certificated in the restricted category under § 21.29 are eligible for Form 8130-7 under § 21.185(c).
- **c.** Non-U.S.-manufactured aircraft type certificated in any other category under § 21.29 are not eligible for certification in the restricted category unless the aircraft was issued Form 8100-2 under § 21.183(c) and was subsequently modified in accordance with section 3 of this chapter. In this instance, § 21.185(b) would be the basis for issuing the restricted airworthiness certificate because, by virtue of being previously certificated in the United States, the aircraft is no longer considered to be an import aircraft.
- **d.** An aircraft must be type certificated under § 21.25 or CAR 8 before a restricted category airworthiness certificate can be issued. However, in the case of an aircraft type certificated in a standard classification and modified for a restricted special purpose operation, the standard TC, along with the STC or other approved data (e.g., changes approved by Form 337) used to approve the modification, can be considered as the equivalent of a restricted TC. The combination of the TC and the STC or other approved design data should include the design parameters that normally would be included in a restricted category TCDS (e.g., maximum weight and CG limits).
- **91. CERTIFICATION PROCEDURES.** The FAA representative should follow the appropriate procedures outlined in paragraph 88 of this order.

92. ELIGIBILITY.

- **a.** Aircraft that are eligible for a special airworthiness certificate, restricted category, are as follows:
- (1) Aircraft type certificated in the restricted category and manufactured under a PC, APIS, or a TC only.
- (2) Aircraft that have been type certificated in the restricted category that were surplus military aircraft of the U.S. Armed Forces and manufactured in the United States.
- (3) Aircraft that are imported into the United States and type certificated in the restricted category in accordance with § 21.29 and that have been certified by the country of manufacture to conform to the approved type design.

Par 90 Page 81

(4) Type certificated, standard category aircraft that have been modified and approved for a restricted purpose under § 21.25, including aircraft described in paragraph 90a of this order.

- **b.** Aircraft may be considered eligible for a special airworthiness certificate, in the restricted category, when found to comply with the noise requirements of part 36, in accordance with § 21.185(d).
- **c.** For modified aircraft that were either surplus military aircraft of the U.S. Armed Forces or previously type certificated in another category (§ 21.185(b)), it shall be determined that:
 - (1) The modification conforms to the FAA-approved data forming the basis for the restricted TC, and
 - (2) The aircraft is in a good state of preservation and repair and is in a condition for safe operation.
- **93. SPECIAL PURPOSE OPERATIONS.** As authorized under the provisions of § 21.25, special purpose operations for restricted category aircraft include:
 - **a.** Agricultural (spraying, dusting, seeding, and livestock and predatory animal control).
 - **b.** Forest and wildlife conservation.
 - **c.** Aerial surveying (photography, mapping, and oil and mineral exploration).
 - **d.** Patrolling (pipe lines, power lines, and canals).
 - e. Weather control (cloud seeding).
 - **f.** Aerial advertising (skywriting, banner towing, airborne signs, and public address systems).
- **g.** Any other operation specified by the Administrator. (When an applicant wishes to obtain approval for a new special purpose operation not previously approved under § 21.25(b)(7), application with supporting justification should be made by letter to the Aircraft Engineering Division, Attn.:
- AIR-110. If accepted, this office will then provide public notice with request for comment in the <u>Federal Register</u> on the new proposed special purpose operation and will consider all comments before making a final decision.)
- **94. STATEMENT OF CONFORMITY.** The holder or licensee of a TC only for a restricted category aircraft manufactured in the United States shall, upon the initial transfer of ownership or application for an original airworthiness certificate for products manufactured under that TC, give the Administrator a Form 8130-9 (§§ 21.130 and 21.183(b)).
- **95. OPERATING LIMITATIONS.** All aircraft type certificated in the restricted category must be operated in compliance with the limitations prescribed in § 91.313. In addition, for turbine-powered aircraft, piston-powered aircraft over 800 HP, rotorcraft, large aircraft (over 12,500 lbs.), and any other

Page 82 Par 92

aircraft as deemed necessary, the limitation concerning pilot qualifications as identified in paragraph 147b(8) of this order, should be prescribed. The FAA may also prescribe additional operating limitations as deemed necessary for the special purpose involved. The additional limitations will be enumerated on a separate sheet, dated, signed, and attached to Form 8130-7.

- **96. AGRICULTURAL AIRCRAFT.** The following provides guidance concerning the means of approval for increases in the maximum certificated weight for aircraft certificated in the restricted category for agricultural operations. Section 21.101 sets forth the provisions that determine the regulations applicable to a change in a TC. Such changes would include an increase in the maximum certificated take-off weight for an aircraft, which is defined in part 43 as a major alteration. For example:
- **a.** If parts 21 and 23 are the original certification basis shown on the TCDS for a restricted category TC, then compliance with the applicable CFR must be shown to substantiate and approve a change to the TC. The provisions of CAR/CAM 8 are not applicable and should not be used (e.g., TCDS A9CE for the Cessna 188 series).
- **b.** If CAR 8 is the basis for issuance of a restricted category TC, whether or not a data sheet exists, then compliance with the applicable sections of CAR/CAM 8 will normally be used to approve the TC change, including increases to the maximum gross weight originally established on the TCDS, placards, or flight manual (e.g., TCDS 2A10 for the Piper PA-25 series). However, if CAR 8 does not provide adequate standards with respect to the change, § 21.101(b) requires compliance with regulations in effect on the date of application for the change (part 23) that the Administrator finds necessary for safety.
- **97. AIRWORTHINESS CERTIFICATE.** When an application is made for a restricted category airworthiness certificate requesting one of the special purposes listed in § 21.25(b)(1) through (6), the purpose will be entered in Block A of Form 8130-7. Carriage of cargo for compensation or hire is prohibited by § 91.313 for any restricted category operation, including any special purpose of § 21.25(b)(1) through (b)(7). If the requested purpose is to include the carriage of cargo that is incidental to the owner/operator's business, Form 8130-7 shall have the following words entered in Block A, (Purpose): "Title 14 CFR § 21.25(b)(7) (other), SEE ATTACHED LIMITATIONS." For all purposes listed in § 21.25(b)(1) through (7), the following words will be entered in Block C (Flight) (after crossing out the words "From" and "To"): "SEE ATTACHED OPERATING LIMITATIONS," and "SEE ITEM D, REVERSE SIDE OF THIS CERTIFICATE."

NOTE: In no case will "Carriage of Cargo" (or similar language) be entered as a purpose in Block A on Form 8130-7.

- **a.** When the carriage of cargo is incidental to the aircraft owner/operator's business, the prescribed limitations will then identify the authorized cargo that may be carried.
- **b.** The additional limitations attached to the airworthiness certificate will specify the aircraft model, N-number, and serial number. All restricted category airworthiness certificates issued for

Par 95 Page 83

aircraft whose special purpose operation includes the carriage of cargo will include the following limitations:

(1) This aircraft is prohibited from carrying cargo for compensation or hire. Carriage of cargo is limited
to such cargo that is incidental to the aircraft owner/operator's business which is other than air transportation.
The authorized cargo that may be carried on this aircraft is

- (2) This aircraft may not be operated over any foreign country without the special permission of that country. Evidence of that permission must be carried aboard the aircraft, along with the U.S. airworthiness certificate, and made available to the FAA or CAA in the country of operation upon request.
- (3) This aircraft has not been shown to meet the requirements of the applicable comprehensive and detailed airworthiness code as provided by Annex 8 to the Convention on International Civil Aviation.
- **c.** Additional operating limitations as prescribed in § 91.313 will be assigned for all special purposes of restricted category aircraft operations and are part of Form 8130-7.
- **d.** The FAA will ensure that the owner/operator is briefed to ensure that it is clearly understood that the restricted aircraft are prohibited by § 91.313(c) from carriage of cargo for compensation or hire. A record of this briefing should remain with the certification file.
- **98. DISPLAY OF MARKS (RESTRICTED).** The FAA shall determine that the aircraft displays nationality and registration marks in accordance with § 45.21 and that the word "RESTRICTED" is displayed in accordance with § 45.23.

99.-100. RESERVED.

Page 84 Par 97

SECTION 3. MULTIPLE AIRWORTHINESS CERTIFICATES

101. GENERAL. Under the provisions of § 21.187, an applicant for an airworthiness certificate in the restricted category, and in one or more other categories, is entitled to the certificate if compliance is shown with the requirements of each category when the aircraft is in the configuration for that category. Additionally, the applicant must show that the aircraft can be converted from one category to another by removing or adding equipment by simple mechanical means.

102. CERTIFICATION PROCEDURES. The FAA shall follow the applicable procedures in paragraph 88 of this order.

103. ELIGIBILITY.

- **a.** An aircraft in the normal, utility, aerobatic, transport, or limited category may be eligible for multiple airworthiness certificates if it can be converted to the restricted category in accordance with §§ 21.25 and 21.187. An aircraft type certificated in both the normal and commuter categories is eligible for an airworthiness certificate in only one category at a time.
- **b.** Procedures for multiple airworthiness certification are a combination of the procedures covering standard and restricted categories, or limited and restricted categories, plus the following:
- (1) The FAA should witness the applicant's method of compliance with §§ 21.187(a)(1) and 21.187(a)(2), and make a determination that the detailed conversion instructions covering the change from one category to the other are adequate. The operating limitations should contain a statement that each conversion from one category to the other must be in accordance with such instructions.
- (2) If one of the airworthiness categories is in the standard configuration, and the aircraft will be used for the carriage of passengers for compensation or hire in the standard configuration, the FAA inspector should evaluate the restricted special purpose operation to determine whether the airworthiness inspection prescribed in § 21.187(b) will be required each time the aircraft is converted from the restricted category to the standard category. Normally, if the special purpose operation involves carriage of maximum loads or the aircraft is subject to contamination by pesticides or herbicides, the airworthiness inspection should be required and an operating limitation to this effect should be prescribed. It should be noted that the foregoing does not apply when the normal category operating limits have been exceeded while operating in the restricted category; however, the procedures in paragraph 107 of this order do apply.
- (3) If the FAA determines that the airworthiness inspection by the FAA or an appropriately certificated mechanic is not necessary because of the nature of the special purpose, the operating limitations should so specify.
- (4) To ensure that each conversion of aircraft with multiple certificates is recorded, an operating limitation shall prescribe that an aircraft maintenance record entry, signed by the person

Par 101 Page 85

making the conversion, must be made each time the aircraft is converted from one category to the other. If an inspection per § 21.187(b) is required, the entry must be signed by the FAA or an appropriately rated mechanic.

- **104. SPECIAL PURPOSE OPERATIONS.** Section 21.25 specifies the special purpose operations for restricted category aircraft. Special purpose operations are not specified for limited and standard category aircraft.
- **105. AIRWORTHINESS CERTIFICATES.** If the requested multiple certification covers restricted and limited categories, Form 8130-7 will be issued for each category with appropriate conditions and operating limitations issued with each certificate. For example, if the requested multiple certification covers restricted and standard category, Form 8100-2 will be issued for the standard classification, and Form 8130-7, with appropriate conditions and operating limitations, will be issued for the restricted category.
- **106. OPERATING LIMITATIONS.** All restricted category aircraft must be operated in accordance with § 91.313, in addition to the operational requirements of part 91. However, additional operating limitations may be prescribed by the FAA as deemed necessary for safe operation. The appropriate operating limitations will be enumerated on a separate sheet and attached to Form 8130-7. The issuance date of the operating limitations must be shown on the face side of Form 8130-7.
- **107. OPERATING WITH MULTIPLE AIRWORTHINESS CERTIFICATES, STANDARD AND RESTRICTED.** The primary requirement for issuance of a standard airworthiness certificate is that the aircraft is found to be in conformity with its type design and is in a condition for safe operation. Any operations outside of the normal category operating limitations while operating in the restricted category (either weight or maneuvering), unless approved for that aircraft, may make it impossible to return the aircraft to the normal category unless a complete engineering evaluation is made. The evaluation must determine what effect the overweight and maneuvering loads had on the aircraft's (including rotorcraft) structure and components. This will assist in establishing an inspection and/or replacement program that would return the aircraft to a condition for safe operation in the standard configuration. Unknown stresses and possible hidden damage to the aircraft structure may have resulted because of the weights, maneuvers, and speeds utilized for the restricted category operations. Therefore, to retain eligibility for return to the standard airworthiness classification after being operated in the restricted category, the following would apply:
- **a.** While being operated in the restricted category, any changes made to the aircraft that are to be retained when in normal category operation, or any operations that are outside of the normal category operating limitations, must be approved in accordance with the regulations and procedures applicable to an aircraft having a standard airworthiness certificate.
- **b.** If the TCDS for an aircraft includes both normal and restricted category, and the maximum gross weight and/or operating limitations for the restricted category are higher than that for normal category, the aircraft is NOT eligible for operation in the standard classification after having been operated in the restricted category unless:

Page 86 Par 103

(1) The TCDS specifically states that the aircraft is eligible for operation in the normal category after having been operated at the limitations applicable to the restricted category; or

- (2) If the TCDS does not have such a note or any other reference, the operations outside of the normal category operating limitations including increased gross weights must be FAA-approved.
- **108. DISPLAY OF MARKS (RESTRICTED OR LIMITED).** The FAA should determine if a method has been provided for displaying the word "RESTRICTED" or "LIMITED." The applicant should be advised that it is the owner's or operator's responsibility to display the word "RESTRICTED" or "LIMITED" when the aircraft is in that corresponding configuration (§ 45.23(b)).

109.-111. RESERVED.

Par 107 Page 87 (and 88)

SECTION 4. LIMITED AIRWORTHINESS CERTIFICATION

112. GENERAL. This section provides guidance concerning the requirements of § 21.189, Issuance of Airworthiness Certificate for Limited Category Aircraft.

113. CERTIFICATION PROCEDURES. The FAA representative shall follow the applicable procedures in paragraph 88 of this order.

114. ELIGIBILITY.

- **a.** An applicant requesting issuance of an airworthiness certificate in the "limited" category must show that the aircraft has been previously issued a limited category TC and that the aircraft conforms to that TC (§ 21.189).
- **b.** The FAA inspector shall make the following determinations for aircraft to be certificated in the limited category:
- (1) The FAA inspector shall verify that the aircraft is one of the type and models that have been issued a limited TC and that the aircraft conforms to the requirements set forth in the pertinent limited category aircraft specification.
- (2) In accordance with § 21.189(a)(2), the applicant must flight test the aircraft. Therefore, the FAA inspector should, upon application, issue an experimental certificate for this purpose. When the aircraft is subsequently submitted for limited certification, determine that the findings of the flight test are entered in the aircraft log book and signed by the pilot who made the flights.
- (3) Since surplus military aircraft may have been subjected to deterioration from prolonged storage or inactivity, the FAA inspector shall ensure that the aircraft is subjected to a thorough inspection to determine its state of preservation and repair and that it is in a condition for safe operation. The applicant shall provide all available documentation, such as technical orders and military inspection records, to support the findings of airworthiness. The inspection may require removing rivets and cutting openings to check the condition of fraying surfaces and closed areas. If the condition of the aircraft indicates that such work is necessary, it should be recommended to the applicant that the inspection would be expedited if an airworthiness inspection is performed by an appropriately rated repair station or mechanic, in accordance with the requirements of part 43.
- **115. OPERATING LIMITATIONS.** All limited category civil aircraft must be operated in compliance with the limitations prescribed in § 91.315. However, an FAA inspector may prescribe additional limitations as necessary for safe operation. The additional operating limitations will be enumerated on a separate sheet and issued with Form 8130-7.
- **116. DISPLAY OF MARKS (LIMITED).** The FAA inspector should determine that a method has been provided for displaying the word "LIMITED." The applicant should also be advised that it is the owner or operator's responsibility to display the word "LIMITED" in accordance with § 45.23(b).

Par 112 Page 89

117. AIRCRAFT ISSUED LIMITED CATEGORY TYPE CERTIFICATES.

Aircraft Manufacturer	Model Eligible	Limited Spec. No
Boeing	B-17F and B-17G	AL-1
North American	B-25, B-25C, B-25G, B-25H, B-25N, and B-25J	AL-2
Douglas	A-26B and A-26C	AL-3
	A-24B(Navy SBD-5)	AL-4
Consolidated-Vultee	PB2Y-3, PB2Y-3R, PB2Y-5, PB2Y-5R,	AL-5
	and PB2Y-5Z	
	LB 30	AL-6
Sikorsky	R-4B Helicopter	AL-7
Grumman	TBF-1, TBF-1C, TBM-1, TBM-1C, TBM-3, and TBM-3E	AL-8
Douglas	A-20B, A-20C, A-20G, A-20H, A-20J	AL-9
Lockheed	P-38E, P-38J, F-5E, P-38L, F-5F, F-5G	AL-10
North American	P-51C, P-51D, P-51K, and P-38M	AL-11
Beech	AT-10, AT-10BH, AT-10GL, and AT-10GF	AL-12
Lockheed	B-34, PV-1, PV-2	AL-13
Northrop	P-61, P-61A, P-61B	AL-14
North American	A-36A	AL-15
Curtiss	O-52	AL-16
Grumman	J2F-3, J2F-4, J2F-5, J2F-6	AL-17
Curtiss-Wright	P-40N, P-40L	AL-18
Sikorsky	R-5A Helicopter	AL-19
Martin	PBM-5	AL-20
Bell Aircraft	P-63C, P-63E	AL-21
North American	BC-1	AL-22
Grumman	F8F-1	AL-23
Chance-Vought	OS2U-1, OS2U-2, OS2U-3, OS2N-1	AL-24
Grumman	FM-2	AL-25
Consolidated-Vultee	L-1, L-1A, L-1B, L-1C, L-1D, L-1E, L-1F	AL-26
North American	BT-9, BT-9A, BT-9B, and BT-9C	AL-27
(Culver)	PQ-14A, PQ-14B	
Superior	YQB-14A, YPQ-14B, Navy TD2C1	AL-28
Sikorsky	YR-6A, R-6A, HOS-1 Helicopters	AL-29
Consolidated	C-87A	AL-30
Curtiss Wright	AT-9, AT-9A	AL-31
North American	BT-14	AL-32
Martin	B-26C	AL-33

NOTE: This list is provided as guidance and should not be used as an official list. Questions regarding aircraft eligible for, or presently holding, limited type certificates should be directed to the applicant's local ACO.

Page 90 Par 117

SECTION 5. PRIMARY CATEGORY AIRCRAFT AIRWORTHINESS CERTIFICATIONS

118. GENERAL.

- **a.** Section 21.24(b) permits the applicant to submit a special inspection and preventive maintenance program as part of the aircraft's type design or supplemental type design. The submitted program will be reviewed and accepted or rejected by the Kansas City, Missouri, Aircraft Evaluation Group (MKC-AEG), with engineering input by the ACO where TC application is made. Special inspection and preventive maintenance programs for primary category rotorcraft will be submitted to the Fort Worth, Texas, Aircraft Evaluation Group (FTW-AEG) with engineering input by the ACO where TC application is made. FSDO's will NOT accept or reject the programs.
- **b.** Section 21.184(a) allows an applicant to obtain a special airworthiness certificate for PCA when the provisions of part 21 are met. Primary category aircraft are not eligible for multiple category airworthiness certificates (§ 21.184(e)).
- **c.** Section 21.184(b) allows an applicant to obtain a special airworthiness certificate for an imported PCA with a § 21.29 TC. The CAA of the country of manufacture must certify, and the Administrator must find after inspection, that the aircraft meets the criteria of § 21.24(a)(1) and is in a condition for safe operation.
- **d.** Section 21.184(c) allows an applicant to exchange a standard airworthiness certificate for a special airworthiness certificate primary category. The conversion will be made through the normal STC process. The only benefit for making a conversion is so the pilot-owner may perform preventive maintenance beyond what is already allowed under part 43, appendix A, Major Alterations, Major Repairs, and Preventive Maintenance. Prior to making the conversion, the applicant should consider the following:
- (1) There must be an FAA-approved special inspection and preventive maintenance program for the specific aircraft model being converted. If there is not an approved program or if any additional preventive maintenance items are to be added, the applicant must submit the program or additional items as part of the STC design data to be approved.
- (2) Only a properly qualified pilot-owner may perform preventive maintenance under the special inspection and preventive maintenance program. To be properly qualified, a pilot-owner must successfully complete an FAA-approved course given by an approved aviation maintenance technician school, the holder of the production certificate for the pilot-owner's aircraft, or another entity approved by the Administrator.
- (3) The same aircraft cannot be returned to a standard airworthiness certificate without showing that it meets all the criteria for a standard airworthiness certificate as prescribed by the regulations. Such a showing historically has been difficult when an aircraft has remained in a different classification or category for a lengthy period. To facilitate the return to a standard airworthiness certificate, the aircraft

Par 118 Page 91

records should indicate, among other requirements, that the aircraft has been maintained according to the manufacturer's instructions, and that any modifications to the aircraft either were removed or approved by the FAA.

- **119. CERTIFICATION PROCEDURES.** The FAA should follow the appropriate procedural steps in paragraph 88 of this order, and the following:
 - **a.** Duration of certificates are unlimited as long the requirements of § 21.181(a)(1) are met.
 - **b.** Section 91.325 identifies the operating limitations unique to PCA.
- **c.** Figures 4-3 through 4-8 and 4-10 through 4-11 provide samples of Forms 8130-6 and 8130-7 applicable to PCA.

120. RESERVED.

Page 92 Par 118

SECTION 6. GENERAL EXPERIMENTAL AIRWORTHINESS CERTIFICATIONS

- 121. GENERAL. Any U.S.-registered aircraft that does not have a current standard airworthiness certificate certifying that the aircraft conforms to a TC cannot be legally operated until it has been issued an experimental airworthiness certificate or special flight permit. Included in the operations requiring the issuance of experimental certificates are those involving flight tests of certificated aircraft that have undergone design changes.
 - **a.** An experimental airworthiness certificate may be issued to an aircraft located in or outside of the United States that is intended for continual operation in another country when it meets the following requirements:
 - (1) The CAA of the country in which the aircraft is located or intended to fly has authorized operation of the aircraft.
 - (2) The Flight Standards Service will have appropriate oversight of the aircraft during the continual operation.
 - **b.** If an experimental airworthiness certificate is issued to an aircraft located in or outside of the United States for time-limited operations in another country, the experimental airworthiness certificate must be accompanied by appropriate operating limitations that have been coordinated with the responsible CAA before issuance.
 - c. Experimental Airworthiness Certificates, Multipurpose. An experimental airworthiness certificate may be issued for more than one of the purposes shown in sections 7, 8, and 9 of this order. When more than one purpose is requested, the issuing FAA representative must ensure that adequately controlled conditions exist as specified in the operating limitations. When issuing an airworthiness certificate for the purposes of research and development, showing compliance with regulations, crew training, and market surveys, the certificate should be made effective for only the length of time reasonable to accomplish the applicant's program, not to exceed one year. The issuance of multiple purpose certificates for research and development and showing compliance should be limited to PC/APIS holders. This may be extended to modifiers only when adequately substantiated, e.g., complex programs. Applicants for a multiple purpose certificate must justify the requested purposes to the satisfaction of the FAA.
 - **d. Listing of Manned-free Balloon or Glider on Special Airworthiness Certificates Issued for Experimental Purposes.** An aircraft eligible for the issuance of an experimental airworthiness certificate under § 21.191 and which clearly has the predominant flight characteristics of either a manned-free balloon or glider will be identified as follows: "MANNED-FREE BALLOON" or "GLIDER" will be placed in parenthesis following "experimental" in the "Category/Designation" block of Form 8130-7. This procedure will ensure the appropriate application of 14 CFR part 61, Certification: Pilots, Flight Instructors, and Ground Instructors (part 61), concerning the medical requirements for the operation of such aircraft. Further guidance can be found in AC 21.17-2, Type Certification Fixed-wing Gliders (Sail planes) Including Powered Gliders.
 - **e.** The requirements for issuing experimental certificates are contained in §§ 21.191, 21.193, and 21.195.

Par 121 Page 93

8130.2D CHG 2 12/18/00

* **f.** For the purpose of this chapter, type certification programs include TC, STC, and amendments to either.

g. Section 91.319 prescribes operating limitations that are applicable to all aircraft having experimental certificates. In addition, the Administrator may prescribe other limitations as may be considered necessary under § 91.319(e).

NOTE: Basic operating limitations for all experimental aircraft shall be issued as prescribed in sections 7, 8, and 9 of this order.

- * **h.** In order to operate under Phase II operating limitations, the operator must make a signed log book entry attesting to meeting the requirements of § 91.319(b).
- i. Experimental military aircraft built under a military contract and identified by military aircraft identification marks do not require registration or the issuance of experimental certificates for flight testing or demonstration prior to acceptance by the military. However, aircraft of military design built independently by manufacturers and not having military identification, will be required to obtain FAA registration and an experimental airworthiness certificate since such aircraft would be considered civil aircraft.
- **j.** The FAA shall determine that the aircraft displays nationality and registration marks in accordance with § 45.21 and that the word "EXPERIMENTAL" is displayed in accordance with § 45.23.

122. ELIGIBILITY.

- **a.** For an aircraft to be eligible for an experimental certificate, the aircraft must be registered and the applicant must satisfy one or more of the purposes stated in § 21.191, as further discussed in sections 7, 8, and 9 of this order.
- **b.** An experimental airworthiness certificate may be issued for an aircraft under a Dealer's Aircraft Registration Certificate for required flight tests by the manufacturer, or for purposes incidental to sale by the manufacturer of the aircraft for which the certificate is issued. In the latter case, the FAA should ensure that the requirements of § 21.195 are met.
- **c.** In assuring compliance with § 21.193(d), the following shall be described in the applicant's program letter:
- (1) Purpose of Experiment, § 21.193(d)(1). An applicant must submit a program letter describing the purpose in sufficient detail to outline the aircraft configuration and program objectives and in a manner that will permit the FAA to prescribe adequate limitations and conditions necessary to ensure safe operation. The main objective is to outline the aircraft configuration and program objectives and not to describe everything in minute detail. The use of the same aircraft for overlapping programs is not precluded and the program letter can outline one or more programs. Upon showing compliance with § 91.319(b), the aircraft can be used to support other aircraft in the program or other experimental programs the manufacturer/applicant has underway, e.g., support crew movements, chase plane, carry

Page 94 Par 121

spare engines, etc. This support activity, in addition to the purpose for which the certificate is to be issued, should be included in the program letter or be included in the procedure described in paragraph 146 of this order.

NOTE: A new program letter will be required when significant changes to the aircraft configuration and program objectives are planned.

- (2) Time or Number of Flights, § 21.193(d)(2). The applicant's program letter must include the estimated time or number of flights required to accomplish the program. The FAA will evaluate the request in comparison to the program in order to establish an appropriate time duration for the special airworthiness certificate.
- (3) Areas. The applicant must provide in the program letter sufficient detail to describe the areas over which the proposed flights are to be conducted. It is the responsibility of the FAA to establish boundaries of the flight test area, and, in densely populated areas or congested airways, takeoff, departure, and landing approach corridors that ensure hazards to persons and property are minimized.
- (4) **Describe Aircraft Configuration.** Except for aircraft converted from a TC, the applicant must describe the aircraft's external configuration. The use of three-view sketches and three dimensional photographs are acceptable.
- **(5) Program Letter.** Figure 4-13 shows a sample program letter that an applicant can use or expand upon as needed.
- **123. DEMILITARIZATION OF FORMER MILITARY AIRCRAFT.** Former military aircraft should be demilitarized prior to application for airworthiness certification. It is not possible to define what the final configuration of these aircraft will be following this demilitarization. Therefore, since the demilitarization process will most likely involve a change to the aircraft configuration, FAA representatives should not consider an application for airworthiness certification unless demilitarization has been completed.
- **a.** It is the policy of the DOD that surplus U.S. military property designated as arms, ammunition, implements of war, and other military items will be demilitarized to the extent necessary to preclude the unauthorized use of these military items. The intent behind this DOD policy is to destroy the military advantages inherent in certain types of property, render harmless that property which is dangerous, and to protect the national interest. This DOD policy mandates that tactical, fighter, and bomber aircraft will be demilitarized to the extent that will render the aircraft not airworthy. This DOD policy is not applicable to military trainer, observation, or liaison aircraft. Additionally, DOD does release a limited number of tactical, fighter, and bomber aircraft for operation in R&D programs. Typically, these aircraft may only be demilitarized to the extent that classified equipment has been removed.

Par 122 Page 95

8130.2D CHG 2

NOTE: This does not mean that all other U.S. surplus military aircraft should have been rendered not airworthy. For example, some U.S. military aircraft that were sold to other countries may be available for public sale. These aircraft are subject to the import requirements that are listed in paragraph 123b of this order. Additionally, other aircraft may have been constructed from surplus parts.

b. Former military aircraft imported from any other country require an import permit issued by the Department of Treasury, Bureau of Alcohol, Tobacco, and Firearms (ATF). This is granted by ATF using an ATF Form 6, Application and Permit for Importation of Firearms, Ammunition, and Implements of War. Additionally, these former military aircraft are required to be demilitarized in order to clear U.S. Customs. Compliance with demilitarization is evidenced by a completed ATF Form 6A, Release and Receipt of Imported Firearms, Ammunition, and Implements of War. Proof of demilitarization will be verified if the applicant presents copies of ATF Form 6 and ATF Form 6A that have been completed by the appropriate Department of Treasury officials. If the applicant is unable to produce ATF Form 6 or 6A, the FAA certificating office should contact the ATF Firearms and Explosives Import Branch to determine if copies of these forms are available for the particular aircraft. In cases where ATF Forms 6 or 6A are not required or not available, the FAA certificating office manager will determine the extent of demilitarization necessary prior to airworthiness certification.

NOTE: Should there be any questions regarding ATF Forms 6 and 6A requirements, contact the ATF Firearms and Explosives Import Branch at the Department of the Treasury.

124. AIRCRAFT EQUIPPED WITH EJECTION SEATS OR JETTISONABLE STORES.

Former military turbine-powered aircraft certificated for the purpose(s) of research and development, exhibition, or air racing, may be eligible to operate with functional ejection seats. Only aircraft certificated for the purpose of research and development may be eligible to operate with functional jettisonable external fuel tanks or stores. The following requirements must be met in order to have these systems operational.

- **a.** The applicant must provide objective evidence that the airport manager of the airport where the aircraft is based has been notified regarding the presence of explosive devices in these systems and the planned operation of an experimental aircraft from that airport.
- **b.** Jettisonable external fuel tank(s) or stores systems must be maintained in accordance with manufacturer's procedures and inspected in accordance with the provisions of the FSDO-approved inspection program for the particular aircraft. The FAA will verify that there is a records entry indicating current serviceability of the jettison system(s).
- **c.** Ejection seat systems must be maintained in accordance with manufacturer's procedures and inspected in accordance with the provisions of the FSDO-approved inspection program for the particular aircraft. The FAA will verify that there is a record entry indicating current serviceability of the ejection system, including the status of any dated shelf-life items.
- **d.** The applicant must have provisions for securing the aircraft to prevent inadvertent operation of the jettison and/or ejection systems whenever the aircraft is parked.

Page 96 Par 123

125. FLIGHT TEST AREAS.

a. General. Section 91.319(b) requires that an unproven aircraft be assigned to a flight test area. The assigned test area is prescribed in accordance with § 91.305. The FAA, when requested, should assist applicants in selecting areas that comply with § 91.305. The FAA is required to evaluate each application to determine that the flight test area does not exceed that which is reasonably required to accomplish the program. Actions pertaining to flight test areas should be coordinated with the nearest office of the Air Traffic Service.

- **b.** Assigned Flight Test Areas. Under §§ 91.319(b) and 91.305, all initial flight operations of experimental aircraft must be limited to the assigned flight test area until the aircraft is shown to be controllable throughout its normal range of speeds and all maneuvers to be executed, and has not displayed any hazardous operating characteristics or design features.
- (1) In the case of the first flight of an aircraft from an airport surrounded by a densely populated area, but with at least one acceptable approach/departure corridor, the FAA shall ensure that a flight corridor is selected where the least number of persons and property may be subjected to possible hazards. In addition, upon leaving such an airport, the aircraft should be required to operate from an outlying airport until its controllability and safety are established, after which the aircraft may return to its base and use the established corridor for subsequent operations. The description of the area selected by the applicant and agreed to by the FAA shall be made a part of the operating limitations; or
- (2) In the case of an aircraft located at any airport surrounded by a densely populated area and lacking any acceptable approach/departure corridor, the FAA shall deny the airworthiness certificate and process the denial in accordance with paragraph 88 of this order. The applicant shall be advised to relocate the aircraft by other means to a suitable airport.

NOTE: An acceptable approach/departure corridor may be considered to exist when the corridor provides reasonable opportunity(s) to execute an off-airport emergency landing that will not jeopardize other persons or property.

c. Operation Within an Assigned Flight Test Area. Except for amateur-built aircraft, there are no specific flight time requirements for operation within an assigned flight test area. Each case must be judged on the individual conditions, such as the type and complexity of the aircraft. For example, flight testing in conjunction with an STC modification may require only one hour in an assigned flight test area while the initial operation of a prototype jet aircraft or a military surplus jet aircraft may require 20 or more hours before the requirements of § 91.319(b) can be met. In any event, the FAA inspector should not amend the operating limitations to permit flight outside of the assigned flight test area until the applicant certifies and the FAA finds compliance with § 91.319(b). This finding by the FAA may be a review of the aircraft records containing a statement by the pilot that the aircraft is controllable throughout its normal range of speeds and throughout all the maneuvers to be executed and has no hazardous operating characteristics or design features. Also, the maintenance history while in the test area must be satisfactory. The certificating inspector may witness flights or inspect the aircraft if deemed necessary. The PC/APIS holder may show compliance with § 91.319(b) in accordance with its FAA-approved experimental operating procedure (see paragraph 146 of this order).

Par 125 Page 97

8130.2D CHG 2 12/18/00

d. Aerobatics.

(1) Aerobatic maneuvers may be permitted while the aircraft is in the assigned flight test area if, in the certificating inspector's judgment, the aircraft has the capability of such flight. However, these maneuvers should not be attempted until sufficient flight experience has been gained to establish that the aircraft is satisfactorily controllable.

- (2) Aerobatic maneuvers that have been demonstrated in the assigned flight test area should be documented in the aircraft records. Only those aerobatic maneuvers that have been successfully accomplished should be permitted after leaving the assigned flight test area.
- (3) Those aircraft owners/operators wishing to include new aerobatic maneuvers will need to make a request for a new flight test area and follow the same conditions as noted in paragraph 125d(2) above.

126. OPERATING OUTSIDE FLIGHT TEST AREAS.

- **a.** Aircraft that have satisfied the requirements outlined under paragraph 125c of this order may be operated outside of an assigned flight test area. Except as provided for in section 9, paragraph 146 of this order, operation of the aircraft outside an assigned flight test area will require issuance of a new experimental airworthiness certificate with the new amended operating limitations.
- **b.** Prior to authorizing an aircraft to operate outside of an assigned flight test area, the FAA should ensure the requirements of § 91.9 have been satisfied and are available in the aircraft. The FAA should prescribe those limitations listed in section 7, 8, and 9 of this order (as appropriate), and any others that might be appropriate. Except for amateur-built aircraft, if any major changes are made to an aircraft after it has been certificated for operation outside of a previously assigned flight test area, the cognizant FAA office must be notified. After the FAA offices have been notified and a determination is made that the aircraft needs to return to a flight test area, an amended certificate should be applied for with new limitations as needed. A new Form 8130-7 is required whenever operating limitations are amended, since the date of the old limitations shown on the corresponding certificate would not be in accordance with the date of the new limitations, and alteration of the certificate to change the date is not permitted.
 - NOTE: Operation of all Group I, II, III, and IV aircraft will be restricted to airports that are within airspace classes C, D, E, or G except in the case of a declared emergency or authorized operations under an airshow waiver. Prior to issuing operating limitations for the aircraft, the certificating inspector will coordinate approach and departure corridors with the Flight Standards District Office (Operations Unit) and Air Traffic Control Facility that has the geographic responsibility for the airport on which the aircraft will be based or operations conducted. In addition, the applicant will provide a highlighted aeronautical map or chart depicting the proposed operational area, including a list of the proposed alternate airports. The radius will not exceed the limits authorized for the applicable aircraft group. The map/chart is part of the aircraft operating limitations and must be carried on board the aircraft when operating.

Page 98 Par 125

SECTION 7. EXPERIMENTAL AMATEUR-BUILT AIRWORTHINESS CERTIFICATIONS

127. GENERAL. Under the provisions of § 21.191(g), an amateur-built aircraft is defined as an aircraft in which the major portion has been fabricated and assembled by persons who undertook the construction project solely for their own education or recreation. The applicant should be advised of the availability of AC 20-27, Certification and Operation of Amateur-Built Aircraft.

a. Eligibility.

- (1) Amateur-built aircraft may be eligible for an experimental airworthiness certificate when the applicant presents satisfactory evidence that the aircraft was fabricated and assembled by an individual or group of individuals:
 - (a) The project was undertaken for educational or recreational purposes.
- **(b)** The FAA finds that the aircraft complies with acceptable aeronautical standards and practices.
- (c) Aircraft which are manufactured and assembled as a business for sale to other persons are not considered to be in compliance with § 21.191(g).
- (2) The determination of the major portion factor may be made by evaluating the amount of work accomplished by the individual or group of individuals, against the total amount of work necessary for the complete project, excluding standard procured items. The "major portion" of the aircraft is considered to mean more than 50 percent of the fabrication and assembly operations. The applicant must submit a notarized FAA Form 8130-12, Eligibility Statement, Amateur-Built Aircraft, certifying the major portion was fabricated and assembled for educational or recreational purposes, and that evidence is available to support this statement. The evidence will be provided to the FAA inspector upon request. If a question arises as to the eligibility regarding the major portion requirement of an amateur-built aircraft, Form 8000-38 may be used. See figure 4-14 for a sample Form 8130-12 and figure 4-15 for a sample Form 8000-38.

NOTE: Applicants will jeopardize eligibility for certification under § 21.191(g) if someone else builds the aircraft.

b. Design and Construction.

(1) To meet the intent of § 21.191(g) and to be eligible for an experimental airworthiness certificate, satisfactory evidence must be presented to show that the aircraft was not built from completely prefabricated parts or kits. However, the applicant cannot be expected to have personally fabricated every part that makes up the aircraft any more than this can be expected of a commercial aircraft manufacturer. Items such as engines and engine accessories, propellers, rotor blades, rotor hubs, tires, wheel and brake assemblies, instruments, and standard aircraft hardware such as pulleys, bell cranks, rod ends, bearings, bolts, rivets, etc., may be procured on the open market.

Par 127 Page 99

(2) The use of used or salvaged major assemblies (e.g., wings, fuselage, empennage, etc.) from type certificated aircraft is permitted, as long as they are in a condition for safe operation. These assemblies will be considered by the FAA in determining the "major portion," but no credit for fabrication and assembly will be given to the builder.

- (3) The FAA should be reasonable in its requests to amateur builders, keeping in mind that in most instances only one aircraft is involved. Accordingly, the builder is not required to have detailed design data, quality systems, procedures, etc., as the holder of a type and production certificate is required to have for the production of duplicate aircraft.
- (4) For a major change, the FAA is not required to modify an experimental amateur-built aircraft's special airworthiness certificate and operating limitations unless the modification creates the need for special restrictions.

c. Kit Construction.

- (1) An aircraft built from a kit may be eligible for amateur-built certification, provided the "major portion" of the aircraft, i.e., more than 50 percent, has been fabricated and assembled by the applicant for education and/or recreation and the applicant has evidence to support the major portion requirement. Based on the criteria set forth in paragraphs 127a and b of this order, it is obvious that an aircraft assembled from a kit composed of completely finished pre-fabricated components, parts, and pre-cut/pre-drilled materials is not eligible for the issuance of an experimental airworthiness certificate as an amateur-built aircraft.
- (2) The major portion of a kit should be composed of raw stock, such as lengths of wood, tubing, extrusions, etc., which may have been cut to an approximate length. A certain quantity of prefabricated parts, such as heat treated ribs, bulkheads, or complex parts made from sheet metal, fiberglass, or polystyrene would also be acceptable. The kit must still meet the major portion of the fabrication and assembly requirement, and the applicant must show to the satisfaction of the FAA inspector that completion of the aircraft is not merely an assembly operation.
- (3) Some kits may include assembly jigs, templates, raw stock, or other means to simplify the fabrication and assembly process. If an applicant proposes to use a kit that has such items provided, the FAA inspector should evaluate the kit to determine whether the builder will still fabricate and assemble the major portion of the aircraft and advise the applicant accordingly.
- **d. Kit Evaluation.** The FAA does not certify aircraft kits or approve kit manufacturers. However, the FAA does perform evaluations of kits for the purpose of determining if an aircraft built from the kit will meet the major portion requirement of § 21.191(g). This evaluation must not be construed as meaning the kit is FAA "certified," "certificated," or "approved," and it is not appropriate to represent it as such. See paragraphs 129, 130, and 131 of this order for kit evaluation criteria.

Page 100 Par 127

e. Advising Applicants.

(1) FAA inspection of an amateur-built aircraft will be limited to a general airworthiness inspection when the aircraft is submitted for airworthiness certification. The FAA will not perform any progressive pre-cover inspections during the construction of the aircraft. These in-process inspections should be conducted by knowledgeable persons, e.g., EAA Technical Counselors, certificated mechanics, etc. All advice given to the amateur builder by the FAA inspector should be made a matter of record for future reference. IN NO INSTANCE WILL THE FAA INSPECTOR ACTUALLY PERFORM ANY OF THE FABRICATION OR CONSTRUCTION WORK.

- (2) Many individuals who desire to build their own aircraft have little or no experience with respect to aeronautical practices, workmanship, or design. An excellent source for advice in such matters is the EAA located in Oshkosh, Wisconsin. Information on EAA programs and benefits may be obtained via the EAA Web Site at http://www.eaa.org.
- (3) When the prospective builder contacts the appropriate FAA office to advise the FAA of the construction project, the inspector should provide the prospective builder with the applicable forms and any guidance necessary to ensure a thorough understanding of applicable regulations.
- (4) The prospective builder, when applying for an airworthiness certificate, should submit to the FAA a three-view sketch, drawing, or photograph of the proposed aircraft project.
- (5) The applicant should be advised that to show compliance with § 91.319(b) they must develop a flight test program that addresses the requirements, goals, and objectives of each test flight. The flight test program should be developed in accordance with AC 90-89, Amateur-Built Aircraft Flight Testing Handbook, as revised, or its equivalent in scope and detail. Flight test programs accomplish two purposes. First, it ensures that the aircraft has been adequately tested and determined to be safe to fly within the aircraft's flight envelope. Second, the flight test data is used to develop an accurate and complete Aircraft Flight Manual and to establish emergency procedures.

NOTE: The EAA Flight Advisor program has been established to assist applicants in developing flight test plans.

- **(6)** The FAA district office, when requested, should furnish the builder with the following forms:
 - (a) Aircraft Registration Application, Form 8050-1.
 - **(b)** Application for Airworthiness Certificate, Form 8130-6.
 - (c) Eligibility Statement Amateur-Built Aircraft, FAA Form 8130-12.
 - (d) Affidavit of ownership for Amateur-Built Aircraft, AC Form 8050-88.

Par 127 Page 101

- (7) At the time of airworthiness certification:
 - (a) The aircraft should be complete in every respect.

(b) The applicant must submit all required documentation. If the applicant cannot, or will not, provide a statement of eligibility, the applicant should be advised that the aircraft cannot be certificated as amateur-built until other satisfactory evidence is provided to substantiate that the major portion of the aircraft was built for educational or recreational purposes.

f. Weight and Balance.

- (1) Prior to certification, the amateur builder should accurately weigh the aircraft in accordance with established weight and balance procedures to determine the aircraft's empty, gross, and most forward and aft center of gravity range, including the weight and balance for the initial flight tests in order to help reduce stall, spin, and other control related accidents. Such limits would be determined by the builder through calculations if the aircraft is self-designed, or as specified in the data for aircraft constructed from a kit or built from purchased plans. The completed weight and balance report, including load limits for crew, oil, fuel, and baggage, should be available in the aircraft along with the other applicable placards, listings, and markings required by § 91.9.
- (2) Prior to certificating the aircraft, the FAA should verify that the weight and balance data is accurate for that aircraft; that the aircraft has been weighed correctly; and that the CG and its most forward and aft CG limits are established.

g. Transfer of Airworthiness Certificates.

- (1) An airworthiness certificate is transferred with the aircraft (§ 21.179), e.g., change of ownership, transfer of registration, etc. There is no FAA inspection required as a result of a transfer of an aircraft with its airworthiness certificate unless it is determined that revised operating limitations are necessary. In this case, a new Form 8130-7 must be issued to reflect the new date of the revised operating limitations. Therefore, Form 8130-6 is required to be submitted by the applicant.
- (2) In some cases, amateur-built aircraft are sold with an expired airworthiness certificate or foreign airworthiness certificate. In such cases, an applicant may request and receive a special airworthiness certificate for the purpose of operating amateur-built aircraft, only if the aircraft was previously certificated in this category. In this case, a new Form 8130-7 would be issued along with new operating limitations, but without the eligibility to obtain a repairman certificate for that aircraft. The new certificate should only be issued after the FAA has verified airworthiness by following the appropriate procedures in paragraph 88 of this order.

h. Operation of Canadian-Registered Amateur-Built Aircraft in the United States. Canadian-registered amateur-built aircraft are issued a "Special Certificate of Airworthiness" with operating limitations set by Transport Canada Civil Aviation. Operation in the United States of Canadian-registered amateur-built aircraft certified under the provisions of Canadian Air Regulations is permitted by the issuance of an SFA under § 91.715. This authorization must be obtained before

Page 102 Par 127

operation in the United States is permitted. The authorization may be obtained electronically via the Flight Standards WebSite at http://www.faa.gov/avr/afs/afs800/formtext.htm. Additional guidance on the issuance of SFA's for Canadian-registered amateur-built aircraft may be found in paragraph 231 of this order.

- i. Prototype Aircraft Produced By An Amateur-Built Aircraft Kit Manufacturer. When persons produce prototype aircraft to be used to prove their design for amateur-built purposes, even though the design is intended to be sold as plans and/or kits, such aircraft are considered to be produced as a furtherance of a business.
- (1) These prototype aircraft are not produced by persons "solely for their own education or recreation," and therefore cannot be certificated as amateur-built aircraft (§ 21.191(g)). An application for amateur-built cannot be accepted for such aircraft, but the aircraft could qualify for the purpose of research and development under § 21.191(a). FAA inspectors may issue experimental certificates for the purpose of research and development as long as the applicant has a bona fide program of research and development.
- (2) Following termination of a research and development program, such prototype aircraft may be eligible for an experimental certificate for the purpose(s) of exhibition and/or air racing with appropriate operating limitations issued for such purpose(s).
- (3) Kit manufacturers may also be eligible to make application for market survey (§ 21.191(f)), for the purpose of conducting market surveys, sales demonstrations, and customer crew training as provided in § 21.195(a). The airworthiness certificate may be issued ONLY after the applicant has satisfied the requirements of § 21.195(d). The following operating limitations will be added when issuing airworthiness certificates under § 21.191(f):
 - NOTE: "Customer crew training" means pilot FAMILIARIZATION with that aircraft rather than training to become a pilot. The manufacturer will only be familiarizing an already qualified pilot with the novel characteristics of the aircraft, not training the customer to obtain a pilot's certificate.
- (a) Condition inspections shall be performed in accordance with part 43, appendix D, at least every 90 days or 100 flight hours, whichever comes first. The inspections must be performed by an FAA-certificated mechanic with appropriate ratings as defined in § 43.3.
- **(b)** Familiarization flights will be conducted over sparsely populated areas only. If aerobatics are involved, the applicant must inform the local FAA office and additional limitations may be imposed as necessary.

NOTE: This should not be construed to enlarge the scope of § 21.191(f) except as specifically provided. Amateur builders are not "manufacturers" for the purposes of §§ 21.191(f) and 21.195(a), and cannot obtain Form 8130-7 under § 21.191(f). Additionally, a person who distributes kits or plans manufactured by another company would not qualify for Form 8130-7 under §§ 21.191(f) and 21.195(a).

Par 127 Page 103

128. CERTIFICATION PROCEDURES. The procedures in this chapter provide guidance material associated with airworthiness certification and the issuance of Form 8130-7.

a. General. The FAA airworthiness certification process will consist of a general airworthiness inspection of the aircraft. This will be accomplished after the aircraft is completed and prior to the issuance of an airworthiness certificate. During this inspection, the FAA should not request extensive disassembly of the aircraft if the builder can provide documented evidence of in-process inspections. These in-process inspections should be conducted by knowledgeable persons, e.g., EAA Technical Counselors, certificated mechanics, etc. The records should indicate what was inspected, by whom, and the date of the inspection. In addition, builders should document construction phases using photographs taken at appropriate times prior to covering or finishing. The photographs should clearly show the methods of construction and quality of workmanship. Such photographic records should be included with the builder's log or other construction records. The only time extensive disassembly should be requested is when there is a question of safety that would endanger the general public. When an aircraft fabricated from a kit is identified as meeting the major portion rule by the FAA, the FAA will review the applicant's documentation supplied with the kit to verify it agrees with the identification and description given in the FAA listing of eligible amateur-built kits. Deviations from the FAA identified kit configuration will require the inspector to make an independent determination that the applicant fabricated and assembled the major portion of the aircraft.

b. Record Inspection and document review. The FAA representative shall:

- (1) Obtain from the applicant a properly executed Form 8130-6 and any other documents required for the certification.
- (2) Obtain from the applicant a program letter identifying the aircraft, the purpose of the certificate, the area over which the operations are to be conducted, the duration of the program, etc.
- (3) Review the documentation provided by the applicant to determine that the registration requirements of part 47 have been met, and assure the aircraft is marked in accordance with part 45.
- (4) Check with AFS-750 to determine if a denial letter exists for the particular aircraft. This may assist the inspector in determining aircraft eligibility.
- (5) Review the aircraft records to determine that any required maintenance, inspections, etc., have been accomplished. Records should be complete.
- **(6)** Review the applicant's weight and balance data for accuracy and currency for the aircraft submitted.
- (7) Ensure there is a signed and dated statement from the owner in the aircraft records that the aircraft has had an inspection performed in accordance with part 43 appendix D, or other approved programs and found to be in a condition for safe operation (appendix 1 of AC 90-89, Amateur-Built Aircraft and Ultralight Flight Testing Handbook, as revised may be used). This statement will support the owner's inspection and airworthy statement on Block III of the Application for Airworthiness Certificate and help reduce errors made during construction of the aircraft.

Page 104 Par 128

NOTE: There is NO requirement for Airframe and Powerplant mechanics to sign off amateur-built airworthiness inspections. The aircraft builder's signature on Form 8130-6, Block III attests to the airworthiness of the amateur-built aircraft.

- **c. Aircraft Inspection.** The FAA shall arrange with the applicant to make the aircraft available for inspection to determine that:
 - (1) The identification plate meets the requirements of § 45.11, as applicable.
- (2) The information on the identification plate is correct, matches the information on Form 8130-6, and is in accordance with § 45.13, as applicable.
- (3) The aircraft nationality and registration marks are in accordance with part 45, subpart C, Nationality and Registration Marks.
- (4) The flight control system, engine(s), propeller(s), pitot static system, and associated instruments operate properly.
- (5) The cockpit instruments are marked appropriately and needed placards are installed and placed for easy reference.
 - **(6)** System controls (e.g., fuel selector(s) and electrical switches/breakers) are appropriately placed, clearly marked, and provide for easy access and operation.
 - (7) An emergency locator transmitter (ELT) is installed, if required (§ 91.207).
 - **d. Certificate Issuance.** Upon satisfactory completion of the airworthiness inspection and documentation review, the FAA will issue the special airworthiness certificate along with the operating limitations for that aircraft. The operating limitations will be attached to Form 8130-7. The FAA should review the operating limitations with the applicant to ensure a clear understanding of the limitations. The FAA inspector may elect to issue amateur-built airworthiness certificates on a one-time basis for determining compliance with § 91.319(b) and continued operation under § 21.191(g). In those instances where the airworthiness certificate is to be issued for an unlimited duration, the operating limitations may be prescribed in two phases in the same document as follows:
 - (1) For the phase I limitations, the FAA will prescribe all operating limitations appropriate for the applicant to demonstrate compliance with § 91.319(b) in the assigned flight test area. This would further include a limitation requiring the owner/operator to endorse the aircraft log book with a statement certifying that the prescribed flight hours have been completed and the aircraft has been shown to comply with § 91.319(b). The owner/operator may then operate in accordance with phase II.
 - (2) For the phase II limitations, the FAA will prescribe operating limitations for the operation of an amateur-built aircraft for an unlimited duration, as appropriate.
 - (3) Under § 91.319(e), the FAA may prescribe any additional limitations in phase I or II deemed necessary in the interest of safety.

Par 128 Page 105

- (4) If the aircraft meets the requirements for the certification requested, the FAA shall:
 - (a) Make an aircraft log book entry.
 - **(b)** Issue Form 8130-7.
- (c) Complete Sections V and VIII of Form 8130-6, in accordance with the instructions contained in chapter 8 of this order.
- (d) Examine, review, and route the certification file in accordance with the instructions contained in chapter 8 of this order.
- (5) If the aircraft does not meet the requirements for the certification requested and the airworthiness certificate is denied, the FAA shall:
- (a) Write a letter to the applicant stating the reason(s) for denying the airworthiness certificate.
- **(b)** Attach a copy of the denial letter to Form 8130-6 and forward to AFS-750 to be made part of the aircraft record.

129. EVALUATION OF AMATEUR-BUILT AIRCRAFT/KITS.

- **a.** The purpose of Form 8000-38 is to record the amount of fabrication and assembly accomplished by the kit manufacturer, and the fabrication and assembly necessary for the amateur builder to complete the aircraft.
- **b.** FAA Form 8000-38, Fabrication/Assembly Operation Checklist, figure 4-15, may be used when:
- (1) Determining whether an aircraft built from a kit would meet the major portion fabrication and assembly requirement of § 21.191(g).
- (2) Settling any question with respect to the major portion requirement that may arise in the certification of an amateur-built aircraft under the provisions of § 21.191(g).
 - NOTE: The use of this checklist is not necessary for an aircraft built from a kit previously found eligible for amateur-built certification or where the builder's records, data, and notarized statement provide ample proof that the builder fabricated and assembled the major portion of the aircraft.
- (3) The aircraft was built from prefabricated major components that are readily available from aircraft parts suppliers.
- (4) The aircraft was built using salvaged or used sections from type certificated standard category aircraft.

Page 106 Par 128

- (5) The aircraft was built from a kit that has not been found eligible by the FAA.
- (6) The aircraft was built from a kit that had been changed by the kit manufacturer after the date of eligibility had been established.
- (7) Providing guidance to a kit manufacturer to determine if a proposed kit-built aircraft meets the major portion requirement of § 21.191(g). By use of this checklist it may be determined at an early stage if a proposed kit would be eligible for amateur-built certification. If not, the kit manufacturer may be able to adjust the kit content to meet the major portion requirement.
- **c.** The totals derived from the KIT MANUFACTURER and AMATEUR columns on the Form 8000-38 indicate the relative portions of the aircraft fabricated and assembled by the kit manufacturer and the amateur builder. To meet the requirements of § 21.191(g), the total in the AMATEUR column MUST be greater than the total in the KIT MANUFACTURER column.
- **d.** It is not necessary that a major portion of the individual parts be fabricated by the amateur builder. If there is some work (e.g., trimming, measuring, cutting, drilling, gluing, lay-up, etc.) required to prepare the individual part for installation/assembly into the aircraft and if this work is performed on a representative number of parts listed under each applicable section of the aircraft, then the kit may be considered eligible provided the major portion of the aircraft has been fabricated and assembled by the amateur builder.

130. KIT EVALUATIONS AT MANUFACTURERS' FACILITIES.

- **a.** The FAA does not certify aircraft kits or approve kit manufacturers. However, the FAA does perform evaluations of kits for the purpose of determining if an aircraft built from the kit will meet the major portion requirement of § 21.191(g). This evaluation should not be construed as meaning the kit or its manufacturer is FAA "certified," "certificated," or "approved," and it is not appropriate to represent it as such.
- **b.** When eligibility of a kit for amateur-built airworthiness certification appears to be questionable, the manufacturer may request evaluation by submitting a letter to the MIO responsible for the geographical area in which the kit manufacturer is located.
- **c.** The responsible MIO will forward the request for evaluation to the appropriate MIDO. The MIDO will conduct the evaluation at the kit manufacturer's facility using Form 8000-38. The kit should be evaluated in the exact configuration as supplied to amateur builders. The use of Form 8000-38 is as follows:
- (1) Upon completion of the evaluation, if the total number of check marks in the AMATEUR column is less than the total in the KIT MANUFACTURER column, the kit manufacturer will be advised that the kit does not meet the major portion requirement of § 21.191(g); or
- (2) If the total number of check marks in the AMATEUR column is greater than the total in the KIT MANUFACTURER column, the kit manufacturer will be advised that the kit meets the major portion requirement of § 21.191(g).

Par 129 Page 107

d. Upon receipt of the completed Form 8000-38 from the MIDO, the MIO will formally notify the kit manufacturer by certified mail of the results. When a kit has been found eligible, the notification should include at least the information in the sample letter illustrated in figure 4-16. When a kit has been found not eligible, the notification should include at least the information in the sample letter illustrated in figure 4-17.

- **e.** The MIDO that performs the kit evaluation will establish a permanent file that should contain the following:
 - (1) A copy of the eligibility or non-eligibility letter that was sent to the kit manufacturer.
 - (2) A copy of Form 8000-38 completed for the kit.
- (3) A copy of the manufacturer's document (parts list, assembly manual, etc.), exactly as sold with the kit. Manufacturers should identify each page of the document by date and/or revision level. This information will help to establish configuration of the kit as evaluated.
- **f.** For kits found eligible, the MIO will send an evaluation report to the Engineering and Manufacturing Branch, AFS-610, P.O. Box 25082, Oklahoma City, Oklahoma 73125. The evaluation report will contain copies of the documents listed in paragraphs 130e(1) and (2) of this order.
- **g.** Upon receipt of the evaluation report, AFS-610 will notify the appropriate FAA field offices by electronic mail of the results of the evaluation and add the kit to the listing of eligible amateur-built aircraft kits. This listing is published by AFS-610, updated semi-annually, and distributed to appropriate FAA field offices.
 - NOTE: The placing of a kit on this list is not a prerequisite for amateur-built airworthiness certification. The purpose of the listing is to assist the FAA by eliminating the need for duplication of evaluations for the major portion determination.
- **131. CHANGES TO ELIGIBLE KITS.** Once a kit has been found eligible for amateur-built status, the manufacturer should coordinate with the FAA any change made to the kit that affects the fabrication and assembly operations.
- **a.** The kit manufacturer should contact the responsible geographic MIO and describe the changes using parts lists, photographs, drawings, etc.
- **b.** The FAA will determine the extent of re-evaluation needed. Major changes which decrease the amount of fabrication and assembly required by the builder(s) may affect kit eligibility. Changes which consist of substituting standard hardware items, e.g., bolts, nuts, rivets, fasteners, etc., will not normally affect eligibility.
- **c.** Derivative models developed from kits previously found eligible may have their eligibility determined based on inspection and evaluation of the original kit, and evaluation of detailed

Page 108 Par 130

documentation of the changes submitted by the kit manufacturer. Inspection of the actual derivative kit is an option of the original evaluating FAA inspection office.

d. Evaluation reports of major kit changes and reports for derivative models will be processed the same as original evaluations. Kits found not eligible after re-evaluation will be removed from the listing of eligible amateur-built aircraft kits.

132. INSTRUCTIONS FOR COMPLETING FORM 8000-38.

- **a.** Enter the kit manufacturer's company name and address.
- **b.** Enter model of kit by name and/or number.
- **c.** List the latest date or revision date of the kit parts list, assembly manual, etc. (document name).
- **d.** Enter type of aircraft (e.g., land, sea, fixed-wing, rotorcraft, etc.).
- **e.** Review each operation for its applicability to the kit under evaluation.
- **f.** Check the respective blocks under "ACCOMPLISHED BY" kit manufacturer and/or amateur builder.
 - **g.** Enter any operations not on the list in blank spaces.
 - **h.** If the operation is not applicable to the kit construction, enter "N/A" in the respective block.
- **i.** Operations that are accomplished by other manufacturers or suppliers are to be checked in the "KIT MANUFACTURER" block.
- **j.** The use of used or salvaged assemblies from standard category aircraft will be checked in the "KIT MANUFACTURER" block.
- **k.** Special tools and fixtures (e.g., jigs, templates, etc.) fabricated by the builder will be given credit. No credit will be given for fabrication of hand tools.
- **l.** When the evaluation is complete, the total number of check marks is to be entered in the respective blocks on page 5 of the checklist.
 - **m.** Sign and date the checklist.

133. FLIGHT TEST AREAS.

a. General. Section 91.319(b) requires that an unproven aircraft be assigned to a flight test area. The assigned test area is prescribed in accordance with § 91.305. The FAA, when requested, should

Par 131 Page 109

8130.2D CHG 2 12/18/00

assist applicants in selecting areas that comply with § 91.305. The FAA is required to evaluate each application to determine that the flight test area does not exceed that which is reasonably required to accomplish the program. Actions pertaining to flight test areas should be coordinated with the nearest office of the Air Traffic Service.

- **b.** Assigned Flight Test Area. Under §§ 91.319(b) and 91.305, all initial flight operations of experimental aircraft must be limited to the assigned flight test area until the aircraft is shown to be controllable throughout its normal range of speeds and all maneuvers to be executed, and has not displayed any hazardous operating characteristics or design features.
- (1) In the case of the first flight of an aircraft from an airport surrounded by a densely populated area, but with at least one acceptable approach/departure route of flight, the FAA shall ensure that a route of flight is selected where the least number of persons and property may be subjected to possible hazards. In addition, upon leaving such an airport, the aircraft should be required to operate from an outlying airport until its controllability and safety are established, after which the aircraft may return to its base and use the established corridor for subsequent operations. The description of the area selected by the applicant and agreed to by the FAA shall be made a part of the operating limitations; or
- (2) In the case of an aircraft located at any airport surrounded by a densely populated area and lacking any acceptable approach/departure route of flight, the FAA shall deny the airworthiness certificate and process the denial in accordance with paragraph 88 of this order. The applicant shall be advised to relocate the aircraft by other means to a suitable airport.

NOTE: An acceptable approach/departure route of flight may be considered to exist when the route of flight provides reasonable opportunity(s) to execute an off-airport emergency landing that will not jeopardize other persons or property.

- **c.** Assigned Flight Test Area. The procedures outlined under section 6, paragraph 125 of this order are applicable to amateur-built aircraft. Although the period of assignment is not established by regulation, the following times are suggested as guidelines when issuing original airworthiness certificates for amateur-built aircraft.
- (1) Amateur-built aircraft issued original airworthiness certificates should be limited to operation within an assigned flight test area for a minimum of 25 hours when a type certificated engine/propeller combination is installed. A minimum of 40 hours is required when a non-type certificated engine, propeller, or engine/propeller combination is installed.
- (2) Amateur-built gliders, balloons, dirigibles, and ultralight vehicles found eligible to meet the requirements of § 21.191(g), for which original airworthiness certification is sought, should be limited to operation within an assigned flight test area for at least 10 hours of operation, including at least five takeoffs and landings.

*

(3) The time frame an amateur-built aircraft is assigned to a flight test area following any major change will be for a minimum of 5 hours.

Page 110 Par 133

d. Operation Outside Flight Test Area. The procedures outlined under section 6, paragraph 126 of this order are applicable for amateur-built aircraft. During operation outside the flight test area, the following placard shall be displayed in the aircraft in full view of all occupants: "NOTE:

PASSENGER WARNING - THIS AIRCRAFT IS AMATEUR-BUILT AND DOES NOT COMPLY WITH FEDERAL SAFETY REGULATIONS FOR STANDARD AIRCRAFT."

NOTE: This placard is not necessary for single place aircraft.

134. ISSUANCE OF EXPERIMENTAL AMATEUR-BUILT OPERATING LIMITATIONS.

- **a.** OPERATING LIMITATIONS SHALL BE DESIGNED TO FIT THE SPECIFIC SITUATION ENCOUNTERED. THE FAA INSPECTOR MAY IMPOSE ANY ADDITIONAL LIMITATIONS DEEMED NECESSARY IN THE INTEREST OF SAFETY. The FAA inspector and/or designee shall review each operating limitation imposed with the applicant to ensure that the operating limitations are understood by the applicant.
 - **b.** The following operating limitations shall be prescribed to experimental amateur-built aircraft:
- (1) No person may operate this aircraft for other than the purpose of meeting the requirements of § 91.319(b) during phase I flight testing, and for recreation and education after meeting these requirements as stated in the program letter (required by § 21.193) for this aircraft. In addition, this aircraft shall be operated in accordance with applicable air traffic and general operating rules of part 91 and all additional limitations herein prescribed under the provisions of § 91.319(e). These operating limitations are a part of the FAA Form 8130-7, special airworthiness certificate, and are to be carried in the aircraft at all times for availability to the pilot in command of the aircraft.
- (2) During phase I flight testing to meet the requirements of § 91.319(b) all flights shall be conducted within the geographical area described as follows: The area shall be described by radius, or coordinates and/or landmarks. The designated area must be over open water or sparsely populated areas having light air traffic. The size of the area shall be that required to safely conduct the type of anticipated maneuvers and tests, as appropriate.

NOTE: In the case of an airport surrounded by a densely populated area, refer to section 6, paragraph 125b(1) of this order.

(3) This aircraft shall be operated for at least (____) hours in the assigned geographic area.

NOTE: The FAA requires a minimum of 25 hours of flight testing for an aircraft with a type certificated engine and propeller combination installed or a minimum of 40 hours when a non-type certificated engine, propeller, or engine/propeller combination is installed. Inspectors may assign longer test hours when it is necessary to determine compliance with § 91.319(b).

Par 133 Page 111

8130.2D CHG 2 12/18/00

- (5) Except for takeoffs and landings, this aircraft may not be operated over densely populated areas or in congested airways.
 - NOTE: This limitation is applicable for phase 1 and 2 and should be issued in accordance with paragraphs 125b(1) and (2) of this order.
- (6) This aircraft is prohibited from operating in congested airways or over densely populated areas unless directed by Air Traffic Control, or unless sufficient altitude is maintained to effect a safe emergency landing in the event of a power unit failure, without hazard to persons or property on the surface.
 - NOTE: This limitation is applicable to the aircraft after it has satisfactorily completed all requirements for phase I flight testing, has the appropriate endorsement in the aircraft logbook, and is operating in phase II.
 - (7) This aircraft is to be operated under Visual Flight Rules (VFR), day only.
- (8) After completion of phase I flight testing, unless appropriately equipped for night and/or instrument flight in accordance with § 91.205, this aircraft is to be operated under VFR, day only.
- (9) Aircraft instruments and equipment installed and used under § 91.205 must be inspected and maintained in accordance with the requirements of part 91. Any maintenance or inspection of this equipment must be recorded in the aircraft maintenance records.
- (10) During the flight-testing phase, no person may be carried in this aircraft during flight unless that person is essential to the purpose of the flight.
- (11) No person may operate this aircraft for carrying persons or property for compensation or hire.
- (12) The pilot in command of this aircraft shall advise each person carried of the experimental nature of this aircraft, and explain that it does not meet the certification requirements of a standard certificated aircraft.
 - (13) This aircraft shall contain the placards, markings, etc. as required by § 91.9.

Page 112 Par 134

(14) This aircraft must display the word EXPERIMENTAL in accordance with § 45.23(b).

(15) This aircraft is prohibited from aerobatic flight; i.e., an intentional maneuver involving an abrupt change in the aircraft's attitude, an abnormal attitude, or abnormal acceleration not necessary for normal flight.

NOTE: If the builder states the aircraft is capable of aerobatic flight, limitation 16 will be used in lieu of limitation 15.

(16) This aircraft may conduct aerobatic flight in accordance with the provisions of § 91.303.
Aerobatics shall not be attempted until sufficient flight experience has been gained to establish that the aircraft is
satisfactorily controllable and in compliance with § 91.319(b). The aircraft may only conduct those aerobatic
flight maneuvers that have been satisfactorily accomplished during flight testing and recorded in the aircraft
maintenance records by use of the following or a similarly worded statement: "I certify that the following
aerobatic maneuvers have been test flown and the aircraft is controllable throughout the maneuver's
normal range of speeds and is safe for operation. The flight tested aerobatics maneuvers are:

NOTE: Aerobatic flights may be permitted in the assigned test area. The applicant should be advised that aerobatics or violent maneuvers should not be attempted until sufficient flight experience has been gained to establish that the aircraft is satisfactorily controllable. These operating limitations may be modified to include only those aerobatics/maneuvers that have been satisfactorily accomplished and recorded in the aircraft records during the flight test period. These aerobatic maneuvers should be permitted upon leaving that assigned test area. Appropriate limitations identifying the aerobatics/maneuvers and conditions under which they may be performed should be prescribed. The certificating inspector may witness aerobatic maneuvers if deemed necessary.

(17) The pilot in command of this aircraft shall hold an appropriate category/class rating. If required, the pilot in command must also hold a type rating per 14 CFR, part 61, or a "Letter of Authorization" issued by an FAA Flight Standards Operations Inspector.

NOTE: This limitation is applicable to any turbojet/turbofan powered aircraft or an aircraft with a maximum takeoff weight exceeding 12,500 pounds, or any other aircraft when deemed necessary. Flight Standards inspectors should refer to Order 8700.1 for further guidance.

(18) The pilot in command of this aircraft shall hold a category/class rating, or an authorized instructor's logbook endorsement. The pilot in command must meet the requirements of § 61.31(e), (f), (g), (h), (i), and (j) as appropriate.

NOTE: This operating limitation applies to most amateur-built aircraft as a standard operating limitation (reference 14 CFR § 61.31(k)).

Par 134 Page 113

- (19) After incorporating a major change as described in § 21.93, the aircraft owner is required to re-establish compliance with § 91.319(b). All operations will be conducted VFR, day only, in a sparsely populated area. The aircraft must remain in flight test for a minimum of 5 hours. Persons non-essential to the flight shall not be carried. The aircraft owner shall make a detailed log book entry describing the change prior to the test flight. Following satisfactory completion of the required number of flight hours in the flight test area, the pilot shall certify in the records that the aircraft has been shown to comply with § 91.319(b). Compliance with § 91.319(b) shall be recorded in the aircraft records with the following or a similarly worded statement: "I certify that the prescribed flight test hours have been completed and the aircraft is controllable throughout its normal range of speeds and throughout all maneuvers to be executed, has no hazardous operating characteristics or design features, and is safe for operation. The following aircraft operating data has been demonstrated during the flight testing: speeds Vso_______, Vx______, and Vy______, and the weight______, and CG location______ at which they were obtained."
- (20) This aircraft shall not be used for glider towing, banner towing, or intentional parachute jumping.
- (21) This aircraft does not meet the requirements of the applicable, comprehensive, and detailed airworthiness code as provided by Annex 8 of the International Civil Aviation Organization (ICAO). The owner/operator of this aircraft must obtain written permission from another country's Civil Aviation Authority (CAA) prior to operating this aircraft in or over that country. That written permission must be carried aboard the aircraft together with the U.S. airworthiness certificate and, upon request, be made available to an FAA inspector or the CAA in the country of operation.
- (22) No person shall operate this aircraft unless within the preceding 12 calendar months it has had a condition inspection performed in accordance with the scope and detail of appendix D to part 43, or other FAA-approved programs, and found to be in a condition for safe operation. This inspection will be recorded in the aircraft maintenance records.
- (23) Condition inspections shall be recorded in the aircraft maintenance records showing the following or a similarly worded statement: "I certify that this aircraft has been inspected on (insert date) in accordance with the scope and detail of appendix D to part 43 and found to be in a condition for safe operation." The entry will include the aircraft total time in service, and the name, signature, certificate number, and type of certificate held by the person performing the inspection.

NOTE: Limitations 24 and 25 will be issued in lieu of limitations 22 and 23 for turbine powered amateur-built aircraft.

- (24) This aircraft shall not be operated unless it is inspected and maintained per an inspection program selected, established, identified, and used as set forth in § 91.409(e), (f), (g), and (h). This inspection shall be recorded in the aircraft maintenance records.
- (25) Inspections shall be recorded in the aircraft maintenance records showing the following or a similarly worded statement: "I certify that this aircraft has been inspected on (insert date) in

Page 114 Par 134

accordance with the scope and detail of the (identify program title) FSDO approved program (insert date) and found to be in a condition for safe operation." The entry will include the aircraft total time in service (cycles if appropriate), and the name, signature, certificate number, and type of certificate held by the person performing the inspection.

- (26) An experimental aircraft builder certificated as a Repairman for this aircraft under § 65.104, or an appropriately rated FAA certificated mechanic, may perform the condition inspection required by these operating limitations.
- (27) Application must be made to the geographically responsible FSDO or MIDO for any revision to these operating limitations
- (28) The pilot in command of this aircraft shall notify air traffic control of the experimental nature of this aircraft when operating into or out of airports with an operational control tower. When filing IFR, the experimental nature of this aircraft shall be listed in the remarks section of the flight plan.

135. RESERVED.

Par 134 Page 115 (and 116)

SECTION 8. CERTIFICATION AND OPERATION OF AIRCRAFT UNDER THE EXPERIMENTAL PURPOSE(S) OF EXHIBITION AND AIR RACING

- **136. GENERAL.** Under the provisions of § 21.191(d) exhibition aircraft are defined as aircraft that exhibit the aircraft's flight capabilities, performance, or unusual characteristics at airshows, motion picture, television, and similar productions, and the maintenance of exhibition flight proficiency, including (for persons exhibiting aircraft) flying to and from such airshows and productions. Under the provisions of § 21.191(e) air racing aircraft are defined as aircraft that participate in air races, including (for such participants) practicing for such air races and flying to and from racing events.
- **a. Exhibition.** Operating an aircraft to demonstrate its flight characteristics or capabilities in connection with sales promotions for the aircraft is not considered to be an eligible operational purpose under exhibition. A certificate for experimental exhibition shall only be issued when an aircraft is to be used for valid exhibition purposes. Included in those purposes are organized airshows, organized air races, organized fly-in activities, organized exhibitions, youth education events, shopping mall/school/similar static displays, organized acrobatic competition, sail plane fly-ins or competitive races or meets, and movie or television productions. The duration of an airworthiness certificate for exhibition will be unlimited.
- **b.** Air Racing. Operating an aircraft to demonstrate its flight characteristics or capabilities in connection with sales promotions for the aircraft is not considered to be an eligible operational purpose under the air racing category. A certificate for experimental air racing should only be issued when an aircraft is to be used for valid air racing purposes. The duration of an airworthiness certificate for air racing will be unlimited.
- **c. Base of Operation.** When an aircraft base of operation is changed or there is a transfer of ownership the owner/operator must notify the local FSDO having jurisdiction over the area in which the aircraft will be based. The owner/operator will provide the local FSDO with a copy of the inspection program identifying the person responsible for scheduling and performing the inspections as well as the requested proficiency areas.
- **d. Experimental Airworthiness Certification Moratorium.** On July 9, 1993, a moratorium was established because of a dramatic increase in applications for special airworthiness certificates and SFA's for non-U.S.-manufactured aircraft that did not hold type certificates issued under § 21.29. The moratorium was lifted on August 18, 1993, with interim guidance provided to certificate these aircraft. Although the moratorium was established for non-U.S.-manufactured aircraft, this policy will be used when issuing a special airworthiness certificate for the experimental purpose(s) of exhibition or air racing, regardless of the country of manufacture.
- **e.** Effectivity. Aircraft that received original airworthiness certification prior to July 9, 1993, ARE NOT affected by this order unless the ORIGINAL AIRWORTHINESS CERTIFICATION PURPOSE CHANGES, e.g., from Research and Development to Exhibition. Those aircraft, except for purpose changes, will not be affected until such time as the FAA works with the public to determine the best strategy to certificate all experimental exhibition and/or air racing aircraft in accordance with the

Par 136 Page 117

new policy. The policy established in this order will not be used in these cases unless specifically requested by the applicant.

NOTE: Proficiency area limitations issued prior to July 9, 1993, will remain in effect despite the issuance of a new airworthiness certificate.

137. FORMER MILITARY AIRCRAFT.

a. Many of the aircraft that are presented for airworthiness certification for the purpose(s) of exhibition or air racing are former military aircraft, both U.S. and non-U.S. The FAA acknowledges the significant role military aircraft have played in our aviation heritage and the importance of preserving their legacy for future generations. The exhibition of former military aircraft at aviation events for demonstration and display provides the public a rare view into our aviation past. Therefore, it is the policy of the FAA to permit the operation of surplus military aircraft for civilian use, consistent with the need to safeguard the general public.

NOTE: It should not be interpreted that all military aircraft require experimental airworthiness certificates. Some models have valid type certificates and could be eligible for a standard airworthiness certificate.

- **b.** Surplus military aircraft have historically operated in the United States for research and development, air racing, and exhibition purposes in the experimental category. It is the policy of the FAA that eligible aircraft will be certificated in the experimental category when operated for the special purposes of Exhibition and/or Air Racing.
- **c.** To ensure the safe operation of these aircraft and minimize adverse environmental impact, the FAA has established appropriate and reasonable operating limitations. Operating limitations developed jointly by the Aircraft Certification Service and Flight Standards Service are contained in paragraphs 142 and 147 of this order.
- **d.** The ability of civilian operators to maintain and operate these aircraft depends upon their background and experience, training and facilities, availability of technical manuals and design information, and the complexity of the aircraft involved. To this end, and to the maximum extent feasible, it is the policy of the FAA to recognize the most complete sources of maintenance and training and to encourage owners, operators, and flight crew members to utilize these sources and successfully complete required training from recognized training organizations. Aircraft inspection guidelines and qualification standards for flight crew members have been developed by the Flight Standards Service and are contained in FAA Order 8300.10, Airworthiness Inspector's Handbook and Order 8700.1, General Aviation Inspector's Handbook.
- **e.** Applicants for certification of former military turbine-powered aircraft (TPA) must be advised that these aircraft were designed and manufactured without the acoustical treatment provided for current commercial and business TPA. They must also be advised of industry-developed procedures and guidelines designed to minimize the impact such aircraft impose at airports and the surrounding communities. Aircraft operators must accept the responsibility for operating their aircraft in such a

Page 118 Par 136

manner as to reduce the noise impact to the lowest practicable level. The EAA has developed operating procedures and a recommended program for reducing the noise impact of TPA. EAA's recommended procedures are contained in its Jet Operations Manual. The FAA certificating inspector must advise persons considering operating such aircraft to become familiar with and use the procedures outlined in the EAA's Jet Operations Manual or other procedures acceptable to the Administrator.

- **f.** In recent years, the number and types of TPA have greatly expanded, mostly as a result of the import of aircraft of non-U.S. manufacture. Examples of these aircraft include models such as the Northrop F-5, which is of U.S. manufacture, and the Mikoyan MiG-15 of non-U.S. manufacture. It is of critical importance to the FAA, the civilian owners and operators of such aircraft, and the general public that these aircraft are operated safely in the National Airspace System.
- **138. BROKERING.** Section 21.191(d) was not intended to allow for the brokering or marketing of experimental aircraft. This includes individuals who manufacture, import, or assemble aircraft, and then apply for and receive experimental exhibition airworthiness certificates so they can sell the aircraft to buyers. Section 21.191(d) ONLY provides for the exhibition of an aircraft's flight capabilities, performance, or unusual characteristics at airshows, motion picture, television, and similar productions. Certificating offices should ensure that all applications for exhibition airworthiness certificates are for the purposes specified under § 21.191(d), and are from the registered owners who will exhibit the aircraft for those purposes. Applicants must also provide the applicable information specified in § 21.193.
- **139. GROUPS OF AIRCRAFT.** Aircraft that have been presented for experimental airworthiness certification for exhibition or air racing range from unpowered gliders to high performance jet aircraft. In order to properly certificate this wide range of aircraft, and in response to the many public comments received, the FAA has divided these aircraft into four groups. This was done in order to establish standardized operating limitations, proficiency areas, and inspection requirements appropriate to each aircraft. Minimum operating limitations for each group are provided in paragraph 142 of this order. The certificating inspector will make a determination of which group the aircraft will operate in based on the following:

a. Group I, Performance Competition Aircraft.

- (1) **Description of Aircraft.** Specialty aircraft are of limited availability and possess design characteristics that make the aircraft suitable for competition. The operational parameters are designed for only one purpose such as maneuverability, flight duration, or speed, and as such would only be used in performance-based competition events and would not be utilized for personal business or transport activity.
- (2) **Type of Aircraft.** Aerobatic aircraft or Powered/Unpowered Gliders. Examples of aircraft that would operate under this group include the Rolladen-Schneider LS-4b, Schleicher ASW-24, Pitts Special, Sukhoi SU-26, Sukhoi SU-29, etc.
- (3) **Proficiency Area.** All proficiency flights will be conducted in airspace within an operational radius of 300 nautical miles from the airport where the aircraft is based.

Par 137 Page 119

(4) Inspection Requirements. These Aircraft must be inspected each year in accordance with an inspection plan that contains the scope and detail of part 43, appendix D.

b. Group II, Turbine-Powered Aircraft.

- (1) **Description of Aircraft.** This group includes any jet, turbo-fan, and turbo-prop; except those TPA that have a design capability of carrying cargo or more than 4 occupants. Those TPA that have a design capability of carrying cargo or more that 4 occupants will be certificated using the guidelines under Group IV.
- (2) **Type of Aircraft.** Examples of aircraft that would operate under this group include the Mikoyan Mig-17, Aero Vodochody L-29, Hispan Aviacion HA-200 Saeta, Fouga CM 170 Magister, Lockheed or Canadair T-33, Grumman OV-1 Mohawk, etc.
- (3) **Proficiency Area.** All proficiency flights will be conducted in airspace within an operational radius of 600 nautical miles from the airport where the aircraft is based. Proficiency flights will be limited to a non-stop flight that begins and ends at the home base airport, with sufficient fuel reserve to meet the applicable operating rules of part 91. Operators who choose to fly to another airport within the assigned proficiency area must notify their geographically responsible FSDO prior to each proficiency flight away from their home base airport (see note at the end of paragraph 126 of this order).
- **(4) Inspection Requirements.** These aircraft must have a FSDO-approved inspection program that meets the requirements of § 91.409(e). Guidance regarding inspection programs are found in Order 8300.10.

c. Group III, Piston Powered: Warbirds, Vintage, Replica, and Unique Aircraft.

- (1) **Description of Aircraft.** This group includes former military aircraft that were designed for military operations. Vintage aircraft are those aircraft that were designed prior to 1945. Replica aircraft are those aircraft that have the same external configuration as an aircraft that was designed prior to 1945. Unique aircraft means those aircraft that are one-of-a-kind.
- (2) **Type of Aircraft.** This group includes U.S. piston-powered Warbirds (regardless of size) and non-U.S. piston-powered aircraft under 12,500 lbs. that meet the above description and do not have a design capability of carrying cargo or more than four occupants. Examples of aircraft that would operate under this group include the North American T-28, Lockheed P-38, North American P-51, Messerschmitt ME-109, Boeing B-17, North American B-25, DeHavilland DHC-1 Chipmunk or Tiger Moth DH 82A, Focke-Wulfe Piaggo (FWP)-149, Nord Stampe SV4C, Bucker Jungman BU-131, etc.
- (3) **Proficiency Area.** All proficiency flights for an aircraft under 800 hp will be conducted in airspace within an operational radius of 300 nautical miles from its designated home base airport. Aircraft 800 hp and above will have a radius of 600 nautical miles from their designated home base airport.

Page 120 Par 139

(4) Inspection Requirements. Aircraft under 800 hp must be inspected each year in accordance with an inspection plan that contains the scope and detail of part 43, appendix D. Aircraft of 800 hp and above must be inspected in accordance with appropriate military technical publications or manufacturer's instructions for the aircraft.

d. Group IV, Other Aircraft.

- (1) **Description of Aircraft.** This group includes all aircraft that do not clearly fit in any of the other groups. This group will include aircraft that should be in the standard category that have been modified but the modification has not been processed under the STC process; and aircraft over 12,500 lbs. or those that have a design capability of carrying cargo or more than four occupants. This group also includes any newly produced aircraft that does not have a TC under § 21.21 or 21.29, with the exception of those aircraft that meet the description of aircraft for Group I. Additionally, this group includes aircraft that would normally be eligible for amateur-built airworthiness certification, but the owner has chosen to not perform the major portion of the fabrication and assembly as required under § 21.191(g).
- (2) **Type of Aircraft.** This group includes aircraft that have a design capability of carrying cargo or more than four occupants, and any other aircraft that does not clearly belong in any of the other groups. Examples of aircraft that would operate under this group include the Lockheed C-130, Antonov AN-2, Antonov AN-24, Iluyshin IL-76, and Cessna 172 with an automobile engine not approved under an STC, etc.
- (3) **Proficiency Area.** The proficiency area is limited to a non-stop flight that begins and ends at the airport where the aircraft is based, with sufficient fuel reserve to meet the applicable operating rules of part 91. An alternate airport selection is not available for aircraft in this group.
- (4) Inspection Requirements. Aircraft that weigh 12,500 lbs. or less must be inspected each year in accordance with an inspection plan that contains the scope and detail of part 43, appendix D. Aircraft over 12,500 lbs. must have a FSDO-approved inspection program that meets the requirements of § 91.409(e).
- **140. SPECIAL CERTIFICATION REQUIREMENTS.** The following provide information and guidance concerning airworthiness certification for experimental aircraft for the purpose(s) of exhibition and/or air racing. These steps are in the normal order of occurrence for the certification of these aircraft.
- **a. Demilitarization of Former Military Aircraft.** For demilitarization of former military aircraft refer to section 6, paragraph 123 of this order.
- **b. Records Inspection.** In addition to the record inspection requirements of paragraph 88a of this order the FAA shall:
- (1) Obtain from the applicant a program letter in accordance with § 21.193(a), setting forth the purpose(s) for which the aircraft will be used. The program letter must be specific as to the intended use under the purpose requested, including which airshows, air races, or exhibition activities (including

Par 139 Page 121

dates and locations) that will be attended. In the case of a movie or television production, the date(s) and location(s) of these productions must be provided. The applicant's program letter should state a reasonable schedule of events to be attended, but should not list events that would obviously be impossible to attend, e.g., listing all airshows scheduled in the United States for the upcoming year. Applicants should be advised that the program letter is subject to review by the FAA and that the owner/operator must notify the local FSDO by letter or facsimile transmission of any amendments to the proposed schedule prior to that flight.

NOTE: Applicants that do not submit a specific program letter do not meet the intent of § 21.193 and shall not be issued a special airworthiness certificate.

- (2) Ensure that the applicant has written in or translated into the English language all the necessary maintenance, inspection, operating, and flight manual(s) to operate the aircraft safely.
- (3) Verify that maintenance records reflect records of inspections, overhauls, repairs, time-in-service on life-limited parts and engines, etc., and that all records are current.

NOTE: The requirements of § 91.409(e) are applicable via an operating limitation issued at the time of airworthiness certification for all turbine aircraft, regardless of weight. This requirement provides for the replacement of life-limited parts at a time specified in documents approved by the Administrator.

(4) If the aircraft is a "Group II" or "Group IV" (only those aircraft over 12,500 lbs. and all turbine-powered aircraft regardless of weight) aircraft as described in paragraph 139 of this order, verify that the applicant has a FSDO-approved inspection program that meets the requirements of § 91.409(e). Guidance regarding inspection programs can be found in Order 8300.10.

NOTE: An airworthiness certificate shall not be issued for these aircraft without a FSDO-approved inspection program.

- (5) Verify that the appropriately rated FAA-certificated mechanic has made an entry in the aircraft records documenting the applicable inspections as referenced in paragraph 140 of this order for all aircraft (including new) within 30 days prior to the submittal FAA Form 8130-6.
- **c. Aircraft Inspection.** The FAA will perform an inspection to the extent necessary to ensure that an inspection of the aircraft and aircraft systems has been accomplished in accordance with the inspection requirements as identified in paragraph 88b of this order. Additionally, the FAA will verify that instruments, instrument markings, and placards are as required by the CFR and are identified in the English language. Verify that all measurements are converted to standard U.S. units of measure for those instruments necessary for operation in the U.S. air traffic system.

NOTE: Depending on the intended operation, the applicable reference would be § 91.205(b), VFR (day); § 91.205(c), VFR (night); or § 91.205(d), IFR. Operators should be alerted that there are specific requirements under part 91 for

Page 122 Par 140

maintenance and inspection of the various aircraft instruments, and that those requirements are applicable for these aircraft if the instruments are installed, e.g., §§ 91.173 through 91.187, 91.215, 91.217, 91.219, 91.411, 91.413, etc.

141. CERTIFICATION PROCEDURES.

- **a.** Once it has been determined that the aircraft meets the requirements for the airworthiness certification requested, the FAA shall:
- (1) Make an aircraft record entry showing the following or a similarly worded statement: "I find this aircraft meets the requirements for a special airworthiness certificate for the purpose(s) of (identify purpose(s)) and have issued a special airworthiness certificate and operating limitations dated (__). The next inspection is due (___). Signed: (John Doe, Aviation Safety Inspector, NM48)."
- (2) Issue the airworthiness certificate and appropriate operating limitations in accordance with this order.
- **b.** If the aircraft does not meet the certification requirements and the airworthiness certificate is denied, the FAA will provide a letter to the applicant stating the reason(s) for denial and, if feasible, identify what steps may be accomplished to meet the certification requirements. Should this occur, a copy of the denial letter will be attached to Form 8130-6 and forwarded to AFS-750, and made a part of the aircraft's record.
- **c.** An FAA inspector may elect to process these aircraft on a one-time certification basis, e.g., via the issuance of only one special airworthiness certificate of unlimited duration. In these instances, when issuing the special airworthiness certificate for the purpose(s) of exhibition and/or air racing, the operating limitations will be prescribed in two phases in the same document.

142. ISSUANCE OF EXPERIMENTAL EXHIBITION AND AIR RACING OPERATING LIMITATIONS.

- **a.** OPERATING LIMITATIONS SHALL BE DESIGNED TO FIT THE SPECIFIC SITUATION ENCOUNTERED. THE FAA INSPECTOR MAY IMPOSE ANY ADDITIONAL LIMITATIONS DEEMED NECESSARY IN THE INTEREST OF SAFETY. The FAA inspector and/or designee shall review each operating limitation imposed, with the applicant, to ensure that the operating limitations are understood by the applicant.
 - **b.** The following operating limitations shall be prescribed as applicable:

NOTE: The Group applicability (I-IV) is identified in bolded parenthesis at the end of each limitation.

Par 140 Page 123

8130.2D CHG 2 12/18/00

(1) No person may operate this aircraft unless the FAA Form 8130-7, Special Airworthiness Certificate, is displayed at the cabin or cockpit entrance so that it is visible to passengers or crew. (Applicability: All)

(2) No person may operate this aircraft for other than the purpose of meeting the requirements of § 91.319(b), as stated in the program letter (required by § 21.193) for this aircraft. This aircraft shall be operated in accordance with applicable air traffic and general operating rules of part 91 and all additional limitations herein prescribed under the provisions of § 91.319(e). These operating limitations are a part of the special airworthiness certificate, and are to be carried in the aircraft at all times and made available to the pilot in command of the aircraft.

(Applicability: All)

(3) This aircraft may only operate from (identify name of outlying airport) until the requirements of § 91.319(b) have been met. The operator will use the described corridor (shown on the attached chart) to transition to that airport. After meeting the requirements of § 91.319(b), the aircraft may return to (enter home base airport name) and the established corridor will be used for all subsequent operations.

(Applicability: All)

NOTE: This limitation will apply to all certificates issued to meet the requirements of § 91.319(b), (assigned test area). This limitation will also be used when the aircraft's home base is located in a densely populated area and/or in a congested airway.

* (4) In accordance with § 47.45, the FAA Aircraft Registry must be notified within 30 days for any change of the aircraft registrant's address. Such notification is to be made by submitting an FAA Form 8050-1, Aircraft Registration Application, to AFS-750 in Oklahoma City. (Applicability: All)

(5) This aircraft shall be operated for at least (____) hours with at least (____) takeoffs and landings (to a full stop) and shall be conducted in the geographic area described and/or shown on the attached chart.

(Applicability: All)

NOTE: This geographical area must be over open water or sparsely populated areas having light air traffic. The size of the area shall be that required to safely conduct the type of anticipated maneuvers and tests. The area shall be described by radius, or coordinates, and/or landmarks. The minimum hours and maximum takeoffs and landings should be based on the aircraft condition, records, and total time on the aircraft and engine(s). To ensure national standardization, when issuing this limitation for turbine-powered aircraft, the maximum hours should not normally exceed ten and the minimum takeoffs and landings should be at least three.

(6) Application must be made to the geographically responsible FSDO for any revision to these operating limitations.

(Applicability: All)

Page 124 Par 142

(7) This aircraft may not be operated over densely populated areas or in congested airways, except when otherwise directed by Air Traffic Control. (Applicability: All)

NOTE: Special operating limitations for particular aircraft to permit takeoffs and landings may be authorized in accordance with § 91.319(c). The certificating inspector should consult with a FSDO operations inspector in order to determine if takeoffs and landings should be authorized. If authorization is given, then the operating limitation will read as follows: "(7) Except for takeoffs and landings, this aircraft may not be operated over densely populated areas or in congested airways, except when otherwise directed by Air Traffic Control or in an emergency situation. When exercising this authorization, the pilot in command must request a departure route that will avoid densely populated areas and congested airways whenever possible."

The FAA certificating inspector will coordinate with the local FSDO operations unit to establish departure/approach corridors that ensure hazards to which persons and property are subjected, and exposure of persons to aircraft noise, are minimized. THIS CONCEPT OF A DEPARTURE/APPROACH CORRIDOR SHALL BE USED WHEN ISSUING OPERATING LIMITATIONS FOR AIRCRAFT THAT ARE BASED AT AIRPORTS WITHIN CLASS B AIRSPACE. ESTABLISHED CORRIDORS WILL BE USED FOR ALL PROFICIENCY FLIGHTS AND EVENT ATTENDANCE.

- (8) This aircraft is to be operated under Visual Flight Rules (VFR), day only. (Applicability: All)
- (9) No person may be carried in this aircraft during flight unless that person is essential to the purpose of the flight.

(Applicability: All)

- (10) No person may operate this aircraft for carrying persons or property for compensation or hire. (Applicability: All)
- (11) Aerobatic maneuvers intended to be performed must be satisfactorily accomplished and recorded in the aircraft records during the flight test period.

 (Applicability: All)

NOTE: In addition to the requirements of § 91.303, appropriate limitations identifying the aerobatic maneuvers and conditions under which they may be performed shall be presented. The FAA may witness aerobatic maneuvers if deemed necessary.

Par 142 Page 125

(12) This aircraft will not be operated unless the replacement times for life-limited parts specified in the applicable technical publications pertaining to the aircraft and its components are complied with. This aircraft, including its related components and systems, must be inspected in accordance with an approved inspection program selected under the provisions of § 91.409(e). This inspection program shall be recorded in the aircraft maintenance records.

(Applicability: Group II, Group IV Turbine Engine)

NOTE: The procedures for approval of this program are described in Order 8300.10.

(13) This aircraft shall not be operated unless it is inspected and maintained in accordance with appropriate military technical publications and/or manufacturer's recommendations. The owner/operator shall select, establish, identify, and use an inspection program as set forth in § 91.409(e), (f), (g), and (h). This inspection program shall be recorded in the aircraft maintenance records.

(Applicability: Group II, Group III over 800 hp, Group IV Turbine Powered, and Group IV over 800 hp)

- (14) Inspections shall be recorded in the aircraft maintenance records showing the following or a similarly worded statement: "I certify that this aircraft has been inspected on (insert date) in accordance with the (identify program, title) FSDO-approved program dated (______), and found to be in a condition for safe operation." The entry will include the aircraft total time in service (cycles if appropriate), and the name, signature, certificate number, and type of certificate held by the person performing the inspection. (Applicability: Group II, Group IV Turbine Engine)
- (15) No person shall operate this aircraft unless within the preceding 12 calendar months it has had a condition inspection performed in accordance with the scope and detail of appendix D to part 43, or other FAA-approved programs, and found to be in a condition for safe operation. This inspection will be recorded in the aircraft maintenance records.

(Applicability: Group I, Group III under 800 hp, Group IV Non-Turbine Engine)

- (16) Condition inspections shall be recorded in the aircraft maintenance records showing the following or a similarly worded statement: "I certify that this aircraft has been inspected on (insert date) in accordance with the scope and detail of appendix D to part 43 and found to be in a condition for safe operation." The entry will include the aircraft total time in service, and the name, signature, certificate number, and type of certificate held by the person performing the inspection. (Applicability: Group III, under 800 hp)
- (17) Inspections shall be recorded in the aircraft maintenance records showing the following or a similarly worded statement: "I certify that this aircraft has been inspected on (insert date) in accordance with the scope and detail of (identify military technical publications and/or manufacturer's instructions) and found to be in a condition for safe operation."

 (Applicability: Group III 800 hp and above)

Page 126 Par 142

12/18/00 8130.2D CHG 2

(18) Only FAA-certificated mechanics with appropriate ratings as authorized by § 43.3 may perform inspections required by these operating limitations. (Applicability: All)

(19) The cognizant FSDO must be notified, and its response received in writing, prior to flying this aircraft after incorporation of a major change as defined by § 21.93. (Applicability: All)

- (20) This aircraft must display the word EXPERIMENTAL in accordance with § 45.23(b). (Applicability: All)
- (21) This aircraft shall contain the placards, markings, etc., required by § 91.9. (Applicability: All)
- (22) The pilot in command of this aircraft must hold an appropriate category/class rating. If required for the type of aircraft to be flown, the pilot in command must also hold either an appropriate type rating or a letter of authorization issued by an FAA Flight Standards Operations Inspector.
- * (Applicability: Group II, Group III 800 hp and above, or more than 12,500 pounds, Group IV turbojet, or more than 12,500 pounds)

NOTE: A letter of authorization is issued in accordance with the procedures described in Order 8700.1, volume 2, chapter 32, section 1, for all training and eligibility requirements. This operating limitation is not applicable to glider aircraft.

(23) The pilot in command of this aircraft shall notify the air traffic control of the experimental nature of this aircraft when operating into or out of airports with operating control towers. The pilot in command shall plan routing that will avoid densely populated areas and congested airways when operating VFR.

(Applicability: All)

(24) The pilot in command of this aircraft should be knowledgeable of and utilize the procedures described in the Experimental Aircraft Association's "Jet Operations Manual" or other procedures acceptable to the Administrator.

(Applicability: Group II, Group IV)

(25) The ejection seat system must be maintained in accordance with the manufacturer's procedures and inspected in accordance with the FSDO-approved inspection program applicable to this aircraft. Additionally, the ejection seat system must be mechanically secured to prevent inadvertent operation of the system whenever the aircraft is parked or out of service.

(As Applicable)

Par 142 Page 127

8130.2D CHG 2 12/18/00

(26) This aircraft is prohibited from flight with any externally mounted equipment unless the equipment is permanently mounted in a manner that will prevent in-flight jettison, and there is an entry in the aircraft records indicating flight testing has been accomplished with this equipment installed.

(As Applicable)

- (27) Following satisfactory completion of the required number of flight hours in the flight test area, the pilot shall certify in the records that the aircraft has been shown to comply with § 91.319(b). Compliance with § 91.319(b) shall be recorded in the aircraft records with the following or a similarly worded statement: "I certify that the prescribed flight test hours have been completed and the aircraft is controllable throughout its normal range of speeds and throughout all maneuvers to be executed, has no hazardous operating characteristics or design features, and is safe for operation." (Applicability: All)
- (28) No person may operate this aircraft for other than the purpose(s) of (identify purpose(s)), to exhibit the aircraft, or participate in events outlined in (identify applicant) program letter (or any amendments) describing compliance with § 21.193(d). Additionally, this aircraft shall be operated in accordance with applicable air traffic and general operating rules of part 91, and all additional limitations herein prescribed under the provisions of § 91.319(e). These operating limitations are a part of the FAA Form 8130-7, Special Airworthiness Certificate, and are to be carried in the aircraft at all times for availability to the pilot.

(Applicability: All)

(29) All proficiency/practice flights shall be conducted within the geographical area described in the applicant's program letter and any amendments to that letter, but that area will not exceed 300 nautical miles of the aircraft's home base airport. An exception is permitted for proficiency flying outside of the area stated above for organized formation flying, training, or checkout in conjunction with a specific event listed in the applicant's program letter (or amendments). The program letter should indicate the location and dates for this proficiency flying.

(Applicability: Group I, Group III under 800 hp)

(30) All proficiency flights will be conducted in airspace with an operational radius of 600 nautical miles from the airport where the aircraft is based. This radius can be reduced if requested by the operator. Proficiency flights are limited to a non-stop flight that begins and ends at the airport where the aircraft is based. One alternate airport may be selected for each flight, within the operational radius of the airport where the aircraft is based. Operations outside this radius for organized formation flying, proficiency flying, or pilot checkout in conjunction with specific events will have to be listed in the applicant's program letter or notification will be sent to the cognizant FSDO, 48 hours PRIOR to the

(Applicability: Group II)

date of the actual event.

Page 128 Par 142

(31) All proficiency/practice flights shall be conducted within the geographical area described in the applicant's program letter and any modifications to that letter, but that area will not exceed 600 nautical miles of the aircraft's home base airport. An exception is permitted for proficiency flying outside of the area stated above for organized formation flying, training, or checkout in conjunction with a specific event listed in the aircraft program letter (or amendments). The program letter should indicate the location and dates for this proficiency flying.

(Applicability: Group III, 800 hp or above)

(32) All proficiency/practice flights shall be conducted within the geographical area described in the applicant's program letter and any modifications to that letter, but that area will not exceed 300 nautical miles of the aircraft's home base airport. Proficiency flights are limited to a non-stop flight that begins and ends at the aircraft home base airport. An alternate airport selection is not permitted for this aircraft. However, an exception is permitted for proficiency flying outside of the area stated above for organized formation flying, training, or checkout in conjunction with a specific event listed in the aircraft program letter (or amendments). The program letter should indicate the location and dates for this proficiency flying.

(Applicability: Group IV)

(33) Proficiency flights are authorized without geographical restrictions when conducted in preparation for participation in sanctioned meets and pursuant to qualify for Federal Aeronautique International (FAI) or Soaring Society of America (SSA) awards. These flights may only take place as defined in the aircraft program letter, and prior to the specific FAI or SSA event. The pilot in command must submit a description of the intended route and/or geographical area intended to be flown to the local FSDO.

(Applicability: Group I, Gliders Only)

- (34) This aircraft is restricted to airports that are within airspace classes C, D, E, and G during proficiency flights, except in the case of a declared emergency or when otherwise directed by Air Traffic Control. (Applicability: All)
- (35) The owner/operator of this aircraft must submit an annual program letter update to the local FSDO that lists air shows, fly-ins, etc., that will be attended during the next year, commencing at the time this aircraft is released into Phase II operation. This list of events may be amended, as applicable, by letter or facsimile transmission to the FSDO prior to the intended operation amendments, and a copy of the highlighted aeronautical chart, when applicable, is carried aboard this aircraft and is available to the pilot.

(Applicability: All)

(36) This aircraft is authorized for flights or static display at air shows, motion pictures, or air races conducted under a waiver issued in accordance with § 91.903.

(Applicability: All)

Par 142 Page 129

(37) After completion of phase I flight testing, unless appropriately equipped for night and/or instrument flight in accordance with § 91.205, this aircraft is to be operated under day only VFR. (Applicability: All)

(38) Aircraft instruments and equipment installed and used under § 91.205 must be inspected and maintained in accordance with the applicable requirements of parts 43 and 91. Any maintenance or inspection of this equipment must be recorded in the aircraft maintenance records.

(Applicability: All)

- (39) No person may be carried in this aircraft during the exhibition of the aircraft's flight capabilities, performance, or unusual characteristics at air shows, motion picture, television, or similar productions, unless essential for the purpose of the flight. Passengers may be carried during flights to and from any event outlined in the program letter or during proficiency flying, limited to the design seating capacity of the aircraft. (Applicability: All)
- (40) The pilot in command of this aircraft shall advise each person carried of the experimental nature of this aircraft, and explain that it does not meet the certification requirements of a standard certificated aircraft. (Applicability: All)
- (41) Aerobatic maneuvers that have been satisfactory accomplished and recorded during the flight test time period may be performed.

(Applicability: All)

(42) Supersonic flight (true flight Mach number greater than 1) is prohibited unless specifically authorized under § 91.817.

(Applicability: Group II, Group IV if applicable)

(43) The special airworthiness certificate and attached operating limitations for this aircraft have no expiration date. However, when an aircraft base of operation is changed or there is a transfer of ownership, the new owner/operator will provide the local FSDO with a copy of the approved inspection program, identifying the person responsible for scheduling and performing the inspections. New proficiency areas must be described in accordance with operating limitations number 28 through 33, as applicable.

(Applicability: Group II, Group IV Turbine Powered)

(44) This aircraft shall not be used for glider towing, banner towing, or intentional parachute jumping. (Applicability: All)

Page 130 Par 142

(45) This aircraft does not meet the requirements of the applicable, comprehensive, and detailed airworthiness code as provided by Annex 8 of the International Civil Aviation Organization (ICAO). The owner/operator of this aircraft must obtain written permission from another country's Civil Aviation Authority (CAA) prior to operating this aircraft in or over that country. That written permission must be carried aboard the aircraft together with the U.S. airworthiness certificate and, upon request, be made available to an FAA inspector or the CAA in the country of operation. (Applicability: All)

(46) Flights to airports other than an alternate airport and the airport where the aircraft is based are allowed for MAINTENANCE of the aircraft. (Maintenance as defined in § 1.1 is the reference for the purpose of these flights.) PRIOR to the flight, the operator must notify and receive permission from the geographically responsible FSDO where the maintenance will take place, and notify the FSDO with the geographic responsibility where the aircraft is based of the intended maintenance flight. The maintenance performed in connection with the flight must be recorded in the aircraft records in accordance with part 43. (Applicability: All)

NOTE: The geographically responsible FSDO and the local area FSDO office where the maintenance will take place must concur prior to approving the flight request.

(47)	The following placard, pertaining to	o gliders and sail planes having ea	xperimental certificates, shall
be displayed in	the cockpit in full view of the pilo	t in addition to the requirements of	of § 91.9. "NOTE: No
person may e	exceed the designer's or builder'	's recommended limitations as	s follows: Maximum gross
weight	_; Center of gravity limits	; Airplane tow speed	; Maximum airspeed
in smooth air	; and, Maximum airs	peed in rough air''	
(Applicability	: Group I)		
1/2 DECED	VFD		

143. KESEKVED.

Par 142 Page 131 (and 132)

SECTION 9. CERTIFICATION AND OPERATION OF AIRCRAFT UNDER THE EXPERIMENTAL PURPOSE(S) OF RESEARCH AND DEVELOPMENT, SHOW COMPLIANCE WITH REGULATIONS, CREW TRAINING, MARKET SURVEYS, AND OPERATING KIT-BUILT AIRCRAFT

- **144. GENERAL.** Under the provisions of § 21.191(a) research and development aircraft are defined as aircraft that test new design concepts, aircraft equipment, installations, operating techniques, or new uses for aircraft. Under the provisions of § 21.191(b) show compliance aircraft are defined as aircraft that conduct flight tests and other operations to show compliance with the regulations. This includes flights to show compliance for the issuance of type and supplemental type certificates, major design changes, and function and reliability requirements. Under the provisions of § 21.191(c) crew training aircraft are defined as aircraft involved in the training of the applicant's flight crews. Under the provisions of § 21.191(f) market survey aircraft are defined as aircraft that are used for conducting market surveys, sales demonstrations, and customer crew training as provided for in § 21.195. Under the provisions of § 21.191(h) operating kit built aircraft is defined as operation of a primary category aircraft that meets the criteria of § 21.24(a)(1) that was assembled by a person from a kit manufactured by a holder of a production certificate for that kit, without the supervision and quality control of the production certificate holder under § 21.184(a).
- **a.** Research and Development. Any aircraft would be eligible for an experimental certificate under this purpose. Although the operations may eventually lead to a TC, they may be conducted by the applicant only as a matter of research or to determine whether an idea warrants further development. In addition to the operations specified in § 21.191(a), the operation of a chase plane, a tanker used for in-flight icing tests, or other aircraft not otherwise eligible for a standard or an experimental certificate (research and development), but necessary for use in direct connection with the research and development project, is considered to be within the scope of this purpose. Aircraft currently certificated in the experimental category for the purposes of exhibition or air racing may also be eligible for a special airworthiness certificate for the experimental purpose of research and development. Also, former military aircraft are often used in R&D projects, and it is appropriate to use the guidance in this order when performing R&D certification of former military aircraft.
- **b.** Showing Compliance with Regulations. This purpose would be considered valid when the applicant for a type certificate, or an aircraft modifier, has revised the TC design data or has applied for an STC or field approval. The purpose is to show compliance to the CFR after the applicant has completed testing under research and development, if applicable, and flight testing by the FAA. In addition to the operations specified in § 21.191(b), the operation of a chase plane or other aircraft not otherwise eligible for a standard or experimental certificate, but necessary for use in direct connection with a type certification project, is considered to be within the scope of this purpose.
- **c.** Crew Training. Under § 21.191(c), this purpose is limited to only the applicant's flight crews, which normally would be the manufacturer's employees necessary to be trained in experimental aircraft for subsequent operation of aircraft being flight tested in type certification programs or for production flight testing. Crew training of the manufacturer's customers in experimental aircraft is covered in paragraph 144d below.

Par 144 Page 133

d. Market Surveys. A U.S. manufacturer of aircraft or engines and persons that alter aircraft may apply for a special airworthiness certificate in the experimental category for the purpose of market surveys, sales demonstrations, and customer crew training (§ 21.195). Amateur-built aircraft kit manufacturers may also be eligible to give customer familiarization training under § 21.191(f). The FAA representative must ensure that the provisions of § 21.195 are met before issuing the experimental certificate, and that the applicant provides the estimated time or number of flights required for the market survey operation and the area or itinerary over which the operations are to be conducted (§ 21.193(d)(2) and (3)). The duration of the certificate should be limited to only the time needed for the described operations, normally not to exceed 90 days, except that a longer duration may be provided for a PC or APIS holder who has an approved procedure for experimental operations. The MIDO manager has the option to extend the duration for other instances.

- **e.** Operating Kit-built Aircraft. If a primary category aircraft kit is assembled without the benefit of the PC holder's supervision, the aircraft may qualify for an experimental certificate per § 21.191(h). The purchaser or owner of the kit is not required to assemble or fabricate any specific portion of the kit; assistance for some or all of the work may be obtained from other sources, such as the PC holder or some other fabricator. The kit, however, must have been manufactured by a PC holder.
- **145. SPECIAL CERTIFICATION REQUIREMENTS.** In addition to the certification procedures in paragraph 88 of this order, refer to section 6, paragraph 123 of this order for demilitarization of former military aircraft.
- **146. PC/APIS HOLDER'S EXPERIMENTAL OPERATING PROCEDURE.** PC and APIS holders may submit for FAA approval a procedure describing the operation of experimental aircraft. The approved procedure may be listed in the operating limitations as indicated in paragraph 147b of this order. The PI may exclude certain aircraft from the privileges of either all or part of this procedure, e.g., first of a model such as the B757/B767 or a non-production research and development aircraft. The procedure should include at least the following:
- **a.** A description of the test area that will be used to show compliance with § 91.319(b). This area shall be described by a radius, coordinates, and/or landmarks, and be over open water or sparsely populated areas having light air traffic. The size of the area shall be that required to safely conduct the type of anticipated maneuvers and tests. Multiple purpose certificates may require individually prescribed geographical areas.
- **b.** A daily flight log should be maintained by the pilot showing compliance with § 91.319(b) and inspection of the aircraft prior to release for flights in the expanded test area. The flight log will be maintained for the duration of the certificate for review by the PI.
- **c.** A description of the method used to conduct and record necessary flights outside the test area, and for maintaining these records. This procedure will remain active for the duration of the certificate, and will eliminate the need for the PC/APIS holder to obtain approval for each flight.
- **d.** A description of the method used to define the persons that may be carried during these operations. This procedure must incorporate the following:

Page 134 Par 144

(1) A requirement that the pilot in command advise each person carried of the experimental nature of the aircraft (§ 91.319(d)).

- (2) A method of recording persons carried on each flight. These records must be maintained for the duration of the certificate for review by the PI.
- (3) A provision that no persons may be carried in the aircraft during flight unless that person is required for the purpose of the flight. Persons other than flight crew may be carried when the following conditions are met:
- (a) The aircraft is of the same basic model that has previously shown compliance with §§ 91.319(b) and 21.195.
 - **(b)** The aircraft has been proven in accordance with paragraph 147b(3) of this order.
- (c) Flight tests do not include intentional maneuvers involving abrupt changes in the aircraft's attitude, abnormal attitudes, or abnormal accelerations/deceleration not necessary for normal flight.
- (d) The procedures specifically cover the types of flying to be permitted while carrying passengers other than crew members.
- (e) The following placard is displayed inside the aircraft, in letters at least 3/8 inches in height and in a location easily visible and legible to all persons entering the aircraft:

"PASSENGER NOTICE: THIS AIRCRAFT DOES NOT COMPLY WITH FEDERAL SAFETY REGULATIONS FOR STANDARD AIRCRAFT."

- **e.** A description of the method used to determine that the aircraft is in a condition appropriate for the purpose intended when changing from one purpose to another (multiple purpose certificates), and to document the results of this determination in a log or daily flight sheet (e.g., changing from research and development to market survey).
 - **f.** Any other condition deemed necessary in the interest of safety by the PI.
- **g.** A copy of this procedure must be carried in the aircraft while operating under the privileges of this procedure. A copy of this procedure may also be included or directly referenced in the PC/APIS holder's quality manual for the convenience of the manufacturer and the PI. Any enforcement deemed appropriate would be under § 91.319 and not part 21, subparts F, Production Under Type Certificate Only, or G, Production Certificates.

Par 146 Page 135

8130.2D CHG 2 12/18/00

147. ISSUANCE OF EXPERIMENTAL RESEARCH AND DEVELOPMENT, SHOW COMPLIANCE WITH REGULATIONS, CREW TRAINING, MARKET SURVEYS, AND OPERATING KIT-BUILT AIRCRAFT OPERATING LIMITATIONS.

a. OPERATING LIMITATIONS SHALL BE DESIGNED TO FIT THE SPECIFIC SITUATION ENCOUNTERED. THE FAA INSPECTOR MAY IMPOSE ANY ADDITIONAL LIMITATIONS DEEMED NECESSARY IN THE INTEREST OF SAFETY. The FAA inspector and/or designee shall review each operating limitation imposed, with the applicant, to ensure that the operating limitations are understood by the applicant.

*

b. The following operating limitations shall be prescribed as applicable:

NOTE: The applicability is identified in bolded parenthesis at the end of each limitation.

- (1) No person may operate this aircraft unless the FAA Form 8130-7, Special Airworthiness Certificate, is displayed at the cabin or cockpit entrance so that it is visible to passengers or crew. (Applicability: All)
- (2) No person may operate this aircraft for other than the purpose of R & D, SHOWING COMPLIANCE WITH REGULATIONS, (ETC.) to accomplish the flight operation outlined in the program letter dated______, describing compliance with § 21.193(d), and made available to the pilot in command of the aircraft. Additionally, this aircraft shall be operated in accordance with applicable air traffic and general operating rules of part 91, and all additional limitations herein prescribed under the provisions of § 91.319(e).

(Applicability: All)

(3) All flights shall be conducted within the geographical area described as follows: The area shall be described by radius, or coordinates and/or landmarks. The designated area must be over open water or sparsely populated areas having light air traffic. The size of the area shall be that required to safely conduct the type of anticipated maneuvers and tests, as appropriate. (Multiple purpose certificates may require individually prescribed geographical areas.)

(Applicability: All)

NOTE: This applies to all certificates issued to show compliance with § 91.319(b). When the FAA finds compliance, the operating limitations will be revised to remove the limitation. The aircraft will not be allowed to operate over densely populated areas or in congested airways in accordance with § 91.319(c). The FAA may permit takeoffs and landings to be conducted over densely populated areas or in congested airways. If this operating limitation is issued it should read, "Except for takeoffs and landings this aircraft shall not be operated over densely populated areas or in congested airways." Limitation #5 may be specified in lieu of this operating

Page 136 Par 147

limitation for PC/APIS holders who have submitted a procedure in accordance with paragraph 146.

(4) All flights of this aircraft shall be conducted within the geographic area indicated on the chart as follows:

(Applicability: All Except Kit Built)

NOTE: This limitation will be prescribed to expand the area after the FAA finds compliance with § 91.319(b). This limitation applies to the following purposes: Research and Development, Showing Compliance, Crew Training, and Market Surveys. Limitation #5 may be specified in lieu of this operating limitation for PC/APIS holders who have submitted a procedure in accordance with paragraph 146 of this order.

(5) All flights shall be conducted in accordance with (Describe the PC/APIS holder's approved operating procedure, e.g., ABC Aircraft Co. Experimental Operating Procedure No. 12 (dated)). (Applicability: All Except Kit Built)

NOTE: Limitation #5 may be specified in lieu of limitations #3 and #4, for PC/APIS holders that have submitted a procedure in accordance with paragraph 146 of this order.

(6) When changing between operating purposes of a multiple purpose certificate, the operator shall determine that the aircraft is in a condition for safe operation and appropriate for the purpose intended. A record entry will be made by an appropriately rated person to document that finding in the aircraft log book. (Applicability: All Except Kit Built)

NOTE: This limitation is not applicable when a PC/APIS holder's experimental operating procedure is specified (see paragraph 146 of this order).

(7) This aircraft shall not be operated unless it is inspected and maintained in accordance with appropriate military technical publications and/or manufacturer's recommendations. The owner/operator shall select, establish, identify, and use an inspection program as set forth in § 91.409(e), (f), (g), and (h). This inspection program shall be recorded in the aircraft maintenance records.

(Applicability: All Except Kit Built)

(8) The pilot in command of this aircraft must hold an appropriate category/class rating. If required for the type of aircraft to be flown, the pilot in command must also hold either an appropriate type rating or a letter of authorization issued by an FAA Flight Standards Operations Inspector. (Applicability: All)

Par 147 Page 137

NOTE: A letter of authorization is issued in accordance with the procedures described in Order 8700.1, volume 2, chapter 32, section 1 for all training and eligibility requirements.

NOTE: This limitation is applicable to any turbine-powered or reciprocating engine powered aircraft with a total power greater than 800 horsepower, rotorcraft, aircraft with a maximum takeoff weight exceeding 12,500 pounds, or any other aircraft when deemed necessary. Flight Standards inspectors should refer to Order 8700.1 for further guidance.

(9) This aircraft is to be operated under Visual Flight Rules (VFR), day only. (Applicability: All)

NOTE: Section 91.319(d)(2) provides for VFR, day only. If other operations are requested, the authorization will be prescribed as a limitation by the appropriate selection of operating limitation #10 and #11 and the deletion of this limitation.

(10) This aircraft may be operated under Visual Flight Rules (VFR), day and/or night. (Applicability: All)

NOTE: Section 91.319(d)(2) provides for VFR, day only, unless otherwise specifically authorized by the Administrator. This limitation gives that authorization. If other operations are requested, the aircraft must be equipped in accordance with the applicable requirements of § 91.205.

(11) This aircraft may be operated under Instrument Flight Rules (IFR), and must be properly equipped for instrument flight in accordance with § 91.205. (Applicability: All)

NOTE: Section 91.319(d)(2) provides for VFR, day only, unless otherwise specifically authorized by the Administrator. This limitation gives that authorization. If other operations are requested, the aircraft must be equipped in accordance with the applicable requirements of § 91.205.

- (12) No person may operate this aircraft for carrying persons or property for compensation or hire. (Applicability: All)
- (13) No person may be carried in this aircraft during flight unless that person is essential to the purpose of the flight.

(Applicability: R&D and Show Compliance Only)

NOTE: This limitation may be deleted for PC/APIS holders and instead limitation # 5 may be specified.

Page 138 Par 147

(14) Persons may be carried in accordance with (Describe the PC/APIS Holder's approved operating procedure, e.g., ABC Aircraft Co. Experimental Operating Procedure No. 12 (dated)). (Applicability: All Except Kit Built)

NOTE: This limitation is applicable only for PC/APIS holders that have submitted a procedure in accordance with paragraph 146 of this order.

- (15) The pilot in command of this aircraft shall advise each person carried of the experimental nature of this aircraft, and explain that it does not meet the certification requirements of a standard certificated aircraft. (Applicability: All)
- (16) This aircraft shall contain the placards, markings, etc., (or other operating instructions developed for an STC modification) as required by § 91.9. (Applicability: All)

NOTE: Inspectors will also identify the flight manual, flight manual supplements, markings, drawings, etc., as required.

(17) This aircraft is prohibited from aerobatic flight; i.e., an intentional maneuver involving an abrupt change in the aircraft's attitude, an abnormal attitude, or abnormal acceleration not necessary for normal flight. (Applicability: All)

NOTE: Aerobatic flights may be permitted in the assigned test area. The applicant should be advised that aerobatics or violent maneuvers should not be attempted until sufficient flight experience has been gained to establish that the aircraft is satisfactorily controllable. These operating limitations may be modified to include only those aerobatics/maneuvers that have been satisfactorily accomplished and recorded in the aircraft records during the flight test period. These aerobatic maneuvers should be permitted upon leaving that assigned test area. Appropriate limitations identifying the aerobatics/maneuvers and conditions under which they may be performed should be prescribed. The certificating inspector may witness aerobatic maneuvers if deemed necessary.

- (18) This aircraft may conduct aerobatic flight in accordance with the provisions of § 91.303. Aerobatics shall not be attempted until sufficient flight experience has been gained to establish that the aircraft is satisfactorily controllable and in compliance with § 91.319(b). Aerobatic maneuvers intended to be performed must be satisfactorily accomplished and recorded in the aircraft records during the flight test period. (Applicability: All)
- (19) The cognizant FSDO must be notified, and its response received in writing, prior to flying this aircraft after incorporation of a major change as defined by § 21.93.

(Applicability: All Except for R&D and Show Compliance)

Par 147 Page 139

NOTE: Limitation #5 may be specified in lieu of this limitation for PC/APIS holders that have submitted a procedure in accordance with paragraph 146.

- (20) This aircraft shall not be used for glider towing, banner towing, or intentional parachute jumping. (Applicability: All)
- (21) No person shall operate this aircraft unless within the preceding 12 calendar months it has had a condition inspection performed in accordance with the scope and detail of appendix D to part 43, or other FAA-approved programs, and found to be in a condition for safe operation. This inspection will be recorded in the aircraft maintenance records.

(Applicability: All)

(22) Only FAA-certificated mechanics with appropriate ratings as authorized by § 43.3 may perform inspections required by these operating limitations.

(Applicability: All)

- (23) Inspections shall be recorded in the aircraft maintenance records showing the following or a similarly worded statement: "I certify that this aircraft has been inspected on (insert date) in accordance with the scope and detail of appendix D to part 43, or other FAA-approved programs and found to be in a condition for safe operation." The entry will include the aircraft total time in service, and the name, signature, certificate number, and type of certificate held by the person performing the inspection.

 (Applicability: All)
- (24) If aircraft, engine, or propeller operating limitations are exceeded, an appropriate entry will be made in the aircraft records.

(Applicability: All except Kit Built)

NOTE: This limitation applies only when an aircraft is temporarily in the experimental category and will be returned to the original certificate status, e.g., STC project.

(25) This aircraft shall not be operated unless it is maintained and inspected in accordance with the requirements of part 43, Maintenance, Preventive Maintenance, Rebuilding, and Alteration. (Applicability: All)

NOTE: This operating limitation is applicable for any aircraft that previously had been issued a different type of airworthiness certificate prior to applying for a special airworthiness certificate (reference § 43.1(b)).

(26) This aircraft must display the word EXPERIMENTAL in accordance with § 45.23(b). (Applicability: All)

Page 140 Par 147

12/18/00 8130.2D CHG 2

(27) The pilot in command of this aircraft shall notify the air traffic control of the experimental nature of this aircraft when operating into or out of airports with operating control towers. The pilot in command shall plan routing that will avoid densely populated areas and congested airways when operating VFR.

(Applicability: All)

- (28) This aircraft does not meet the requirements of the applicable, comprehensive, and detailed airworthiness code as provided by Annex 8 of the International Civil Aviation Organization (ICAO). The owner/operator of this aircraft must obtain written permission from another country's Civil Aviation Authority (CAA) prior to operating this aircraft in or over that country. That written permission must be carried aboard the aircraft together with the U.S. airworthiness certificate and, upon request, be made available to an FAA inspector or the CAA in the country of operation. (Applicability: All)
- (29) Aircraft instruments and equipment installed and used under § 91.205 must be inspected and maintained in accordance with the requirements of parts 43 and 91. Any maintenance or inspection of this equipment must be recorded in the aircraft maintenance records. (Applicability: All)
- (30) Application must be made to the geographically responsible FSDO or MIDO (insert name of office) for any revision to these operating limitations. (Applicability: All)
- (31) Section 47.45 requires that the FAA Aircraft Registry must be notified within 30 days of any change in the aircraft registrant's address. Such notification is to be made by submitting an FAA Form 8050-1, Aircraft Registration Application, to AFS-750 in Oklahoma City. (Applicability: All)

148.-149. RESERVED.

Page 141 (and 142)

SECTION 10. PROVISIONAL AIRWORTHINESS CERTIFICATION

- **150. GENERAL.** Under the provisions of part 21, subpart I, two classes of provisional airworthiness certificates may be issued. Class I certificates may be issued for all categories, whereas Class II certificates are issued for transport category aircraft only. In each case, a corresponding provisional TC or provisional amendment to the TC must be in effect to be eligible for a corresponding provisional airworthiness certificate.
- **151. ELIGIBILITY.** Only a U.S. aircraft manufacturer, aircraft engine manufacturer, or certificated air carrier may apply for provisional airworthiness certificates as provided in part 21, subpart I. Since the aircraft is normally one that is being used in the type certification process, the FAA should already be generally familiar with its progress and conformity status. Therefore, upon determining that the application and attachments are satisfactory, inspection of the aircraft is necessary only to the extent required to determine that it is in a condition for safe operation when operated within its operating limitations.
- **152. SPECIAL PURPOSE OPERATIONS.** The special purpose operations for which provisionally certificated aircraft may be operated are contained in § 91.317. These operations include:
 - **a.** Training flight crews, including simulated air carrier operations.
 - **b.** Demonstration flights by the manufacturer for prospective purchasers.
 - **c.** Market surveys by the manufacturer.
- **d.** Flight checking of instruments, accessories, and equipment that does not affect the basic airworthiness of the aircraft, or
 - **e.** Service testing of aircraft.
- **153. STATEMENT OF CONFORMITY.** A properly completed Form 8130-9 containing the information required by §§ 21.221 and 21.223 may be used by the manufacturer as its conformity statement and should be attached to Form 8130-6.
- **154. CERTIFICATION PROCEDURES.** The FAA should follow the appropriate procedures outlined in paragraph 88 of this order.
- **155. SPECIAL AIRWORTHINESS CERTIFICATE, FAA FORM 8130-7.** Upon a satisfactory determination that the aircraft conforms to its provisional TC or provisional amendment to a TC and is in a condition for safe operation, the FAA should issue Form 8130-7. The issuance of a provisional airworthiness certificate, corresponding with a provisional amendment to a TC, § 21.225, is considered to be an original issuance in the provisional category.

Par 150 Page 143

156. OPERATING LIMITATIONS. Operating limitations established for the issuance of the provisional TC are considered to be a part of the provisional airworthiness certificate issued to an individual aircraft. The FAA should determine that they are available in the aircraft in compliance with § 91.9. Limitations and restrictions as required by § 91.317, and which are not included in placards or the provisional flight manual, should be enumerated on a separate sheet and displayed with the provisional airworthiness certificate.

157.-170. RESERVED.

Page 144 Par 156

SECTION 11. SPECIAL FLIGHT PERMITS

171. GENERAL.

- **a.** Special flight permits are issued for aircraft that may not currently meet applicable airworthiness requirements, but are capable of safe flight. A special flight permit is not an authorization to deviate from the requirements of part 91.
- (1) Section 21.197(a) applies to aircraft which may not meet applicable airworthiness requirements and which will be operated for a purpose specified in § 21.197(a)(1) through (5).
- (2) Section 21.197(b) applies to those aircraft which meet all the applicable airworthiness requirements except those which cannot be met because of the overweight condition.
- (3) Section 21.197(c) applies only to holders of operating certificates issued under parts 121 or 135 for aircraft operated and maintained under a continuous airworthiness maintenance program. The instructions for issuance of a special flight permit with a continuing authorization are contained in Order 8300.10, volume II, chapter 89.
- **b.** Forms 8130-6 and 8130-7 are used for the administration of §§ 21.197 and 21.199. The instructions for completion of these forms are contained in chapter 8 of this order, except as noted in this section.
- **c.** Special flight permits for purposes other than production flight testing and customer demonstration flights will be issued by the FSDO/MIDO/IFO having jurisdiction over the geographical area in which the flight is to originate. If the applicant's aircraft is outside the jurisdiction of the FSDO/MIDO/IFO receiving the request, the applicant should be referred to the appropriate office. This paragraph does not apply to part 121 or 135 certificate holders.
- **d.** Special flight permits issued to part 121 or 135 certificate holders who do not have a continuous authorization, will normally be issued by their Certificate Holding District Office (CHDO). However, these special flight permits may be issued by the office having geographical responsibility, with the concurrence of the CHDO.
- **e.** Under special conditions, special flight permits may be issued to part 145 repair facilities for the purpose of delivering aircraft from international locations to the United States. In this instance, the special flight permit will be issued by the CHDO having jurisdiction over the repair facility under the following conditions:
- (1) Applicable to U.S.-registered aircraft which do not currently meet their standard airworthiness certificate, due to the installation of non-standard auxiliary fuel systems. Auxiliary fuel system installations must be accomplished by an FAA certificated repair facility which is specifically airframe rated for the desired installation.

Par 171 Page 145

(2) Procedures relating to the application and issuance of special flight permits, the installation of auxiliary fuel systems, and any conditions and limitations for flight must be incorporated into the repair facility's operations specifications.

NOTE: The FAA office issuing the special flight permit, under these special conditions, must assure compliance to all other guidelines outlined within this order. The CHDO may request the IFO having jurisdiction over the geographical area in which the flight is to originate to inspect the aircraft prior to flight utilizing an ASI or qualified designee.

f. The validity of the special flight permit is not affected by the operation of the aircraft outside the border of the United States, so long as it is operated for the intended purpose under § 21.197 and within the time frame specified on the permit. The special flight permit does not authorize flight over countries other than the United States without permission of that country. If such operation is contemplated, the effective date of the permit is contingent upon compliance with Section D(2) of the permit and it becomes the responsibility of the owner/operator to obtain such permission.

NOTE: Paragraph 171(f) does not apply to authorizations covered by Order 8300.10, volume II, chapter 89.

- **g.** No person may operate a product to which an AD applies, except in accordance with the requirements of the AD (§ 39.3). If an AD requires compliance before further flight and does not have a provision for the issuance of special flight permits, the operation of the aircraft to which it applies would not be appropriate, and a special flight permit shall not be issued.
- **h.** If the product is not an aircraft, and the AD does not provide for the product's operation during a ferry flight, the product may not be operated during such a flight (§ 39.3). If the aircraft on which the product is installed can be safely operated without operating the product, a special flight permit could be issued with a limitation that the product be rendered inoperative in flight (§ 21.197(a)).
- **172. PURPOSES.** Section 21.197 prescribes the general purposes for which a special flight permit may be issued. The following specific operations are also considered to be within the scope of the general provisions:
- **a.** Any flight of a U.S.-registered aircraft covered by § 21.197, if the aircraft is capable of safe flight, even though a TC has not been issued.
- **b.** The delivery of an aircraft of either U.S. or non-U.S. manufacture to the base of the purchaser or to a storage point in the United States.
- **c.** The operation of non-air carrier four engine aircraft with one engine inoperative. The provisions of § 91.611 should be used as a guide.
- **d.** Flying an aircraft whose annual inspection has expired to a base where an annual inspection can be accomplished.

Page 146 Par 171

e. Flying an amateur-built aircraft whose condition inspection has expired to a base where the condition inspection can be accomplished.

173. APPLICATION AND ISSUANCE (GENERAL).

- **a.** When the application for a special flight permit is found in compliance with all requirements, the FAA should issue Form 8130-7, together with operating limitations deemed necessary for safe operation. The operating limitations should be enumerated on a separate sheet, identified by the aircraft registration and serial number, dated, and signed. The applicant should be advised that Form 8130-7 and attached operating limitations must be displayed in the aircraft in accordance with § 91.203(b).
- **b.** The FAA may assist the applicant by completing Form 8130-6 based on information furnished by telephone, letter, or facsimile (FAX). The name of the applicant should be entered in the space provided for the applicant's signature. A notation as to how the information was received should be entered above the name, e.g., "Received by letter dated______." If the information provided is adequate, and all requirements for issuance are satisfied, the FAA inspector may issue a telegraphic or FAX special flight permit with appropriate limitations (except § 21.197(b) for overweight operations). These limitations will include inspection requirements as deemed necessary. The telegraphic or FAX special flight permit and prescribed operating limitations must be displayed in the aircraft in accordance with § 91.203(b) prior to conducting the special flight.

NOTE: This privilege is not extended to FAA designees since they are required to physically perform the inspection necessary to insure the aircraft is eligible for the special flight permit.

- **c.** If a district office processes numerous applications for telegraphic/FAX special flight permits, a standard format with blanks for notification pertinent to each individual issuance may be filed with the local office.
- **d.** When Form 8130-6 has been completed, the FAA inspector will complete a copy of the sample telegraphic/FAX special flight permit to include any additional operating limitations that may be required. The completed and signed permit may then be transmitted by FAX. The FAX permit that is received for display in the aircraft at the point of departure will be considered the original permit.
- **e.** A copy of each certification document should be retained in the files of the issuing office. Only copies required per paragraph 243a(1) of this order, as applicable, are to be forwarded to AFS-750.

174. AIRCRAFT INSPECTIONS.

- **a.** It is the responsibility of the FAA to determine what inspections or tests are necessary to ensure that the aircraft is capable of safe flight for the intended purpose.
- **b.** The FAA should make, or require the applicant to make, appropriate inspections or tests considered necessary for safe flight.

Par 172 Page 147

c. The FAA shall personally inspect damaged aircraft or an aircraft where the airworthiness is questionable in any respect. The FAA shall personally inspect those aircraft models for which a U.S. TC has never been issued.

NOTE: If an affirmative, technical determination cannot be made that a particular aircraft is capable of safe operation because of insufficient design, inspection, and maintenance data that are normally available for a type certificated aircraft, the special flight permit should not be issued.

- **d.** When the FAA requires the applicant to make the inspection, the applicant must be advised that such inspections must be:
- (1) Accomplished by an appropriately certificated mechanic or repair station familiar with all the procedures and requirements contained in this chapter.
- (2) Documented by an appropriate entry in the aircraft log book by the authorized person who conducted the inspection.
- **175. SPECIAL OPERATING LIMITATIONS.** The FAA should establish limitations as deemed necessary for safe operation. Since individual circumstances may vary greatly, a list of limitations applicable in every case cannot be provided. The objective is to assure safe operation of the aircraft. If necessary, solicit the technical assistance of other FAA offices or specialties. Limitations should be clear and concise so they can be easily understood. In addition to the limitations deemed necessary for the particular flight, the following items should be considered when establishing operating limitations:
 - **a.** Conformity to the aircraft's technical data.
 - **b.** Operational equipment necessary for safe operation of the aircraft.
- **c.** Special crew member and pilot qualifications required. For flights, which involve long distances where various weather conditions may be encountered, the pilot in command should also be appropriately instrument rated.
 - **d.** Aircraft weight limits.
 - e. Fuel and fuel distribution limits.
 - **f.** Center of gravity limits.
 - **g.** Maneuvers to which the aircraft is limited.
 - **h.** Limits on usage of flight equipment, such as autopilots, etc.
 - i. Meteorological conditions to be avoided and the inspections required if inadvertently encountered.

Page 148 Par 174

- j. Airspeed limits.
- **k.** Operation in the overweight condition must be conducted to avoid cities, towns, villages, and congested areas, or any other areas where the flights might create hazardous exposure to persons or property.
 - **l.** Runway selections if considered necessary for safety.
- **m.** Communications required with airport tower personnel to inform them prior to takeoff or landing of the non-standard condition of the aircraft.
- **n.** When flight over another country is planned, the inspector must emphasize to the applicant that special permission must be obtained from the country over which the aircraft will be operated. In addition, Section C of Form 8130-7 should contain the remark "subject to paragraph D(2), reverse side." (figure 4-19).
 - NOTE: When required to fly over an ICAO country, the operating limitations issued with the special flight permit should include, when appropriate, the following statement: This aircraft does not comply with the International Standards of Annex 8 to the Convention on International Civil Aviation as follows: Describe here the item(s) which do not comply with the airworthiness requirements for standard aircraft.
 - **o.** Any other limitation that should be prescribed for the particular flight.

176. SPECIAL FLIGHT PERMITS FOR OPERATION OF OVERWEIGHT AIRCRAFT.

a. General.

- (1) The FAA has two primary concerns when issuing special flight permits for the temporary operation of overweight aircraft:
 - (a) That the public will be guarded in the event of an accident.
- **(b)** That when the aircraft is returned to a standard configuration, it has not been rendered unairworthy due to the overweight operations.
- (2) With safety being the primary concern, it is essential that the processing office utilize the technical assistance of other FAA offices or specialties as deemed necessary to assure the highest degree of safety possible. All installations such as long range fuel system and navigational equipment must be installed in accordance with FAA-approved data.
- (3) Applications where the proposed maximum weight does not exceed 110 percent of the maximum certificated weight, and the certificated CG limits are not exceeded, may be processed by district offices without obtaining an engineering evaluation (except for rotorcraft).

Par 175 Page 149

(4) Applications where the proposed maximum weight exceeds 110 percent of the maximum certificated weight, or the CG limits exceed the certificated limits, must be coordinated with an ACO for engineering evaluation of the structural integrity and any other provisions deemed necessary.

- (5) All applications for rotorcraft must be coordinated with an ACO for an engineering evaluation of the structural integrity, flight integrity, or any other provisions deemed necessary.
- (6) The processing of an application should encompass a review of the airworthiness status of the basic aircraft, an evaluation of the added installations that constitute the excess weight, required crew qualifications, and proposed operating limitations.

b. Added Installations.

(1) Technical Data.

- (a) When the application submitted falls under the provisions of paragraph 176a(4) or (5) of this order, any drawings and reports substantiating structural integrity submitted with the application should be in sufficient detail to allow a determination that the added installations are structurally and functionally safe and to allow a conformity inspection of the added installations.
 - **(b)** The structural report should reference the drawings used for the installation(s).

(2) Record of Installation(s).

- (a) The installation(s) added to the aircraft for the intended overweight flight must be recorded in accordance with the requirements of § 43.9.
- **(b)** The following statement must be entered in Section 3 of Form 337: "No person may operate this aircraft, as altered herein, unless it has within it an appropriate and current special flight permit issued under part 21." (figure 4-20)
- (3) Auxiliary Fuel System Installations. In the evaluation of the auxiliary fuel system installations, the following items should be considered:
- (a) The aircraft and auxiliary fuel system must meet all applicable airworthiness requirements, except those which the aircraft cannot meet because of its overweight condition, and must be found safe for the intended flight.
- **(b)** Fuel tank(s) installed in a pressurized area should be tested for the maximum pressure differential existing between cabin pressurization and aircraft maximum operating altitude with fuel tank(s) empty.
- (c) Adequate ventilation should be provided for the fuel tank(s) and the area in which the fuel tank(s) is/are located to prevent the accumulation of fumes which would be detrimental to the crew or present a fire or explosion hazard.

Page 150 Par 176

(d) A means should be provided to readily determine the quantity of fuel in the auxiliary tank(s) prior to takeoff. In addition, a means should be provided to indicate the quantity of fuel in tanks that have a vapor/excess fuel return line, both prior to takeoff and during flight.

- (e) The location of the fuel tank(s) in the aircraft is a major factor in determining that the aircraft is safe for flight since the added fuel and fuel facilities have the greatest effect on the aircraft center of gravity. In addition, the fuel system installation shall not restrict entrance to or exit from the aircraft as provided by the applicable CFR. If required under § 23.1001 (Amendment 23-7), the aircraft should have an adequate fuel jettison system installed.
- **(f)** Auxiliary fuel systems which are not complete, that is, not connected to the basic aircraft fuel system, should not be considered for issuance of a special flight permit.
- (4) Engine Oil Quantity. The applicant will show that the oil supply provided for each engine is sufficient to ensure satisfactory cooling and system circulation for the duration of the flight. If considered necessary, an oil transfer system for replenishing the engine oil while the aircraft is in flight should be provided.

(5) Maximum Weight and Center of Gravity Limits.

- (a) Section 21.197(b) limits the excess weight over the certificated maximum weight to additional fuel, fuel carrying facilities, and navigational equipment added for the intended flight. It should be determined that this part of the maximum weight complies with this requirement.
- **(b)** When numerous alterations are performed, it may be necessary to weigh the aircraft to establish the aircraft weight and the CG limits. The computations should be evaluated for accuracy. It may also be necessary to require flight test at the new maximum weight and CG limits to determine that the aircraft is safe for operation. Computed weight and balance information should be reflected on Form 337, Section 8.
- (c) Operation of rotorcraft over the certificated maximum weight presents some unique conditions over and above those encountered with fixed-wing aircraft. Special attention should be given to this type of aircraft. A careful evaluation should be made to determine what effect the overweight operation may have upon the retirement times of critical parts.
- **(6)** Operating limitations should be prescribed as deemed necessary. Reference paragraphs 147 and 175 of this order, and include:
- (a) Operation in the overweight condition must be conducted to avoid cities, towns, villages, and congested areas, or any other areas where the flights might create hazardous exposure to persons or property.
- **(b)** Runway (specify) must be used for overweight takeoff (and landing when appropriate). If an en route stop is scheduled, the following must be added to this limitation: Contact FAA office, (city, routing symbol, and telephone number) for runway to be used for overweight landing and takeoff at (city).

Par 176 Page 151

(c) A copy of Form 337 covering the additional fuel-carrying facilities and equipment shall be in the aircraft.

- (d) Special entries to identify required inspection of the aircraft for possible damage due to overweight operation upon completion of overweight flight(s).
- 177. SPECIAL FLIGHT PERMIT FOR PRODUCTION FLIGHT TESTING. A special flight permit issued for production flight testing may be used by a manufacturer to meet the requirements of § 91.203 when operating new production aircraft for the purpose of production flight testing, as provided in § 21.197. This permit may be used with Form 8050-3 and Aeronautical Center Form 8050-6, A Dealer's Aircraft Registration Certificate, or Form 8050-1. The permit is valid only for the purpose of production flight testing and is transferable from one aircraft to another. The applicable operating limitations are printed in Block B on the reverse side of Form 8130-7 (figure 4-1).

a. Eligibility.

- (1) A manufacturer producing aircraft under any of the following subparts of part 21 is eligible to obtain special flight permits for production flight testing:
 - (a) Subpart F (It is not necessary for the manufacturer to have an APIS);
 - (b) Subpart G; or
 - (c) Subpart J.
- (2) A manufacturer producing aircraft prior to issuance of the TC is also eligible for a special flight permit for production flight testing provided the following conditions are met:
- (a) The manufacturer holds a TC and a currently effective PC for at least one other aircraft in the same category.
 - **(b)** The FAA official flight test program is in process.
- (c) A prototype aircraft of that model has been flown by the manufacturer under an experimental certificate to assure that there are no adverse flight characteristics and that production test pilots are fully familiar with the aircraft.
- (d) An FAA-accepted production flight test procedure and checklist, for the aircraft involved, will be used to assure that all requirements for production test flights are accomplished.
- (e) The aircraft is not being flown by the manufacturer for purposes other than production flight tests.
 - (f) Limitations have been established to define the production flight test area.

Page 152 Par 176

b. Application and Issue.

(1) An eligible manufacturer should apply for the issuance of as many special flight permits for production flight testing as deemed necessary for satisfactory coverage of the aircraft involved. The number of special flight permits for production flight testing issued to the manufacturer shall be limited to actual need.

- (2) The manufacturer should establish procedures for control of the permits while they are in their possession. Additionally, the manufacturer should establish suitable controls to ensure that the permits are controlled and placed only in aircraft undergoing production flight testing.
- (3) A MIDO which has issued special flight permits for production flight testing should maintain suitable accountability records which will show expiration dates not to exceed 12 months from the date of issuance, and the quantity of permits issued to each manufacturer. It is recommended that each permit issued be numbered serially in the upper right corner of the airworthiness certificate by the issuing office; e.g., SW-MIDO-41. The same serial number may be reassigned to a manufacturer each year. The issuing official shall sign each permit and associated limitations in ink over the typed name. A copy of the letter of transmittal should be forwarded by the issuing MIDO to the MIO.

178. SPECIAL FLIGHT PERMIT FOR CONDUCTING CUSTOMER DEMONSTRATION

FLIGHTS. A special flight permit may be used by a manufacturer to meet the requirements of § 91.203 when operating a new production aircraft for the purpose of conducting customer demonstration flights, reference § 21.197(a)(5). This permit may be used with Form 8050-3, Form 8050-6, or Form 8050-1. This permit is valid only for the above purpose and will not be issued in conjunction with any other special flight permit purposes.

NOTE: The meaning of the word "customer" for the purpose of this airworthiness certificate means any person or organization judged by the manufacturer to be an acknowledged or potential aircraft purchaser.

- **a. Eligibility.** A special flight permit for conducting customer demonstration flights may be issued when the following conditions are met:
 - (1) The new production aircraft was produced under a PC or TC only.
- (2) The PC/TC holder has satisfactorily completed production flight tests. Completion of production flight tests indicates acceptance by the production flight test pilot and no further flight tests are required or planned.

b. Application and Issue.

(1) A letter from the manufacturer should accompany the application describing the customer demonstration flights to be made if sufficient information cannot be included on the application.

Par 177 Page 153

(2) Upon receipt of a properly executed application, the issuing FAA representative shall inspect the aircraft and prescribe the operating limitations in accordance with paragraphs 147 and 175 of this order, as deemed necessary for safe operation. It is not necessary to repeat the limitations on the reverse side of Form 8130-7 except for the statement "Subject to D(2) on reverse side" which shall be entered in Block C on the face side of the form. The demonstration flight area(s) shall also be listed on the operating limitations. Special flight permits should be issued only for the period needed to complete demonstration flights, usually not to exceed 90 days.

- (3) If it is determined by the MIDO that the PC holder has appropriate procedures instituted to safe-guard the storage and issuance of special flight permits for customer demonstration flights, permits that are transferable from one aircraft to another may be issued. It shall still be necessary to prescribe operating limitations in accordance with paragraphs 147 and 175 of this order, as deemed necessary for safe operation. The statement "Subject to D(2) on the reverse side" shall be entered in Block C on the face side of Form 8130-7. The expiration date shown on Form 8130-7 and the associated limitations shall not exceed 12 months from the date of issuance. The permits issued in this manner should be serialized so as to differentiate them from any production flight permits which may have been issued. The number of special flight permits for conducting customer demonstration flights issued to a manufacturer shall be limited to actual need.
- (4) The MIDO issuing special flight permits for customer demonstration flights will maintain a copy of the complete file in accordance with record retention requirements.

179. SPECIAL FLIGHT PERMIT FOR CERTAIN LARGE AIRCRAFT TO WHICH PART 125 IS NOT APPLICABLE (SEATING CAPACITY OF 20 OR MORE OR MAXIMUM PAYLOAD CAPACITY OF 6000 POUNDS OR MORE).

a. Eligibility. A special flight permit may be issued for certain large aircraft to which part 125 is not applicable. In those cases, the following provisions must be met.

b. Application and Issue.

- (1) Prior to issuance of a special flight permit, the applicant must select, identify in the aircraft maintenance records, and use one of the programs specified in § 91.409(f). If the program selected contains provisions addressing inspection of the aircraft applicable to the situation, then those provisions may be used to ensure safe operation of the aircraft. If the program selected does not contain those provisions, the FAA will specify the appropriate inspections and/or tests required to ensure safe operation.
- (2) In some cases the applicant may not intend to place the aircraft in further service following the flight authorized by the special flight permit. In this case the applicant may wish to select, identify, and use the inspections and/or tests required by the FAA to ensure safe operation of the aircraft, as the inspection program for use under § 91.409(f)(4). Unless provisions for additional flights are provided for in the FAA-approved program, no additional flights are permitted.
 - (3) The following examples are provided to illustrate how the above procedures may be applied:

Page 154 Par 178

EXAMPLE 1: ABC Airlines, operating B-777 aircraft in air carrier service, wishes to lease another B-777 from XYZ Leasing. The subject aircraft has been in storage for one year. ABC Airlines wishes to operate the aircraft from the point of storage to a maintenance facility prior to placing the aircraft in service with the airline. ABC Airlines may choose to select, identify in the maintenance records, and use the inspection program that is part of ABC Airlines Continuous Airworthiness Maintenance Program (CAMP), for its B-777, as provided in § 91.409(f)(4). If the selected CAMP contains provisions for inspection prior to flight of aircraft being removed from storage, those provisions may be used to ensure safe operation of the aircraft. If the CAMP does not contain such provisions, the CAMP may still be selected; however, the FAA shall require ABC Airlines to make appropriate inspections or tests necessary to ensure safe operation.

- **EXAMPLE 2:** XYZ Leasing Company wishes to operate its A-300 from one storage location to another. Upon application for the special flight permit, XYZ submits a description of the inspections and tests it considers necessary to ensure safe operation of the aircraft. Upon review of the submitted description, the FAA issues the special flight permit with the conditions and limitations under which XYZ may operate its aircraft following the satisfactory completion of the inspections and tests described. XYZ may then select, identify, and use the description of inspections and tests approved by the FAA by issuance of the special flight permit conditions and limitations, as the inspection program under which the aircraft is to be operated.
- (4) The scope and detail of the inspections and/or tests required to ensure safe operation may vary considerably depending on the purpose for which the permit is issued and/or the conditions or circumstances surrounding the subject aircraft. In-service aircraft that have been routinely maintained and/or inspected under an approved inspection program may not require more than the normal inspections that are routinely required by the approved program.
- (5) Aircraft that have been damaged, or out of service for an extended period of time, may require additional inspections or tests to ensure safety. Aircraft that have been damaged may require engineering evaluations or special tests to determine airworthiness. In the case of aircraft that have been out of service, the circumstances surrounding storage of the aircraft should be evaluated. In many cases aircraft in storage have been routinely maintained, inspected, and preventive maintenance performed at regular intervals. These aircraft would normally require less attention prior to any anticipated flight. However, any aircraft that has been in storage for an extended period of time requires, at the very least, an extensive visual inspection by a properly certificated mechanic, an inspection of the fuel storage and delivery systems for contamination, and operational checks of all systems and equipment that may be required to function on the intended flight.
- (6) Indiscriminate operation of these types of aircraft should be discouraged by restricting the operation of the aircraft to specific airports and to a specific flight path. The special flight permit should not be issued for a duration in excess of 7 days.
- (7) When the flight characteristics of the aircraft have not been appreciably altered, persons other than crew members and/or persons essential to the operation of the aircraft may be carried aboard

Par 179 Page 155

during flight operations authorized by a special flight permit. In those cases, the passenger-carrying requirements of part 91 will apply.

- (8) An FAA operations inspector, type rated in the aircraft, should be consulted regarding the adequacy and appropriateness of the conditions and limitations of the special flight permit.
- (9) The issuance of special flight permits for large aircraft will be accomplished by the FSDO having geographic responsibility for the area in which the aircraft is located. A CHDO may issue a special flight permit for its part 121, 125, 133, or 137 certificate holders who do not have a continuing authorization, but only for those aircraft listed on the certificate holder's aircraft listing. A CHDO may not issue a special flight permit for aircraft located outside the CHDO's geographic boundaries unless that aircraft is listed on the certificate holder's aircraft listing.
- (10) In order to provide proper surveillance and oversight of the flight operations of these types of aircraft, it is recommended that the issuing office advise the destination FSDO or regional airworthiness branch of the conditions and limitations of the special flight permit, and the aircraft's anticipated arrival time and destination.
- (11) The operation of noise-restricted (§ 91.805) aircraft requires an SFA issued in accordance with SFAR No. 64. A special flight permit is not required in these instances and will not be issued unless the aircraft does not meet applicable airworthiness standards as provided in § 21.197. All other inspection program requirements apply.

180.-183. RESERVED.

Page 156 Par 179

12/18/00 8130.2D CHG 2

FIGURE 4-1. SAMPLE FAA FORM 8130-7, SPECIAL AIRWORTHINESS CERTIFICATE

UNITED STATES OF AMERICA DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION SPECIAL AIRWORTHINESS CERTIFICATE											
Α	CATEGORY/DESIGNATION										
^	PURPOSE										
В	MANU-	NAME									
	FACTURER	ADDRESS									
С	FLIGHT	FROM									
	1 LIGITI	ТО	,								
D	N-		SERIAL NO.								
	BUILDER		MODEL								
	DATE OF IS	SUANCE	EXPIRY								
	OPERATING	S LIMITATIONS DATED	ARE PART OF THIS CERTIFICATE								
E	SIGNATURE OF	FAA REPRESENTATIVE	DESIGNATION OR OFFICE NO.								
Any alteration, reproduction or misuse of this certificate may be punishable by a fine not exceeding \$1,000 or imprisonment not exceeding 3 years, or both. THIS CERTIFICATE MUST BE DISPLAYED IN THE AIRCRAFT IN ACCORDANCE WITH APPLICABLE FEDERAL AVIATION REGULATION.											

FAA Form 8130-7 (10/82) SEE RE VERSE SIDE

Α	This airworthiness certificate is issued under the authority of the Federal Aviation Act of 1958 and the Federal Aviation Regulations (FAR)
В	This airworthiness certificate authorizes the manufacturer named on the reverse side to conduct production flight tests, and only production flight tests, of aircraft registered in his name. No person may conduct production flight tests under this certificate: (1) Carrying persons or property for compensation or hire: and/or (2) Carrying persons not essential to the purpose of the flight.
С	This airworthiness certificate authorizes the flight specified on the reverse side for the purpose shown in Block A
D	This airworthiness certificate certifies that as of the date of issuance, the aircraft to which issued has been inspected and found to meet the requirements of the applicable FAR. The aircraft does not meet the requirements of the applicable comprehensive and detailed airworthiness code as provided by Annex 8 to the Convention On International Civil Aviation. No person may operate the aircraft described on the reverse side: (1) except in accordance with the applicable FAR and in accordance with conditions and limitations which may be prescribed by the Administrator as part of this certificate; (2) over any foreign country without the special permission of that country.
E	Unless sooner surrendered, suspended.,or revoked, this airworthiness certificate is effective for the duration and under the conditions prescribed in FAR Part 21, Section 21.181 or 21.217.

8130.2D CHG 2 12/18/00

FIGURE 4-2. SAMPLE FAA FORM 8130-7, SPECIAL AIRWORTHINESS CERTIFICATE FOR RESTRICTED CATEGORY AIRCRAFT CERTIFICATED UNDER § 21.25(b)(7)

UNITED STATES OF AMERICA DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION SPECIAL AIRWORTHINESS CERTIFICATE											
_	A CATEGORY/DESIGNATION RESTRICTED										
PURPOSE 14 CFR 21.25(b) (7) (OTHER), SEE ATTACHED LIMITATIONS											
В	MANU-	NAME									
	FACTURER	ADDRESS									
С	FLIGHT	FROM SEE ATTACHED OPER ATING LIMITATIONS									
	I LIGITI	TO SEE ITEM D, REVERSE SIDE OF T	OF THIS CERTIFICATE								
D	N-		SERIAL NO.								
	BUILDER		MODEL								
	DATE OF IS	SUANCE	EXPIRY								
_	OPERATING	S LIMITATIONS DATED	ARE PART OF THIS CERTIFICATE								
E	SIGNATURE OF	FAA REPRESENTATIVE	DESIGNATION OR OFFICE NO.								
impr	Any alteration, reproduction or misuse of this certificate may be punishable by a fine not exceeding \$1,000 or imprisonment not exceeding 3 years, or both. THIS CERTIFICATE MUST BE DISPLAYED IN THE AIRCRAFT IN ACCORDANCE WITH APPLICABLE FEDERAL AVIATION REGULATION.										

FAA Form 8130-7 (10/82) SEE RE VERSE SIDE

12/18/00 8130.2D CHG 2

FIGURE 4-3. SAMPLE FAA FORM 8130-6, AIRWORTHINESS APPLICATION FOR PRIMARY CATEGORY AIRCRAFT CERTIFICATED UNDER § 21.184(a) (FACE SIDE)

																							Form O.M.	Approved B. No. 2120-0018
of Tra	ansipo ral A	rtment rtation viation				PPLIC IRWO CERT	RTH	IINE	SS					INSTRUCTION use only. Sub space is required II and VI or VII	mit origi red, use	inal o an a	nly to ttach	an aut	horiz	zed FAA R	epres	enta	tive.	If additional
Aum	- NOEZ							RAFT BUILDER'S NAME (Make)					3. AIRCRAFT MODEL DESIGNATION 4. YR. MFR. FAA CODING											
μõ	N2EZ Flight Corp 5. AIRCR AFT SER IAL NO. 6. ENGINE BUILDER									· · ·				C-1A ENGINE MODEL	DEGIONI			1991						
I. AIRCRAFT DESCRIPTION		0002	AFT S	EKIAL	NO.	TCM		IILDEK	5 NAM	IE (N	лаке)			-360-ES	DESIGNA	ATION								
- 8	8. N O		R OF	ENGI	IES	9. PROI McC			ER'S	NAM	1E (Make	9)		PROPELLER MO A34C209	ODEL DE	SIGN	MOITA	N	1	1. AIRC RAF		Check	if app	licable)
	-	PLICA	TION		EBY MADE FOR: (Che								_				_	_					_	T
	Α	1			DARD AIRWORTHINES						1	ORMA	L	UTILITY	ACR	OBAT	IC	TRAN	SPO	RT	GLIDE	R		BALLOON
	B SPECIAL AIR WORTHINESS CERTI						TE (C	heck ap	oropria	ate ite	ems) Pr	imary C	Cate	gory										
				2	LIMITED																			
۾ ا				5	PROVISIONAL (In	dicate class	s)				1 2	CLASS												
ESTE	RESTRICTED (India									_	1			TURE AND PEST	CONTR	ΩI	2	ΙΔE	RIAL		3	_	ΔED	IAL ADVERTISING
l o						cate opera	tion(s)	to			4			Wildlife conserva			5			LLING	6	+	-	ATHER CONTROL
Z Z				5	be conducted)					- ⊢	7		_	E OF CARGO	100119		0	-		(Specify)	L	_	1,,,,	er con mor
II. CERTIFI CATION REQUESTED										1		_	H AND DEVELO	PMENT		2	_		UR BUILT	3		EXH	IBITION	
E C	S 4 4				EXPERIMENTAL (Indicate op	erati on	(s)		t	4	RACIN					5	CI	REW	TRAINING	Ť		-	SURVEY
H					to be conducted)					F	0	TO SH	IOW	COMPLIANCE	NITH FAR	۲	-				-	-	-	
=											1	FERRY	Y FL	IGHT FOR REPA	AIRS, ALT	ERA	RATIONS, MAINTENANCE OR STORAGE							
					SPECIAL FLIGHT I						2			E FROM AREA C										
	operation to be conduc complete Section VI of applicable on reverse s						for VII as 3 OPER 4 DELIV				OPER/	ATIC	ON IN EXCESS O	FMAXIM	IUM C	ERTI	FICATE	TAP	Œ-OFF WE	GHT				
						se side)				/ERING OR EXPORT 5 PRODUCTION FLIGHT TESTING														
	С	6			IDI E AIDIMODE IINEO	OFFICIO		O	DO1/5	_	6	CUSTOMER DEMONSTRATION FLIGHTS fed Operation" and "Standard" or "Limited," as applicable.)												
	-						_			κe	sirrciea C	регано	n a	na standard or	Limited,				 .					
					NER (As shown on certi	nicate of an	rcratt re	egistratio	on)				ADI	DRESS		II- I	DEAL	ER, CHE	CKF	HEKE				
	Fl	ME ight	Coı	p.									10 Lane Ave., Doby, TX 78907											
	В.				FICATION BASIS (Chec							dicated)												
Z Z	\times	AIRCRAFT SPECIFICATION OR TYPE CERTIFICATE DATA SHEET (Give No. and Revision No.) CE785									AIRWORTHINESS DIRECTIVES (Check if all applicable AD's complied with and give latest AD No.) 92-25													
IFICATION		AIR		T LISTI	NG (Give page num ber(s))							SUPPLEMENTAL TYPE CERTIFICATE (List number of each STC incorpor ated) N/A											
#	c.	AIRCI	RAFT	OPER/	ATION AND MAINTENA	NCE RECO	ORDS																	
OWNER'S CERTIFICATION	\times	COM	CK IF IPLIA 91.1	NCF W	RDS IN ITH	2.1	AIRFR	AME HO	OURS				EXPERIMENTAL ONLY (Enter hours flow n since issued or re newed) -0-					last certificate						
	Adr	ninistra	ition ir	accord	I hereby certify that I ance with Section 501 of or the airworthiness cert	the Feder	al Avia	tion Act	(or his	s age 58, ar	ent) of the	e aircrat	ft de	escribed above; that Aviation Regu	hat the ai	ircraft nd tha	is re	gistered aircrafth	with as b	the Federal een inspecte	Aviation de la notation de la notati	n is		
		TE OF /27/		јсатіо 3	DN			TLE (Pr			QA							NATURE e Quai	ity					
	Α.	THE A	RCR	AFT DE	SCRIBED ABOVE HAS	BEEN INS	PECTE	DAND	FOUN	ID AI	R WORT	HY BY:	(Co	omplete this section	on only if i	FAR p				es).				
NOE YOU	2			part 12 ificate l	n or 127 CERTIFICATE	HOLDER	(Give	3			ERTIFIC ertificate		MEC	CHANIC (Give			6		CER No.)	TIFICATED	REPAI	R ST	ATION	I (Give Certificate
IV. INSPECTION AGENCY VERFICATION	5		AIR	CRAFT	MANUFACTURER (Giv	ve name or	name or firm)																	
2 1	DA	TE				TITLE											SIG	NATURE						
		(Chec	k ALL	appli ca	able blocks in items A ar	nd B)							Τ	THE CERTIF	ICATE RI	EQUE	STEC)						
	Α.	find th	at the	ai rcrat	t described in Section I	or VII meet	s requi	rements	for:			4	t	AMENDMEN					RRE	NT AIRWOR	RTHINI	ESS C	ERTI	FICATE
₹ ĕ					cial flight permit under S	ection VII						\top \times	F.	AA INSPECTOR			I	FAA	ESI	GNEE				
V. FAA REPRESENTATIVE CERTIFICATION		was co		ed by:									С	ERTIFICATE HO	LDER UN	IDER:	I	FAR 6	i5	FAR 121		or 135	5	FAR 145
V. F RESB RTIFIC	DA	TE			DISTRICT OFFICE			DESIGN	EE'S S	iGN/	ATURE A	AND NO).				FA	A INSPEC	TOR	'S SIGNATI	JRE			
<u> </u>							4									1	B	ob God	oda	v				
	01	/27/	199	3	CE43													ob Go						

FAA Form 8130-6 (11-88) SUPERSEDES PREVIOUS EDITION

8130.2D CHG 2 12/18/00

FIGURE 4-3. SAMPLE FAA FORM 8130-6, AIRWORTHINESS APPLICATION FOR PRIMARY CATEGORY AIRCRAFT CERTIFICATED UNDER § 21.184(a) (CONTINUED) (REVERSE SIDE)

	lα.	MANU	JFACTURER								
					1						
	NA	AME			ADI	DRESS					
Z 9	\vdash				1						
ĔĒ	В.	PROD	UCTION BASIS (Check applicab	l e item)							
2 2			PRODUCTION CERTIFICATE	(Give production certificate number)							
8 =		\vdash	TYPE CERTIFICATE ONLY	,					_		
£ £											
VI. PRODUCTION FLIGHT TE STING			APPROVED PRODUCTION IN	SPE CTION SYSTEM							
	C.	GIVE (QUANTITY OF CERTIFICATES	REQUIRED FOR OPERATING NEEDS							
	-		APPLICATION	NAME AND TITLE (Print or type)							
	D/	A I E OF	APPLICATION	NAME AND THEE (TIME OF Gyps)			SIGNATURE				
	Δ	DESC	RIPTION OF AIRCRAFT								
	⊢										
	RE	GISTE	RED OWNER		ADI	DRESS					
	ы	III DEG	R (Make)		MO	DEL			_		
		JILDER	(Wake)		IVIC	DEL					
	SE	RIAL	NUMBER		REG	GISTRATION MARK					
	⊢				_						
	В.	DESC	RIPTION OF FLIGHT	CUSTOMER DEMONSTI	RATIO	ON FLIGHTS (Check if a	applicable)				
	FR	ROM			TO						
	_				_						
	VIA	Ą			DEF	PARTURE DATE		DURATION			
12											
Ĕ	\vdash				_			!			
Ę	C.	CREV		AIRCRAFT AND ITS EQUIPMENT							
₫.			PILOT CO-PIL	OT FLIGHT ENGINEER OTHER (Sp.	ecify)						
료	п	THE A	JRC RAFT DOES NOT MEET TH	HE APPLICABLE AIRWORTHINESS REQUIREMENT	SAS	FOLLOWS:					
8	١			ie / i reio/ibee / ii / i o i i i i i i i i i i i i i i	0710	. 0220110.					
E											
ă											
9											
8											
Z Z											
₹											
œ											
Ӗ											
0											
l iii											
ğ											
8											
<u>-</u>											
Σ											
VII. S PECIAL FLIGHT PERMIT PURPOSES OTHER THAN PRODUCTION FLIGHT TEST	H										
노	E.	THEF	OLLOWING RESTRICTIONS AF	RE CONSIDERED NECESSARY FOR SAFE OPERAT	ION:	(Use attachment if neces sary)					
<u>5</u>											
료											
₹											
S											
≡											
_											
	_	0EDT	FIG. 4 FIGN. 11								
	30	CEKI	re with Title 49 of the United Sta	am the registered owner (or his agent) of the aircraft tes Code 44101 et seq. and applicable Federal Aviation	ibed above; that the aircraft is re	gistered with the Fed sheen inspected and	deral Aviation Administration in				
	de	scribe	de with true 45 of the Offices of	tes code 44101 et seq. and applicable Federal Aviation	iikeg	diations, and that the arteratina	3 Deen mape cle u and	an worthy for the might			
	_		-								
	DA	ATE		NAME AND TITLE (Print or type)			SIGNATURE				
<u> </u>	\vdash	_									
1	1	/ A. C	perating Limitations and Marking	s in Compliance with FAR	G. Statement of Conformity, FAA Form 8130-9 (Attach when required)						
SS	Γ	91.3	1 as applicable								
불흔동	\vdash	۱.			H. Foreign Airworthiness Certification for Import Aircraft						
VIII. AIRWORTHINESS DOCUMENTATION (FAA use only)	L	B. C	current Operating Limitations Atta	iched		(Attach when required)					
S E S		C . F	ata, Drawings, Photographs, etc	. (Attach when required)	I. Previous Airworthiness Certificate Issued in Accordance with						
A u	\forall	-			-						
돌전조		1	current Weight and Balance Inform		1	FAR	CAR	(Original Attached)			
Ęŏ,	1	E. N	lajor Repair and Alter ation, FAA	Form 337 (Attach when required)	1/	J. Current Airworthiness Certifi	cate Issued in Accord	dance with			
Γ	F. This inspection Recorded in Aircraft Records				1^	FAR 21.184(a)		(Copy attached)			

FIGURE 4-4. SAMPLE FAA FORM 8130-7, SPECIAL AIRWORTHINESS CERTIFICATE FOR PRIMARY CATEGORY AIRCRAFT CERTIFICATED UNDER § 21.184(a) (FACE SIDE ONLY)

	UNITED STATES OF AMERICA DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION SPECIAL AIRWORTHINESS CERTIFICATE										
	CATEGORY	DESIGNATION PRIMARY CATEGO	PRY								
Α	PURPOSE]	N/A									
В	MANU-	NAME N/A									
В	FACTURER	ADDRESS N/A									
С	C FLIGHT FROM N/A										
C	FLIGHT	TO N/A									
D	N- 2EZ		SERIAL NO. F0002								
	BUILDER F	light Corp.	MODEL F-C-1A								
	DATE OF IS	SUANCE	EXPIRY Unlimited								
	OPERATING	S LIMITATIONS DATED	ARE PART OF THIS CERTIFICATE								
E SIGNATURE OF FAA REPRESENTATIVE DESIGNATION OR OFFICE NO.											
	Bob Gooday										
	Bob Gooday										

Any alteration, reproduction or misuse of this certificate may be punishable by a fine not exceeding \$1,000 or imprisonment not exceeding 3 years, or both. THIS CERTIFICATE MUST BE DISPLAYED IN THE AIRCRAFT IN ACCORDANCE WITH APPLICABLE FEDERAL AVIATION REGULATION.

FAA Form 8130-7 (10/82) SEE RE VERSE SIDE

FIGURE 4-5. SAMPLE FAA FORM 8130-6, AIRWORTHINESS APPLICATION FOR PRIMARY CATEGORY AIRCRAFT CERTIFICATED UNDER § 21.184(b) (FACE SIDE)

																							0.	M.B	No. 2	120-0018
U.S. E of Tra Feder Admi	al Av	iation			Al	PLIC RWC CER	DRTI	HINI	ESS					u	NSTRUCTION use only. Subm space is require I and VI or VII a	it origi d, use	inal on an att	ly to ar	authoriz	zed F.	AA Rep	reser	ntativ	e. I	f addition	onal
	1. RI			ON MAR	К	2. AIRC			DER'S	NAME	(Mak	ke)			RCRAFT MODE	DESIG	SNATIC		R. MFR.	FAA	CODING	3				
I. AIRCRAFT DESCRIPTION	5. AI			ER IAL N	0.	6. ENG	SINE BU		R'S NA	AME (/	Make)		7	7. EN	NGINE MODEL D	ESIGNA	ATION	1	-							
P.A	8. NI	JMBE	R OF	ENGINE	:S	9. PRC	PELLE	R BUI	LDER'	SNAN	ME (M	fake)	+	10. P	PROPELLER MOI	DEL DE	SIGNA	TION	1	1. AIR	CRAFTI	S (Ch	eck if	appl i	icable)	
	On	e				McC	Caule	ey					1	2A	34C209				<u> </u>	ίм	IPORT					
	APP	LICAT	TION	S HERE	BY MADE FOR: (Check	k applica	bl e iten	ns)						_										_		
	Α	1			ARD AIRWORTHINESS								RMAL		UTILITY	ACR	OBATIO	т :	RANSPO	RT	G	LIDER			BALLO	NC
	В		\preceq		LAIR WORTHINESS CI	ERTIFIC	ATE (0	Check a	approp	riate it	tems)	Prima	ary Ca	ateg	ory											
			ļ	2	LIMITED																					
e l				5	PROVISIONAL (Indi	cate clas	s)			-	1 2	_	LASS													
II. CERTIFICATION REQUESTED			ŀ							_	1	_	LASS		JRE AND PEST O	ONTR	OI.	2	AFRIAI			3	-1,	EDI	AL ADVE	RTISING
Βg				3	RESTRICTED (India	ate opera	ation(s,) to		ŀ	4				Vildlife conservation		OL.	5	PATRO		3	6	_		THER CO	
N N					be conducted)					ŀ	7	\rightarrow			OF CARGO	,		0	OTHER	(Sner	rify)		_			
ATIC			ŀ	+							1	_			AND DEVELOP	MENT		2	AMATE	• •	•••	3	E	XHIE	BITION	
틸				4	EXPERIM ENTAL (In to be conducted)	oficate op	oerati o	n(s)		Ī	4	R/	ACING	3				5	CREW	TRAIN	NING			икт.	SURVEY	,
CER					lo be conducted)						0	TC	O SHC	w c	COMPLIANCE W	TH FAF	₹									
Ĭ≟											1	FE	ERRY	FLIC	GHT FOR REPAI	RS, ALT	ERATI	ONS, M	AINTENA	NCE (OR STO	RAGE				
					SPECIAL FLIGHT PI operation to be cond			е		-	2	_			FROM AREA OF											
				8	complete Section Vi	or VII as	S			-	3	+			N IN EXCESS OF	MAXIM	UM CE		T							
					applicable on reverse	e side)				ŀ	6	-			G OR EXPORT			5	PRODU	JCTIO	ON FLIGH	IT TES	TING	i		
	С	6	-	MI II TIP	LE AIR WORTHINESS (CERTIFI	CATE	(Check	k ABON	\rightarrow					R DEMONSTRAT			dicable l								
		_	_		ER (As shown on certifi						20117010	за оро	10007	Car ic	a diamana a L	Jiiii Cu,			CHECK I	HERE						
		ne ght l			,				,				A	DDF	ress Chain Rd., l											
		_												59 (Chain Rd.,	Perry,	, KS	6/98	/							
	В. /				CATION BASIS (Check								ated)		AIDWODTHINE	CC DID I	FOTING	C (Ch-			I- ADI					
NO.	X				FICATION OR TYPE CI EU Rev. 3		AIED	MIASI	песі	(Give	NO. an	ш		X	AIRWORTHINE latest AD No.) 9										give	
IFICATI		N/A		T LISTIN	G (Give page num ber(s,))							>	\times	GL234A	LTYPE	CERT	FICATE	(List num	ber of	f each ST	°C inc o	orpora	ited)		
CERT	C. /	AIRCR	AFT	OPERAT	ION AND MAINTENAN	_																				
OWNER'S CERTIFICATION	X	CHE COM FAR	IPLIA	RECOR NCE WIT '3.	DSIN H	3.0	AIRFF	RAME	HOUR	:S							3	EXPERI issued o -0-	MENTAL (r renewed)	ONLY)	(Enter h	ours flo	ow n s	incel	last certi i	icate
≝	Admi airw	inistrat orthy a	ion in ind eli	accordar gible for	I hereby certify that I a nce with Section 501 of t the airworthiness certif	he Fede	ral Avi	ation A	er (or l	his ago 1958, a	ent) of and ap	f the ai pli cabl	rcraft le Fed	des	scribed above; tha I Aviation Regula	it the ai tions; a	nd that	the airc	rafthasb	the Fe een in:	ederal Av	iation and is				
	01/	27/1	199:			NAME Harr	y Joi	nes, I	Man	ager	r, Qı								Jones							
	A.T	HE AIF	RCRA	FT DES	CRIBED ABOVE HAS B	EEN INS	SPECT	ED AN	ID FOL	UND A	IR WC	ORTHY	′ BY: (Con	nplete this section	only if	FAR pa	rt 21 . 18	3(d) appli	es).						
NOT:	2			part 121 ficate No	or 127 CERTIFICATE I	HOLDER	(Give	1	3			IFICAT cate No		ECH	HANIC (Give			6	CER ³ No.)	TIFICA	ATED RE	PAIR :	STAT	ION	(Give Ce	rtificate
IV. INSPECTION AGENCY VERIFICATION	5		AIRC	RAFTN	IANUFACTURER (Give	name or	r firm)																			
-	DAT	E				TITLE												SIGNAT	URE							
					le blocks in items A and										THE CERTIFIC	ATERI	EQUES	TED								
	A. If	ind tha	at the	aircraft o	described in Section I or	VII mee	ts requ	ui reme i	nts for:	:			4		AMENDMENT	OR MO	DIFICA	TION O	FCURRE	NT All	RWORT	HINES	SCE	RTIF	ICATE	
HOL NOI		spection			al flight permit under Se	ction VII							M		AINSPECTOR			+ +	AA DESI				_			
SENT	DAT		ru dul	ou by.	DISTRICT OFFICE		П	DESIG	NFF'S	SSIGN	IATIIE	RE ANT) NO	CE	RTIFICATE HOLI	DER UN	IDER:		SPECTOR		AR 121, 1 GNATUR		135	_	FAR 145	
V. FAA REPRESENTATIVE CERTIFICATION	ME DATE DISTRICT OFFICE DESIGNEE'S SIGNATURE AND NO												_ 010		-											
, E.	02/	/09 /1	199:	3	CE45		4										1	Sue I								

FAA Form 8130-6 (11-88) SUPERSEDES PREVIOUS EDITION

FIGURE 4-5. SAMPLE FAA FORM 8130-6, AIRWORTHINESS APPLICATION FOR PRIMARY CATEGORY AIRCRAFT CERTIFICATED UNDER § 21.184(b) (CONTINUED) (REVERSE SIDE)

	_						
	A.1	MANUFACTURER					
	NA	ME		ADI	DRESS		
	Ι			1	-		
z o							
유를	В.	PRODUCTION BASIS (Check applic	abl e item)				
UC ES		PRODUCTION CERTIFICAT	E (Give production certificate number)				
OD I		TYPE CERTIFICATE ONLY					
VI. PRODUCTION FLIGHT TE STING		APPROVED PRODUCTION	NODE OTION OVOTEN				
≥ ⊑							
	C. (GIVE QUANTITY OF CERTIFICATE	S R EQUIRED FOR OPERATING NEEDS				
	DA	TE OF APPLICATION	NAME AND TITLE (Print or type)			SIGNATURE	
	_	DESCRIPTION OF AIRCRAFT					
	-			1			
	RE	GISTERED OWNER		ADI	DRESS		
	BU	ILDER (Make)		МО	DEL		
	OE!	RIAL NUMBER		DE/	GISTRATION MARK		
	J SEI	KIALNOWBEK		KE	SISTRATION WARK		
	_						
		DESCRIPTION OF FLIGHT	CUSTOMER DEMONST	RATIO	ON FLIGHTS (Check if a	pplicable)	
	FR	OM		TO			
	VIA			DE	PARTURE DATE		DURATION
	"	•			74CONE BALL		DOTATION.
ES	_						
Ε	C. (HE AIRCRAFT AND ITS EQUIPMENT				
호		PILOT CO-F	PILOT FLIGHT ENGINEER OTHER (Sp	ecify)			
표	D.	THE AIRCRAFT DOES NOT MEET	THE APPLICABLE AIRWORTHINESS REQUIREMENT	SAS	FOLLOWS:		
Ó							
5							
2							
õ							
Z							
₹							
R							
뿓							
0							
SES							
2							
Ä							
╘							
VII. S PECIAL FLIGHT PERMIT PUR POSES O THER THAN PRODUCTION FLIGHT TEST							
<u>-</u>	E. 1	THE FOLLOWING RESTRICTIONS	ARE CONSIDERED NECESSARY FOR SAFE OPERAT	TION:	(Use attachment if necessary)		
B.							
교							
Ι¥Γ							
Si .							
S.							
₹							
	-						
	F. 0	CERTIFICATION - I hereby certify that	t I am the registered owner (or his agent) of the aircraft	descr	ibed above; that the aircraft is re	gistered with the Fed	eral Aviation Admini stration in
			States Code 44101 et seq. and applicable Federal Aviation	n R eg	ulations; and that the aircraft has	s been inspected and	is air worthy for the flight
	des	cribed.					
	DA	TE	NAME AND TITLE (Print or type)			SIGNATURE	
						-	
	\vdash			_			
m	X	A. Operating Limitations and Markin	ngs in Compliance with FAR		G. Statement of Conformity, FA	A Form 8130-9 (Atta	ch when required)
N C	ľÌ	91.31 as applicable			H. Foreign Airworthiness Certif	cation for Import Airc	raft
nly)		B. Current Operating Limitations A	ttached	へ	(Attach when required)		
VIII. AIR WOR THINESS DOCUMENTATION (FAA use only)	\vdash			1	I. Previous Airworthiness Certif	cate Issued in Accor	dance with
WC ME	K	C. Data, Drawings, Photographs, e		-			
A P C P	K	D. Current Weight and Balance Info	rmation Available in Aircraft	Ь.	FAR	CAR	(Original Attached)
 DQ		E. Major Repair and Alteration, FA	A Form 337 (Attach when required)		J. Current Airworthiness Certifi	cate Issued in Accord	dance with
F. This country Broads & Alexander Broads							(C

FIGURE 4-6. SAMPLE FAA FORM 8130-7, SPECIAL AIRWORTHINESS CERTIFICATE FOR PRIMARY CATEGORY AIRCRAFT CERTIFICATED UNDER § 21.184(b) (FACE SIDE ONLY)

	UNITED STATES OF AMERICA DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION SPECIAL AIRWORTHINESS CERTIFICATE											
A	CATEGORY/DESIGNATION Primary Category											
	PURPOSE											
В	MANU-	NAME N/A										
"	FACTURER	ADDRESS N/A										
С	FLIGHT	FROM N/A										
	FLIGITI	TO N/A										
D	N- 345FT		SERIAL NO. FL009									
	BUILDER FI	ight LTD.	MODEL FL-1A									
	DATE OF ISS	SUANCE 02-09-1993	EXPIRY Unlimited									
	OPERATING	LIMITATIONS DATED	ARE PART OF THIS CERTIFICATE									
E	E SIGNATURE OF FAA REPRESENTATIVE DESIGNATION OR OFFICE NO.											
Sue Lacy NE58												
Sue Lacy												
	Any alteration, reproduction or misuse of this certificate may be punishable by a fine not exceeding \$1,000 or imprisonment not exceeding 3 years, or both. THIS CERTIFICATE MUST BE DISPLAYED IN THE AIRCRAFT IN ACCORDANCE WITH APPLICABLE FEDERAL AVIATION REGULATION.											

FAA Form 8130-7 (10/82) SEE REVERSE SIDE

FIGURE 4-7. SAMPLE FAA FORM 8130-6, AIRWORTHINESS APPLICATION FOR PRIMARY CATEGORY AIRCRAFT CERTIFICATED UNDER § 21.184(c) (FACE SIDE)

APPLICATION FOR AIRWORTHINESS CRETIFICATE INTERPRETATION MANUE LARGER TEACH MANUE L	_																								Approved B. No. 2120-0018
NABOTION TO NAME Central Comment Central C	of T	ran dera	sport IAvi	ation ation			Al	RWC	ORTHI	NES					u	ise only. Sub pace is requ	omit orig ired, use	inal or an at	nly to a	n authori	zed FAA	Represe	entat	ive.	If additional
SECRET SERIANO. SERVINEES OF ENGINES DEPONDED 172A-001 SERVINEES OF ENGINES DEPONDED 172A-001 A 1 STRONGHO ARMONTHRISES CERTIFICATE (Anni deponder imperiod in the control of the con			1. RE	GIST		ION MAF	RK	2. AIR	CRAFT BU	LDER'	S NAM	E (Ma	ke)				ELDESIG	GNATIC			FAA COI	DING			
One MCCRUTE IN CASE STANDARD ARROPORT (Check appricade intent) A 1 1 STANDARD ARROPORTH NESS CERTIFICATE (Check appricade intent) A 1 1 STANDARD ARROPORTH NESS CERTIFICATE (Check appricade intent) B 2 SECULA ARROPORTH NESS CERTIFICATE (Check appricade intent) 5 PROVISIONAL (Indicate class) 2 CLASS II 2 CLASS II 3 DESTRICTED (Indicate operatory) 4 RESTRICTED (Indicate operatory) 5 DRATIGUAL STANDARD (Indicate operatory) 4 RESTRICTED (Indicate operatory) 5 DRATIGUAL STANDARD (Indicate operatory) 4 RESTRICTED (Indicate operatory) 5 DRATIGUAL STANDARD (Indicate operatory) 6 DRATIGUAL STANDARD (Indicate operatory) 7 DRATIGUAL STANDARD (Indicate operatory) 8 DRATIGUAL STANDARD (Indicate operatory) 8 DRATIGUAL STANDARD (Indicate operatory) 9 DRATIGUAL STANDARD (Indicate operatory) 1 DRATIGUAL	μÑ	ŀ	_	_		DED IAL A	10			EDIC N	IANAT.	/8.4-1	,	_											
One MCCRUTE IN CASE STANDARD ARROPORT (Check appricade intent) A 1 1 STANDARD ARROPORTH NESS CERTIFICATE (Check appricade intent) A 1 1 STANDARD ARROPORTH NESS CERTIFICATE (Check appricade intent) B 2 SECULA ARROPORTH NESS CERTIFICATE (Check appricade intent) 5 PROVISIONAL (Indicate class) 2 CLASS II 2 CLASS II 3 DESTRICTED (Indicate operatory) 4 RESTRICTED (Indicate operatory) 5 DRATIGUAL STANDARD (Indicate operatory) 4 RESTRICTED (Indicate operatory) 5 DRATIGUAL STANDARD (Indicate operatory) 4 RESTRICTED (Indicate operatory) 5 DRATIGUAL STANDARD (Indicate operatory) 6 DRATIGUAL STANDARD (Indicate operatory) 7 DRATIGUAL STANDARD (Indicate operatory) 8 DRATIGUAL STANDARD (Indicate operatory) 8 DRATIGUAL STANDARD (Indicate operatory) 9 DRATIGUAL STANDARD (Indicate operatory) 1 DRATIGUAL	AIRCR		172	2A-	001			Con	tinental					(0-300-D										
APPLICATION IS HERREY MADE FOR: (Check appricate) among) A 1 STANDARD ARMORTHMSS CERTIFICATE (Check appricate) many) B 1 STANDARD ARMORTHMSS CERTIFICATE (Check appricate) many) B 2 STANDARD ARMORTHMSS CERTIFICATE (Check appricate) many) B 3 STANDARD ARMORTHMSS CERTIFICATE (Check appricate) many) B 4 CLASSI 2 CLASSI 3 DRESTRICTED (red cate operator(s) to 1 AGRICULTURE AND PRIST CONTROL 2 ABRIAL 3 ABRIAL ADMIRTISHING ADDIRECT (Middle conservation) 1 DRAMA (AGRICULTURE AND PRIST CONTROL 2 ABRIAL 3 ABRIAL ADMIRTISHING ADDIRECT (Middle conservation) 1 DRAMA (AGRICULTURE AND PRIST CONTROL 2 ABRIAL 3 ABRIAL ADMIRTISHING ADDIRECT (MIDDLE CONTROL 2 ABRIAL 3 ABRIAL ADMIRTISHING ADDIRECT (MIDLE CONTROL 2 ABRIAL 3 ABRIAL ADMIRTISHING ADDIRECT (MIDEL CONTROL 2 ABRIAL 3 ABRIAL ADMIRTISHING ADDIRECT (MIDLE CONTROL 2 ABRIAL 3 ABRIAL ADMIRTS (MIDLE CONTROL 2 ABRIAL 3 AB	-"	- 1			R O	ENGIN	ES	1		UILDEF	R'S NA	ME (A	Make)	- 1			ODEL DE	SIGNA	TION	1			heck	if app	licable)
		_													1C	172/EM					IMPOR	RT			
Second any work timbes certificate (Check appropriate ham) Printary Callagory		ŀ	_	_	TION					dianta d	noto aor		1		Г	T						I		Т	I
Base		ŀ	\rightarrow		\vee								1		_		ACR	OBATI		TRANSPO	ORT	GLIDE	R	_	BALLOON
1		ŀ			\triangle			EKTIFIC	AIE (Chec	каррго	ургане	iteris)	Prima	ary Ca	teg	ory									
S						2	LIMITED					1	CI	1224	_										
BESTRICTED (Indicate operation(4) b BESTRICTED (Indicate operation(4) b CONTROL 1 FOREST (Wildide corporation) 5 PATROLLING 3 MERINAL DIVERSITY 1 FOREST (Wildide corporation) 5 PATROLLING 6 WEATHER CONTROL 2 AMATEUR BULT 3 EAHBITON 4 EXPERIMENTAL (Indicate operation(4) 1 RESEARCH AND DEVELOPMENT 2 AMATEUR BULT 3 EAHBITON 5 CREW TRAINING MKT. SURVEY 6 DESCRIPTION OF THE (Species) MKT. SURVEY 1 FERRY FURSH TO REPARK ALIBEATION. MANY TENANCE OR STORAGE 5 SPECIAL FLIGHT PERMIT (Indicate 2 EVALUATE FROM AREA OF IMPERION COMPULANCE WITH FAR 5 SPECIAL FLIGHT PERMIT (Indicate 2 EVALUATE FROM AREA OF IMPERION COMPUTATION FLIGHT STORAGE 5 SPECIAL FLIGHT PERMIT (Indicate 2 EVALUATE FROM AREA OF IMPERION COMPUTATION FLIGHT STORAGE 5 SPECIAL FLIGHT PERMIT (Indicate 2 EVALUATE FROM AREA OF IMPERION COMPUTATION FLIGHT STORAGE 5 SPECIAL FLIGHT PERMIT (Indicate 2 EVALUATE FROM AREA OF IMPERION COMPUTATION FLIGHT STORAGE 5 SPECIAL FLIGHT PERMIT (Indicate 2 EVALUATE FLOW AREA OF IMPERION COMPUTATION FLIGHT STORAGE 5 SPECIAL FLIGHT PERMIT (Indicate 2 EVALUATE FLOW AREA OF IMPERION COMPUTATION FLIGHT STORAGE 6 CUSTOMER DEMONSTRATION FLIGHT STORAGE SPECIAL FLIGHT PERMIT (INDICATE SPECIAL FLIGHT PERMIT STORAGE SPECIAL FLIGHT PERMIT SPECIAL FLIGHT PERMI	B					5	PROVISIONAL (Indi-	cate clas	ss)			_	_												
SPECIAL FLIGHT PERMIT (Indicate goe aid in a bit conductar), then applicable on reverse side) C S MULTIPLE ARROWORTHINESS CERTIFICATE (Check ABOVE "Restricted Operation" in "Standard" or "Limited" as applicable) A. REGISTER ED OWNER (As shown on certificate of aircraft registration) F DEALER, CHECK HERE	JEST						+					\vdash	AC	GRICU	JLTL	JRE AND PES	T CONTR	OL	2	AERIA	L	3	Г	AER	IAL ADVERTISING
SPECIAL FLIGHT PERMIT (Indicate goe aid in a bit conductar), then applicable on reverse side) C S MULTIPLE ARROWORTHINESS CERTIFICATE (Check ABOVE "Restricted Operation" in "Standard" or "Limited" as applicable) A. REGISTER ED OWNER (As shown on certificate of aircraft registration) F DEALER, CHECK HERE	Eg					3		ate oper	ration(s) to			4	FC	OREST	Т (И	Vildlife conserv	ation)		5	PATRO	DLLING	6		WEA	ATHER CONTROL
SPECIAL FLIGHT PERMIT (Indicate goe aid in a bit conductar), then applicable on reverse side) C S MULTIPLE ARROWORTHINESS CERTIFICATE (Check ABOVE "Restricted Operation" in "Standard" or "Limited" as applicable) A. REGISTER ED OWNER (As shown on certificate of aircraft registration) F DEALER, CHECK HERE	N N					i l	De Conducted)					7	C	ARRIA	GE	OF CARGO			0	OTHER	R (Specify)		_		
SPECIAL FLIGHT PERMIT (Indicate goe aid in a bit conductar), then applicable on reverse side) C S MULTIPLE ARROWORTHINESS CERTIFICATE (Check ABOVE "Restricted Operation" in "Standard" or "Limited" as applicable) A. REGISTER ED OWNER (As shown on certificate of aircraft registration) F DEALER, CHECK HERE	Į.											1	RI	ESEAF	RCH	AND DEVELO	OPMENT		2	_		3		EXH	IBITION
SPECIAL FLIGHT PERMIT (Indicate goe aid in a bit conductar), then applicable on reverse side) C S MULTIPLE ARROWORTHINESS CERTIFICATE (Check ABOVE "Restricted Operation" in "Standard" or "Limited" as applicable) A. REGISTER ED OWNER (As shown on certificate of aircraft registration) F DEALER, CHECK HERE	Ĭ					4		idica te oj	peration(s)			4	R	ACING	}				5	CREW	TRAINING	3		мкт	SURVEY
SPECIAL FLIGHT PERMIT (Indicate goe aid in a bit conductar), then applicable on reverse side) C S MULTIPLE ARROWORTHINESS CERTIFICATE (Check ABOVE "Restricted Operation" in "Standard" or "Limited" as applicable) A. REGISTER ED OWNER (As shown on certificate of aircraft registration) F DEALER, CHECK HERE	SER											\vdash	_												
ARCAST CERTIFICATION ADDRESS AND AND MANTENANCE RECORDS	=					i l						\vdash									ANCE OR S	STORAGE			
DEPURENCE OF EXPORT S COMPLETE SCIENCY FOR A STATE S CONTROL S						i l						_	_												
The control of the co						8	complete Section Vi	lor VII a				_						иом с							
A. REGISTER ED OWNER (As shown on our lifecate of aircraft registration) B. A. REGISTER ED OWNER (As shown on our lifecate of aircraft registration) B. A. REGISTER ED OWNER (As shown on our lifecate of aircraft registration) B. A. REGISTER ED OWNER (As shown on our lifecate of aircraft registration) B. A. REGISTER ED OWNER (As shown on our lifecate of aircraft registration) B. A. REGISTER ED OWNER (As shown on our lifecate of aircraft registration) B. A. REGISTER ED OWNER (As shown on our lifecate of aircraft registration) B. A. REGISTER ED OWNER (As shown on our lifecate of aircraft registration) B. A. REGISTER ED OWNER (As shown on our lifecate of aircraft registration) B. A. REGISTER ED OWNER (As shown on our lifecate of aircraft registration) B. A. REGISTER ED OWNER (As shown on our lifecate of aircraft registration) B. A. REGISTER ED OWNER (As shown on our lifecate of aircraft registration) B. A. REGISTER ED OWNER (As shown on our lifecate of aircraft shown as indicated) A. A. REGISTER ED OWNER (As shown on our lifecate of aircraft shown as indicated) A. A. REGISTER ED OWNER (As shown on our lifecate of aircraft shown as indicated) A. A. REGISTER ED OWNER (As shown on our lifecate of aircraft shown as indicated) A. A. REGISTER ED OWNER (As shown on our lifecate of aircraft shown as indicated) A. A. A. REGISTER ED OWNER (As shown on our lifecate of aircraft shown as indicated) A. A. REGISTER ED OWNER (As shown on our lifecate of aircraft shown on our life aircraft shown on our life aircraft shown on our life at a life aircraft shown on our life at a life aircraft shown on our life at a life air and life at a life air and life at a life air and life air and life air and life aircraft shown on our life at a life air and lif						i l	applicable on reverse	e side)										101170	5	PROD	UCTION FI	LIGHT TE	STIN	IG	
A. REGISTER ED OWNER (As shown on certificate of aircraft registration) NAME Mr. S. Flint B. ARCRAFT CERTIFICATION BASIS (Chack applicable blocks and complete items as indicated) ARRORAFT SECIFICATION BASIS (Chack applicable blocks and complete items as indicated) ARRORAFT SECIFICATION BASIS (Chack applicable blocks and complete items as indicated) ARRORAFT SECIFICATION TYPE CERTIFICATE DATA SHEET (Give No. and latest AD No.) 92-26 ARCRAFT LISTING (Give page number(s)) N/A ARCRAFT LISTING (Give page number(s)) N/A C. ARCRAFT OPERATION AND MAINTENANCE RECORDS ARRORAFT LISTING (Give page number(s)) N/A D. CERTIFICATION - Inversely certify that I amther registered owner (or his agent) of the aircraft described above, that the aircraft is registered with the Federal Aviation Administration in accordance with Section 51 of the Federal Aviation Act of 1958, and applicable federal Aviation Regulations; and that the aircraft is sepastered with the Federal Aviation Act of 1958, and applicable federal Aviation Regulations; and that the aircraft is sepastered with the Federal Aviation Act of 1958, and applicable federal Aviation Regulations; and that the aircraft is sepastered with the Federal Aviation Regulations; and that the aircraft is registered with the Federal Aviation		ŀ	С	6		MULTIE	L AIR WORTHINESS	CERTIFI	ICATE (Che	ck ABC	OVF "R	\rightarrow							nlicable)					
MANE Mr. S. Flint ADDRESS 346 Oak Street, Livittown, FL 98712	\vdash	+			STER																HERE -			1	
B. ARCRAFT CERTIFICATION BASIS (Check applicable blocks and complete litems as indicated) ARCRAFT SPECIFICATION OR TYPE CERTIFICATE DATA SHEET (Give No. and latest AD No.) 92-26 ARCRAFT SPECIFICATION OR TYPE CERTIFICATE DATA SHEET (Give No. and latest AD No.) 92-26 ARCRAFT SPECIFICATION OR TYPE CERTIFICATE DATA SHEET (Give No. and latest AD No.) 92-26 ARCRAFT SPECIFICATION OR TYPE CERTIFICATE DATA SHEET (Give No. and latest AD No.) 92-26 ARCRAFT SPECIFICATION AND MAINTENANCE RECORDS ARCRAFT OPERATION AND MAINTENANCE RECORDS CHECKIF RECORDS IN STALL ARCRAFT LONG (Give page number(s)) D. CARTIFICATION - Inhereby certify that I amther registered owner (or his agent) of the aircraft described above; that the aircraft registered with the Federal Aviation Administration in accordance with Section 501 of the Federal Aviation Administration in accordance with Section 501 of the Federal Aviation Administration in accordance with Section 501 of the Federal Aviation Administration in accordance with Section 501 of the Federal Aviation Administration in accordance with Section 501 of the Federal Aviation Administration in accordance with Section 501 of the Federal Aviation Administration in accordance with Section 501 of the Federal Aviation Administration in accordance with Section 501 of the Federal Aviation Administration in accordance with Section 501 of the Federal Aviation Administration in accordance with Section 501 of the Federal Aviation Regulations; and that the air craft has been inspected and is airwortly and eligible for the air vorthiness certificate requested. DATE OF APPLICATION A. THE AIRCRAFT DESCRIBED ABOVE HAS BEEN INSPECTED AND FOUND AIRWORTHY BY: (Complete this section only If FAR part 21.183(d) applies). A. THE AIRCRAFT DESCRIBED ABOVE HAS BEEN INSPECTED AND FOUND AIRWORTHY BY: (Complete this section only If FAR part 21.183(d) applies). A. THE AIRCRAFT MANUFACTURER (Give name or firm) DATE A. THE CERTIFICATE REQUESTED A. Indid that the air craft described in Section I or VII meets req														A	DDF	RESS									
AIRCRAFT ISTING (Give page number(s)) N/A C. AIRCRAFT LISTING (Give page number(s)) N/A C. AIRCRAFT MANUFACTURE (Give page number(s)) N/A D. CERTIFICATION NAME AND TITLE (Print or type) N/A A. THE AIRCRAFT DESCRIBED ABOVE HAS BEEN INSPECTED AND FOUND AIR WORTHY BY: (Complete this section only If FAR part 21 . 182(d) applies). C. FAR part 121 or 127 CERTIFICATE HOLDER (Give page number or firm) DATE (Creack ALL applicable blocks in items A and 8) A. Indid that the air craft described in Section for VII meets requirements for: A. AIRCRAFT MANUFACTURER (Give name or firm) DATE (Creack ALL applicable blocks in items A and 8) A. Indid that the aircraft described in Section for VII meets requirements for: A. AIRCRAFT MANUFACTURER (Give name or firm) DATE (Creack ALL applicable blocks in items A and 8) A. Indid that the aircraft described in Section for VII meets requirements for: A. AIRCRAFT MANUFACTURER (Give name or firm) DATE (Creack ALL applicable blocks in items A and 8) A. Indid that the aircraft described in Section for VII me		L	Mr	. S.	Flir	ıt								3	46	Oak Stre	et, Liv	ıttow	n, Fl	. 98712	2				
ARCRAFT LISTING (Give page number(s)) N/A ARCRAFT LISTING (Give page number(s)) N/A C. ARCRAFT OPERATION AND MAINTENANCE RECORDS D. CERTIFICATION - I hereby certify that I amthe registered owner (or his agent) of the aircraft described above; that the aircraft is registered with the Federal Aviation Administration in accordance with Section 501 of the Federal Aviation Administration in accordance with Section 501 of the Federal Aviation Administration in accordance with Section 501 of the Federal Aviation Administration in accordance with Section 501 of the Federal Aviation Administration in accordance with Section 501 of the Federal Aviation Regulations; and that the aircraft has been inspected and is airworthy and eligible for the airworthiness certificate requested. DATE SCRIPTION SIGNATURE SIGNATURE SIGNATURE SIGNATURE SIGNATURE SIGNATURE SIGNATURE SIGNATURE AMENDMENT OR MODIFICATION OF CURRENT AIRWORTHINESS CERTIFICATE AMENDMENT OR MODIFICATION OF CURRENT AI		ŀ	B. /											ated)	_										
D. CERTIFICATION - Thereby certify that I am the registered owner (or his agent) of the aircraft described above; that the aircraft is registered with the Federal Aviation Administration in accordance with Section 50 1 of the Federal Aviation Act of 1958, and applicable Federal Aviation Regulations; and that the aircraft has been inspected and is airworthy and eligible for the airworth manufacture in the requised of the airworth manufacture in the airworth manufacture in the requised of the airworth manufacture in the airworth manufacture in the airworth manufacture in the requised of the airworth manufacture in the airworth manuf	N N	,	\times	AIR(Revi	SION I	T SPECI	.12 Rev. 35	ERTIFIC	CATE DATA	SHEE	T (Give	No. a	ind	>	\times	AIRWORTHIN latest AD No.)	92-26	ECTIV	ES (Che	ck if all ap	plicable AD	D's compl	ied w	ith an	d give
D. CERTIFICATION - Thereby certify that I am the registered owner (or his agent) of the aircraft described above; that the aircraft is registered with the Federal Aviation Administration in accordance with Section 50 1 of the Federal Aviation Act of 1958, and applicable Federal Aviation Regulations; and that the aircraft has been inspected and is airworthy and eligible for the airworth manufacture in the requised of the airworth manufacture in the airworth manufacture in the requised of the airworth manufacture in the airworth manufacture in the airworth manufacture in the requised of the airworth manufacture in the airworth manuf	IFICATI					T LISTIN	.IG (Give page num ber(s)))						>	\times			ECERT	IFICAT	E (List nun	nber of eac	h STC in	corpo	r ated)	
D. CERTIFICATION - Thereby certify that I am the registered owner (or his agent) of the aircraft described above; that the aircraft is registered with the Federal Aviation Administration in accordance with Section 50 1 of the Federal Aviation Act of 1958, and applicable Federal Aviation Regulations; and that the aircraft has been inspected and is airworthy and eligible for the airworth manufacture in the requised of the airworth manufacture in the airworth manufacture in the requised of the airworth manufacture in the airworth manufacture in the airworth manufacture in the requised of the airworth manufacture in the airworth manuf		Ī	C. /	AIRCE	RAFT	OPERA	FION AND MAINTENAN							•											
D. CERTIFICATION - Thereby certify that I am the registered owner (or his agent) of the aircraft described above; that the aircraft is registered with the Federal Aviation Administration in accordance with Section 50 1 of the Federal Aviation Act of 1958, and applicable Federal Aviation Regulations; and that the aircraft has been inspected and is airworthy and eligible for the airworth manufacture in the requised of the airworth manufacture in the airworth manufacture in the requised of the airworth manufacture in the airworth manufacture in the airworth manufacture in the requised of the airworth manufacture in the airworth manuf	WER'S	,	\times	CON	APLIA	NCE WI	RDS IN TH	3400	LAIRFRAM 0.0	E HOU	IRS							3	issued 15.2	IMENTAL or re newed	ONLY (En	ter hours	flow n	since	last certificate
O1/23/1993 Mr. S. Flint, Owner S. Flint, Owner S. Flint, Owner S. Flint O1/23/1993 Mr. S. Flint, Owner S. Flint O1/23/1993 Mr. S. Flint, Owner S. Flint O1/23/1993 Mr. S. Flint, Owner S. Flint O1/23/1993 Mr. S. Flin			Admi	nistra	ition ir	n accorda	nce with Section 501 of t	he Fede	eral Aviation																
2 FAR part 121 or 127 CERTIFICATE HOLDER (Give 3 CERTIFICATED MECHANIC (Give Certificate No.) 5 AIRCRAFT MANUFACTURER (Give name or firm) 5 DATE TITLE (Check ALL applicable blocks in Items A and B) A.1 find that the air craft described in Section I or VII meets requirements for: 8. Inspection for a special flight permit under Section VII was conducted by: DATE DATE DISTRICT OFFICE DESIGNEE'S SIGNATURE AND NO. FAA INSPECTOR FAA INSPECTOR FAA INSPECTOR'S SIGNATURE 1 Joe Mendez		- 1					N	Mr.	S. Flint	(Print	or type	9)													
AIRCRAFT MANUFACTURER (Give name or firm) DATE TITLE (Check ALL applicable blocks in Items A and B) A. I find that the air craft described in Section I or VII meets requirements for: B. Inspection for a special flight permit under Section VII was conducted by: DATE DISTRICT OFFICE DESIGNEE'S SIGNATURE AND NO. Certificate No.) No.)			A. TI	HE AI	RCR.	AFT DES	SCRIBED ABOVE HAS E	EEN INS	SPECTED A	ND FO	DUND	AIR W	ORTHY	/ BY: (Con	nplete this sect	ion only if	FAR p	art 21 . 1	83(d) appl	ies).				
A. I find that the air craft described in Section I or VII meets requirements for: B. Irspection for a special flight permit under Section VII was conducted by: DATE DISTRICT OFFICE DESIGNEE'S SIGNATURE AND NO. THE CERTIFICATE REQUESTED AMENDMENT OR MODIFICATION OF CURRENT AIRWORTHINESS CERTIFICATE FAA INSPECTOR FAA DESIGNEE CERTIFICATE HOLDER UNDER: FAA INSPECTOR'S SIGNATURE THE CERTIFICATE HOLDER UNDER AIRWORTHINESS CERTIFICATE THE CERTIFICATE HOLDER UNDER AI	NOE >	NO.	2		FAR	part 121 tificate N	or 127 CERTIFICATE I	HOLDER	R (Give	3					ECH	HANIC (Give			6		TIFICATE) REPAIR	R STA	ATION	(Give Certificate
A. I find that the air craft described in Section I or VII meets requirements for: A. I find that the air craft described in Section I or VII meets requirements for: A. I find that the air craft described in Section I or VII meets requirements for: A. I find that the air craft described in Section I or VII meets requirements for: A. I find that the air craft described in Section I or VII meets requirements for: A. I find that the air craft described in Section I or VII meets requirements for: A. I find that the air craft described in Section I or VII meets requirements for: A. I find that the air craft described in Section I or VII meets requirements for: A. I find that the air craft described in Section I or VII meets requirements for: A. I find that the air craft described in Section I or VII meets requirements for: A. I find that the air craft described in Section I or VII meets requirements for: A. I find that the air craft described in Section I or VII meets requirements for: A. I find that the air craft described in Section I or VII meets requirements for: A. I find that the air craft described in Section I or VII meets requirements for: A. I find that the air craft described in Section I or VII meets requirements for: A. I find that the air craft described in Section I or VII meets requirements for: A. I find that the air craft described in Section I or VII meets requirements for: A. I find that the air craft described in Section I or VII meets requirements for: A. I find that the air craft described in Section I or VII meets requirements for: A. I find that the air craft described in Section I or VII meets requirements for: A. I find that the air craft described in Section I or VII meets requirements for: A. I find that the air craft described in Section I or VII meets requirements for: A. I find that the air craft described in Section I or VII meets requirements for: A. I find that the air craft described in Section I or VII meets requirements for: A. I find that the air craft d	, INSPEC	VERIFICA	5		AIR	CRAFT	MANUFACTURER (Give	n ame o	or firm)	•										·					
A. I find that the aircraft described in Section I or VII meets requirements for: 4	_		DAT	E				TITLE											SIGNA	TURE					
B. Inspection for a special flight permit under Section VII Sec			(Chec	k ALL	appli cab	ole blocks in items A and	1B)							×	THE CERTIF	ICATE R	EQUE	STED						
		- 1	A.If	ind th	at the	aircraft	described in Section I or	r VII mee	ets requiren	nents fo	or:			4	`	AMENDMEN	IT OR MC	DDIFIC	ATION (F CURRE	NT AIRW	ORTHINE	SSC	ERTIF	FICATE
	INE	z l					al flight permit under Se	ction VII						X	FA	A INSPECTOR			П	FAA DESI	GNEE				
	FAA	5			nduc	.ed by:	T		<u> </u>					Ш	CE	RTIFICATE HO	DLDER UN	NDER:					r 135	Ш	FAR 145
	'RESE		DAT	E			DISTRICT OFFICE		DES	IGNEE	'S SIG	NATUI	KE ANI	NO.					FAAI	ISPECTOR	R 'S SIGNA	IURE			
	R. P.	- 1	01/	27/	199	3	SW NW67		4									1							

FAA Form 8130-6 (11-88) SUPERSEDES PREVIOUS EDITION

FIGURE 4-7. SAMPLE FAA FORM 8130-6, AIRWORTHINESS APPLICATION FOR PRIMARY CATEGORY AIRCRAFT CERTIFICATED UNDER § 21.184(c) (CONTINUED) (REVERSE SIDE)

	_												
	A.	MANU	JFACTURER										
1		AME			I AD	DRESS							
	INA	AIVIE			AD	DRESS							
Zΰ	_												
은 롣	В.	PROD	UCTION BASIS (Check applicate	le item)									
ည်း	-												
골 뿐			PRODUCTION CERTIFICATE	(Give production certificate number)									
모유			TYPE CERTIFICATE ONLY										
VI. PRODUCTION FLIGHT TE STING		-											
놀로			APPROVED PRODUCTION IN	SPECTION SYSTEM									
	_	GIVE I	DUANTITY OF CERTIFICATES	R EQUIRED FOR OPERATING NEEDS									
	_												
	DA	ATE OF	APPLICATION	NAME AND TITLE (Print or type)			SIGNATURE						
	_												
	A.	DESC	RIPTION OF AIRCRAFT										
	_	_			_								
	RE	GISTE	RED OWNER		AD	DRESS							
	\vdash				_								
	BU	JILDEF	R (Make)		MC	DEL							
	SE	RIAL	NUMBER		RE	GISTRATION MARK							
	_	DESC	RIPTION OF FLIGHT	CUSTOMER DEMONSTR	RATI	ON FLIGHTS (Check if a	nnolicable)						
			KIFTION OF FLIGHT				· //····						
	FR	ROM			то								
					_								
	VI	A.			DE	PARTURE DATE		DURATION					
E													
#		CDEV	A DECLUBED TO OBEDATE THE	E AID OD A ET AND ITO FOLLIDMENT									
보	С.	CREV		E AIRCRAFT AND ITS EQUIPMENT									
<u> 5</u>			PILOT CO-PIL	OT FLIGHT ENGINEER OTHER (Sp.	ecify)								
I II	ь	TUE /	IDC DAET DOES NOT MEET TO	HE APPLICABLE ALRWORTHINESS REQUIR EMENTS	e ve	EOITOWS:							
Z	١.			TE / W T E10/102E / W TO TO THINKE GO THE GOINT EINE FOT	0710	. 020110.							
Ĕ													
3													
ا ق													
2													
<u>-</u>													
l ≨													
T T													
œ													
≝													
6													
S													
S													
l E													
5													
₾													
Ē													
VII. S PECIAL FLIGHT PERMIT PURPOSES OTHER THAN PRODUCTION FLIGHT TEST													
-	E.	THEE	OLLOWING RESTRICTIONS AF	RE CONSIDERED NECESSARY FOR SAFE OPERAT	TION:	(Use attachment if neces sarv)							
토						(,,							
2													
E													
甘													
렸													
22													
o.													
₹													
1	ĺ												
	-												
	F.	CERT	IFICATION - I hereby certify that I	am the registered owner (or his agent) of the aircraft	desci	ribed above; that the aircraft is re	gistered with the Fed	deral Aviation Administration in					
	ac	cordan	ce with Title 49 of the United Sta	ites Code 44101 et seq. and applicable Federal Aviation	n R eg	ulations; and that the aircraft has	s been inspected and	lis airworthy for the flight					
	de	scr ibe	d.										
1	\vdash												
1	DA	ATE		NAME AND TITLE (Print or type)			SIGNATURE						
1	ĺ			1									
	L												
			hoorating Limitations and Maria	n in Compliance with EAR	Т	C Statement of Carfeering	A Form 9400 0 /***	anh uuhan raaviraali					
m	IX	A. C	perating Limitations and Marking	s in Compilance with FAK	\vdash	G. Statement of Conformity, FA	va rorm 8130-9 (Atta	ich when requirea)					
őΖ	ľÌ	່າ ^{ອ⊺.3}	1 as applicable		1	H Foreign Airworthinges C+	ication for Import A:						
불은중	\vdash	+			+	H. Foreign Airworthiness Certif	ioadurior Import Airo	of CHIL					
E F E	ĺ	B. C	urrent Operating Limitations Atta	ched	1	(Attach when required)							
R F S		1	Late Describes D' : 1	/Attack volume and discount		I. Previous Airworthiness Certif	i cate lequed in Accor	dance with					
N iii S	L	C. D	ata, Drawings, Photographs, etc	. (Attach when required)	\bot	I I TOVIOUS ATI WOT BILLIESS CETTI	I COLO ISSUEU III ACCOI	udince with					
& 5 ₹	IX	p. c	Current Weight and Balance Infor	nation Available in Aircraft	/	far 21.191(b)	CAR	(Original Attached)					
14 S F	ŕ	1			+								
VIII. AIR WOR THINESS DOCUMENTATION (FAA use only)	1	E. N	lajor Repair and Alteration, FAA	Form 337 (Attach when required)	1	J. Current Airworthiness Certifi	cate Issued in Accor-	dance with					
Γ	∇	_	his inspection Recorded in Aircra		ヘ	FAR 21.191(c)		(Copy attached)					

FIGURE 4-8. SAMPLE FAA FORM 8130-7, SPECIAL AIRWORTHINESS CERTIFICATE FOR PRIMARY CATEGORY AIRCRAFT CERTIFICATED UNDER § 21.184(c) (FACE SIDE ONLY)

	UNITED STATES OF AMERICA DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION SPECIAL AIRWORTHINESS CERTIFICATE											
A	CATEGORY/DESIGNATION Primary Category											
	PURPOSE											
В	MANU-	NAME N/A										
	FACTURER	ADDRESS N/A										
С	FLIGHT	FROM N/A										
	I LIGITI	TO N/A										
D	N- 7897T		SERIAL NO. 172A-001									
	BUILDER C	essna Aircraft Corp.	MODEL 172A									
	DATE OF IS	SUANCE 01-27-1993	EXPIRY Unlimited									
	OPERATING	LIMITATIONS DATED N/A	ARE PART OF THIS CERTIFICATE									
E	E SIGNATURE OF FAA REPRESENTATIVE DESIGNATION OR OFFICE NO.											
Jose Mendez NW24												
	Jose Mendez											
impris	Any alteration, reproduction or misuse of this certificate may be punishable by a fine not exceeding \$1,000 or imprisonment not exceeding 3 years, or both. THIS CERTIFICATE MUST BE DISPLAYED IN THE AIRCRAFT IN ACCORDANCE WITH APPLICABLE FEDERAL AVIATION REGULATION.											

FAA Form 8130-7 (10/82) SEE REVERSE SIDE

FIGURE 4-9. SAMPLE OPERATING LIMITATIONS FOR PRIMARY CATEGORY AIRCRAFT CERTIFICATED UNDER § 21.184(c)

PRIMARY CATEGORY AIRCRAFT OPERATING LIMITATIONS

Make: CESSNA Registration Number: N7897T Model: 172A Serial Number: 172A-001

- 1. No person may operate a primary category aircraft for carrying persons or property for compensation or hire
- 2. No person may operate a primary category aircraft that is maintained by the pilot-owner under an approved special inspection and maintenance program except:
 - a. The pilot-owner; or
- b. A designee of the pilot-owner, provided that the pilot-owner does not receive compensation for the use of the aircraft.
- 3. No person may operate a primary category aircraft certificated under FAR 21.184 unless within the preceding 12 calendar months the annual inspection required by FAR 91.409(a) has been performed. A 100-hour inspection required by FAR 91.409(b) is required if the aircraft is used for rental or flight instruction for hire. The aircraft may only be returned to service by persons authorized by FAR 43.7.
- 4. A primary category aircraft does not meet the requirements of applicable, comprehensive, and detailed airworthiness code as provided by Annex 8 to the Convention on International Civil Aviation. It may not be operated over any other country without the special permission of the country. Evidence of that permission must be carried aboard the aircraft along with the U.S. airworthiness certificate, and be made available to the FAA or CAA in the country of operation upon request.

FIGURE 4-10. SAMPLE FAA FORM 8130-6, AIRWORTHINESS APPLICATION FOR PRIMARY CATEGORY AIRCRAFT CERTIFICATED UNDER § 21.191(h) (FACE SIDE)

																							orm App D.M.B. N	proved lo. 2120-0018
Fed	eral A	artmer ortatio viatio ration	it n n			PPLIC IRWC	ORTH		SS					INSTRUCTION use only. Sub space is required If and VI or VII	mit origir red, use :	nal on an atta	ly to ar	n author	ized FA	A Re	prese	ıs; th	nese are	for FAA dditional
Aui	_		TRA	TION MAI	RK	2. AIRC	CRAFT	BU ILDEF	R'S NA	ME (/	Make)		3.	AIRCRAFT MODI	EL DE SIG	NATIO	N 4.1	R. MFR.	FAAC	ODIN	G			
FS		654				Nigh							N7-XRay 1990											
I. AIRCRAFT DESCRIPTION	1	XO9		SER IAL N	NO.	6. ENG		JILDER'S	NAME	E (Ma	ake)		7. ENGINE MODEL DESIGNATION IO-360-ES											
PES-	8.	NUME	ER C	F ENGIN	ES	9. PRO	PELLE	R BUILD	ER'S N	IAME	(Make	e)	10	D. PROPELLER MO	ODEL DES	SIGNA	TION	1	11. AIRC	RAFT	IS (Cr	neck i	f applicab	le)
	С	ne				McC	Caule	y					2	A34C209					IMP	ORT				
	A	PLIC	ATIO	IS HERI	EBY MADE FOR: (Chec	k applica	ble item	ıs)																
	A	1	Ļ	STAND	ARD AIRWORTHINES	SCERTIF	FICATE	(Indicate	catego	ory)	N	IORM.	AL	UTILITY	ACRO	BATIC	1	RANSPO	ORT	G	LIDEF	2	BA	LLOON
	В		\perp	SPECIA	AL AIR WORTHINESS C	ERTIFIC	ATE (C	Check app	oropriat	e iten	^{ns)} Pr	imary												
				2	LIMITED																			
				5	PROVISIONAL (Ind	icate clas	ss)			1	\perp	CLAS												
STE					,					2		CLAS					- 1							
l ä					RESTRICTED (India	cate opera	ation(s)	to		1	+			LTURE AND PEST		DL	2	AERIA			3	\rightarrow		ADVER TISING
1 2				3	be conducted)					7	-			(Wildlife conserva	ition)		5	-	OLLING		6		WEATHE	R CONTROL
CERTIFI CATION REQUESTED										1	+			GE OF CARGO	DMENT	-	0	_	R (Specify EUR BUI		3	_	FXHIBITI	ON
2				4	EXPERIMENTAL (II	ndicate op	oerati on	n(s)		4		RACI		CH AND DEVELO	FIVIEINI	-	5	_	/ TRAINI		3	_	MKT. SU	***
E					to be conducted)					0			-	V COMPLIANCE V	VITH FAR		-	OILLI	110		ш			
= S										1	+			LIGHT FOR REPA			ONS, M	AINTEN	ANCE OF	R STO	RAGE			
					SPECIAL FLIGHT P	ERMIT (Indi cate	,		2		EVAC	CUA	TE FROM AREA C	F IMPEN	DING	DANGE	۲						
				8	operation to be con- complete Section V					3		OPER	RAT	ION IN EXCESS O	FMAXIMU	ЈМ СЕ	RTIFIC	ATED TA	KE-OFF	WEIG	НТ			
					applicable on revers		•			4		DELI	/ER	ING OR EXPORT			5	PROD	UCTION	FLIGI	HT TES	STING	3	
	L									6	\rightarrow			IER DEMONSTRA										
	С	1		1	PLE AIR WORTHINESS		_			Restr	ricted C)pera ti	ion"	and "Standard" or	"Limited,"									
		REG	ISTE	R ED OWI	NER (As shown on certif	icate of a	ircraft r	egistratio	n)					200				CHECK				_		
		lary	Tes	t									7	DRESS 8 China Driv	e, Jum	ping	, TX	89765	5					
	В.	AIRC	RAF	T CERTIF	FICATION BASIS (Checi	k appli cab	ble bloc	ks and co	m plete	item	s as in	dicated	d)											
Z	\times	AIF	CRA		IFICATION OR TYPE C								>	AIRWORTHINI latest AD No.)	ess dir e 92-25	CTIVE	S (Che	ck if all ap	plicable	AD's	complie	ed wit	th and give	9
OWNER'S CERTIFICATION			CRA A	FT LISTIN	NG (Give page num ber(s	;))								SUPPLEMENT N/A	ALTYPE	CERTI	FICATE	(List nur	nber of e	ach S1	C inc	orpor	ated)	
#	C.	AIRC	RAF	T OPERA	TION AND MAINTENAN									•										
NER'S	×	√l cc	ECK MPLI R 91.	IF RECOI ANCE WI 173.	RDS IN TH	TOTAL 2.2	AIRFR	RAME HO	URS							3		MENTAL r re newe		Enter h	ours fl	ow n s	since last	certi ficate
<u>≡</u>	Ac	ministr	ation	in accorda	- I hereby certify that I ance with Section 501 of the airworthiness certi	the Feder	ral Avia	ation Act	(or his of 1958	agent B, and	t) of the I applic	e ai rcra cable F	aft ede	described above; the eral Aviation Regu	hat the air lations; ar	craft is	s registe the airc	ered with raft has b	the Fede	eral Av	viation and is			
		ATE OF		PLI CATIO	N			ITLE (Pri		pe)						- 1	SIGNAT Mary							
	Α.	THE A	AIRCE	RAFT DES	SCRIBED ABOVE HAS E	BEEN INS	SPECTE	D AND I	FOUND) AIR	WORT	HY BY	/: (C	Complete this section	on only if F	AR pa	rt 21 . 18	33(d) appi	ies).					
NOE: X	2			R part 12° rtificate N	1 or 127 CERTIFICATE o.)	HOLDER	R (Give	3			RTIFIC rtificate		ME	CHANIC (Give			6	CEF No.)	RTIFICAT	ED R	EPAIR	STA	TION (Giv	re Certificate
N. INSPECTION AGENCY	5		AIF	RCRAFT	MANUFACTURER (Giv	e name or	r firm)											'						
2 1		ATE				TITLE											SIGNAT	URE						
	_				ble blocks in items A and described in Section I o		ets recei	iremente	for:			L	1	THE CERTIF										
w	\perp						i eyu	ens	ю.			4	`	AMENDMEN	T OR MOI	DIFICA	1			VORT	HINES	SSCE	RTIFICA	TE
AHVE	В.			or a speci cted by:	ial flight permit under Se	ection VII						P	_	FAA INSPECTOR	I DER	DEC	-	AA DES		401	1.07	405	1	2.445
V. FAA PRESENT	B. Inspection for a special flight permit under Section VII was conducted by: DATE DISTRICT OFFICE DESIGNEE'S SIGNATURE AND 4						CERTIFICATE HOLDER UNDER: FAR 65 FAR 121, 127 or 135 FAR 145 FAA INSPECTOR'S SIGNATURE					< 145												
E		02/12/1993 CE34 4											1		Kim y Kim									

FAA Form 8130-6 (11-88) SUPERSEDES PREVIOUS EDITION

FIGURE 4-10. SAMPLE FAA FORM 8130-6, AIRWORTHINESS APPLICATION FOR PRIMARY CATEGORY AIRCRAFT CERTIFICATED UNDER § 21.191(h) (CONTINUED) (REVERSE SIDE)

	_													
	A.	MANU	JFACTURER											
		AME			1 400	DRESS								
	I N	AME			ADI	DRESS								
Z 0	\vdash													
₽₽	В.	PROD	UCTION BASIS (Check applicab	le item)										
SS				(Give production certificate number)										
ğΕ		-		(Give production certificate namber)										
VI. PRODUCTION FLIGHT TE STING			TYPE CERTIFICATE ONLY											
= =			APPROVED PRODUCTION IN	SPECTION SYSTEM										
> 11	-	-												
	C.	GIVE (QUANTITY OF CERTIFICATES I	R EQUIRED FOR OPERATING NEEDS -										
	D/	ATE OF	APPLICATION	NAME AND TITLE (Print or type)			SIGNATURE							
	⊢													
	Α.	DESC	RIPTION OF AIRCRAFT											
	-	-01075	DED OWNED		1.5	2250								
	K	GISTE	RED OWNER		ADI	DRESS								
	BI	III DES	R (Make)		МО	DEL								
	"	JILDER	(iviake)		IVIO	DEL								
	SE	RIAL	NUMBER		RF	GISTRATION MARK								
	"		TOMBER											
	ᆫ													
	Ιв.	DESC	RIPTION OF FLIGHT	CUSTOMER DEMONSTI	RATIO	ON FLIGHTS (Check if a	applicable)							
		ROM			то									
		COIVI			110									
	VI	A			DE	PARTURE DATE		DURATION						
	l "				DEI	ACTORE DATE		BOILATION						
ST	1				1			1						
"		0051	, DECLUDED TO OBED THE TUI	AIDADAET AND ITA FOLLIDAENT										
노	C.	CREV		AIRCRAFT AND ITS EQUIPMENT										
2			PILOT CO-PIL	OT FLIGHT ENGINEER OTHER (Spi	ecify)									
표	D.	THE A	IRC RAFT DOES NOT MEET TH	HE APPLICABLE AIRWORTHINESS REQUIREMENT	SAS	FOLLOWS:								
6														
- E														
Ž														
ö														
2														
N Z														
1 =														
œ														
뿔														
-														
S														
So														
<u>8</u>														
- ₹														
⊨														
VII. S PECIAL FLIGHT PERMIT PURPOSES OTHER THAN PRODUCTION FLIGHT TEST														
2	E	THEE	OU OWING PESTRICTIONS AS	RE CONSIDERED NECESSARY FOR SAFE OPERAT	ION:	(Hea attachment if naces can)								
노	١	111121	OLLOW ING RESTRICTIONS AT	RE CONSIDERED NECESSART FOR SAFE OF ERA	1014.	(Ose autoriment in necessary)								
의														
Ε.														
₹														
ñ														
S														
≓														
_														
	\vdash													
	F.	CERT	IFICATION - I hereby certify that I	am the registered owner (or his agent) of the aircraft	descr	ibed above; that the aircraft is re	gistered with the Fed	deral Aviation Administration in						
	ao	cordan	ce with Title 49 of the United Sta	tes Code 44101 et seq. and applicable Federal Aviation	n R eg	ulations; and that the aircraft ha	s been inspected and	d is airworthy for the flight						
	de	scribe	1											
	<u></u>	ATE		NAME AND TITLE (Print or type)										
	104	AIE.		HAMIL AND TITLE (FILITOT type)			SIGNATURE							
	1													
—					Т		4.5							
	ľ×	1 A. C	perating Limitations and Marking	s in Compliance with FAR	\vdash	G. Statement of Conformity, FA	AA Form 8130-9 (Atta	ach when required)						
S Z	ľÌ	91.3	1 as applicable			H. Foreign Airworthiness Certif	ication for Import Airc	craft						
불은중	H	P -	herront Opporating 11-sit-si Arr	n had	1	(Attach when required)	.cc.aurror impurt AITC	or said						
VIII. AIRWORTHINESS DOCUMENTATION (FAA use only)	\vdash	-	current Operating Limitations Atta											
S EN	Ι	C. F.	ata, Drawings, Photographs, etc	. (Attach when required)		I. Previous Airworthiness Certif	i cate Issued in Accor	dance with						
A W	\vdash	-			1									
₽ Z Z	\triangle	D. C	current Weight and Balance Inform	TRILLOH AVAITABLE IN AIRCRATE	\perp	FAR	CAR	(Original Attached)						
<u></u> 60 €	Ι -	E. N	lajor Repair and Alteration, FAA	Form 337 (Attach when required)	K,	J. Current Airworthiness Certifi	cate Issued in Accord	dance with						
>	∇	-	his inspection Recorded in Aircra		火	FAR 21.191(h)								
1	\sim	J F. T	nis inspection Recorded in Aircra	II RECORDS	1 '	FAR ∠1.191(n)		(Copy attached)						

FIGURE 4-11. SAMPLE FAA FORM 8130-7, SPECIAL AIRWORTHINESS CERTIFICATE, FOR PRIMARY CATEGORY AIRCRAFT CERTIFICATED UNDER § 21.191(h) (FACE SIDE ONLY)

	UNITED STATES OF AMERICA DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION SPECIAL AIRWORTHINESS CERTIFICATE											
Α	CATEGORY/DESIGNATION Experimental											
	PURPOSE (Operating Kit-Built Aircraft										
В	MANU-	NAME N/A										
	FACTURER	ADDRESS N/A										
С	FLIGHT	FROM N/A										
	FLIGITI	TO N/A										
D	N- 654GL		SERIAL NO. NX09									
	BUILDER N	ight-Test	MODEL N7-XRay									
	DATE OF ISS	SUANCE 02-12-1993	EXPIRY Unlimited									
_	OPERATING	LIMITATIONS DATED 02-12-1993	ARE PART OF THIS CERTIFICATE									
E	SIGNATURE OF FAA REPRESENTATIVE DESIGNATION OR OFFICE NO.											
Larry Kim CE34												
	Larry Kim											
impris	Any alteration, reproduction or misuse of this certificate may be punishable by a fine not exceeding \$1,000 or imprisonment not exceeding 3 years, or both. THIS CERTIFICATE MUST BE DISPLAYED IN THE AIRCRAFT IN ACCORDANCE WITH APPLICABLE FEDERAL AVIATION REGULATION.											

FAA Form 8130-7 (10/82) SEE REVERSE SIDE

FIGURE 4-12. SAMPLE FAA FORM 8130-7, SPECIAL AIRWORTHINESS CERTIFICATE AND OPERATING LIMITATIONS FOR PRIMARY CATEGORY AIRCRAFT CERTIFICATED UNDER § 21.191(h)



Small Airplane Directorate

U.S. Department of Transportation Federal Aviation Administration

EXPERIMENTAL - KIT BUILT AIRCRAFT OPERATING LIMITATION

MAKE: Night-Test MODEL: N7-XRay

S/N: NX09 REG. NUMBER: N654GL

- 1. This aircraft shall not be operated outside the assigned test area until it has been shown to comply with Federal Aviation Regulation (FAR) Section 91.319(b). A log book entry shall be made by the person finding compliance. Flight test area (describe area needed to test aircraft).
- 2. No person may operate this aircraft for other than the purpose for which the special airworthiness certificate was issued and the aircraft shall be operating in accordance with the applicable FAA Air Traffic and General Operating Rules.
- 3. No operations shall be conducted over densely populated areas or in congested airways, except for takeoffs and landings.
- 4. Operator of this aircraft shall notify the control tower of the experimental nature of this aircraft when operating into or out of airports with operating control towers.
- 5. Unless appropriately equipped for night and/or instrument flight in accordance with FAR 91.205, this aircraft shall be operated Day VFR only.
- 6. This aircraft shall contain the placards, markings, etc., required by FAR 91.9, as applicable.
- 7. No person may operate this aircraft for carrying persons or property for compensation or hire.
- 8. The person operating this aircraft shall advise each person carried of the experimental nature of this aircraft.
- 9. Aerobatic flights are limited to the aerobatics described in the aircraft log book or contained in placards are permitted.
- 10. Any major change to this aircraft, as defined by FAR 21.93, invalidates the special airworthiness certificate issued for this aircraft.
- 11. FAA-certificated mechanics holding an Airframe and Powerplant rating, and appropriately rated repair station may perform condition inspections in accordance with Appendix D of Part 43.
- 12. Condition inspections shall be recorded in the aircraft maintenance records showing the following or a similarly worded statement: "I certify that this aircraft has been inspected on (insert date) in accordance with the scope and detail of Appendix D of Part 43 and found to be in a condition for safe operation." The entry will include the aircraft total time-in-service, name, signature, and certificate type and number of the person performing the inspection.

Date	FAA Representative	Designation

FIGURE 4-13. SAMPLE PROGRAM LETTER

RESEARCH AND DEVELOPMENT/SHOWING COMPLIANCE APPLICANT PROGRAM LETTER SPECIAL AIRWORTHINESS CERTIFICATE

Registered Owner (as	shown on Certificate of Aircraft	Registration)	
NAME		ADDRESS	
2. Aircraft Description			
Registration Mark	2. Aircraft Build	er	3. Yr. Mfg.
4. Aircraft Serial No.	5. Aircraft Mode	el Designation	
3. Describe Program Pur	pose for which the aircraft is to	be used (FAR 21.	193(d)(1).
4. List estimated flight h	ours required for program.		Hrs.:
	of flights required for program.		No. Flts:
List estimated duration	n for programs (FAR 21.193(d)	(2)).	No. Days:
5. Describe the area (FAR 21.193(d)(3)).	as over which the flights a	are to be condu	ucted, and address of base operation
(D)	G 11 (11 1 11 1		
craft) (FAR 21.193(b)(4)		drawings or three-	-view dimensioned photographs of the air-
		T	
7. Date Na	ame and Title (Print or Type)		Signature

FIGURE 4-14. SAMPLE FAA FORM 8130-12, ELIGIBILITY STATEMENT, AMATEUR-BUILT AIRCRAFT

Form Approved O.M.B. NO. 2120-0018

		O.M.B. NO. 2120-001			
U.S. Department of Transportation Federal Aviation Administration	InstructionsPrint or type all information except signature. Submit original to an authorized FAA representative. Applicant completes Section I thru III. Notary Public completes Section IV.				
I REGISTERE	D OWNER INFORMATION				
Name(s)					
Address(es)					
No. & Street	City	State Zip			
Telephone No.(s)()	Rucinese				
Nesidence	Dusiness				
II AIRCE	RAFT INFORMATION				
Model	Engine(s) Make				
Assigned Serial No	Engine(s) Sorial No.(s)				
Assigned denai No.	Eligine(s) Seliai No.(s)				
Registration No.	Prop./Rotor(s) Make				
Aircraft Fabricated: Plar☐ K☐	Prop./Rotor(s) Serial No.(s)				
III MAJOR PORTION ELIC	GIBILITY STATEMENT OF APPLICANT				
I certify the aircraft identified in Section II above by————————————————————————————————————	me of Pers(671(∉a) se Print)				
for my (their) education or recreation. I (we) hat make them available to the FAA upon request.	ave records to support this stateme	nt and will			
N	NOTICE				
Whoever in any matter within the jurisdiction of knowingly and willfully falsifies, conceals or comaterial fact, or who makes any false, fictitious makes or uses any false writing or document knor fraudulent statement or entry, shall be fined rathan 5 years, or both (U.S. Code, Title 18, Sec. 1	vers up by any trick, scheme, or de or fraudulent statements or represe nowing the same to contain any fals not more than \$10,000 or imprisoned	vice a entations, or se, fictitious			
APPLICANT'S I hereby certify that all statements and answers complete and true to the best of my knowledge, of the basis for issuance of any FAA certificate Privacy Act statement that accompanies this for	, and I agree that they are to be con t me. I have also read and underst	sidered part			
Signature of Applicant I(n Ink)					
IV NOTAF	RIZATION STATEMENT				

FAA Form 8130-12(4-89)

FIGURE 4-15. SAMPLE FAA FORM 8000-38, FABRICATION/ASSEMBLY OPERATION CHECKLIST

FABRICATION/ASSEMBLY OPERATION CHECK	KLIST	
Company Name		
Address		<u></u>
Aircraft Model Document Name and Date		.
Type of Aircraft		_·
	A	ich ad Du
	Kit Manufacturer	ished By Amateur
FUSELAGE	Kit ivianuiacturei	Amaleui
FoseLage FoseLage FoseLage FoseLage		
Fabricate Special Tools of Fixtures Fabricate Longitudinal Members, Cores or Shells		
Fabricate Bulkheads or Cross Members		
Assemble Fuselage Basic Structure		
Fabricate Brackets and Fittings		
Install Brackets and Fittings		
7. Fabricate Cables, Wire, and Lines		
Install Cables, Wires, and Lines		
9. Fabricate Fuselage Covering or Skin		
10. Install Fuselage Covering or Skin		
11. Fabricate Windshield/Windows/Canopy		
12. Install Windshield/Windows/Canopy		
1,		
WINGS		
Fabricate Special Tools or Fixtures		
2. Fabricate Wing Spars		
3. Fabricate Wing Ribs or Cores		
Fabricate Wing Leading and Trailing Edge		
5. Fabricate Drag/Anti-Drag Truss Members		
6. Fabricate Wing Brackets and Fittings		
7. Fabricate Wing Tips		
8. Assemble Basic Wing Structures		
Install Wing Leading/Trailing Edge and Tips		
10. Install Drag/Anti-Drag Truss		
11. Fabricate Cables, Wires and Lines		
12. Install Cables, Wires, and Lines		
13. Fabricate Wing Covering or Skin		
14. Install Wing Covering or Skin		
15. Fabricate Wing Struts/Wires		
16. Install and Rig Wings and Struts		

FAA Form 8000-38 (12-91)

FIGURE 4-15. SAMPLE FAA FORM 8000-38, FABRICATION/ASSEMBLY OPERATION CHECKLIST (CONTINUED)

FABRICATION/ASSEMBLY OPERATION CHECKLIST (Cor Ki FLIGHT CONTROLS 1. Fabricate Special Tools or Fixtures 2. Fabricate Aileron Spars 3. Fabricate Aileron Ribs or Cores 4. Assemble Aileron Structure 5. Fabricate Aileron Leading and Trailing Edge 6. Assemble Aileron Leading and Trailing Edge 7. Fabricate Aileron Brackets and Fittings 8. Install Aileron Brackets and Fittings 9. Fabricate Aileron Covering or Skin 1. Fabricate Aileron Trim Tab 2. Install Aileron Trim Tab 3. Install Aileron Trim Tab 4. Fabricate Flap Ribs or Cores 6. Assemble Flap Leading and Trailing Edge 8. Assemble Flap Leading and Trailing Edge 9. Fabricate Flap Leading and Trailing Edge 9. Fabricate Flap Brackets and Fittings 10. Install Flap Brackets and Fittings 11. Fabricate Flap Leading and Trailing Edge 12. Install Flap Brackets and Fittings 13. Install Flap Brackets and Fittings 14. Fabricate Flap Covering or Skin 15. Fabricate Flap Covering or Skin 16. Install Flap Brackets and Fittings 17. Fabricate Flap Covering or Skin 18. Install Flap Covering or Skin 19. Install Flap Covering or Skin 19. Install Flap Covering or Skin 19. Install Brackets Elevator Ribs or Cores 19. Fabricate Elevator Ribs or Cores 19. Assemble Elevator Structure 19. Fabricate Elevator Leading and Trailing Edge	ntinued) Accomplis It Manufacturer	shed By Amateur
FLIGHT CONTROLS 1. Fabricate Special Tools or Fixtures 2. Fabricate Aileron Spars 3. Fabricate Aileron Ribs or Cores 4. Assemble Aileron Structure 5. Fabricate Aileron Leading and Trailing Edge 6. Assemble Aileron Leading and Trailing Edge 7. Fabricate Aileron Brackets and Fittings 8. Install Aileron Brackets and Fittings 9. Fabricate Aileron Covering or Skin 0. Install Aileron Covering or Skin 1. Fabricate Aileron Trim Tab 2. Install Aileron Trim Tab 3. Install and Rig Aileron 4. Fabricate Flap Spars 5. Fabricate Flap Ribs or Cores 6. Assemble Flap Structure 7. Fabricate Flap Leading and Trailing Edge 8. Assemble Flap Brackets and Fittings 10. Install Flap Brackets and Fittings 11. Fabricate Flap Covering or Skin 12. Install Flap Covering or Skin 13. Install Flap Brackets and Fittings 14. Fabricate Flap Covering or Skin 15. Install Flap Covering or Skin 16. Install Flap Covering or Skin 17. Fabricate Flap Covering or Skin 18. Install and Rig Flap 19. Install Flap Covering or Skin 19. Install Flap Covering or Skin 19. Install Flap Covering or Skin 19. Install Elevator Spars 19. Fabricate Elevator Spars 19. Fabricate Elevator Ribs or Cores 19. Assemble Elevator Structure	<u>'</u> _	•
FLIGHT CONTROLS 1. Fabricate Special Tools or Fixtures 2. Fabricate Aileron Spars 3. Fabricate Aileron Ribs or Cores 4. Assemble Aileron Structure 5. Fabricate Aileron Leading and Trailing Edge 6. Assemble Aileron Leading and Trailing Edge 7. Fabricate Aileron Brackets and Fittings 8. Install Aileron Brackets and Fittings 9. Fabricate Aileron Covering or Skin 0. Install Aileron Covering or Skin 1. Fabricate Aileron Trim Tab 2. Install Aileron Trim Tab 3. Install and Rig Aileron 4. Fabricate Flap Spars 5. Fabricate Flap Ribs or Cores 6. Assemble Flap Structure 7. Fabricate Flap Leading and Trailing Edge 8. Assemble Flap Brackets and Fittings 10. Install Flap Brackets and Fittings 11. Fabricate Flap Covering or Skin 12. Install Flap Covering or Skin 13. Install Flap Brackets and Fittings 14. Fabricate Flap Covering or Skin 15. Install Flap Covering or Skin 16. Install Flap Covering or Skin 17. Fabricate Flap Covering or Skin 18. Install and Rig Flap 19. Install Flap Covering or Skin 19. Install Flap Covering or Skin 19. Install Flap Covering or Skin 19. Install Elevator Spars 19. Fabricate Elevator Spars 19. Fabricate Elevator Ribs or Cores 19. Assemble Elevator Structure	it Manufacturer	Amateur
1. Fabricate Special Tools or Fixtures 2. Fabricate Aileron Spars 3. Fabricate Aileron Ribs or Cores 4. Assemble Aileron Structure 5. Fabricate Aileron Leading and Trailing Edge 6. Assemble Aileron Leading and Trailing Edge 7. Fabricate Aileron Brackets and Fittings 8. Install Aileron Brackets and Fittings 9. Fabricate Aileron Covering or Skin 0. Install Aileron Covering or Skin 1. Fabricate Aileron Trim Tab 2. Install Aileron Trim Tab 3. Install and Rig Aileron 4. Fabricate Flap Spars 5. Fabricate Flap Spars 6. Assemble Flap Structure 7. Fabricate Flap Leading and Trailing Edge 8. Assemble Flap Leading and Trailing Edge 9. Fabricate Flap Brackets and Fittings 10. Install Flap Brackets and Fittings 11. Fabricate Flap Covering or Skin 12. Install Flap Covering or Skin 13. Install and Rig Flap 14. Fabricate Elevator Spars 15. Fabricate Elevator Ribs or Cores 16. Assemble Elevator Structure		
2. Fabricate Aileron Spars 3. Fabricate Aileron Ribs or Cores 4. Assemble Aileron Structure 5. Fabricate Aileron Leading and Trailing Edge 6. Assemble Aileron Leading and Trailing Edge 7. Fabricate Aileron Brackets and Fittings 8. Install Aileron Brackets and Fittings 9. Fabricate Aileron Covering or Skin 0. Install Aileron Covering or Skin 1. Fabricate Aileron Trim Tab 2. Install Aileron Trim Tab 3. Install and Rig Aileron 4. Fabricate Flap Spars 5. Fabricate Flap Ribs or Cores 6. Assemble Flap Structure 7. Fabricate Flap Leading and Trailing Edge 8. Assemble Flap Leading and Trailing Edge 9. Fabricate Flap Brackets and Fittings 20. Install Flap Brackets and Fittings 21. Fabricate Flap Covering or Skin 22. Install Flap Covering or Skin 23. Install and Rig Flap 24. Fabricate Elevator Spars 25. Fabricate Elevator Ribs or Cores 26. Assemble Elevator Structure		
3. Fabricate Aileron Ribs or Cores 4. Assemble Aileron Structure 5. Fabricate Aileron Leading and Trailing Edge 6. Assemble Aileron Leading and Trailing Edge 7. Fabricate Aileron Brackets and Fittings 8. Install Aileron Brackets and Fittings 9. Fabricate Aileron Covering or Skin 0. Install Aileron Covering or Skin 1. Fabricate Aileron Trim Tab 2. Install Aileron Trim Tab 3. Install and Rig Aileron 4. Fabricate Flap Spars 5. Fabricate Flap Ribs or Cores 6. Assemble Flap Structure 7. Fabricate Flap Leading and Trailing Edge 8. Assemble Flap Leading and Trailing Edge 9. Fabricate Flap Brackets and Fittings 20. Install Flap Brackets and Fittings 21. Fabricate Flap Covering or Skin 22. Install Flap Covering or Skin 23. Install and Rig Flap 24. Fabricate Elevator Spars 25. Fabricate Elevator Ribs or Cores 26. Assemble Elevator Structure		
4. Assemble Aileron Structure 5. Fabricate Aileron Leading and Trailing Edge 6. Assemble Aileron Leading and Trailing Edge 7. Fabricate Aileron Brackets and Fittings 8. Install Aileron Brackets and Fittings 9. Fabricate Aileron Covering or Skin 0. Install Aileron Covering or Skin 1. Fabricate Aileron Trim Tab 2. Install Aileron Trim Tab 3. Install and Rig Aileron 4. Fabricate Flap Spars 5. Fabricate Flap Ribs or Cores 6. Assemble Flap Structure 7. Fabricate Flap Leading and Trailing Edge 8. Assemble Flap Leading and Trailing Edge 9. Fabricate Flap Brackets and Fittings 10. Install Flap Brackets and Fittings 11. Fabricate Flap Covering or Skin 12. Install Flap Covering or Skin 13. Install and Rig Flap 14. Fabricate Elevator Spars 15. Fabricate Elevator Ribs or Cores 16. Assemble Elevator Structure		
5. Fabricate Aileron Leading and Trailing Edge 6. Assemble Aileron Brackets and Fittings 8. Install Aileron Brackets and Fittings 9. Fabricate Aileron Covering or Skin 0. Install Aileron Covering or Skin 1. Fabricate Aileron Trim Tab 2. Install Aileron Trim Tab 3. Install and Rig Aileron 4. Fabricate Flap Spars 5. Fabricate Flap Ribs or Cores 6. Assemble Flap Structure 7. Fabricate Flap Leading and Trailing Edge 8. Assemble Flap Brackets and Fittings 9. Fabricate Flap Brackets and Fittings 10. Install Flap Brackets and Fittings 11. Fabricate Flap Covering or Skin 12. Install Flap Covering or Skin 13. Install and Rig Flap 14. Fabricate Elevator Spars 15. Fabricate Elevator Spars 16. Assemble Elevator Structure		
6. Assemble Aileron Leading and Trailing Edge 7. Fabricate Aileron Brackets and Fittings 8. Install Aileron Brackets and Fittings 9. Fabricate Aileron Covering or Skin 0. Install Aileron Covering or Skin 1. Fabricate Aileron Trim Tab 2. Install Aileron Trim Tab 3. Install and Rig Aileron 4. Fabricate Flap Spars 5. Fabricate Flap Ribs or Cores 6. Assemble Flap Structure 7. Fabricate Flap Leading and Trailing Edge 8. Assemble Flap Leading and Trailing Edge 9. Fabricate Flap Brackets and Fittings 20. Install Flap Brackets and Fittings 21. Fabricate Flap Covering or Skin 22. Install Flap Covering or Skin 23. Install and Rig Flap 24. Fabricate Elevator Spars 25. Fabricate Elevator Ribs or Cores 26. Assemble Elevator Structure		
6. Assemble Aileron Leading and Trailing Edge 7. Fabricate Aileron Brackets and Fittings 8. Install Aileron Brackets and Fittings 9. Fabricate Aileron Covering or Skin 0. Install Aileron Covering or Skin 1. Fabricate Aileron Trim Tab 2. Install Aileron Trim Tab 3. Install and Rig Aileron 4. Fabricate Flap Spars 5. Fabricate Flap Ribs or Cores 6. Assemble Flap Structure 7. Fabricate Flap Leading and Trailing Edge 8. Assemble Flap Leading and Trailing Edge 9. Fabricate Flap Brackets and Fittings 20. Install Flap Brackets and Fittings 21. Fabricate Flap Covering or Skin 22. Install Flap Covering or Skin 23. Install and Rig Flap 24. Fabricate Elevator Spars 25. Fabricate Elevator Ribs or Cores 26. Assemble Elevator Structure		
7. Fabricate Aileron Brackets and Fittings 8. Install Aileron Brackets and Fittings 9. Fabricate Aileron Covering or Skin 0. Install Aileron Covering or Skin 1. Fabricate Aileron Trim Tab 2. Install Aileron Trim Tab 3. Install and Rig Aileron 4. Fabricate Flap Spars 5. Fabricate Flap Ribs or Cores 6. Assemble Flap Structure 7. Fabricate Flap Leading and Trailing Edge 8. Assemble Flap Leading and Trailing Edge 9. Fabricate Flap Brackets and Fittings 20. Install Flap Brackets and Fittings 21. Fabricate Flap Covering or Skin 22. Install Flap Covering or Skin 23. Install and Rig Flap 24. Fabricate Elevator Spars 25. Fabricate Elevator Ribs or Cores 26. Assemble Elevator Structure		
8. Install Aileron Brackets and Fittings 9. Fabricate Aileron Covering or Skin 0. Install Aileron Covering or Skin 1. Fabricate Aileron Trim Tab 2. Install Aileron Trim Tab 3. Install and Rig Aileron 4. Fabricate Flap Spars 5. Fabricate Flap Ribs or Cores 6. Assemble Flap Structure 7. Fabricate Flap Leading and Trailing Edge 8. Assemble Flap Leading and Trailing Edge 9. Fabricate Flap Brackets and Fittings 20. Install Flap Brackets and Fittings 21. Fabricate Flap Covering or Skin 22. Install Flap Covering or Skin 23. Install and Rig Flap 24. Fabricate Elevator Spars 25. Fabricate Elevator Ribs or Cores 26. Assemble Elevator Structure		
9. Fabricate Aileron Covering or Skin 0. Install Aileron Covering or Skin 1. Fabricate Aileron Trim Tab 2. Install Aileron Trim Tab 3. Install and Rig Aileron 4. Fabricate Flap Spars 5. Fabricate Flap Ribs or Cores 6. Assemble Flap Structure 7. Fabricate Flap Leading and Trailing Edge 8. Assemble Flap Leading and Trailing Edge 9. Fabricate Flap Brackets and Fittings 20. Install Flap Brackets and Fittings 21. Fabricate Flap Covering or Skin 22. Install Flap Covering or Skin 23. Install and Rig Flap 24. Fabricate Elevator Spars 25. Fabricate Elevator Ribs or Cores 26. Assemble Elevator Structure		
O. Install Aileron Covering or Skin 1. Fabricate Aileron Trim Tab 2. Install Aileron Trim Tab 3. Install and Rig Aileron 4. Fabricate Flap Spars 5. Fabricate Flap Ribs or Cores 6. Assemble Flap Structure 7. Fabricate Flap Leading and Trailing Edge 8. Assemble Flap Leading and Trailing Edge 9. Fabricate Flap Brackets and Fittings 20. Install Flap Brackets and Fittings 21. Fabricate Flap Covering or Skin 22. Install Flap Covering or Skin 23. Install and Rig Flap 24. Fabricate Elevator Spars 25. Fabricate Elevator Ribs or Cores 26. Assemble Elevator Structure		
1. Fabricate Aileron Trim Tab 2. Install Aileron Trim Tab 3. Install and Rig Aileron 4. Fabricate Flap Spars 5. Fabricate Flap Ribs or Cores 6. Assemble Flap Structure 7. Fabricate Flap Leading and Trailing Edge 8. Assemble Flap Leading and Trailing Edge 9. Fabricate Flap Brackets and Fittings 20. Install Flap Brackets and Fittings 21. Fabricate Flap Covering or Skin 22. Install Flap Covering or Skin 23. Install and Rig Flap 24. Fabricate Elevator Spars 25. Fabricate Elevator Ribs or Cores 26. Assemble Elevator Structure		
2. Install Aileron Trim Tab 3. Install and Rig Aileron 4. Fabricate Flap Spars 5. Fabricate Flap Ribs or Cores 6. Assemble Flap Structure 7. Fabricate Flap Leading and Trailing Edge 8. Assemble Flap Leading and Trailing Edge 9. Fabricate Flap Brackets and Fittings 20. Install Flap Brackets and Fittings 21. Fabricate Flap Covering or Skin 22. Install Flap Covering or Skin 23. Install and Rig Flap 24. Fabricate Elevator Spars 25. Fabricate Elevator Ribs or Cores 26. Assemble Elevator Structure		
3. Install and Rig Aileron 4. Fabricate Flap Spars 5. Fabricate Flap Ribs or Cores 6. Assemble Flap Structure 7. Fabricate Flap Leading and Trailing Edge 8. Assemble Flap Leading and Trailing Edge 9. Fabricate Flap Brackets and Fittings 20. Install Flap Brackets and Fittings 21. Fabricate Flap Covering or Skin 22. Install Flap Covering or Skin 23. Install and Rig Flap 24. Fabricate Elevator Spars 25. Fabricate Elevator Ribs or Cores 26. Assemble Elevator Structure		
4. Fabricate Flap Spars 5. Fabricate Flap Ribs or Cores 6. Assemble Flap Structure 7. Fabricate Flap Leading and Trailing Edge 8. Assemble Flap Leading and Trailing Edge 9. Fabricate Flap Brackets and Fittings 20. Install Flap Brackets and Fittings 21. Fabricate Flap Covering or Skin 22. Install Flap Covering or Skin 23. Install and Rig Flap 24. Fabricate Elevator Spars 25. Fabricate Elevator Ribs or Cores 26. Assemble Elevator Structure		
5. Fabricate Flap Ribs or Cores 6. Assemble Flap Structure 7. Fabricate Flap Leading and Trailing Edge 8. Assemble Flap Leading and Trailing Edge 9. Fabricate Flap Brackets and Fittings 20. Install Flap Brackets and Fittings 21. Fabricate Flap Covering or Skin 22. Install Flap Covering or Skin 23. Install and Rig Flap 24. Fabricate Elevator Spars 25. Fabricate Elevator Structure		
6. Assemble Flap Structure 7. Fabricate Flap Leading and Trailing Edge 8. Assemble Flap Leading and Trailing Edge 9. Fabricate Flap Brackets and Fittings 20. Install Flap Brackets and Fittings 21. Fabricate Flap Covering or Skin 22. Install Flap Covering or Skin 23. Install and Rig Flap 24. Fabricate Elevator Spars 25. Fabricate Elevator Ribs or Cores 26. Assemble Elevator Structure		
7. Fabricate Flap Leading and Trailing Edge 8. Assemble Flap Leading and Trailing Edge 9. Fabricate Flap Brackets and Fittings 20. Install Flap Brackets and Fittings 21. Fabricate Flap Covering or Skin 22. Install Flap Covering or Skin 23. Install and Rig Flap 24. Fabricate Elevator Spars 25. Fabricate Elevator Ribs or Cores 26. Assemble Elevator Structure		
8. Assemble Flap Leading and Trailing Edge 9. Fabricate Flap Brackets and Fittings 20. Install Flap Brackets and Fittings 21. Fabricate Flap Covering or Skin 22. Install Flap Covering or Skin 23. Install and Rig Flap 24. Fabricate Elevator Spars 25. Fabricate Elevator Ribs or Cores 26. Assemble Elevator Structure		
9. Fabricate Flap Brackets and Fittings 20. Install Flap Brackets and Fittings 21. Fabricate Flap Covering or Skin 22. Install Flap Covering or Skin 23. Install and Rig Flap 24. Fabricate Elevator Spars 25. Fabricate Elevator Ribs or Cores 26. Assemble Elevator Structure		
20. Install Flap Brackets and Fittings 21. Fabricate Flap Covering or Skin 22. Install Flap Covering or Skin 23. Install and Rig Flap 24. Fabricate Elevator Spars 25. Fabricate Elevator Ribs or Cores 26. Assemble Elevator Structure		
21. Fabricate Flap Covering or Skin 22. Install Flap Covering or Skin 23. Install and Rig Flap 24. Fabricate Elevator Spars 25. Fabricate Elevator Ribs or Cores 26. Assemble Elevator Structure		
22. Install Flap Covering or Skin 23. Install and Rig Flap 24. Fabricate Elevator Spars 25. Fabricate Elevator Ribs or Cores 26. Assemble Elevator Structure		
23. Install and Rig Flap 24. Fabricate Elevator Spars 25. Fabricate Elevator Ribs or Cores 26. Assemble Elevator Structure		
24. Fabricate Elevator Spars 25. Fabricate Elevator Ribs or Cores 26. Assemble Elevator Structure		
25. Fabricate Elevator Ribs or Cores 26. Assemble Elevator Structure		
26. Assemble Elevator Structure		
28. Assemble Elevator Leading and Trailing Edge		
29. Fabricate Elevator Brackets and Fittings		
30. Install Elevator Brackets and Fittings		
81. Fabricate Elevator Covering or Skin		
22. Install Elevator Covering or Skin		
33. Fabricate Elevator Trim Tab		
34. Install Elevator Trim Tab		
25. Install and Rig Elevator		
36. Fabricate Rudder Spar		
87. Fabricate Rudder Ribs or Cores		
88. Assemble Rudder Structure		
89. Fabricate Rudder Leading and Trailing Edge		
10. Assemble Rudder Leading and Trailing Edge		
11. Fabricate Rudder Brackets and Fittings		
12. Install Rudder Brackets and Fittings		
3. Fabricate Rudder Covering or Skin		
44. Install Rudder Covering or Skin		
15. Fabricate Rudder Trim Tab		
6. Install Rudder Trim Tab		
Fr. Install and Rig Rudder		
7. motan and my model		

FAA Form 8000-38 (12-91)

FIGURE 4-15. SAMPLE FAA FORM 8000-38, FABRICATION/ASSEMBLY OPERATION CHECKLIST (CONTINUED)

CHECKLIST (CONTIN		
FABRICATION/ASSEMBLY OPERATION CHE	,	h - 4 D
	Accomplis	•
EMPENINA OF	Kit Manufacturer	Amateur
EMPENNAGE		
Fabricate Special Tools of Fixtures		
2. Fabricate Spars		
3. Fabricate Ribs or Cores		
4. Fabricate Leading and Trailing Edges		
5. Fabricate Tips		
6. Fabricate Brackets and Fittings		
7. Assemble Empennage Structures		
8. Install Leading/Trailing Edges and Tips		
9. Install Fittings		
10. Fabricate Cables, Wires, and Lines		
11. Install Cables, Wires and Lines		
12. Fabricate Empennage Covering or Skin		
13. Install Empennage Covering or Skin		
CANARD		
Fabricate Canard		
Assemble Canard Structure		
3. Install and Rig Canard		
LANDING GEAR		
Fabricate Special Tools or Fixtures		
2. Fabricate Struts		
3. Fabricate Brakes System		
Fabricate Retraction System		
5. Fabricate Cables, Wires and Lines		
6. Assemble Wheels, Brakes, Tires, Landing Gear		
7. Install Landing Gear System Components		
ÿ , , , ,		
PROPULSION		
Fabricate Special Tools of Fixtures		
Fabricate Engine Mount		
Fabricate Engine Cooling System/Baffles		
Fabricate Induction System		
Fabricate Exhaust System		
Fabricate Engine Controls		
Fabricate Engine Controls Fabricate Brackets and Fittings		
Fabricate Cables, Wires and Lines		
S. Fabricate Cables, Wires and Lines S. Assemble Engine	+	
Assemble Engine Install Engine and Items Listed Above	+	
	+	
11. Fabricate Engine Cowling		
12. Install Engine Cowling		
13. Fabricate Propeller		
14. Install Propeller		
15. Fabricate Fuel Tank		

FAA Form 8000-38 (12-91)

FIGURE 4-15. SAMPLE FAA FORM 8000-38, FABRICATION/ASSEMBLY OPERATION CHECKLIST (CONTINUED)

CHECKLIST (CONTIN		
FABRICATION/ASSEMBLY OPERATION CHEC	,	had Du
	Accomplis Kit Manufacturar	
DDODIII CION (Continue d)	Kit Manufacturer	Amateur
PROPULSION (Continued)	·	
16. Install Fuel Tank		
17. Fabricate Fuel System Components		
18. Install Fuel System Components		
MAIN DOTOD DDIVE OVETEMS AND CONTRO	OL MECHANICA(C)	
MAIN ROTOR DRIVE SYSTEMS AND CONTROL 1. Fabricate Special Static and Dynamic Main Rotor Rigging Tools	JL IVIECHAINISIVI(S)	
Pabricate Special Static and Dynamic Main Rotor Rigging Tools Fabricate/Assemble Main Rotor Drive Train		
Install Main Rotor Drive Train Assembly		
Install Main Rotor Drive Hall Assembly Fabricate/Assemble Main Rotor Shaft and Hub Assembly		
Install Main Rotor Shaft and Hub Assembly		
Align Main Rotor Shaft-Drive Train, Shaft and Hub Assembly		
7. Fabricate Main Rotor Rotating Controls		
Restricte Main Rotor Rotating Controls Install Main Rotor Rotating Controls		
Fabricate Main Rotor Non-Rotating Controls		
Rig Main Rotor Rotating and Non-Rotating Controls		
11. Fabricate Main Rotor Blades		
12 Install Main Rotor Blades on Rotor Hub		
Statically Balance and Rig Main Rotor System		
14. Dynamically Track and Balance Main Rotor System		
14. Dynamically Track and Balance Main Noter Cystem		
TAIL ROTOR DRIVE SYSTEMS AND CONTRO	DL MECHANISM(S)	
Fabricate Special Static Tail Rotor Rigging Tools		
Fabricate Vertical Trim Fin		
Install Vertical Trim Fin		
Fabricate Horizontal Stabilizer		
Install Horizontal Stabilizer		
Fabricate Tail Rotor Drive System		
7. Install Tail Rotor Drive System		
Fabricate Tail Cone or Frame		
Install and Rig Tail Cone or Frame		
10. Rig Vertical Trim Fin		
11. Fabricate Tail Rotor Shaft and Hub Assembly		
12. Install Tail Rotor Shaft and Hub Assembly		
13. Fabricate Tail Rotor Rotating and Non-Rotating Controls		
14. Rig Tail Rotor Rotating and Non-Rotating Controls		
15. Fabricate/Assemble Tail Rotor Blades		
16. Install Tail Rotor Blades		
17. Statically Balance and Rig Tail Rotor System		
18. Dynamically Track and Balance Tail Rotor System		
10. 2 j Olin Tradit and Balance Tall Hotel Oyotelli		

FIGURE 4-15. SAMPLE FAA FORM 8000-38, FABRICATION/ASSEMBLY OPERATION CHECKLIST (CONTINUED)

FABRICATION/ASSEMBLY OPERATION CHECKLIST (Continued)					
		Accomplished By			
		Kit Manufacturer	Amateur		
	OCKPIT/INTERIOR				
Fabricate Instrument Panel					
Install Instrument Panel and Instruments					
3. Fabricate Seats					
4. Install Seats					
5. Fabricate Electrical Wiring, Controls/Switches					
6. Install Electrical System Controls/Switches					
	TOTAL				
Comments		<u> </u>			
Printed Name	Cianatura	T	Date		
Fillited Natile	Signature		Dale		

FIGURE 4-16. SAMPLE LETTER TO KIT MANUFACTURER WHEN KIT IS DETERMINED ELIGIBLE



Federal Aviation Administration

Pioneer Aircraft Company 7897 Bold Place Carson City, VA 78098

Attn: John B. Maker President

Dear Mr. Maker:

The Federal Aviation Administration (FAA) has completed evaluation of the (<u>Aircraft Model</u>) kit. We have determined that the kit, as evaluated at your facility on (<u>date</u>) and defined by (<u>document name</u>, <u>date/revision</u>), meets the intent of Federal Aviation Regulations (FAR) § 21.191(g) because the major portion of a completed aircraft may be fabricated and assembled by person(s) who will undertake the construction project solely for their own education or recreation. The FAA Engineering and Manufacturing Branch, AFS-610, will notify the appropriate FAA field offices of the eligibility of the kit and add the kit to the listing of eligible amateur-built aircraft kits.

This evaluation should not be construed as meaning the kit or (<u>kit manufacturer's name</u>) is **FAA CERTIFIED**, **CERTIFICATED**, **OR APPROVED** and it is not appropriate to represent it as such. The kit may be represented as eligible for airworthiness certification under FAR § 21.191(g).

Copies of the kit parts list, identified by the date and/or revision, should be provided with kits supplied to customers. This will assist builders in identifying the configuration of the kits to personnel who will be responsible for determining the eligibility of the completed aircraft for airworthiness certification.

If ownership of the company changes, there is a change in the manufacturing facility location, or changes are made to the kit that affect fabrication and assembly operations, this FAA Manufacturing Inspection Office (MIO) shall be notified.

Failure to notify this MIO may result in removal of the kit from the listing of eligible amateur-built aircraft kits.

Sincerely,

Frank L. Brown Manager, Manufacturing Inspection Office

FIGURE 4-17. SAMPLE LETTER TO KIT MANUFACTURER WHEN KIT IS DETERMINED NOT ELIGIBLE



Federal Aviation Administration

Rocky Aircraft 67 Runway Ave. Panama, TX 65432

Attn: Joe C. Bath President

Dear Mr. Bath:

The Federal Aviation Administration (FAA) has completed evaluation of the (<u>Aircraft Model</u>) kit. We have determined that the kit, as evaluated at your facility on (<u>date</u>) and defined by (<u>document name</u>, <u>date/revision</u>), does not meet the intent of Federal Aviation Regulations § 21.191(g) because the major portion of a completed aircraft would not be fabricated and assembled by person(s) who will undertake the construction project solely for their own education or recreation.

The results of the evaluation were discussed with you on ($\underline{\text{date}}$) by ($\underline{\text{FAA representative}}$). You may adjust kit materials to comply with the major portion requirement and request reevaluation.

Sincerely,

Manager, Manufacturing Inspection Office

FIGURE 4-18. SAMPLE UNLIMITED FAA FORM 8130-7

	UNITED STATES OF AMERICA DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION SPECIAL AIRWORTHINESS CERTIFICATE					
Α	CATEGORY/	DESIGNATION RESTRICTED				
	PURPOSE A	AGRICULTURAL				
В	MANU-	NAME N/A				
	FACTURER	ADDRESS N/A				
С	FLIGHT	FROM SEE ATTACHED OPERATING LIM	ITATIONS N/A			
TO SEE ITEM D., REVERSE SIDE OF THIS CERTIFICATE N/A						
D	N- 32104		SERIAL NO. 2245			
	BUILDER B	ELL	MODEL 47G-4			
	DATE OF ISS	SUANCE 12-20-1993	EXPIRY Unlimited			
_	OPERATING	LIMITATIONS DATED 12-20-1993	ARE PART OF THIS CERTIFICATE			
E		FAA REPRESENTATIVE	DESIGNATION OR OFFICE NO.			
	Bart J. Johnso		NW-XX			
	Bart J. Johnson					
impris	Any alteration, reproduction or misuse of this certificate may be punishable by a fine not exceeding \$1,000 or imprisonment not exceeding 3 years, or both. THIS CERTIFICATE MUST BE DISPLAYED IN THE AIRCRAFT IN					
ACCC	DRDANCE WITH A	APPLICABLE FEDERAL AVIATION REGULATION.				

FAA Form 8130-7 (10/82) SEE REVERSE SIDE

FIGURE 4-19. SAMPLE FAA FORM 8130-7, SPECIAL FLIGHT PERMIT

UNITED STATES OF AMERICA DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION SPECIAL AIRWORTHINESS CERTIFICATE						
Α	CATEGORY	/DESIGNATION Special Flight Permit				
	PURPOSE I	Production Flight Testing				
В	MANU-	NAME The Boeing Company				
	FACTURER	ADDRESS P.O. Box 767, Renton, Washington	on 13567			
С	FLIGHT	FROM N/A				
	FLIGHT	TO N/A				
D	N- N/A		SERIAL NO. N/A			
	BUILDER N	/A	MODEL N/A			
	DATE OF ISS	SUANCE 07-15-1993	EXPIRY 07-15-1993			
	OPERATING	S LIMITATIONS DATED N/A	ARE PART OF THIS CERTIFICATE			
E		FAA REPRESENTATIVE	DESIGNATION OR OFFICE NO.			
	Sam T. Smith		NM-XX			
	Sam T. Smith					
Any alteration, reproduction or misuse of this certificate may be punishable by a fine not exceeding \$1,000 or imprisorment not exceeding 3 years, or both. THIS CERTIFICATE MUST BE DISPLAYED IN THE AIRCRAFT IN ACCORDANCE WITH APPLICABLE FEDERAL AVIATION REGULATION.						

FAA Form 8130-7 (10/82) SEE REVERSE SIDE

FIGURE 4-20. SAMPLE FAA FORM 337, MAJOR REPAIR AND ALTERATION

of Transportation Federal Aviati	US Department of Transportation Federal Aviation Administration								Form Approved OMB No. 2120-0020 For FAA Use Only Office Identification			
and disposit	tion of this form.	Γhis ι	entries. See FAR report is required 11 Federal Aviation	by law	(49 L	J.S.C. 1421). F						
	Make						Model					
1. Aircraft	Beech						D50A	15				
	Serial No. 4312						Nationality N93142	y and Registration	on M	ark		
	_	wn o	n registration certii	icate)				As shown on reg	aistra	ation certi	ificate)	
2. Owner	Ted K. Bauer		, rogicu aucir coru	.0010)			1496 Oak		y, our		outo	
					3. F	or FAA Use Or	nly					
	y operate this ai visions of 14 CF		ft, as altered here: art 21.	in, unle	ess it h	as within it an	appropria	te and current S	Spec	ial Flight	t Permit issu	ed
					4. U	nit Identification	on				5. Type	
Unit		Ма	ke			Model		Serial	No.		Repair	Alteration
AIRFRAME	(As described in Item 1 above)											
POWERPLAN ⁻	Г											
PROPELLER												
APPLIANCE	Туре											
AFFLIANCE	Manufacturer											
						nformity State	nent			0.0		
A. Agency's N	ame and Address	3			B. F	Kind of Agency	Marchaelle			C. Certifi	cate No.	
Flight Inc.						U.S. Certificated Mechanic Foreign Certificated Mechanic		1234				
419 Harford I					X	Certificated Repair Station			Airframe Class 3			
Windsor Lock	s, CT 06066					Manufacturer						
have be	en made in accor	danc	alteration made to e with the requirer rrect to the best o	nents o	f Part	43 of the U.S. F	4 above a ederal Avi	and described o ation Regulation	n the	e reverse d that the	or attachmer e information	nts hereto
Date					Sig	nature of Autho	rized Indivi	dual				
						Wilborn						
11/10/1993						Wilborn						
			rsons specified be	low, the	unit id	I for Return To dentified in item APPROVED	4 was inst	pected in the ma	nner	prescrib	ed by the	
X FAA	Flt. Standards		Manufacturer		1	pection Authoriz		Other (Spec	cify)			
BY FAA	Designee		Repair Station		Car	son Approved bada Airworthin	ess Group					
Date of Approv	val or Rejection		Certificate or Designation No.	,	Sig	nature of Autho	rized Indivi	dual				
11/12/1993					A.V	V. Reed						

FAA Form 337 (12-88)

CHAPTER 5. EXPORT APPROVAL PROCEDURES

SECTION 1. GENERAL INFORMATION

184. GENERAL. This chapter provides policy and procedures for the issuance of export approvals under the provisions of part 21, Subpart L, Export Airworthiness Approvals.

a. A number of countries have identified special requirements and conditions with which the FAA must comply. Compliance by the exporter is required before the importing country will validate the FAA export approval. AC 21-2, Export Airworthiness Approval Procedures, identifies these special requirements. Appendix 2 of AC 21-2 refers to the various countries requirements. Specific requirements are also identified in BASA Implementation Procedures for Airworthiness. In many cases, the documents referenced are not available in FAA district offices in a translated form. In such cases, it will be necessary for interested parties, not the FAA, to obtain these documents directly from the appropriate CAA.

NOTE: The most recent updates to AC 21-2 may be accessed via the internet at http://www.fedworld.gov. At the "Pick From List," select "FAA Information and Documents." At the FAA File Search Screen, enter "AC 21-2" and click on "Start Search." The AC is available in .PDF file format to be printed or downloaded.

- **b.** Special requirements are those administrative requirements that must be satisfied as a condition of shipment at the time of export. These may include the requirement for an FAA Form 8130-4, Export Certificate of Airworthiness, copies of log books, flight manuals, etc. When a product does not meet the special requirements of an importing country, the exporter must obtain a written statement from the CAA of that country indicating acceptance of the deviation. This statement must accompany each application for an Export C of A.
- **c.** When any requirements, in addition to the special requirements determined necessary by the importing country for its certification basis (e.g., changes to meet environmental conditions), cannot or will not be satisfied, the exporter must obtain a written statement from the CAA of the importing country indicating acceptance of the deviation. Exporters are encouraged to obtain information on additional requirements directly from the CAA of the importing country.
- **d.** In addition to a letter of acceptance from the importing CAA, the items not complied with shall be identified in the exceptions block of the Export C of A.
- **e.** Advisory Circular 21-23, Airworthiness Certification of Civil Aircraft, Engines, Propellers, and Related Products Imported to the United States, list the countries with which the United States has concluded formal bilateral agreements for reciprocal acceptance of Export Certificates of Airworthiness. AC 21-18 also includes the scope of each agreement. Special requirements listed in AC 21-2 include those submitted by some of the bilateral agreement countries, as well as special requirements submitted by countries with whom no formal agreement is in effect.

Par 184 Page 185

f. An export approval may be issued upon request for a product to be exported to a country not covered in either AC 21-2 or AC 21-18. Such an approval would certify compliance with U.S. airworthiness standards only. Assurance of compliance with any other requirements which the country may impose would be the responsibility of the exporter and importer.

- **g.** Form 8130-4 certifies compliance with applicable requirements but DOES NOT CONSTITUTE AUTHORITY TO OPERATE AN AIRCRAFT. When issued on new aircraft, the certification is considered original. When the aircraft is imported back into the United States, the certification is considered recurrent.
- **h.** Additional information and guidance concerning airworthiness certificates and/or flight permits can be found in AC 20-65, U.S. Airworthiness Certificates and Authorizations for Operation of Domestic and Foreign Aircraft.

185.-187. RESERVED.

SECTION 2. EXPORT APPROVALS

188. SECTION 21.323, ELIGIBILITY.

- **a.** Individuals engaged in exporting civil aircraft and related products, including individual aircraft owners and their representatives, are eligible for an export airworthiness approval for a Class I or Class II product provided all the applicable requirements are met. Only those manufacturers who have an FAA production approval and who employ a designated representative of the Administrator are eligible to obtain export airworthiness approvals for Class III products covered by their production approvals.
- (1) Section 21.323(a) allows any exporter, or his authorized representative, to obtain an export airworthiness approval for Class I or Class II products.
- (2) Section 21.323(b) allows any manufacturer to obtain an export airworthiness approval for a Class III product if the manufacturer:
- (a) Employs a designated representative of the Administrator who has been authorized to issue that approval.
 - (b) Holds either a PC, PMA, APIS, or a TSO authorization for that product.
 - **b.** Section 21.321 defines Class I, II, and III products as follows:
 - (1) A Class I product is a completed aircraft, aircraft engine, or propeller.
- (2) A Class II product is a major component of a Class I product (e.g., wing, fuselage, empennage assembly, landing gears, power transmission, control surface, etc.) the failure of which would jeopardize the safety of a Class I product; or any part, material or appliance approved and manufactured under a TSO system in the "C" series.
- (3) A Class III product is any part or component which is not a Class I or II product and includes standard parts, (e.g., those designated as AN, NAS, SAE, etc.). In general, Class III products are detail parts and minor assemblies whose failure would not jeopardize the safety of a TC product.
- **189. SECTION 21.325, EXPORT AIRWORTHINESS APPROVALS.** This section covers product(s) which may be approved for export. A sample export airworthiness approval form is shown in figure 5-1 of this order.
- **a.** Unassembled Aircraft. All new aircraft presented for export approval must be completely assembled and flight tested. Because compliance with the PC rules ensure conformity with the approved type design, aircraft certificated under parts 23 and 27, or CAR parts 3, 4a, and 6, as well as gliders manufactured under a PC, are exempt from this requirement. Under § 21.335(b) the exporter is required to furnish to the CAA the manufacturer's assembly instructions and the FAA-approved flight test check-off form. Care should be taken to ensure the importing country has no special requirements that prohibit exporting under these conditions.

Par 188 Page 187

NOTE: Section 21.325(b)(1) authorizes the issuance of Export Certificates of Airworthiness for new or used Class I products. A used U.S.-manufactured aircraft, which is foreign owned and located in the United States, would be eligible for an Export C of A subject to compliance with the other requirements of part 21, subpart L.

- b. Products Located in Countries Other Than the United States. Section 21.325(b)(2) permits the issuance of export approvals for used aircraft, aircraft engines, and propellers located in other countries. The applicable FAA international office is responsible for determining whether the acceptance of these products, any necessary FAA inspections, and the issuance of these approvals would create an undue burden on the FAA. This regulation was adopted as a service to U.S. citizens abroad to assist them in the legitimate disposal of used airworthy products to other countries. Caution should be exercised to ensure that this feature of the regulation is not used as a means of obtaining an easy "rubber stamp" approval. Before accepting an application, the responsible international office should assure itself that the applicant is able and willing to meet all applicable requirements.
- c. Issuance of Export Certificate of Airworthiness for U.S.-manufactured Aircraft Located in Another Country. The FAA will not issue Form 8130-4 to U.S.-manufactured aircraft located in another country unless it possesses a valid U.S. airworthiness certificate. The aircraft would then meet the requirements of § 21.325.
- **d.** The Date of Issuance of an Export Airworthiness Approval. The date of issuance of an export airworthiness approval is the date the product was inspected by the FAA, found to comply with the applicable requirements, and determined to be airworthy.
- **190. SECTION 21.327, APPLICATION.** Part I of Form 8130-1, Application for Export Certificate of Airworthiness, must be completed for Class I products. Part II of the application must be completed for Class II products. Class II products manufactured by a PC holder and Class III products produced by any PAH do not require a written application. In these cases, an oral application or request should be made to the FAA as specified in § 21.327. Chapter 8 of this order provides instructions for filling out the form.

191. ISSUANCE OF FAA FORM 8130-4, EXPORT CERTIFICATE OF AIRWORTHINESS, FOR CLASS I PRODUCTS (§ 21.329).

- **a.** An Export C of A may be issued only for COMPLETE Class I products shown by the applicant to meet the applicable requirements specified under § 21.329. Aircraft exported disassembled under the provisions of § 21.325(b)(1)(i), (ii), or (iii), are considered complete aircraft.
- **b.** Under the provisions of this section, new or used U.S.-manufactured aircraft do not require a standard airworthiness certificate or a special airworthiness certificate in the restricted or primary category to be issued prior to export, but are required to meet the requirements for such a certificate. Aircraft manufactured in another country are required to possess a valid U.S. standard airworthiness
- certificate issued under the provisions of § 21.183(c), or a special airworthiness certificate in the restricted category issued under the provisions of § 21.185(c). Any other aircraft not meeting the requirements for a standard airworthiness certificate, or a special airworthiness certificate in the restricted or primary category, are not

Page 188 Par 189

eligible to receive an Export C of A. For example, aircraft issued a special airworthiness certificate in the limited, provisional, or experimental category would not be eligible.

- 192. ISSUANCE OF FAA FORM 8130-3, AIRWORTHINESS APPROVAL TAG, FOR CLASS II PRODUCTS (§ 21.331). Instructions for completing Form 8130-3 are found in Order 8130.21.
- **193. ISSUANCE OF FORM 8130-3, AIRWORTHINESS APPROVAL TAG, FOR CLASS III PRODUCTS (§ 21.333).** Instructions for completing Form 8130-3 are found in Order 8130.21.
- **194. RESPONSIBILITIES OF EXPORTERS** (§ **21.335**). Each exporter receiving an export airworthiness approval for a product shall:
- **a.** Forward all documents and information necessary for proper operation of the products being exported to the CAA of the importing country.
- **b.** Forward the manufacturer's assembly instructions, and an FAA-approved flight test check-off form, to the CAA of the importing country when unassembled aircraft are being exported.
- **c.** Remove, or cause to be removed, any temporary installation incorporated on an aircraft for the purpose of export delivery and restore the aircraft to the approved configuration upon completion of the delivery flight.
- **d.** Secure all proper foreign entry clearances from all the countries involved when conducting sales demonstration or delivery flights.
- **e.** The FAA should remind the exporter of the regulatory responsibilities under § 21.335 when title to an aircraft passes or has passed to a foreign purchaser:
- (1) Request cancellation of the U.S. registration and airworthiness certificates, giving the date of the transfer of title, the name and address of the new owner, and the name of the country to which the aircraft is being exported.
- (2) Return the registration and airworthiness certificates, Form 8050-3 and Form 8100-2, to AFS-750.
- (3) Submit a statement certifying that the U.S. identification and registration numbers have been removed from the aircraft and send the statement to AFS-750 at the following address (§ 45.33):

Federal Aviation Administration Aircraft Registration Branch, AFS-750 P.O. Box 25504 Oklahoma City, OK 73125-0504

195. SPECIAL EXPORT AIRWORTHINESS APPROVAL FOR AIRCRAFT (§ **21.339**). The purpose of § 21.339 is to make it possible for an aircraft manufacturer, distributor, or exporter to

Par 191 Page 189

conduct sales demonstrations to prospective customers in various countries and to complete a sale without incurring the delay and expense of returning the aircraft to the United States for an FAA inspection and issuance of Form 8130-4. The following procedures apply for the issuance of an Export C of A under § 21.339:

- **a.** Prior to issuance of the Export C of A, the FAA should determine that all of the conditions specified in § 21.339 have been met. The FAA should ensure that the exporter has all of the documents and data required by each country listed on the itinerary readily available for immediate shipment. The applicant must meet the airworthiness requirements of those other countries before Form 8130-4 is issued.
- **b.** The FAA should screen the special requirements of each prospective importing country to determine that there is no conflict. If a conflict exists, the exporter should be advised that before an Export C of A can be issued, a statement must be obtained from each country affected, stating that the Export C of A would be validated if the aircraft is sold in that country. The statements should be referenced under "Exceptions" on Form 8130-4.
- c. Upon a satisfactory showing that all the requirements of § 21.339 have been met, the FAA should issue the Export C of A. The FAA should list all countries identified on the itinerary on the supplement supplied with Form 8130-4. The certificate should be dated with the date the FAA inspector or designee issued the certificate. The serial number of the Export Assignment Card should be placed in the top right hand corner of the Export C of A and supplement. The application form, Number Assignment Card, and a copy of the Export C of A should then be forwarded to AFS-750. When issuing the Export C of A, the exporter should be advised to make ink or typewriter deletions of all countries listed on the attached supplement EXCEPT the country where the aircraft is eventually sold. The country where the aircraft is sold will be entered by the exporter, in the appropriate space on Form 8130-4 in permanent type ink or by typewriter.

NOTE: The "E" card number should be recorded in the aircraft log book for future traceability of the Export C of A.

196. RESERVED.

197. DETERMINATION OF "NEW" AND "USED" PRODUCTS.

- **a.** The regulations do not define "new" or "used" products. There should be no problem in making this determination with uninstalled aircraft engines, propellers, or parts thereof, since any "time in service" makes them "used" products.
- **b.** An aircraft may be considered "new" as long as ownership is retained by the manufacturer, distributor, or dealer, if there is no intervening private owner, lease, or time sharing arrangements, and the aircraft has not been used in any pilot school and/or air taxi operation. An aircraft is still considered "new" regardless of the amount of operating time logged by the manufacturer, distributor, or dealer when:

Page 190 Par 195

(1) The aircraft is built from spare and surplus parts, even though the parts may be "used" as well as "new" and has been operated under an experimental airworthiness certificate only for the purpose of conducting flight tests for meeting the requirements set forth in § 21.127 by the applicant and by an FAA test pilot.

- (2) The aircraft has been maintained in accordance with the overhaul provisions of part 43 as applicable.
 - (3) The U.S. Export C of A reflects the information required by paragraph 198 of this order.
- **198. PREPARATION OF EXPORT C OF A.** Upon determining that the product is satisfactory, Form 8130-4 (GPO pad only) will be prepared in duplicate. When the product being exported is an aircraft, the make, model, and serial number of all engines and propellers installed thereon shall also be listed. If the product has been determined noncompliant with any requirements, the Export C of A should not be issued until the applicant corrects the deficiency or the exporter obtains a statement from the CAA of the importing country that it will validate the Export C of A. The noncompliance(s) should be listed on the Export C of A under "Exceptions," referencing the importing country CAA statements.

NOTE: This form does not constitute authority to operate an aircraft.

a. When other than a domestic manufactured Class I product is being exported to a third party
country with whom a bilateral agreement is in effect, the following statement will be inserted on the
Export C of A under the heading: "Exceptions:" "This (product) was not manufactured in the United
States and this certificate is not issued pursuant to the bilateral agreement providing for the reciprocal
recognition of airworthiness certificates between the United States and the Government of (name of
country) which has stated its willingness to accept this certificate under these conditions, as indicated in
their communication, reference dated"

NOTE: The above statement would not be applicable if certain bilateral agreements provide for "third party" country acceptance of airworthiness from an importing country which is not the country of manufacture.

- **b.** The Export C of A is an official U.S. Government document issued to other countries. All entries must be typewritten and no erasures or strikeovers are permitted. The original and duplicate copy of the certificate shall be signed in dark (preferably black) permanent type ink over the typed name of the FAA inspector or designee. The original will be given to the applicant or applicant's representative, together with those documents required with the product. Provisions should be made to preclude the Export C of A from becoming mutilated in transit.
- **c.** The following instructions apply to preparation of the Export C of A when temporary installations, such as provisions for extra fuel or navigational equipment, have been made for the purpose of export delivery:
- (1) If the Export C of A is issued AFTER the installation has been made, either by the manufacturer or by other persons, the following statement or equivalent should be inserted under

Par 197 Page 191

"Exceptions:" "A temporary (insert type of installation) has been installed in this aircraft in conformity with (insert drawing numbers, or other data to which conformity was shown) to facilitate its delivery flight. This certificate is valid when the temporary installation is removed." Copies of all referenced drawings and data should accompany the original Export C of A when it is submitted to the applicant or the applicant's representative.

- (2) If the Export C of A is issued PRIOR to making the temporary installation, such as at the manufacturer's plant, and the aircraft is then flown to another location for installation of the temporary equipment, the Export C of A should reflect the configuration of the aircraft at the time the certificate was issued. It then becomes the responsibility of the exporter and importer to secure whatever installation documents or data that may be required by the CAA of the country of import. The U.S. Export C of A should not be amended, reissued, or revalidated after original issuance.
- **d.** If there are no exceptions, type the word "None" after the word "Exception." If additional information is to be provided, it is permissible to type in the words "Additional Information" under the exceptions block. If the importing country has notified the FAA that it wishes to have a conforming statement to its approved design, a statement similar to the following example shall be included for new Class I products: "This product (insert aircraft, aircraft engine, or propeller) conforms to (insert importing country) approved Type Certificate Number (insert number)."

NOTE: The conforming statement does not apply to USED aircraft, aircraft engines, or propellers.

- **e.** The entries at the bottom of the form should be completed as follows:
- (1) Signature of Authorized Representative. The name and FAA authority of the person signing the form should be typed adjacent to or under the signature with the signature signed in black ink on the original and copy(s).
 - (2) Date. Enter the date the inspection of the aircraft was completed.
 - (3) District office or designee number.
 - (a) An FAA inspector should enter the district office designation.
- **(b)** An individual designee should enter the letters DMIR/DAR and the designation number.
- (c) An authorized representative under an ODAR should enter the letters ODAR and the designation number.
 - (d) A DOA should enter the name of the company and PC number.

Page 192 Par 198

199. APPROVAL OF MODIFICATIONS. In many instances, an aircraft that conforms to the type design may be modified prior to export, in accordance with the purchaser's requirements. The responsibility for approval and recording of such modifications would primarily be dependent upon the registration status of the aircraft. The following guidelines should be used in issuing Export C of A for modified aircraft.

- **a.** If the aircraft is modified while under U.S. registry, the applicable rules in parts 21 or 43 may apply. Depending upon whether any airworthiness certificate had been issued, any test flying which is necessary would require the issuance of an experimental certificate. The Export C of A would not require any listing of exceptions, since the aircraft would meet the appropriate FAA standards, whether the Export C of A is issued before or after the FAA-approved modifications.
- **b.** If the aircraft is modified after it has been removed from U.S. registry, approval of the modifications becomes the responsibility of the CAA of the country of registry or intended registry. The applicant or exporter is responsible for obtaining the approval. Any test flying that may be necessary would require the issuance of an SFA. The Export C of A would require no listing of exceptions if the aircraft conformed to the type design before the modifications; but if the Export C of A is issued after the aircraft is modified, then reference to the documentary evidence of non-U.S. approval should be shown under exceptions.

200. EXPORT CERTIFICATE OF AIRWORTHINESS NUMBER ASSIGNMENT CARD.

- **a.** Aeronautical Center Form 8050-72, Export Certificate Number Assignment Card, is a serial numbered card used to facilitate the identification and recording of the official export files in Oklahoma City and is accountable. These cards will be furnished by AFS-750 when requested by the Regional or Directorate Offices. The cards will be distributed to the district offices, who are accountable for controlling them (figure 5-3).
- **b.** This card is to be completed by the FAA from the information submitted in the application, ensuring that the identity of the product and the application agree. Insert the card serial number on both the application, Form 8130-1, and on Form 8130-4.
- **c.** Corrections may be made and information erased on this card if necessary. For example, if the card is completed for a product to be exported, and it is later decided not to export that product, the entered information on the card may be erased and the card used for another product.

NOTE: District offices will provide FAA designees with a supply of these cards as required. Regional/district offices will maintain accountability records of these cards.

Par 199 Page 193

201. ROUTING AND PROCESSING OF EXPORT FILES. After the issuance of Form 8130-4, the FAA inspector or designee must complete Part III of Form 8130-1. All files, including those processed by designees and DOA manufacturers, should be reviewed by the responsible district office prior to sending them to AFS-750. A file review will be indicated by a signature of the reviewing inspector, the district office number, and the date placed in Block 23 of Form 8130-1. If the file is not checked, omit the signature in Item 23, but fill in the district office number and date. The documents specified in paragraph 243 of this order, including special export files processed under § 21.339, will be forwarded promptly to AFS-750 as the final step in the certification process.

- **202. ISSUANCE OF EXPORT C OF A FOR AIRCRAFT TYPE CERTIFICATED IN MULTIPLE CATEGORIES.** To retain eligibility for issuance of an Export C of A as a standard aircraft after having been operated in the restricted category, the following would apply:
- **a.** While being operated in the restricted category, any changes made to the aircraft that are to be retained when in normal category operation, or any operations that are outside of the standard category operating limitations, must be approved in accordance with the regulations and procedures applicable to an aircraft having a standard airworthiness certificate.
- **b.** If the TCDS for an aircraft includes both standard and restricted category, and the maximum gross weight and/or other operating limitations for the restricted category are higher than that for standard category, the aircraft is NOT eligible for issuance of an Export C of A as a standard aircraft, after having been operated in the restricted category, unless:
- (1) The TCDS specifically states that the aircraft is eligible for operation in the standard category after having been operated at the limitations applicable to the restricted category, or
- (2) If the TCDS does not have such a note or other reference, the operations outside of the standard category operating limitations, including increased gross weight, had been approved as appropriate for an aircraft having a standard airworthiness certificate.
- **203. ISSUANCE OF EXPORT C OF A FOR RESTRICTED CATEGORY AIRCRAFT.** The following comment will be included under EXCEPTIONS: "The above is a Restricted Category Aircraft. This aircraft has not been determined to meet the international standards concerning the airworthiness of aircraft as provided for in Annex 8 to the Convention on International Civil Aviation."
- **204. CONTROVERSIAL INFORMATION.** If for any reason the previously listed information results in a controversy or is contrary to existing requirements, the exporter should be advised that the issue is to be settled between the exporter, importer, and the CAA of the importing country.

205.-207. RESERVED.

Page 194 Par 201

FIGURE 5-1. SAMPLE FAA FORM 8130-4, EXPORT CERTIFICATE OF AIRWORTHINESS

The United States of America Department of Transportation	
Federal Aviation Administration Washington, D.C.	No
Export Certificate of Sirwort	hiness
This certifies that the product iddentified below and particularly described in Specification(s) of Numbered has been examined and as of the date of this certificate, with a comprehensive and detailed airworthiness code of the United States Government, and requirements of the importing country filed with the United States Government, except as not attests to compliance with any agreements or contracts between the vender and purchaser, no an aircraft.	is considered airworthy in accordance is in compliance with those special ted below. This certificate in no way
Product:	
Manufacturer:	
Model:	
Serial No.:	
New Newly Overhauled	
Used Aircraft	
Country to which exported:	
Exceptions:	
Signature of Authorized Representative	
 Date	District Office or Designee Number

FAA Form 8130-4 (7-68) Formerly Form FAA 26

¹For complete aircraft, list applicable specification or Type Certificate Data Sheet numbers for the aircraft, engine, and propeller. Applicable specifications or Type Certificate Data Sheet, if not attached to this export certificate, will have been forwarded to the appropriate governmental office of the importing country.

FIGURE 5-2. FAA FORM 8130-1, APPLICATION FOR EXPORT AIRWORTHINESS APPROVAL (FACE SIDE)

US Department of Transportation Federal Aviation Administration	APP CERTIFI	Export Certificate	FORM APPROVE O.M.B. No. 2120-00				
INSTRUCTIONS - This application is to be submitted to an authorized FAA representative (one copy) when the product(s) to be exported is (are) presented for inspection. Use Part I for Class I products and Part II for Class II. For complete aircraft execute items 1 thorough 11, as applicable. For engines and propellers, omit item 5A. Part III is for FAA use only.							
Part I - APPL	ICATION FOR EXPORT CER	RTIFICATE OF	AIRWO	RTHINESS (Complete item	s 1-11)		
Application is mad	le for an export certificate of a			e product(s) described below w WLY OVERHAULED	hich is (are):		
Name and address of exporter 3. Name and address of foreign purchaser 4. Country of destination							
Description of proc	duct(s)					Operating	time (Hours)
Type (a)	Make and Model (b)	Identificati No.	tion	Serial Nos. (c)	FAA Spec. No. (d)	Since overhaul	(e) Total
A. AIRCRAFT							
B. ENGINES							
C. PROPELLERS							
Does the product comply with all applicable Federal Aviation Regulations, Airworthiness Directives, and other FAA requirements? YES NO (Explain in "Remarks")							
7. Have applicable special requirements of the importing country been complied with? YES NO (Explain in "Remarks")							
8. Date title passed of	or is expected to pass to forei	gn purchaser:					
	ment, preservation and packar of above methods:	aging methods u	used to p	orotect product(s) against corros	sion and damage	(List Spec. No.	or Title):
10. Remarks							
				ne above statements are true ar noted under item 10 "Remarks		s) described herei	n is
(are) airworthy and in condition for safe operation except as may be noted under item 10 "Remarks," above. Signature of applicant or authorized representative Title Date							

FAA Form 8130-1 (11-88) Supersedes Previous Edition

12/18/00 8130.2D CHG 2

FIGURE 5-2. FAA FORM 8130-1, APPLICATION FOR EXPORT AIRWORTHINESS APPROVAL (CONTINUED) (REVERSE SIDE)

Part II - APPLICATION FOR APPROVAL OF AERON	AUTICAL PARTS	(Complete items 12-20)		
12. Name and address of exporter	13. Name and	d address of foreign purchaser	14. Country of destination	
15. Parts are eligible for installation on	Make and model	Class I product	FAA Spec. No.	
16. The parts are (check one)	NEW	☐ NEWLY OVERHAULED		
17. The parts are described (Check one)			Invoice/packing sheet No.	
□ Below by name, part number, □ On the attached invoice or packing sheet, and quantity □ by name, part number and quantity □ □				
Name (a)		Part number (b)	Quantity (c)	
18. Have applicable special requirements of the importing country been complied with? YES NO (Explain in item 10 "Remarks")				
Preservation and packing methods used to protect parts a	gainst corrosion and	d damage (List Spec. No. or Title):		
Effective duration of above methods:				
20. EXPORTER'S CERTIFICATION -I certify that the foregoing	g statements are tru	e and that the parts described herein ar	e airworthy,	
conform to FAA approved design data, and are in condition		except as may be noted under item 10 "		
Signature of applicant or authorized representative	Title		Date	
Part III – APPROVAL (FOR FAA USE ONLY)	1			
21. It is considered that the product(s) described in Part I or Part and conform(s) to pertinent requirements except as noted		hy ck one)	Part I Part II	
Signature		Number	Date	
(Check one) DMIR DAR	☐ DELEGA	TION OPTION	FAA INSPECTOR	
22. Give quantity of approval tags, FAA Form 8130-3, issued f	or the parts describe	ed in Part II.	Quantity	
23. EXPORT FILE SPOT CHECKED BY:				
FAA Supervising Inspector		D.O. No.	Date	

8130.2D CHG 2 12/18/00

FIGURE 5-3. AC FORM 8050-72, EXPORT CERTIFICATE NUMBER ASSIGNMENT CARD

	TMENT OF TRANSPOR		CERTIFICATE N	O E 2	244100	
	RT CERTIFICATE N ASSIGNMENT CAR		DATE ISSUED			
PRODUCT		MANUFACTUR	RER	TYPE I	EXPORT C OF A TYPE DESIGN CONFORMITY	
MODEL		SERIAL NO.*f			EXCEPTIONS LISTED NO EXCEPTIONS CHECK ONE	
EXPORTER						
FOREIGN PUR	CHASER					
ADDRESS						
IDENTIFICATIO	ON MARK DISPLAYED-U.S					
EXPORT PROCESSED BY	SIGNATURE-AUTHORIZ	ED REP.	AGENCY REPRESENTED		AGENCY OR DESIGNEE NO.	
AC Form 80	50-72 (10-78)		* Indicate additional s	serial numbers	s on reverse side.	

CHAPTER 6. IMPORT PROCEDURES

SECTION 1. GENERAL INFORMATION

- **208. GENERAL.** This chapter provides guidance and procedures relating to U.S. airworthiness certification and approval of imported products. This includes aircraft, aircraft engines, propellers, components, appliances, and materials imported from other countries with which the United States has a bilateral agreement.
- **a.** Aircraft and their related products, manufactured outside the United States, that are being imported into the United States for FAA airworthiness acceptance must be accompanied by one of the following:
 - (1) An Export C of A.
- (2) A certifying statement issued by the CAA of the country of manufacture, or by the exporting CAA in the case of a "third country," as addressed in paragraph 213 of this order.
- **b.** Any deviations from the FAA-approved design must be noted on the certifying statement. Any deviations must be resolved by the installer before the product is eligible for installation on any U.S.-registered aircraft or product thereof.
- **c.** The importing document for Class II and III products issued from another country should contain essentially the same information as Form 8130-3, and will be signed by a person or organization authorized by the CAA of the exporting country.
- **d.** FAA airworthiness approvals for civil aeronautical products imported into the United States are processed in the following manner:
- (1) Issuance of U.S. airworthiness certificates for completed aircraft are processed in accordance with the procedures outlined in paragraph 211 of this order.
- (2) Aircraft engines, propellers, materials, parts, and appliances are considered to meet the requirements of the CFR when the product is accompanied by a certification from the appropriate CAA, certifying the product conforms to the FAA-approved design and is in a condition for safe operation as outlined in paragraph 218 of this order.
- **e.** The FAA requirements for the approval of civil aeronautical production articles imported to the United States are set forth in the following regulations.
 - (1) Part 21, subpart H, establishes the procedural requirements for U.S. airworthiness certification.

Par 208 Page 199

8130.2D 9/30/99

(a) Section 21.183(c) is the basis for issuing a U.S. standard airworthiness certificate for imported aircraft which have been type certificated by the FAA under the provisions of § 21.29. The regulatory basis for issuance of U.S. standard airworthiness certificates to all other aircraft imported into the United States is § 21.183(d). An example is an aircraft type certificated under the provisions of § 21.21, and manufactured abroad under a licensing agreement.

- **(b)** Section 21.185(c) is the basis for issuing a restricted category airworthiness certificate for aircraft imported into the United States which have been type certificated by the FAA under the provisions of § 21.29.
- (2) Part 21, subpart N, establishes the procedural requirements for airworthiness approval or acceptance of aircraft engines, propellers, materials, parts, and appliances manufactured outside the United States.
- (3) Part 21, subpart O, Technical Standard Order Authorizations, establishes procedures for TSO products, and § 21.617 covers "letter of TSO design approval" for import appliances.
- **f.** An Export C of A, or other certifying statements, issued by either the FAA or CAA, assists in airworthiness certification on behalf of the new country of registry. This export certificate does not constitute an "airworthiness certificate" within the meaning of § 44704(d) or § 44711(a)(1) of Title 49. However, issuance of an Export C of A does constitute original certification.
- **g.** Modifications or repairs made to an aircraft or related product subsequent to export certification by the CAA may invalidate that certification unless the modifications or repairs are approved by the FAA.

209.-210. RESERVED.

12/18/00 8130.2D CHG 2

SECTION 2. IMPORT AIRCRAFT

- **211. REQUIREMENTS FOR U.S. AIRWORTHINESS CERTIFICATION.** The FAA regulations concerning issuance of airworthiness certificates for U.S.-registered aircraft (new or used) are contained in part 21, subpart H. Most of the requirements apply equally to aircraft that were manufactured outside the United States. Any additional requirements called out in parts 36, 39, 45, 47, 49, and 91 must also be met before the aircraft can be certificated. These include:
- **a.** United States Registration. A U.S. registration application must be completed and submitted, and nationality and registration markings must be applied, before a U.S. airworthiness certificate may be issued. Since these are statutory requirements, the FAA can not issue an exemption from this requirement. Evidence of de-registration from the exporting country and U.S. registration is required prior to the issuance of a U.S. airworthiness certificate. The requirements for U.S. registration are in part 47, recording of aircraft titles and security documents are covered in part 49, and aircraft nationality and registration marking requirements are contained in part 45, subpart C.
- **b. Product Identification.** Prior to the issuance of a U.S. airworthiness certificate, the aircraft must have an identification plate in accordance with § 21.182, and which meets the requirements of part 45, subpart B, Identification of Aircraft and Related Products.
- **c.** Noise and Emissions Requirements. In addition to meeting the airworthiness standards, an aircraft must meet the noise standards of §§ 21.93(b), 21.183(e), or 21.185(d), part 36, SFAR 41, or part 91, subpart I, Operating Noise Limits, as applicable.
- **d. Approved Flight Manuals, Markings, and Placards.** The aircraft must be accompanied by an approved flight manual in the English language as identified on the FAA TCDS. Also, the aircraft must have the appropriate markings and placards in the English language as specified in the FAA TCDS, flight manual, or other approved data as required by § 91.9.
- **e.** Logbooks and Maintenance Records. Aircraft must be accompanied by the log books and maintenance records as specified in § 91.417 to determine the status of required inspections, life limits, and AD compliance for the airframe, engine, propeller, rotor, and appliance of an aircraft.
- **f.** Aircraft Location. A U.S. airworthiness certificate will not be issued to an aircraft located outside the United States, unless the FAA finds no undue burden in administering the applicable regulations. Procedures have been established to use the services of the CAA of the country of manufacture. For issuance of a U.S. standard airworthiness certificate for new aircraft manufactured outside the United States, see appendix 1 of this order. Applicants for airworthiness certification should consult with the FAA prior to making any firm commitments to determine if certification is possible.

212. APPLICATION.

a. Application for a U.S. airworthiness certificate should be made by the registered owner, or an agent who has a letter of authorization from the registered owner, on Form 8130-6.

Par 211 Page 201

8130.2D 9/30/99

b. When the applicant has completed and signed the application, it should be submitted to the Certification Office, along with the CAA Export C of A.

c. Approved flight manuals, log books, and maintenance records should be made available for examination by the FAA, upon request.

213. AIRWORTHINESS DETERMINATION.

- **a.** In all cases, the FAA is required by Title 49 to make a finding that the aircraft conforms to an FAA-approved TC and that it is in a condition for safe operation before the FAA issues an airworthiness certificate for that aircraft. The FAA may base its findings, wholly or partially, on the export certification document (e.g., an Export C of A) issued by the CAA of another country, provided a bilateral agreement exists.
- **b.** Sections 21.183(c) and 21.185(c) provide that an import aircraft type certificated under the procedures of § 21.29 is entitled to a U.S. airworthiness certificate (standard or special) if the CAA of the country of manufacture certifies, and the FAA finds, that the aircraft conforms to its approved TC and is found to be in a condition for safe operation.
- **c.** The CAA certifications shall be made by issuance of an export certification document which contains the certification statement noted on the corresponding FAA TCDS or certifies that the aircraft meets its FAA-approved type design and is in a condition for safe operation.
- d. The United States has bilateral agreements with certain countries which provide for the import of products from a country other than the country of manufacture (Third Party). In these instances, the applicant for a U.S. airworthiness certificate may show compliance with the requirements of § 21.183(c) by submitting a statement from the exporting country which certifies that the aircraft conforms to the U.S. TC and that it is in a condition for safe operation, together with the original or a certified copy of the Export C of A issued by the CAA of the country in which the aircraft was manufactured. Configuration variations, modifications, and major repairs that are not FAA-approved must be identified and approved or the differences resolved before the aircraft is accepted by the FAA. The application for a U.S. airworthiness certificate should cite §§ 21.183(d) or 21.185(b) as the basis for certification. The procedures outlined in this paragraph may also apply where the BAA/BASA Implementation Procedures for Airworthiness with the exporting country does not contain a "third country" provision and the Export C of A issued by the exporting CAA is endorsed by the CAA of the country of manufacture.
- **e.** Paragraph 208a(2) of this order may also be applied to U.S.-manufactured aircraft being returned to the United States from a registry of another country, provided the bilateral agreements between the United States and the last country of registry contain the "third country" provision.
- **f.** The bilateral agreements which include a "third country" provision are summarized in AC 21-23, Airworthiness Certification of Civil Aircraft, Engines, Propellers and Related Products Imported to the United States, appendix 4 (Note 7).

Page 202 Par 212

g. Applicants should be cautioned that it may be impractical to obtain a U.S. airworthiness certificate for an aircraft operated under the registry of another country subsequent to the issuance of an Export C of A by the CAA of the country of manufacture. This includes U.S.-manufactured aircraft being returned to the U.S. registry. Applicants should be able to identify repairs and modifications, and document the equipment installed and any maintenance accomplished, on the aircraft from the time the export certificate was issued and the date of application for the U.S. airworthiness certificate. The applicant must show that the aircraft has remained in or has been returned to its FAA-approved TC and is in a condition for safe operation. This may involve extensive inspections accomplished by designees, the CAA of the country of manufacture, the aircraft manufacturer, repair stations, etc., before a U.S. airworthiness certificate can be issued.

- h. In instances where an aircraft manufactured outside the United States was originally exported to another country, and the CAA of the country of manufacture has issued an Export C of A attesting conformance to a design not approved by the FAA, such certificates may be useful to establish a baseline for showing conformity to the FAA-approved design after modification. In these cases, or when the Export C of A may not be available, it would be helpful if the applicant obtained a statement from the CAA of the country of manufacture. The statement certifies that when originally exported from that country, the aircraft met its FAA-approved design and/or identifies any differences between the configuration identified in their original export certification and the FAA-approved design. The applicant must obtain the necessary technical data needed to convert the aircraft to its FAA-approved design configuration. This method may involve extensive inspections to be accomplished by designees, the CAA of the country of manufacture, the aircraft manufacturer, persons authorized under part 43, etc., before the applicant can show conformity to the FAA-approved design. Attempts to obtain a U.S. airworthiness certificate via this method may prove to be impracticable for the applicant; in some instances the applicant may ultimately be unable to obtain the desired U.S. airworthiness certificate.
- i. The FAA will not normally issue a U.S. airworthiness certificate for an aircraft manufactured outside the United States when no export certification is available. To be acceptable, aircraft manufactured outside the United States must be controlled under bilateral procedures with assurance of conformity and condition provided by the CAA in the country of manufacture. Without assurance in the form of an export certificate or a certifying statement from the CAA of the country of manufacture, there is no practical way for an applicant to show, or for the FAA to find that the aircraft is in conformance with the FAA-approved design and is in a condition for safe operation.
- **j.** Inspections by the FAA should be conducted to determine that no changes or modifications have been made, and that the condition of the aircraft has not deteriorated subsequent to export certification by the CAA. Flight testing may be required prior to issuance of a U.S. airworthiness certificate if the aircraft has been disassembled and reassembled subsequent to export certification by the CAA.

214. AIRWORTHINESS CERTIFICATION OF AIRCRAFT WITH MANDATORY CONTINUING AIRWORTHINESS INFORMATION (MCAI).

a. When an unsafe condition is found to exist in a U.S. type certificated product that is not currently on the U.S. Register, ACO's may utilize an alternate procedure concerning the issuance of AD's. Under this alternate procedure each MCAI received will be reviewed to determine whether it

Par 213 Page 203

8130.2D 9/30/99

meets established criteria for required corrective action. No further action will be taken for an MCAI that does not meet this criteria. An AD will be issued for an MCAI that meets this criteria if there is one or more aircraft of the affected design currently certificated in the United States. If no aircraft of the affected design currently has a U.S. airworthiness certificate, the responsible directorate may elect to defer publishing any AD's on the MCAI's that meet those criteria until an application for airworthiness certificate is made for an aircraft of that design. A list of each MCAI that is deferred will be maintained by the responsible directorate. A statement similar to the following will be found in the "Serial Nos. eligible product" section of the TCDS for an aircraft design on which AD's have not been issued for some or all of the required MCAI's:

"For issuance of an airworthiness certificate in accordance with § 21.183(c), [airworthiness authority of the state of design] must certify that the aircraft conforms to the type design and is in a condition for safe operation. In that regard, [airworthiness authority of the state of design] will certify that the aircraft complies with all applicable mandatory continuing airworthiness information (MCAI) it has issued. For issuance of an airworthiness certificate in accordance with § 21.183(d), the certificating inspector, or other authorized person, must find that the product conforms to type design and is in a condition for safe operation. In order to make that finding, the certificating inspector or other authorized person should contact [appropriate office within the cognizant directorate] prior to issuance to determine whether showing compliance with certain MCAI is necessary to support a finding that the airplane is in a condition for safe operation."

- **b.** In some instances, the TCDS will also indicate that certain AD's have been issued for the affected model. Compliance with any applicable AD is required, in addition to compliance with the MCAI.
- **c.** After the first aircraft is U.S. certificated, the responsible directorate will amend the TCDS to list the required MCAI's (formerly found on the responsible directorate's listing). Compliance must be shown before subsequent aircraft can be found to be in a condition for safe operation and issued an airworthiness certificate. The directorate will issue AD's for any subsequent MCAI's that meet the required criteria for corrective action and will not issue any retroactive AD's for any MCAI's listed as effective prior to the first aircraft being certificated.
- **d.** This alternative procedure may also be used in situations where an aircraft of the affected model was once certificated in this country, but is not currently.

NOTE: This procedure is not considered appropriate at this time for other products, i.e., engines and propellers, since there is presently no reliable means to ensure that none have been imported and installed in U.S.-registered aircraft.

215. CERTIFICATION PROCEDURES. The procedures identified above are generally common to issuance of all classifications of airworthiness certificates, and are consistent with the procedures identified in chapter 3 and 4 of this order.

216.-217. RESERVED.

Page 204 Par 214

SECTION 3. AIRCRAFT ENGINES, PROPELLERS, MATERIALS, PARTS, AND APPLIANCES

218. AIRWORTHINESS DETERMINATION.

- **a.** Section 21.500 provides for the airworthiness acceptance of aircraft engines or propellers manufactured outside the United States for which a U.S. TC has been issued. These products are considered approved for installation on a U.S.-registered aircraft when a current Export C of A has been issued by the CAA of the country of manufacture. The C of A certifies that the engine or propeller:
 - (1) Conforms to its U.S. T.C. and is found to be in a condition for safe operation.
 - (2) Has been subjected to a final operational check by the manufacturer.
- **b.** Section 21.502 provides for the airworthiness acceptance of materials, parts, and appliances (essentially replacement/modification parts) manufactured outside the United States for which some form of FAA design approval has been granted. These products are considered approved for installation on U.S.-registered aircraft when a current Export C of A has been issued by the CAA of the country of manufacture which certifies that the product conforms to their FAA-approved design and are in condition for safe operation on the date the certification was issued.
- **c.** Section 21.617(c) addresses products that are covered by an FAA letter of TSO design approval for imports. Neither the FAA letter of TSO design approval, nor the Export C of A issued by the CAA of the country of manufacture, conveys installation approval. Installation approval for a TSO product must be obtained, in a manner acceptable to the FAA, at the time of installation if not already accomplished. Approval for return to service must be performed by a person authorized in part 43.
- **d.** Various types of export certification documents are utilized by the CAA's. In some cases, these certifications may be in the form of an official CAA certificate or authorized release tag or forms which may be signed by private persons, when so authorized by the CAA. The FAA will accept the various types of certifications, provided they represent a certification from the appropriate CAA attesting that the product being exported is in conformity to the U.S. type design and is in a condition for safe operation, and are appropriately endorsed by the CAA or a duly authorized designee. The CAA of the exporting country should confirm a designee's scope of authority when so requested by the FAA. These certifications serve to comply with the requirements for an Export C of A for the purpose of §§ 21.500 or 21.502. In those instances where the certifying language differs from that stated in this paragraph, the FAA should request a letter from the CAA stating that the language used meets the intent of §§ 21.500 or 21.502, as appropriate. The CAA airworthiness certification documentation is essential for the FAA to determine that the product is acceptable for installation on U.S.-registered aircraft.

219. IDENTIFICATION AND MARKING.

a. Aircraft engines or propellers to be installed on U.S.-registered aircraft must be identified in a manner specified in § 45.11 with the information specified in § 45.13.

Par 218 Page 205

b. Critical components to be used as spare, replacement, or modification parts on U.S.-registered aircraft, or on engines or propellers to be installed on U.S.-registered aircraft, must be identified with a part number and serial number.

- **c.** Appliances and articles approved by an FAA letter of TSO design approval must be marked in accordance with the requirements outlined in part 21, subpart O, and any additional marking requirements specified in the particular TSO.
- **d.** Parts and materials to be used as spare, replacement, or modification parts on U.S.-registered aircraft must be identified by a part number and the manufacturer's name or trademark. The CAA certification must contain information concerning the model designation of the FAA type certificated product for which the part or material is eligible for installation. Products produced pursuant to part 21, subpart O, are not subject to this requirement, since model eligibility is established at the time of installation.
- **e.** The products must be accompanied by maintenance records equivalent to those specified in § 91.417 that reflect the status of required inspections, life limits, etc.
- **220. RETURN TO SERVICE.** Regardless of the existence of an export certificate, it remains the responsibility of the person authorized to return the aircraft, airframe, engine, propeller, or appliance (on which the product has been installed) to service under § 43.5, to determine that the imported product:
 - a. Has not been modified, changed, or damaged subsequent to the time of export certification.
 - **b.** Complies with all applicable AD's issued under part 39.
 - **c.** Is installed in accordance with FAA-approved design data.
 - **d.** Is in a condition for safe operation.
 - **e.** Has all the necessary maintenance documentation available.
- 221. SPECIAL MAINTENANCE RECORDS CONSIDERATION. United States operators, such as air carriers, air travel clubs, and operators for compensation and hire, certificated by the FAA for operation under parts 121, 125, and 135, will be required to have sufficient maintenance data on the aircraft or related product. This will enable the operator to integrate the aircraft or related product into its own FAA-approved maintenance program. United States operators will have difficulty doing this unless the records are complete and are in the English language, or can be translated into the English language. It is vitally important for operators and potential U.S. operators of imported aircraft, including U.S.-manufactured aircraft, to realize that an FAA airworthiness certificate does not automatically render the aircraft or product eligible for operation. FAA operating requirements may specify the need for maintenance records, additional inspections, tests, and installation of instruments and equipment which are over and above the basic airworthiness certification requirements.

Page 206 Par 219

222.-223. RESERVED.

Page 207 (and 208)

12/18/00 8130.2D CHG 2

CHAPTER 7. SPECIAL FLIGHT AUTHORIZATIONS FOR NON-U.S.-REGISTERED CIVIL AIRCRAFT

224. GENERAL.

a. The navigation of non-U.S. registered civil aircraft in the United States is permitted under § 41703(a) of Title 49. This section is implemented by 14 CFR part 375, Navigation of Foreign Civil Aircraft Within the United States (part 375), which sets forth the rules, conditions, and limitations governing the navigation of non-U.S. civil aircraft in the United States. Part 375 also specifies that non-U.S. civil aircraft being operated in the United States shall carry a current and effective AIRWORTHINESS and REGISTRATION certificate issued or rendered valid by the country of registry. Part 375 also allows the operation in U.S. airspace, subject in some cases to prior DOT approval, of aircraft that do not carry current airworthiness certificates, but that have been issued an SFA by the FAA.

NOTE: An SFA may be issued for any purpose, but should not be issued when there is any evidence of intent to circumvent any CFR provisions; e.g., §§ 21.183(c), 21.185(c), or part 129, Operations: Foreign Air Carriers and Foreign Operators of U.S.-registered Aircraft Engaged in Common Carriage (§ 129.1).

b. A non-U.S. civil aircraft that does not have a current airworthiness certificate issued by the country of registry requires an SFA issued by the FAA (§ 91.715(a)). An aircraft registered in a country that is not a member of the ICAO would IN ALL CASES require an authorization from the DOT and an SFA issued by the FAA to be navigated in the United States.

NOTE: A listing of ICAO member countries is contained in AC 21-2.

225. ELIGIBILITY.

- **a. General.** Section 91.715 is applicable to a non-U.S. civil aircraft which DOES NOT have a current airworthiness certificate or equivalent to a U.S. standard airworthiness certificate, which indicates that the aircraft complies with a detailed and comprehensive airworthiness code as provided by ICAO Annex 8. An SFA is required for an aircraft carrying an airworthiness certificate, flight permit, or similar document issued by the country of registry that is equivalent to a U.S. special airworthiness certificate. See 14 CFR § 375.10, Certain Foreign Civil Aircraft Registered in ICAO Member States, for details concerning aircraft manufactured in a country prior to that country becoming a member of ICAO.
 - **b. Basic Eligibility.** An SFA will be issued when the following conditions exist:
- (1) The aircraft is registered in an ICAO member country but does not have an airworthiness certificate attesting that the aircraft complies with ICAO Annex 8 requirements, or its airworthiness certificate is invalidated. An aircraft with an invalidated airworthiness certificate issued by the aircraft state of registry may be an aircraft that has been repaired, altered, or modified at a U.S. located facility and requires flight testing.

Par 224 Page 209

8130.2D CHG 2 12/18/00

(2) The aircraft is registered in a non-ICAO member country regardless of the type of airworthiness certificate issued or its planned operation. An SFA is also required and may be issued for such aircraft; however, the issuing inspector should be aware that the airworthiness requirements of the country of registry may be unknown.

(3) If a DOT authorization is required and is being obtained concurrently with the SFA, the SFA should include a limitation stating that a copy of the DOT authorization should be carried in the aircraft when operating under the SFA. Inquiries regarding DOT authorization should be referred to:

Department of Transportation Office of International Aviation Foreign Carrier Licensing Division 400 7th Street S.W. Washington, D.C. 20590

- **c. Basic Ineligibility.** An SFA shall not be issued when the following conditions exist:
- (1) If the aircraft is of foreign military registry (non-civil) and a SFA is requested, the applicant should be referred to the United States Department of State. Such aircraft may enter the United States only with a diplomatic clearance that would be issued solely on a government-to-government, non-commercial basis.
- (2) If aircraft registered in certain countries have special overflight approval requirements under the nationally mandated Special Interest Flight (SIF) program. A list of the designated countries and requirements of the program are contained in FAA Order 7110.65, Air Traffic Control, chapter 8, Section 2. For requests involving aircraft identified under the SIF program, the non-U.S. owner or operator, or U.S. individual or firm acting on behalf of the owner or operator, must request overflight clearance from the FAA Office of International Aviation, AIA-100. The request must include the complete itinerary, schedule, and proposed routing through U.S. airspace. AIA-100 should be contacted for complete information.
- **226. BLANKET SPECIAL FLIGHT AUTHORIZATIONS.** An SFA may be requested for an operation that will be conducted many times during a given period or for a number of aircraft engaged in the same operation (e.g., ferry flight). Therefore, a blanket SFA may be issued when deemed appropriate by the issuing office manager. If it appears the applicant is trying to circumvent U.S. registration and certification requirements, i.e., experimental exhibition, the SFA should not be issued.

227. APPLICATION.

a. General. The application for an SFA may be in the form of a letter, telegram, or telephone facsimile from the non-U.S. owner or operator, or from a U.S. individual or firm authorized to act on behalf of the registered owner or operator. The application should be addressed to the Flight Standards Division Manager or Aircraft Certification Directorate Manager of the FAA region in which the applicant is located, or to the region within which the U.S. point of entry is located. If the aircraft is coming into the United States for original certification, the SFA should be issued by the supporting MIDO.

Page 210 Par 225

12/18/00 8130.2D CHG 2

b. Individual Aircraft Authorizations. An application for an SFA should contain the following information, as applicable, and any other information deemed appropriate by the cognizant FAA field office.

- (1) The name and address of the applicant, if different from that of the registered owner. If the applicant is not the registered owner, a letter from the owner appointing the applicant as agent will also be submitted.
 - (2) The name and address of the registered owner of the aircraft.
 - (3) The operating purpose for which the SFA is requested.
- (4) The type of airworthiness document, if any, issued for the aircraft by the country of registry.
- (5) Information such as total aircraft time, maintenance status, date of last inspection, type of inspection, and the name and title of the person performing the inspection. This information is necessary to establish that the requested flight(s) will not adversely affect safety.
 - (6) The make, model, and serial number of the aircraft.
- (7) The assigned non-U.S. nationality and registration marks, and a valid copy of the registration document issued by the country of registry and translated into the English language.
- (8) The base of operations for the proposed flights and the areas where the flights will be conducted.
 - (9) The proposed U.S. port of entry and the itinerary while operating in the United States.
 - (10) For aircraft being exported, the route to the U.S. border and ultimate destination.
- (11) Whether the aircraft is to be modified in accordance with FAA-approved STC data, and will require maintenance flight testing in the U.S.
 - (12) Whether the aircraft will be used as a "test aircraft" in the development of a U.S. STC, and will require flight testing for the purpose of "showing compliance with the regulations."
 - (13) If a damaged aircraft is involved, the operating limitations, if any, assigned by the country of registry after its inspection.
 - (14) The duration for which the SFA is requested.
 - **c. Blanket Authorizations.** An application for a blanket SFA should normally contain the following information:
 - (1) The name and address of the promotion sponsor, or the manufacturer when the purpose is for export, as appropriate.

Par 227 Page 211

8130.2D CHG 2 12/18/00

(2) The purpose(s) for which the blanket SFA is requested and the number of signed copies required to meet operating needs.

- (3) Enough information to establish that the flights will not adversely affect safety.
- (4) For air shows, etc., the name and address of the registered owner, pilot if not the owner, make, model, serial number, registration number, type of airworthiness certificate carried, reason why the aircraft does not comply with standard airworthiness requirements, and aircraft maintenance provisions. The listing of owners, pilots, and aircraft participating may be provided separately.
 - (5) Any other information deemed appropriate by the certificating inspector.

228. ISSUANCE.

- **a. General.** The Aircraft Certification Directorate or Flight Standards Division Managers may delegate authority for issuance of SFA's according to FAA Order 1100.5, FAA Organization-Field, chapter 2, Section 3. If the applicant is a U.S. firm or individual acting on behalf of a non-U.S. applicant, the local office is responsible for processing the SFA. If the non-U.S. owner or operator is applying on its own behalf from its country, the Region or Directorate having jurisdiction over FAA matters in that country is the office responsible for processing the application.
- **b. Format.** The various formats shown in figures 7-1 through 7-9 shall be followed during the preparation of an SFA.
- **c. Numbering.** Each SFA issued will be assigned a number beginning with "01" and prefixed by the appropriate location identifier code of the FAA office, e.g., CE-39-01 or SW-41-01, as required by the latest version of FAA Order 1370.66, Aviation Safety Analysis System: Location Identifier Codes. If an SFA is extended, based on valid reasons provided by the applicant, a new SFA should be issued using the number assigned to the original followed by the suffix letter "A" e.g., CE-39-01A. In some cases an SFA may require extension more than once. The second extension would still use the original number followed by the suffix letter "B."
- **d. Control.** The FAA issuing office must establish a permanent file for record and must keep at least one copy of each SFA issued. This file serves as a control in assigning sequential numbers to new issuances. An alternate system for control may be used at the Region's or Directorate's discretion. The transmittal letter should advise that the applicant is accountable for each signed copy. When authorized to make copies for export purposes, a file should be maintained containing the following information:
 - (1) Name and address of the aircraft owner.
 - (2) Nationality and registration marks displayed on the aircraft.
 - (3) Make, model, and serial number of the aircraft.
 - (4) Date the copy is issued for the aircraft.
 - (5) Signature of authorized representative.

Page 212 Par 227

e. Aircraft Inspection. The aircraft should be inspected prior to issuance of the SFA to ensure that it is capable of safe flight. The FAA inspector may make, or require the applicant to make, appropriate inspections or tests considered necessary for safety.

- **229. DURATION.** Discretion should be used by the issuing Directorate/Region when determining the duration of an SFA issued for an individual aircraft. For example, if the purpose is one where delays may be expected, such as in STC projects or extended ferry flights, the region or directorate may allow for possible delays by establishing a duration for the SFA longer than that requested by the applicant to preclude the need for extensions. Generally, the duration of the SFA would be as requested by the applicant.
- 230. OPERATING LIMITATIONS. Since an SFA is issued to cover operation of an aircraft which may not meet the airworthiness standards established by ICAO, appropriate limitations must be prescribed to minimize hazards to persons or property. Certain limitations would be applicable for all SFA's issued under § 91.715(b). The special operating limitations for specific operations are not intended to be all inclusive and the issuing directorate/region may prescribe any additional limitations deemed necessary in the interest of safety. The following paragraphs provide examples of minimum and special limitations for specific operations.
- **a. Minimum Operating Limitations.** The following are applicable to all SFA's issued unless otherwise noted. The phrase "An authorized representative of the Administrator may prescribe additional operating restrictions and limitations necessary for safe operation." should be stated on all SFA's before the following operating limitations:
- (1) A copy of this authorization shall be displayed in the aircraft when operating under the terms of this SFA.
- (2) The identification markings assigned to the aircraft by the country of registry must be displayed on the aircraft according to that country's applicable requirements.
 - (3) Persons or property shall not be carried for compensation or hire.
- (4) No person may be carried in this aircraft during flight unless that person is essential to the purpose of the flight and has been advised of the content of this authorization and of the airworthiness status of the aircraft.
- (5) This aircraft shall be operated only by airmen holding appropriate certificates or licenses issued or validated by the United States or the country of registry (The pilot qualification limitation, paragraphs 134b(17), 142b(22), and 147b(8) of this order, should be prescribed for turbine-powered, piston-powered aircraft over 800 horsepower, aircraft over 12,500 pounds, rotorcraft, and any other aircraft when deemed necessary. The phrase "or equivalent issued or validated by the country of registry" should be added to the pilot qualification limitation referenced in paragraph 134b(17), 142b(22), and 147b(8) of this order).
- **(6)** All flights shall be conducted in compliance with the applicable general operating and flight rules of § 91.711.

Par 228 Page 213

(7) All flights shall be conducted under Visual Flight Rules (VFR), day only, unless otherwise authorized (e.g., IFR operations may be authorized for aircraft whose operating altitudes require IFR operations).

- (8) Except when otherwise directed by Air Traffic Control, or in the event of an emergency, all flights shall be conducted to avoid areas having heavy air traffic, cities, towns, villages, congested areas, or any other area where flights might create hazardous exposure to persons or property.
- (9) The operator of the aircraft shall advise Air Traffic Control of the nature of the flight when establishing communications.
- (10) Permission for flights over or into countries other than the United States must be obtained by the owner or operator of the aircraft from the CAA of that country.
- (11) This authorization shall remain in effect until (insert expiration date) unless superseded or rescinded.
- **b. Damaged Aircraft.** The minimum operating limitations would apply to any aircraft operated under this section. Additional limitations may be prescribed as individual conditions warrant.
- (1) Aircraft Located in the United States. The determination that the aircraft has been damaged to the extent that the airworthiness certificate is invalid is the responsibility of the country of registry. Under ICAO Annex 8, the country of registry may either prohibit further flights of the aircraft until it is restored to an airworthy condition, or may prescribe limitations under which the aircraft would be safe to fly to a base, either inside or outside the United States, where repairs can be made. The appropriate directorate or region should contact the CAA of the country of registry to determine the course of action to be pursued.
- (a) Should the country of registry choose to inspect the aircraft, any limitations it prescribes should be considered special limitations and made part of the SFA in addition to all of the applicable U.S. limitations.
- **(b)** In the event the country of registry requests the FAA to inspect the aircraft on its behalf, the Regional Office or Directorate should arrange for inspection of the aircraft by personnel from the nearest FSDO or MIDO. Any limitations considered necessary because of the inspection should be prescribed as special limitations in addition to the minimum limitations.
- (2) Aircraft Located Outside the United States. An applicant with a non-U.S.-registered aircraft needing repair, who wants the repair to be accomplished at a manufacturer or repair facility in the United States, may do so regardless of the country in which the damage was sustained. The country of registry remains responsible for inspection of the aircraft and for establishing any necessary special operating conditions and limitations. The responsible FAA office would issue the SFA including any limitations provided by the country of registry. The applicant should be notified in writing that approval for flights over or into countries other than the United States must be obtained from the CAA of the countries involved.

Page 214 Par 230

c. Change in Nationality. This paragraph applies when the certificate of airworthiness for an aircraft has been invalidated by the new country of registry. If the aircraft complies with U.S. and/or ICAO airworthiness requirements, except for the invalidated airworthiness certificate, it may not be necessary to prescribe the limitations specified in paragraphs 230a(4), (7), (8), or (9) of this order, as individual circumstances warrant. The minimum number of operating limitations should be prescribed, including a limitation establishing a flight itinerary by the most practical direct route.

- **d.** U.S.-Manufactured Aircraft. This paragraph applies whenever title to a U.S.-manufactured aircraft passes to a non-U.S. buyer for which no airworthiness certificate has been issued. It should be noted that a U.S.-manufactured aircraft need not have a registration certificate issued by the country of the non-U.S. buyer, but must bear the identification marks issued by the country of registry or intended registry. The procedures in this paragraph are also applicable to a non-U.S. civil aircraft of U.S. manufacture which is brought to the United States for alterations which invalidate its non-U.S. airworthiness certificate. The various purposes are described below:
- (1) **Flight Testing.** The Region or Directorate should carefully evaluate the reasons why the flight test must be conducted in the United States, the qualifications of the individual or company in the United States who will be primarily responsible for the flight test operations, and the nature of the flight tests. The conclusions reached from that evaluation are an important factor in determining the special operating limitations that should be prescribed in addition to the minimum limitations. The following special operating limitations would generally be applicable, but may be altered or added to as deemed appropriate:
- (a) All flight tests shall be conducted in compliance with § 91.305. (If the flight tests involve dropping of materials, e.g., water drops to test a new forest fire suppression system, § 91.15 should also be cited in this limitation.)
- **(b)** Prior to conducting any flight test, contact the MIDO or FSDO for any additional operating restrictions or limitations necessary for the protection of persons and property.
- (c) All maintenance and inspection of the aircraft shall be conducted under the direct supervision of qualified personnel holding appropriate licenses issued or rendered valid by the (insert country of registry) CAA and according to (insert country of registry) aircraft maintenance requirements.
- (d) Except for flight tests conducted according to the terms of this authorization, additional flights within the United States shall be limited to those necessary to proceed from (specify origin) to (insert the name of the airport or other area from which the flight test will be conducted), and return to (specify destination) by the most practical direct route except for deviations necessary to maintain VFR weather conditions.
- (e) Permission for flights over or into countries other than the United States must be obtained by the owner or operator of the aircraft from the CAA of that country.

Par 230 Page 215

(2) Training of non-U.S. buyers, employees, or designees. For operations under this purpose, all of the minimum operating limitations should be applied except the limitation under paragraph 230a(7) of this order. In most cases, an SFA issued for this purpose would be a "blanket" authorization issued to an aircraft manufacturer. The following special operating limitations, in addition to the required standard limitations, are worded in a manner to indicate that more than one aircraft is involved. If an SFA under this paragraph is issued for a single aircraft, an appropriate change should be made.

- (a) Each aircraft operated for customer crew training flights shall carry this SFA attached with a statement including the name and address of the aircraft owner, the aircraft's assigned nationality and registration marks, and the dates on which the customer crew training flights are scheduled to begin and end (this limitation applies only if a "blanket" authorization has been issued, and should replace the minimum operating limitation listed in paragraph 230a(1) of this order when deemed appropriate).
- **(b)** All customer crew training and aircraft maintenance shall be conducted under the direct supervision of (insert name of manufacturer) personnel.
- (c) Customer crew training flights on any one aircraft shall be conducted during a time interval not to exceed 30 days.
- (d) Before beginning customer crew training flights with any one aircraft, (insert name of manufacturer) shall submit to the local FAA Manufacturing Inspector the information specified in paragraph (a) above pertaining to that aircraft.

(3) Ferrying an Aircraft for Export Delivery.

- (a) Individual Aircraft Authorizations. All the minimum operating limitations should be prescribed for an aircraft operated for this purpose except that the limitations under paragraphs 230a(4), (7), (8), and (9) of this order may be omitted if the aircraft has a valid Form 8130-4 with no major exceptions listed, and/or is not carrying extra fuel or navigational equipment. If temporary fuel system(s)/equipment are installed and/or the aircraft is to be operated in excess of its maximum certificated takeoff weight, the limitations in paragraph 175 of this order should be included as applicable. The following special limitations should be applied in all cases:
- 1. Permission for flights over or into countries other than the United States must be obtained by the owner or operator of the aircraft from the CAA of that country.
- 2. The aircraft shall be flown to the United States border from the point of departure by the most direct route not in conflict with other operating conditions and limitations of this authorization.
- 3. The aircraft shall not be operated with temporary fuel system(s) or temporary navigation equipment installed, or at a weight in excess of its maximum certificated takeoff weight, unless approved by the CAA of the country of registry in writing.

Page 216 Par 230

(b) Blanket Authorization. The limitations applicable to an individual aircraft authorization generally apply to a blanket authorization. Since the manufacturer is authorized to issue copies without individual FAA review, the blanket authorization should be worded in such a manner that any possible situation will be covered by each copy issued. A sample blanket authorization has been developed to show all of the operating limitations that should be prescribed (figure 7-6).

- **e. Non-U.S. manufactured Aircraft.** The procedures provided under paragraph 230d of this order are also applicable to a non-U.S. manufactured aircraft brought to the United States for alterations which invalidate its airworthiness certificate.
- **f. Demonstration or Test.** The issuing Directorate should determine that the applicant for an SFA for demonstration has satisfied, as applicable, the items listed in part 91. Persons having an interest in the demonstration (e.g., customers) may be carried in an aircraft issued an SFA for demonstration and the operating limitations should be revised accordingly. Paragraph 230d(1) of this order applies to testing of the aircraft or part thereof.
- **g.** Airshows. Application is made to the Directorate or Region in which the airshow is located. Non-U.S.-registered amateur-built experimental aircraft do not require DOT authorization when the purpose is for public demonstration at an airshow in the United States. However, in the case of an aircraft to be operated in the United States for the purpose of demonstration at an airshow, the application may be made to the Flight Standards Service Division Manager or Aircraft Certification Service Directorate Manager of the FAA Region in which the airshow is located.

231. SPECIAL FLIGHT AUTHORIZATIONS FOR OPERATION OF CANADIAN-REGISTERED AMATEUR-BUILT AIRCRAFT IN THE UNITED STATES.

- **a.** Operation in the United States of Canadian-registered amateur-built aircraft certificated under the provisions of Canadian Air Regulation 230 (3) and Airworthiness Manual, chapter 549, is permitted by the issuance of an SFA under § 91.715. The SFA must be obtained before operation in the United States is permitted.
- **b.** A SFA may be obtained from the FAA for operation of a Canadian-registered amateur-built aircraft in U.S. airspace by submitting either a written or electronic application. Written applications should be forwarded to the Flight Standards Service Division Manager or Aircraft Certification Service Directorate Manager of the FAA region where the event is to take place. Written applications will be reviewed at the region or directorate level, prepared according to the procedures in this chapter, and the SFA mailed to the applicant when approved. Electronic SFA's may be obtained from any FSDO or directly through the Flight Standards WebSite at http://www.faa.gov/avr/afs/afs800/formtext.htm. Possession of the electronic SFA constitutes a valid authorization for operation in U.S. airspace, provided the operator of the amateur-built aircraft complies with the operating limitations that are a part of the special flight authorization.

Par 230 Page 217

c. The FAA issuing office will prepare the SFA according to the procedures contained in this chapter. The duration of the authorization shall be limited to that requested by the applicant, not to exceed 180 days. Extension of the duration of the authorization may be granted by the issuing FAA office in 180-day increments.

232.-235. RESERVED.

Page 218 Par 231

FIGURE 7-1. SAMPLE SPECIAL FLIGHT AUTHORIZATION FOR THE FLIGHT OF AN AIRCRAFT TO A PLACE WHERE REPAIRS OR ALTERATIONS ARE TO BE MADE



U.S. Department of Transportation

Federal Aviation Administration

NON-U.S. CIVIL AIRCRAFT SPECIAL FLIGHT AUTHORIZATION (SFA)

Authorization No.: NE-03-09
Aircraft Make: Cessna
Aircraft Model: 180H
Serial No.: 18051515
Nationality and Registration Marks: CF-ABC

Name and address of Registered Owner: Mr. Richard A. Roe

777 Quebec Street

Smithton, Ontario, Canada

Pursuant to the Code of Federal Regulations (14 CFR) § 91.715, Mr. Richard A. Roe is hereby authorized to operate the aircraft identified above for the purpose of flying it from Hartford, Connecticut, to Ontario, Canada, for permanent repair of damage incurred during a landing accident at Hartford. A representative of the Canadian Air Transport Administration has inspected the aircraft and found it safe for the intended flight provided that the airspeed does not exceed 130 knots and no passengers are carried aboard the aircraft. In consideration of the foregoing, all operations shall be in accordance with the following restrictions and limitations. An authorized representative of the Administrator may prescribe additional operating restrictions and limitations necessary for safe operation.

- 1. A copy of this authorization shall be displayed in the aircraft when operating under the terms of this SFA.
- 2. The identification markings assigned to the aircraft by the country of registry must be displayed on the aircraft according to that country's applicable requirements.
- 3. This aircraft shall be operated only by airmen holding appropriate certificates or licenses issued or validated by the United States or the country of registry.
- 4. All flights shall be conducted in compliance with applicable general operating and flight rules of § 91.711.
- 5. All flights shall be conducted under Visual Flight Rules (VFR), day only, unless otherwise authorized.
- 6. Except when otherwise directed by Air Traffic Control, or in the event of an emergency, all flights shall be conducted to avoid areas having heavy air traffic, cities, towns, villages, congested areas, or any other area where flights might create hazardous exposure to persons or property.
- 7. Persons or property shall not be carried for compensation or hire.

FIGURE 7-1. SAMPLE SPECIAL FLIGHT AUTHORIZATION FOR THE FLIGHT OF AN AIRCRAFT TO A PLACE WHERE REPAIRS OR ALTERATIONS ARE TO BE MADE (CONTINUED)

8. No person may be carried in this aircraft during flight unless that person is essential to the purpose of the	he
flight and has been advised of the content of this authorization and of the airworthiness status of the air-	
craft.	

- 9. All flights shall be conducted at airspeeds not to exceed 130 knots.
- 10. Permission for flights over or into countries other than the United States must be obtained by the owner or operator of the aircraft from the CAA of that country.
- 11. The operator of the aircraft shall advise Air Traffic Control of the nature of the flight when establishing communications.
- 12. This authorization shall remain in effect until March 16, 2000 unless superseded or rescinded.

J.A. Smith, Manager, Flight Standards Division New England Region

Issued in Burlington, Massachusetts, March 4, 2000.

FIGURE 7-2. SAMPLE SPECIAL FLIGHT AUTHORIZATION FOR THE FLIGHT OF AN AIRCRAFT TO A NEW COUNTRY OF REGISTRY. (THIS FORMAT IS GENERALLY APPLICABLE TO A SINGLE AIRCRAFT AUTHORIZATION FOR FERRY FLIGHTS)



U.S.Department of Transportation

Federal Aviation Administration

NON-U.S. CIVIL AIRCRAFT SPECIAL FLIGHT AUTHORIZATION (SFA)

Authorization No.:

Aircraft Make:

Aircraft Model:

Serial No.:

Nationality and Registration Marks:

SO-11-01

Beech

D185

A-23456

HK-ABC

Name and address of Registered Owner: Mr. Hernando Restrepo

22 Calle de Presidente Fusagasuga, Colombia

Pursuant to the Code of Federal Regulations (14 CFR) § 91.715, Mr. Hernando Restrepo is hereby authorized to operate the aircraft identified above for the purpose of flying from Atlanta, Georgia, to Fusagasuga, Colombia. The aircraft identified above was under Canadian registry and held a current and valid Canadian airworthiness certificate before its sale to Mr. Restrepo. A current and valid Colombian airworthiness certificate will not be issued until after its entry into Colombia. In consideration of the foregoing, all operations of the aircraft shall be in accordance with the following restrictions and limitations. An authorized representative of the Administrator may prescribe additional operating restrictions and limitations necessary for safe operation.

- 1. A copy of this authorization shall be displayed in the aircraft when operating under the terms of this SFA.
- 2. The identification markings assigned to the aircraft by the country of registry must be displayed on the aircraft according to that country's applicable requirements.
- 3. Persons or property shall not be carried for compensation or hire.
- 4. This aircraft shall be operated only by airmen holding appropriate certificates or licenses issued or validated by the United States or the country of registry.
- 5. All flights shall be conducted in compliance with the applicable general operating and flight rules § 91.711.
- 6. Permission for flights over or into countries other than the United States must be obtained by the owner or operator of the aircraft from the CAA of that country.

8130.2D 9/30/99

FIGURE 7-2. SAMPLE SPECIAL FLIGHT AUTHORIZATION FOR THE FLIGHT OF AN AIRCRAFT TO A NEW COUNTRY OF REGISTRY. THIS FORMAT IS GENERALLY APPLICABLE TO A SINGLE AIRCRAFT AUTHORIZATION FOR FERRY FLIGHTS (CONTINUED)

Flights to the U.S. border from the point of departure shall be by the most practical direct route not in flict with other operating limitations of this authorization.
This authorization shall remain in effect until March 15, 2000 or unless superseded or rescinded.
. Smith, Manager Flight
andards Division uthern Region
ued in Atlanta, Georgia, on March 2, 2000.

FIGURE 7-3. SAMPLE SPECIAL AUTHORIZATION FOR THE PURPOSE OF FLIGHT TESTING



Federal Aviation Administration

NON-U.S. CIVIL AIRCRAFT SPECIAL FLIGHT AUTHORIZATION (SFA)

Authorization No. ASW-1

Aircraft Make: McDonnell Douglas

Aircraft Model: DC-9-11 Serial No.: 12345 Nationality and Registration Marks: CF-POH

Name and address of Registered Owner: Canada Air, Montreal, Canada

Name and Address of Agent: John Doe Company,

21 Blackfoot Drive

San Antonio, Texas 78216

Pursuant to the Code of Federal Regulations (14 CFR) § 91.715, the John Doe Company is hereby authorized to operate the aircraft identified above for the purpose of conducting flight test(s) required to obtain a Supplemental Type Certificate (STC) covering the installation in the aircraft of General Electric CGY2 turbofan engines. All operations of the aircraft shall be in accordance with the following restrictions and limitations. An authorized representative of the Administrator may prescribe additional operating restrictions and limit ations necessary for safe operations.

- 1. A copy of this authorization shall be displayed in the aircraft at all times when operating under the terms of this SFA.
- 2. The identification markings assigned to the aircraft by the country of registry must be displayed on the aircraft according to that country's applicable requirements.
- 3. Persons or property shall not be carried for compensation or hire.
- 4. No person may be carried in the aircraft during flight unless that person is essential to the purpose of the flight and has been advised of the contents of this authorization and of the airworthiness status of the aircraft.
- 5. The aircraft shall be operated only by airmen holding appropriate certificates or licenses issued or validated by the United States or the country of registry. The pilot in command of this aircraft must hold an appropriate category/class rating. If required for the type of aircraft to be flown, the pilot in command must also hold either an appropriate type rating or a letter of authorization issued by an FAA Flight Standards Operations Inspector, or equivalent issued or validated by the country of registry.

FIGURE 7-3. SAMPLE SPECIAL FLIGHT AUTHORIZATION FOR THE PURPOSE OF FLIGHT TESTING (CONTINUED)

- 6. All flights shall be conducted in compliance with the applicable general operating and flight rules of § 91.711.
- 7. All flight tests shall be conducted in compliance with § 91.305.
- 8. All flights shall be conducted under Visual Flight Rules (VFR), day only, unless otherwise authorized.
- 9. Except when otherwise directed by Air Traffic Control, or in the event of an emergency, all flights shall be conducted to avoid areas having heavy air traffic, cities, towns, villages, congested areas, or any other area where flights might create hazardous exposure to persons or property.
- 10. Prior to conducting any flight test, contact the MIDO or FSDO for any additional operating restrictions or limitations necessary for the protection of persons or property.
- 11. All maintenance and inspection of the aircraft shall be conducted under the direct supervision of qualified personnel holding appropriate licenses issued or rendered valid by the Canadian Department of Transportation and according to Canadian aircraft maintenance requirements.
- 12. Except for flight tests conducted according to the terms of this authorization, additional flights within the United States shall be limited to those necessary to proceed to Montreal, Canada, by the most practical direct route except for deviations necessary to maintain VFR weather conditions.
- 13. Permission for flights over or into countries other than the United States must be obtained by the owner or operator of the aircraft from the CAA of that country.
- 14. The operator of the aircraft shall advise Air Traffic Control of the nature of the flight when establishing communications.
- 15. This authorization shall remain in effect until October 4, 2000, or unless superseded or rescinded.

J.A. Smith, Manager, Manufacturing Inspection Office Rotorcraft Directorate

Issued in Fort Worth, Texas, on September 29, 2000.

FIGURE 7-4. SAMPLE "BLANKET" SPECIAL FLIGHT AUTHORIZATION FOR CUSTOMER CREW TRAINING



Federal Aviation Administration

NON-U.S. CIVIL AIRCRAFT SPECIAL FLIGHT AUTHORIZATION (SFA)

Authorization No.: NE-02-43

This authorization is issued pursuant to the Code of Federal Regulations (14 CFR) § 91.715 to the Yankee Airplane Company, John Hancock Airport, Boston, Massachusetts 02111. This constitutes authority in lieu of an airworthiness certificate. For the purpose of giving customer crew training to the buyer, its employees, or designees in any aircraft manufactured by the Yankee Airplane Company when the aircraft has been placed under non-U.S. registry, each aircraft operated under this authorization must be operated according to the following restrictions and limitations. An authorized representative of the Administrator may prescribe operating restrictions and limitations necessary for safe operation.

- 1. Each aircraft operated for customer crew training flights shall carry this SFA attached with a statement including the name and address of the aircraft owner, the aircraft's assigned nationality and registration marks, and the dates on which the customer crew training flights are scheduled to begin and end.
- 2. All customer crew training and aircraft maintenance shall be conducted under the direct supervision of qualified Yankee Airplane Company personnel.
- 3. Customer crew training flights on any one aircraft shall be conducted during an interval not to exceed 30 days.
- 4. Before beginning customer crew training flights with any one aircraft, the Yankee Airplane Company shall submit to the local FAA Manufacturing Inspector the information specified in paragraph 1 pertaining to that aircraft.
- 5. The identification markings assigned to the aircraft by the country of registry must be displayed on the aircraft according to that country's applicable requirements.
- 6. Persons or property shall not be carried for compensation or hire.
- 7. No person may be carried in the aircraft during flight unless that person is essential to the purpose of the flight and has been advised of the contents of this authorization and of the airworthiness status of the aircraft.
- 8. This aircraft shall be operated only by airmen holding appropriate certificates or licenses issued or validated by the United States or the country of registry.
- 9. All flights shall be conducted in compliance with the applicable general operating and flight rules of § 91.711.

FIGURE 7-4. SAMPLE "BLANKET" SPECIAL FLIGHT AUTHORIZATION FOR CUSTOMER CREW TRAINING (CONTINUED)

10. Except when otherwise directed by Air Traffic Control, or in the event of an emergency, all flights shall be conducted to avoid areas having heavy air traffic, cities, towns, villages, congested areas, or any other area where flights might create hazardous exposure to persons or property.
11. The operator of the aircraft shall advise Air Traffic Control of the nature of the flight when establishing

- 12. Permission for flights over or into countries other than the United States must be obtained by the owner or operator of the aircraft from the CAA of that country.
- 13. This authorization shall remain in effect indefinitely unless superseded or rescinded.

J.A. Smith, Manager, Flight Standards Division New England Region

Issued in Burlington, Massachusetts, on February 29, 2000.

FIGURE 7-5. SAMPLE SPECIAL FLIGHT AUTHORIZATION FOR EXPORT DELIVERY



Federal Aviation Administration

NON-U.S. CIVIL AIRCRAFT SPECIAL FLIGHT AUTHORIZATION (SFA)

Authorization No.:

Aircraft Make:

Model:

Serial No.:

Nationality and Registration Marks:

Nationality and Registration Marks:

Nationality Authorization Marks:

Nationality

Registered Owner: <u>Joseph A. Banco, Via Banco, Rome, Italy</u>

Pursuant to the Code of Federal Regulations (14 CFR) § 91.715, Mr. Joseph A. Banco is hereby authorized to operate the aircraft identified above for the purpose of export and delivery from Westfield, Massachusetts, to Rome, Italy. This aircraft is on Italian registry and an airworthiness certificate has not yet been issued. An authorized representative of the Administrator may prescribe additional operating restrictions and limitations necessary for safe operation.

- 1. A copy of this authorization shall be displayed in the aircraft when operating under the terms of this SFA.
- 2. The identification markings assigned to the aircraft by the country of registry must be displayed on the aircraft according to that country's applicable requirements.
- 3. No person may be carried in this aircraft during flight unless that person is essential to the purpose of the flight and has been advised of the content of this authorization and of the airworthiness status of the aircraft.
- 4. The aircraft shall not be operated with temporary fuel system(s) or temporary navigation equipment installed or at a weight in excess of its maximum certificated takeoff weight, unless approved, by the CAA country of registry in writing.
- 5. Except when otherwise directed by Air Traffic Control, or in the event of an emergency, all flights shall be conducted to avoid areas having heavy air traffic, cities, towns, villages, congested areas, or any other areas where the flights might create hazardous exposure to persons or property.

FIGURE 7-5. SAMPLE SPECIAL FLIGHT AUTHORIZATION FOR EXPORT DELIVERY (CONTINUED)

- 6. This aircraft shall be operated only by airmen holding appropriate certificates or licenses issued or validated by the United States or country of registry.
- 7. All flights shall be conducted in compliance with the applicable general operating and flight § 91.711.
- 8. All flights shall be conducted under Visual Flight Rules (VFR), day only, unless otherwise authorized.
- 9. Permission for flights over or into countries other than the United States must be obtained by the owner or operator of the aircraft from the CAA of that country.
- 10. The aircraft shall be flown to the United States border from the point of departure by the most practical direct route not in conflict with the other operating conditions and limitations of this authorization.
- 11. Persons or property shall not be carried for compensation or hire.
- 12. The operator of the aircraft shall advise Air Traffic Control of the nature of the flight when establishing communications.
- 13. This authorization shall remain in effect until May 30, 2000, unless superseded or rescinded.

J.A. Smith, Manager, Flight Standards Division New England Region

Issued in Burlington, Massachusetts, on May 4, 2000.

FIGURE 7-6. SAMPLE "BLANKET" SPECIAL FLIGHT AUTHORIZATION FOR DELIVERING AIRCRAFT FOR THE PURPOSE OF EXPORT DELIVERY



Federal Aviation Administration

NON-U.S. CIVIL AIRCRAFT SPECIAL FLIGHT AUTHORIZATION (SFA)

Authorization No.: WP-26-22

This authorization is issued to the John Smith Airplane Company, 711 Water Boulevard, San Diego, California 82101, pursuant to the Code of Federal Regulations (14 CFR) § 91.715. A copy of this authorization furnished by the above constitutes authority in lieu of an airworthiness certificate for the purpose of export delivery of aircraft manufactured by that Company. This authorization is applicable to aircraft that are on a non-U.S. registry and have no airworthiness certificate. An authorized representative of the Administrator may prescribe additional operating restrictions and limitations necessary for safe operation.

- 1. A copy of this authorization shall be displayed in the aircraft when operating under the terms of this SFA.
- 2. No person may be carried in this aircraft during flight unless that person is essential to the purpose of the flight and has been advised of the content of this authorization and of the airworthiness status of the aircraft.
- 3. The identification markings assigned to the aircraft by the country of registry must be displayed on the aircraft according to that country's applicable requirements.
- 4. The aircraft shall not be operated with temporary fuel system(s) or temporary equipment installed, or at a weight in excess of its maximum certificated takeoff weight, unless approved by the CAA of the country of registry in writing.
 - 5. Persons or property may not be carried in the aircraft for compensation or hire.
- 6. The aircraft shall be flown to the United States border from the point of departure by the most direct route not in conflict with the other operating conditions and limitations of this authorization.
- 7. Permission for flights over or into countries other than the United States must be obtained by the owner or operator of the aircraft from the CAA of that country.
- 8. The aircraft shall be operated according to the applicable general operating and flight rules of § 91.711.

FIGURE 7-6. SAMPLE SPECIAL "BLANKET" FLIGHT AUTHORIZATION FOR DELIVERING AIRCRAFT FOR THE PURPOSE OF EXPORT DELIVERY (CONTINUED)

9. This aircraft shall be operated only by airmen holding appropriate certificates or licenses issued or validated by the United States or the country of registry.
10. All flights shall be conducted under Visual Flight Rules (VFR), day only, unless otherwise authorized.
11. Except when otherwise directed by Air Traffic Control, or in the event of an emergency, all flights shall be conducted to avoid areas having heavy air traffic, cities, towns, villages, congested areas, or any other areas where the flights might create hazardous exposure to persons or property.
12. The operator of the aircraft shall advise Air Traffic Control of the nature of the flight when establishing communications.
13. This authorization shall remain in effect until December 31, 2000.
J.A. Smith, Manager, Flight Standards Division Western-Pacific Region
Issued in Los Angeles, California, on January 4, 2000.

FIGURE 7-7. SAMPLE SPECIAL FLIGHT AUTHORIZATION FOR THE PURPOSE OF DEMONSTRATION



Federal Aviation Administration

NON-US CIVIL AIRCRAFT SPECIAL FLIGHT AUTHORIZATION (SFA)

Authorization No.:

Aircraft Make:

Model:

Serial No.:

NE-01-31

Hansa

HFB-320

Serial No.:

1024

Nationality and Registration Marks:

D-CARO

Name and Address of Registered Owner: <u>Hamburger Flugzeugbau G.M.B.H.</u>

2103 Hamburg

Finkenwerder Postfact 109, Germany

Pursuant to the Code of Federal Regulations (14 CFR) § 91.715, Hamburger Flugzeugbau G.M.B.H. is hereby authorized to operate the aircraft identified above for the purpose of conducting demonstration flights in the United States. The aircraft has been issued a provisional certificate of airworthiness by the Luftfahrt-Bundesamt and has been shown to meet standards equivalent to those required for provisional certification of a U.S.-registered civil aircraft. All operations of the aircraft shall be in accordance with the following restrictions and limitations. An authorized representative of the Administrator may prescribe additional operating restrictions and limitations necessary for safe operation.

- 1. A copy of this authorization shall be displayed in the aircraft when operating under the terms of this SFA.
- 2. The identification markings assigned to the aircraft by the country of registry must be displayed on the aircraft according to that country's applicable requirements.
- 3. Persons or property shall not be carried for compensation or hire.
- 4. No person may be carried in this aircraft during flight unless that person is essential to the purpose of the flight and has been advised of the content of this authorization and of the airworthiness status of the aircraft.
- 5. The aircraft shall be operated only by airmen holding appropriate certificates or licenses issued or validated by the United States or the country of registry. The pilot in command of this aircraft must hold an appropriate category/class rating. If required for the type of aircraft to be flown, the pilot in command must also hold either an appropriate type rating or a letter of authorization issued by an FAA Flight Standards Operations Inspector, or equivalent issued or validated by the country of registry.

FIGURE 7-7. SAMPLE SPECIAL FLIGHT AUTHORIZATION FOR THE PURPOSE OF DEMONSTRATION (CONTINUED)

- 6. All flights shall be conducted in compliance with the applicable general operating and flight § 91.711.
- 7. All flights shall be conducted under Visual Flight Rules (VFR), day only, unless otherwise authorized.
- 8. Except when otherwise directed by Air Traffic Control, or in the event of an emergency, all flights shall be conducted to avoid areas having heavy air traffic, cities, towns, villages, congested areas or any other area where flights might create hazardous exposure to persons or property.
- 9. Except for demonstration flights conducted according to the terms of this authorization, additional flights within the United States shall be limited to those necessary to proceed from Hamburg, Germany, to Denver International Airport, and return to Hamburg, Germany by the most practical direct route except for deviations necessary to maintain VFR weather conditions.
- 10. Prior to conducting any demonstration flight, contact the MIDO or FSDO for any additional operating restrictions or limitations necessary for the protection of persons and property.
- 11. Permission for flights over or into countries other than the United States must be obtained by the owner or operator of the aircraft from the CAA of that country.
- 12. The operator of the aircraft shall advise Air Traffic Control of the nature of the flight when establishing communications.
- 13. This authorization shall remain in effect until April 14, 2000 unless superseded or rescinded.

J.A. Smith, Manager, Flight Standards Division New England Region

Issued in Burlington, Massachusetts, on February 16, 2000.

FIGURE 7-8. SAMPLE SPECIAL FLIGHT AUTHORIZATION FOR CANADIAN-REGISTERED AMATEUR-BUILT AIRCRAFT (EXAMPLE: AUTHORIZATION FOR THE PURPOSE OF ATTENDING AN AIRSHOW)



Federal Aviation Administration

NON-U.S. CIVIL AIRCRAFT SPECIAL FLIGHT AUTHORIZATION (SFA)

Authorization No.: NE-26-75
Aircraft Make: Taylor
Model: 125
Serial No.: 560
Nationality and Registration Marks: CF-APB
Name and Address of Registered Owner: John Doe

241 Blue Hill Road

Montreal, Canada

Name and Address of Agent: <u>Jack D. Jones</u>

13 Water Street

New York City, New York

Pursuant to the Code of Federal Regulations (14 CFR) § 91.715, Mr. John Doe of Montreal, Canada, is hereby authorized to operate the aircraft identified above for the purpose of attending the airshow at Seattle, Washington, July 3 through July 5, 2000. The aircraft has been issued a Canadian flight permit. All operations of the aircraft shall be in accordance with the following restrictions and limitations. An authorized representative of the Administrator may prescribe additional operating restrictions and limitations necessary for safe operation.

- 1. A copy of this authorization shall be displayed in the aircraft when operating under the terms of this SFA
- 2. The identification markings assigned to the aircraft by the country of registry must be displayed on the aircraft according to that country's applicable requirements.
- 3. Persons or property shall not be carried for compensation or hire on board the aircraft.
- 4. The aircraft shall be operated under Visual Flight Rules (VFR), day only.
- 5. Except when otherwise directed by Air Traffic Control, or in the event of an emergency, all flights shall be conducted to avoid areas having heavy air traffic, cities, towns, villages, congested areas, or any other area where the flights might create hazardous exposure to persons or property.
- 6. The operator of the aircraft shall advise Air Traffic Control of the nature of the flight when establishing communications.

FIGURE 7-8. SAMPLE SPECIAL FLIGHT AUTHORIZATION FOR CANADIAN-REGISTERED AMATEUR-BUILT AIRCRAFT (EXAMPLE: AUTHORIZATION FOR THE PURPOSE OF ATTENDING AN AIRSHOW) (CONTINUED)

- 7. The aircraft shall be operated according to restrictions imposed by Transport Canada Aviation provided those restrictions do not limit or change the conditions herein imposed.
- 8. All flights shall be conducted in compliance with the general operating and flight rules of § 91.711.
- 9. No person may be carried in this aircraft during flight unless that person is essential to the purpose of the flight and has been advised of the content of this authorization and of the airworthiness status of the aircraft
- 10. The aircraft shall be operated only by airmen holding appropriate certificates or licenses issued or validated by the United States or the country of registry. The pilot in command of this aircraft must hold an appropriate category/class rating. If required for the type of aircraft to be flown, the pilot in command must also hold either an appropriate type rating or a letter of authorization issued by an FAA Flight Standards Operations Inspector, or equivalent issued or validated by the country of registry.
- 11. The operator of the aircraft shall advise Air Traffic Control of the nature of the flight when establishing communications.
- 12. This authorization is effective July 1, 2000, and terminates on July 7, 2000, unless superseded or rescinded.

J.A. Smith, Manager, Manufacturing Inspection Office Engine and Propeller Directorate

Issued in Burlington, Massachusetts, on June 23, 2000.

FIGURE 7-9. SAMPLE "BLANKET" SPECIAL FLIGHT AUTHORIZATION FOR GLIDER MEET



Federal Aviation Administration

NON-U.S. CIVIL AIRCRAFT SPECIAL FLIGHT AUTHORIZATION (SFA)

Authorization No.: <u>SW-42-55</u>

This authorization is issued pursuant to the Code of Federal Regulations (14 CFR) § 91.309 to the Soaring Society of America (SSA) and to each of the participants in the meet authorized by it to permit operation of non-U.S.-registered aircraft in the United States. In consideration of the foregoing, all operations shall be in accordance with the following restrictions and limitations. An authorized representative of the Administrator may prescribe additional operating restrictions and limitations necessary for safe operation.

- 1. A copy of this authorization shall be displayed in the aircraft when operating under the terms of this SFA.
- 2. A current airworthiness certificate issued by the country of registry must be carried on board each aircraft being operated under this authorization and must be produced upon request for inspection by the Federal Aviation Administration (FAA).
- 3. The operator of the aircraft shall advise Air Traffic Control of the nature of the flight when establishing communications.
- 4. Except when otherwise directed by Air Traffic Control, or in the case of emergency all flights shall be conducted to avoid congested areas, or any other area where flights might create hazardous exposure to persons or property.
- 5. All flights shall be conducted in compliance with the applicable general operating and flight § 91.711.
- 6. The identification markings assigned to the aircraft by the country of registry must be displayed on the aircraft according to that country's applicable requirements.
- 7. Persons or property shall not be carried for compensation or hire on board the aircraft.
- 8. No person may be carried in this aircraft during flight unless that person is essential to the purpose of the flight and has been advised of the content of this authorization and of the airworthiness status of the aircraft
- 9. The aircraft shall be operated only by airmen holding appropriate certificates or licenses issued or validated by the United States or the country of registry. The pilot in command of this aircraft must hold an appropriate category/class rating. If required for the type of aircraft to be flown, the pilot in command must also hold either an appropriate type rating or a letter of authorization issued by an FAA Flight Standards Operations Inspector, or equivalent issued or validated by the country of registry.

FIGURE 7-9. SAMPLE "BLANKET" SPECIAL FLIGHT FOR GLIDER MEET (CONTINUED)

10. The	aircraft shall be operated under Visual Flight Rules (VFR), day only.
11. Per or opera	mission for flights over or into countries other than the United States must be obtained by the owner tor of the aircraft from the CAA of that country.
12. A caboard e	opy of the DOT Authorization for non-U.S. civil aircraft participating in the meet shall be carried ach applicable aircraft operating under this SFA.
13. Thi	s authorization shall remain in effect until July 10, 2000 unless superseded or rescinded.
Inspec	th, Manager, Manufacturing tion Office ft Directorate
Issued in	Fort Worth, Texas, on June 10, 2000.

CHAPTER 8. PROCESSING FORMS, REPORTS, AND CERTIFICATION FILES

236. GENERAL.

- **a.** This chapter describes the requirements for completion and processing of the various forms and certificates used for airworthiness certification. Information entered on these documents should be typewritten when possible. THE USE OF PENCIL, ERASURES, STRIKEOVERS, ETC., ON AIRWORTHINESS FORMS OTHER THAN APPLICATIONS AND AC FORM 8050-72 IS NOT PERMITTED. Application forms may be corrected by the applicant or the FAA, provided the person making the changes initials beside the area of correction.
- **b.** The signature of the FAA inspector or designee on any FAA certificate or form shall be made in "PERMANENT TYPE" ink on the original and required copies. When the reverse side of the certificate is used, the statement "See Reverse Side" should be typed on the face of the certificate. Below the last line of information on a certificate there should be a line with the word "END" typed in caps in the center of the page.
- **237. APPLICATION FOR AIRWORTHINESS CERTIFICATE.** Form 8130-6 is required whenever an airworthiness certificate is requested, including any request for amendment or modification to a current airworthiness certificate, including operating limitations. AC 21-12 also provides instructions for completion of Form 8130-6.
- **a.** Instructions for Completing Form 8130-6. The applicant or authorized agent should complete Sections I through IV, as applicable, for the type of airworthiness certificate being requested. If the application is for a special flight permit only, Sections II and VI, or II and VII, as applicable, should be filled out. The following instructions and explanations apply for entries that are not clearly self-explanatory:
- (1) **Section I. Aircraft Description.** The FAA should verify the applicant's entries from the aircraft registration certificate, aircraft identification plate, TCDS, and/or aircraft specification sheet.

NOTE: This section is not completed when an application is being made for a special flight permit.

- (a) **Registration Mark.** Enter the U.S. nationality designator (letter "N") followed by the registration marks as shown on the aircraft registration certificate (part 45, subpart C).
- **(b) Aircraft Builder's Name (Make).** Enter the name of the builder or manufacturer as it appears on the aircraft identification plate (§ 45.13(a)(1)).
- 1. For amateur-built aircraft, the aircraft make is the name of the builder. When two or more persons are involved, enter only the name of the individual that is listed first on the aircraft's identification plate.

Par 236 Page 237

2. For aircraft built from spare and surplus parts, the aircraft make is that of the TC holder (as it appears on the applicable aircraft listing, specification, or TCDS) together with the name of builder, e.g., Bell-Jackson.

- **3.** For surplus military aircraft (not assembled from spare and surplus parts), the builder's name will be as listed on the aircraft identification plate.
- (c) Aircraft Model Designation. Enter the model designation as shown on the aircraft identification plate. Trade names should not be used (§ 45.13(a)(2)).
- 1. If the application is for a military aircraft, enter the civil model designation along with the military model designation in parentheses. If the civil model designation is the same as the military enter only one designation without parentheses.
- 2. For aircraft built from spare and surplus parts, the model designation should be the civil model that is shown on the TCDS to which the applicant shows conformity. If the aircraft built from spare and surplus parts has a military model designation, place this designation in parentheses along with the civil designation.
- **3.** For military aircraft type certificated in the restricted category under the provisions of § 21.25(a)(2), only the military designation will be entered.
- **4.** For amateur-built aircraft, the model may be any designation as selected by the builder. If the aircraft was purchased as a kit, the model designation assigned by the kit supplier should be used. However, it should agree with the identification plate and the aircraft registration certificate.
- **(d) Year of Manufacture.** Enter the year of manufacture as shown on the aircraft identification plate or as reflected in the aircraft log book.
- 1. For aircraft eligible for standard airworthiness certificates, the year of manufacture is the date (entered by the manufacturer) in the inspection records that reflects when the aircraft was completed and met the FAA-approved type design data.
- 2. For aircraft other than the above, the year of manufacture is the date entered by the builder in the inspection records or log book establishing that the aircraft is airworthy and eligible for the certificate requested.
- **(e) Serial Number.** Enter the serial number as shown on the aircraft identification plate per § 45.13(a)(3).
- 1. For surplus military aircraft, enter the manufacturer's civil serial number. The military serial number should be placed in parentheses following the civil serial number. If no civil serial number exists, enter the military number.

Page 238 Par 237

2. For aircraft built from spare and surplus parts, enter the serial number assigned by the builder, providing it could not be confused with those assigned by an original manufacturer who builds the same type of aircraft under a production approval. It is suggested that a letter prefix or suffix, such as the builder's name or initials, be used with the number to provide for positive identification.

- **3.** For amateur-built aircraft, the serial number may be any arbitrary number assigned by the builder, as shown on the ID plate.
- (f) Engine Builder's Name (Make). The engine make is the name of the manufacturer as it appears on the engine identification plate (§ 45.13(a)(1)). Abbreviations may be used, e.g., "P&W, G.E., CMC," etc. When no engines are installed, as in the case of the glider or balloon, enter "N/A."
- **(g) Engine Model Designation.** When engine(s) are installed, enter the complete designation as shown on the engine identification plate; e.g., "R2800-99W," "TVO-435-AIA," "I0-470-R," etc. (§ 45.13(a)(2)).
 - (h) **Number of Engines.** When applicable, enter the number of engines installed on the aircraft.
- (i) **Propeller Builder's Name (Make).** Enter the name of the manufacturer as shown on the propeller identification data. Enter "N/A" if propellers are not installed (§ 45.13(a)(1)).
- **(j) Propeller Model Designation.** When applicable, enter the model designation as shown on the propeller identification data (§ 45.13(a)(2)).
- **(k) Aircraft is Import.** This block should be checked only if the aircraft was manufactured in a country other than the United States and is being certified under the provisions of § 21.183(c).
- (2) Section II. Certification Requested. All entries in this section are generally self explanatory, except as noted. The following paragraphs reference applicable CFR and other material to assist the applicant in the completion of Form 8130-6 for each certification that may be requested. If the aircraft was type certificated prior to the adoption of "Categories," enter in the open space at the top of Section II above the standard category blocks "Category N/A Certification basis (enter e.g., CAR 04A, etc., as shown in aircraft specification or listing)." See the applicable chapter of this order for examples of airworthiness applications.

(a) Standard Airworthiness Certificate.

- 1. Section 21.175(a).
- 2. AC 20-65, U.S. Airworthiness Certificates and Authorizations for Operation of Domestic and Foreign Aircraft.

Par 237 Page 239

3. If Form 8130-6 does not contain "Commuter" in Block A1, "Standard Airworthiness Certificate," and this category is desired, the word "Commuter" is typed or printed above the line, in the space to the right of the words "Application is Hereby Made For."

(b) Special Airworthiness Certificate. Section 21.175(b). The applicant should check the appropriate block for class or purpose intended, in addition to the requested category.

1. Limited Airworthiness Certificate.

- (aa) Section 21.189.
- **(bb)** AC 20-65, U.S. Airworthiness Certificates and Authorizations for Operation of Domestic and Foreign Aircraft.
- **2. Provisional Airworthiness Certificate.** Section 21.221 for a Class I certificate and section 21.223 for a Class II certificate.

3. Restricted Airworthiness Certificate.

- (aa) Sections 21.25 and 21.185.
- **(bb)** AC 20-65, U.S. Airworthiness Certificates and Authorizations for Operation of Domestic and Foreign Aircraft.

4. Experimental Certificate.

- (aa) Sections 21.191, 21.193, and 21.195.
- (**bb**) AC 20-27, Certification and Operation of Amateur-Built Aircraft, and AC 20-65, U.S. Airworthiness Certificates and Authorizations for Operation of Domestic and Foreign Aircraft.

5. Special Flight Permit.

- (aa) Sections 21.197 and 21.199.
- **(bb)** AC 20-65, U.S. Airworthiness Certificates and Authorization for Operation of Domestic and Foreign Aircraft, and AC 21-4, Special Flight Permits for Operation of Overweight Aircraft.
- (cc) When applying for a special flight permit, the applicant should complete only Section II of the face side of the form, and either Section VI or VII on the reverse side. The FAA completes only Section V for issuance of a special flight permit. Section V is NOT completed when issued for the purpose of production flight testing.

Page 240 Par 237

6. Multiple Airworthiness Certificate, i.e., Standard/Restricted or Restricted/Limited.

- (aa) Section 21.187.
- **(bb)** AC 20-65, U.S. Airworthiness Certificates and Authorization for Operation of Domestic and Foreign Aircraft.
 - (3) Section III. Owner's Certification.

NOTE: Do not complete this section when application is being made for a special flight permit.

- (a) **Registered Owner.** Enter this information exactly as it is shown on the aircraft registration certificate. Part 47 prescribes the requirements for registering aircraft under sections 44101 44103 of Title 49.
- **(b) If Dealer, Check Here.** This block should be checked ONLY if the aircraft is registered under a dealer's aircraft registration certificate (part 47, subpart C, Dealer's Aircraft Registration Certificate).
- (c) Aircraft Certification Basis (Aircraft Specification or Type Certificate Data Sheet and/or Aircraft Listing Block). This item should be completed when application is being made for a standard, provisional, limited, restricted, or multiple airworthiness certificate.
- 1. When application is being made for a multiple airworthiness certificate, the certification basis for each certificate being requested should be entered.
- 2. If the TCDS or specification for a new aircraft or model has been approved, but not yet published, the date of approval, the TC or specification number, and the word "Preliminary" should be entered.
 - 3. Enter "N/A" when the application is being made for an experimental certificate.
- (d) Airworthiness Directives. This block should be completed to indicate compliance with all applicable AD's, regardless of what type of airworthiness certificate is being requested. List the number of the last AD SUPPLEMENT available in the biweekly series, as of the date of the application, regardless of whether or not that AD supplement applies to the aircraft (part 39 and § 21.99).
 - (e) Aircraft Listing. Enter N/A.
- **(f) Supplemental Type Certificate.** This block should be completed only when one or more STC's have been incorporated. The identification number of each STC installed should be shown. If more space is required, an attachment may be used. This block is applicable to all certification categories (part 21, subpart E).

Par 237 Page 241

(g) Aircraft Operation and Maintenance Records.

- 1. Check If Records are in Compliance with FAR 91.173 (now § 91.417). (Section 91.173 on Form 8130-6, Rev. 11-88, was designated as § 91.417 by 54FR 34291.) This block is applicable to all aircraft covered by this section and should be checked to indicate that the record-keeping requirements of § 91.417 have been met. For example, § 91.417(a)(2)(ii) requires a maintenance record of the current status of life-limited parts of each airframe, engine, propeller, rotor, and appliance, while compliance with § 91.417(a)(2)(i) would require that total time in service be entered in the aircraft's maintenance records.
- **2. Total Airframe Hours.** This block is applicable to all aircraft covered by this section. The total time in service of the aircraft, including production flight test time, should be entered.
- **3. Experimental Only.** When application is being made for the renewal of an experimental certificate or change back to a standard certificate, the hours flown since the previous certificate was issued or renewed should be entered. If the application is for an original issuance of an experimental certificate, zero hours should be entered.
- **(h) Certification.** If the signature is by the owner's agent, a notarized letter from the registered owner authorizing the agent to act on the owner's behalf is required.
- (4) Section IV. Inspection Agency Verification. This section should be completed only if application is being made for a standard airworthiness certificate in accordance with § 21.183(d). This section should be left blank for all other certification actions.
 - NOTE: Section 21.183(d)(2) exempts an "experimentally certificated aircraft that had previously been issued a different airworthiness certificate under this section being returned to the standard airworthiness category, from the 100-hour inspection set forth in § 43.15."
- (5) Section V. FAA Representative Certification. This section will be completed by the FAA INSPECTOR OR DESIGNEE that inspects the aircraft and issues the certificate.
 - (a) Check all applicable blocks in Items A and B.
- **(b) District Office.** An FAA inspector should enter the appropriate district or regional office designation. Designees and DOA manufacturers should enter the designation of the district office responsible for monitoring their activities.
- (c) **Designee's Signature and No.** For DOA manufacturers or DAS, the authorization number, preceded by "DOA" or "DAS" as applicable, should be entered. The DMIR, DAR, or DOA appointee signature will be signed in ink over the typed or printed name on the original and copy(s). The typed name and signature must be legible and should not obliterate preprinted information on Form 8130-6.

Page 242 Par 237

(d) **FAA Inspector's Signature.** The FAA inspector's name should be typed or printed in this box with the signature above.

- (6) Section VI. Production Flight Testing. This section should be completed ONLY BY A MANUFACTURER applying for a special flight permit for the purpose of flight testing production aircraft (§ 21.197(a)(3)). All required entries are self-explanatory.
 - (7) Section VII. Special Flight Permit Purposes Other Than Production Flight Test.
- (a) **Item A. Description of Aircraft.** The entries in this section should be the same as the corresponding data recorded on the aircraft's registration certificate and, as applicable, on the aircraft's identification plate.
 - **(b) Item B. Description of Flight.** Self-explanatory except that:
- 1. The "Via" block should contain the name of an airport or city at some intermediate point in the flight to provide a general description of the route flown. For example, a flight from Kansas City, Missouri, to Dallas, Texas, may be via Wichita, Kansas, and Oklahoma City, Oklahoma (§ 21.199(a)(2)).
- 2. The "Duration" entry should reflect the overall duration of the special flight permit and need not be the same as the planned duration of the actual flight. Factors such as fueling stops, weather conditions, overnight stops, or any other reasonable condition should be given consideration when establishing the duration.
- (c) Item **D.** The Aircraft Does Not Meet the Applicable Airworthiness Requirements As Follows. This entry should specifically detail the conditions in which the aircraft does not comply with the applicable airworthiness requirements (§ 21.199(a)(4)).
- (d) Item E. The Following Restrictions are Considered Necessary for Safe Operation. This entry should contain in detail the restrictions the applicant considers necessary for safe operation of the aircraft; e.g., reduced airspeed or weight, turbulence avoidance, crew limitations or qualifications, and the like. This item should be carefully reviewed by the FAA to determine that the restriction would ensure safe operation of the aircraft, and any deficiencies should be resolved prior to issuance of the special flight permit. The FAA may also prescribe additional conditions and limitations as deemed necessary for safe operation.
- **(8) Section VIII. Airworthiness Documentation.** This section will be completed by the FAA IN-SPECTOR OR DESIGNEE who inspects the aircraft and issues the airworthiness certificate. However, this section is not applicable when a special flight permit is being issued.

Par 237 Page 243

(a) Item A. Operating Limitations and Markings in Compliance with FAR 91.31 (now section 91.9 as applicable). (§ 91.31 on Form 8130-6, Rev. 11-88, was redesignated as § 91.9.) THIS BLOCK APPLIES TO ALL AIRCRAFT COVERED BY THIS SECTION. The FAA should check this block to determine that an FAA-approved Aircraft Flight Manual, listing of operation limitation, placards, etc., as applicable to the category of certificate requested, is in the aircraft in accordance with § 91.9.

- **(b) Item B. Current Operating Limitations Attached.** Check this block when operating limitations have been issued and a copy is attached for retention in the permanent record. (Applicable to aircraft certificated in categories other than standard.)
 - (c) Items C, D, and E. These items are self-explanatory.

(d) Item F. This Inspection Recorded in Aircraft Records. The following is considered a
satisfactory statement for the aircraft record entry: "I find that the aircraft meets the requirements for the certifi-
cation requested and have issued a (Standard) (Special) Airworthiness Certificate dated The next
inspection is due"
Signed: John Smith, Aviation Safety Inspector, SW-41.

NOTE: The next inspection date is not necessary when the aircraft is under a continuous maintenance program.

NOTE: In the case of aircraft that had a previous due date, the date entered is the same. The aircraft gains no additional time because it was not in the standard category.

- (e) Item G. Self-explanatory.
- (f) Item H. Foreign Airworthiness Certification for Import Aircraft (attach when required). Check the block to indicate that certification of another country is required for the certification action and that a copy is attached for retention in the aircraft permanent records.
- (g) Item I. Previous Airworthiness Certificate Issued in Accordance with FAR (now CFR), or CAR. If applicable, insert in the space the appropriate CFR or CAR under which the previous airworthiness certificate was issued, and check the block to indicate that the original of the certificate is attached. IF THE PREVIOUSLY ISSUED CERTIFICATE IS NOT AVAILABLE, THE FAA SHOULD STATE THE REASON ON AN ATTACHMENT.
- (h) Item J. Current Airworthiness Certificate Issuance in Accordance with FAR (now CFR). The applicable section of part 21, subpart H, should be entered, except that a DOA manufacturer should:
- 1. Enter § 21.183(a) or (b) for a standard airworthiness certificate, depending upon whether the aircraft had been added to the PC under § 21.267, or § 21.185 for a restricted category airworthiness certificate.

Page 244 Par 237

- 2. Add "per § 21.273," to indicate the delegation authority.
- **b.** Instructions for Reviewing Completed Form 8130-6. The FAA should review the form to determine that all applicable entries have been made, and on issuance of the airworthiness certificate should complete Section V. In the event that an airworthiness certificate is denied, Sections V and VIII should not be completed. A letter of denial, or a statement of the reason for denial, should be attached to the form and forwarded to AFS-750 as part of the aircraft records.
- **238. COMPLETION OF FAA FORM 8100-2.** The blocks on Form 8100-2 are to be completed from the information obtained with completed Form 8130-6.
- **a.** Nationality and Registration Marks. Insert the capital letter "N" followed by the registration number assigned to the aircraft.
 - **b. Manufacturer and Model.** Example: Beech-C33.
 - c. Aircraft Serial Number. Self-explanatory.
- **d. Category.** Enter the appropriate category as defined in paragraph 237 of this order. If there is no category, as in the case of aircraft certificated prior to adoption of the regulations which established categories, enter the aircraft specification, TCDS or listing number as applicable. For example, "CAR 4a" for a Bellanca 14-13; "ATC 614" for an Aeronca LC.
- **e. Authority and Basis for Issuance.** Under "Exceptions" enter the exemption number and brief description of any exemptions from the applicable airworthiness standards (CAR 3, 4b, 5, 6, 7, or equivalent CFR) that have been granted for the aircraft (see aircraft specification or TCDS). If no exemptions exist, enter "None."
- **f. Date of Issuance.** Enter the date the certificate is issued. Enter the date of the original certificate and insert the letter "E" or "R." When the certificate is being amended enter "A" along with the current date of airworthiness certification.
- **g. FAA Representative.** The name of the FAA inspector or designee issuing the certificate should be typed under the signature. The signature should be in permanent type ink on the original and copies.
- **h. Designation Number.** The following should be inserted as applicable to the person issuing the certificate.
 - (1) **FAA Inspector.** The office identifier, e.g., SW-MIDO-41.
- (2) **DMIR/DAR/ODAR.** The designee's number (e.g., DMIR-123456-SW, DAR-123456-NM. etc.).
- (3) **DOA.** The letter "DOA" followed by the PC number or the authorization number if one has been assigned by the region.

Par 237 Page 245

- (4) **Designated Alteration Station.** The letters "DAS" followed by the DAS number.
- **239. COMPLETION OF FAA FORM 8130-7.** The blocks on Form 8130-7 should be completed using all applicable information obtained from completed Form 8130-6.
 - **a. Section A.** This section is applicable to ALL categories of special airworthiness certificates.
- (1) Category/Designation. Enter the category of special airworthiness certificate being issued, as outlined under paragraph 237 of this order; e.g., restricted, limited, etc. For experimentally certificated manned-free balloons or gliders, the words "Manned-Free Balloon" or "Glider" are to be put in parentheses behind the word "Experimental" for the respective type of aircraft.
- (2) **Purpose.** Enter the operating purpose for which the special airworthiness certificate is issued, as shown by the blocks checked by the applicant under Section II, Block B, on Form 8130-6. If the application is for a "limited" category airworthiness certificate, the "Purpose" entry should be "N/A."
- **b.** Section **B.** The name and address of the manufacturer should be entered ONLY if the application is for a special flight permit for the purpose of PRODUCTION FLIGHT TESTING. In all other cases, the entry in both spaces under this section should be "N/A."

c. Section C.

- (1) This section is applicable for a special flight permit for purposes other than production flight testing. For production flight testing the entry in both spaces should be "N/A." For other purposes, the "Flight From" and "Flight To" spaces should be the same as that shown on Form 8130-6, Section VII, Item B.
- (2) When the aircraft is to be flown outside the United States, the following additional information should be entered in section "C" on the face side of the special airworthiness certificate: "Subject to paragraph D(2) on reverse side."
- **d. Section D.** This section is applicable to all categories and purposes EXCEPT PRODUCTION FLIGHT TESTING. If the purpose is production flight testing, the entries in all spaces should be "N/A." For all other categories and purposes, information to complete the entries in this section would be contained in Section I of the application for airworthiness certificate.

e. Section E.

(1) **Date of Issuance.** Enter the date the certificate is issued. However, in those cases where a certificate is being exchanged or replaced, enter the date of the original certificate and insert the letter "E" or "R."

Page 246 Par 238

(2) Expiry. The date of expiry should be entered if the application is for "Experimental" or "Special Flight Permit." An experimental certificate for research and development, showing compliance with regulations, crew training, or market surveys is effective for one year after the date of issue or renewal, unless a shorter period is deemed necessary. The duration of amateur-built, exhibition, and air racing experimental certificates will be unlimited unless good cause exists to establish a specific period. For "provisional," the entry should be per § 21.217.

- (3) Operating Limitations Dated _____are a Part of this Certificate. The date of the operating limitations should be entered. DO NOT REPEAT OR PARAPHRASE LIMITATIONS PRINTED ON THE REVERSE SIDE OF THE CERTIFICATE. Enter "N/A" if the limitations on the reverse side of the certificate are adequate for the purpose.
- (4) Signature of FAA Representative: Designation or Office No. This space should be completed for ALL categories and purposes. Entries are the same as those explained in paragraphs 238g and h of this order.

240. RESERVED.

241. COMPLETION OF FAA FORM 8130-4.

- **a.** Form 8130-4 should be filled out in duplicate. The original remains with the product and the duplicate is forwarded to AFS-750.
- **b.** Place the Export Certificate Number Assignment Card, AC 8050-72, number in the "No." block at top right corner of the form.
- **c.** In the space provided in the certifying statement, enter the information identified per note (1) at the bottom of Form 8130-4.
 - **d.** Product, manufacturer, model, etc., items are self-explanatory.
- **e.** The "Exceptions" space should identify any non-compliance(s) to type design, importing country requirements, and the addition of any temporary installations required for delivery. If none exist, then type in the word "NONE."
- **f.** If other information is deemed necessary to be provided, a statement may be typed in after the "Exceptions" space and identified with the words "Additional Information." For example, some importing countries want a statement that the product complies with a type design approved by their country's CAA.
 - **g.** The rest of the items are self-explanatory.

h. Lost Form 8130-4.

(1) When Form 8130-4 has been declared lost, the following information is required:

Par 239 Page 247

- (a) A written statement from the importer stating the tag has been lost.
- **(b)** Evidence of previous export, traceable through invoice to model and serial number from the exporter.
- (2) When these actions have been taken, a copy of the original form can be provided, if available. The replacement approval or a copy of the original lost approval must have an original signature and the same data as the lost Form 8130-4.
- **242. COMPLETION OF FAA FORM 8130-1.** Part I of the application should be completed for Class I products and Part II for Class II products. For completing the application, all items are self explanatory except as noted. Items in Part I and II are for applicant completion, and Part III for FAA use only. Instructions for completion of Part I and II are used to aid the FAA in review of the form as submitted by the applicant. The completed Form 8130-1 should be filed in the district office and retained for a minimum of 2 years, then destroyed in accordance with standard agency procedures. Chapter 5 of this order contains further information on the usage of this form.
- **a. Export Certificate No.** This block is left blank by the applicant. The FAA will enter the serial number from Form 8050-72.
 - b. Part I (For Class I Products).
 - (1) **Items 1 through 4.** Self-explanatory.
 - (2) **Item 5.** Description of product(s) Self-explanatory, except as follows:
- (a) For an aircraft not under U.S. registry, insert in the "Identification No." block the nationality and registration marks supplied by the country of registry or intended registry and which are displayed on the aircraft. For U.S.-registered aircraft, insert the identification marks as assigned under part 47. Any questions concerning the marking requirements of the importing country should be resolved between the exporter/importer and the CAA of that country.
- **(b)** Under "FAA Spec. No.," insert the pertinent specification number or the TCDS number, whichever is applicable.
- (c) For new and used aircraft, insert in the "Operating Time (Hours)" block the operating hours since the annual type inspection required by § 21.329, and the total time in service. Since used aircraft engines and propellers must have been newly overhauled under § 21.329(e), the operating time since overhaul would reflect only run-in time as required to complete the overhaul process.
- (d) For aircraft, the blocks for engine(s) and propeller(s) should be completed to reflect the required information, as applicable.

Page 248 Par 241

12/18/00 8130.2D CHG 2

(3) Items 6 and 7. These items are self-explanatory; however, if the "No" box is checked, explain the deviations in item 10 and attach the original or true copy of documents stating that the product will be acceptable with the deviations listed, as received from the CAA of the importing country.

- **(4) Item 8.** This item provides a means of establishing the date the ownership of the stated Class I product is expected to pass to the purchaser.
- (5) Item 9. This item provides a means of documenting the preservation and packaging methods used to protect against corrosion and damage. It is recommended that all products be appropriately treated for corrosion and damage prevention.
- (6) Item 10. This space should be used to convey the information required under Items 6 and 7. This space may also be used by the exporter to convey any other information pertinent to the issuance of the export airworthiness approval. Additional sheets may be attached, as necessary, and appropriately cross-referenced. In addition, list the documentation required by the regulation to be submitted with the application (§ 21.327). After review by the FAA, those documents which are required to be furnished to the importing country under § 21.335 will be returned to the applicant.
- (7) **Item 11.** This certification is to be dated and signed in ink over the printed or typed name of the authorized representative of the exporter. The representative's title should be typed or printed in the space provided.

c. Part II (For Class II Products).

- (1) Items 12 through 14. Self-explanatory.
- (2) **Item 15.** The instructions contained in Order 8130.21 for entering eligibility information shall be used.

Note: No entry is required in the "FAA Spec No." box.

- (3) **Item 16.** Self-explanatory.
- (4) Item 17. This item provides for the description and listing of the Class II products (parts) being exported. If the quantity and variety of the parts are too numerous to list in the space provided, check the second block and, on the line provided, specifically identify (and attach) a copy of the exporter's shipping document covering the parts concerned. Otherwise, check the first block and list the parts in the space provided. In either case, if more than one type of Class II product is involved, they are to be listed according to the Class I product for which they are eligible. List serial numbers, or equivalent means of identifying each physical product, and quantities in the space provided.
- (5) Item 18. This item is self-explanatory. If the "No" box is checked, explain the noncompliance in Item 10 and attach the original, or a true copy, of the documents stating that the product will be acceptable with the deviation(s) listed, as received from the CAA of the importing country.

Par 242 Page 249

8130.2D 9/30/99

(6) Item 19. This item provides a means of documenting the preservation and packaging methods used to protect against corrosion and damage. It is recommended that all products be appropriately treated for corrosion and damage prevention.

(7) **Item 20.** This certification is to be dated and signed in ink over the printed or typed name of the authorized representative of the exporter. The representative's title should be typed or printed in the space provided.

d. Part III. Approval (For FAA Use Only).

- (1) **Item 21.** Signature of the FAA inspector or designee should be in permanent ink over the typed name. The number should be the office identifier or designee designation number. DOA manufacturers would use their authorization number as assigned by the FAA.
- (2) Item 23. Spot check of the file will be indicated by signature of the supervising inspector in permanent ink over the typed name with the district or regional office and date. If the file is not spot checked, omit the name and signature but enter the district or regional office number and date.

243. EXAMINATION, REVIEW, AND ROUTING OF CERTIFICATION FILES.

a. It is the responsibility of all FAA inspectors and designees to examine in detail each certification file processed to ensure accuracy, completeness, legibility, and compliance with applicable requirements, including all necessary attachments. The following list represents the primary data that is required for retention in the permanent files. These documents should be submitted to AFS-750 as applicable to the certification action. Do not include any documentation that is not required in support of the certification action.

(1) Airworthiness Certificates.

- (a) The original Form 8130-6.
- **(b)** Applications for special flight permits for operation of overweight aircraft only (§ 21.197(b)).
- (c) Applications for an experimental airworthiness certificate should include the data required by § 21.193, as applicable.
 - (d) The original Form 8130-9.
- (e) A copy of Form 8130-2 or any other data, drawings, photographs, etc. (when applicable).
- **(f)** A copy of Form 337 (when applicable). Do not include referenced data forming the basis for approval of the repair or alteration.

Page 250 Par 242

(g) A copy of Form 8100-2, or Form 8130-7 as applicable. When Form 8130-7 is issued as a special flight permit, submit only those copies which permit operation of overweight aircraft (§ 21.197(b)). Superseded, terminated, or canceled airworthiness certificates should be included if a recurrent certificate is issued.

- **(h)** A copy of operating limitations, if issued.
- (i) A copy of the checklist and inspection record for aircraft built from spare and surplus parts.
- (j) The foreign airworthiness certificate for aircraft imported (if applicable).

(2) Export for Class I product.

- (a) The original Form 8130-1.
- **(b)** The statement of acceptance from an importing country listing the specific noncompliance(s) (if applicable).
 - **(c)** A copy of Form 8130-4.
 - (d) The original Form 8050-72.
- (3) **Export of Class II and III Products.** Retain the following in the district or regional office. DMIR's, ODAR's, and DOA's may retain the records at their facility as long as their authorization is valid:
- (a) The original application for Export C of A, as applicable, along with any data showing acceptance of deviations from the CAA of the country of import (for Class II only).
 - **(b)** A copy of Form 8130-3.
 - **(c)** Form 8100-1.
- (4) Import of a Class I product manufactured in a bilateral country. Retain the following in the district or regional office:
- (a) Aircraft. A certificate of airworthiness issued by the country the aircraft was manufactured in which states the aircraft conforms to its type design and is in a condition for safe operation.
- **(b) Aircraft Engine and Propeller.** A certification from the country of manufacture for engines and propellers is required to be submitted when they are a part of, or are to be installed on, an aircraft.

Par 243 Page 251

NOTE: A certification may be accepted from a third party country when the acceptance is permitted by the BAA or BASA IPA.

- (c) The applicable documents listed in paragraph 243a(1) of this order.
- **b.** In addition to the above mentioned data, the district or regional offices should maintain copies of any other data they deem appropriate to substantiate the certification of the product. This includes Form 8100-1, eligibility statements, program letters, etc.
- **c.** The appropriate district or regional office should ensure that all airworthiness actions processed by FAA designees are submitted to the district or regional office for review and transmittal to AFS-750.

244.-250. RESERVED.

Page 252 Par 243

12/18/00 8130.2D CHG 2

FIGURE 8-1. FORMS LISTING AND AVAILABILITY

1. The following forms are available through normal distribution channels:

FORM NUMBER, TITLE, NATIONAL STOCK NUMBER, AND UNIT OF ISSUE

FAA Form 337, Major Repair and Alteration (Airframe, Powerplant, or Appliance, 0052-00-025-8001, Hundred.

FAA Form 8100-1, Conformity Inspection Record, 0052-00-039-3000, Sheet.

FAA Form 8100-2, Standard Airworthiness Certificate, 0052-00-0-040-8001, Pad.

FAA Form 8130-1, Application for Export Certificate of Airworthiness, 0052-00-024-9004, Sheet.

FAA Form 8130-2, Conformity Certificate Military Aircraft, 0052-00-037-1001, Hundred.

* FAA Form 8130-3, Airworthiness Approval Tag, 0052-00-012-9005, Pad.

FAA Form 8130-4, Export Certificate of Airworthiness, 0052-00-010-3001, Hundred.

FAA Form 8130-6, Application for Airworthiness Certificate, 0052-00-024-7004, Sheet.

FAA Form 8130-7, Special Airworthiness Certificate, 0052-693-4000, Pad.

FAA Form 8130-9, Statement of Conformity, 0052-00-025-3002, Sheet.

FAA Form 8130-10, Surplus Military Record, 0052-00-851-9000, Sheet.

FAA Form 8130-12, Eligibility Statement Amateur-Built Aircraft, 0052-00889-9001, Sheet.

2. The following forms are NOT available through normal distribution channels:

AC Form 8050-64, Assignment of Special Registration Numbers, is available from the FAA Aircraft Registry.

AC Form 8050-72, Export Certificate Number Assignment Card, is available from the FAA Aircraft Registry.

AC Form 4100 series, Non-certificated Public Aircraft Document, is available from the Aircraft Maintenance and Engineering Division, Oklahoma City, Oklahoma.

12/18/00 8130.2D CHG 2 Appendix 1

APPENDIX 1. ISSUANCE OF U.S. STANDARD AIRWORTHINESS CERTIFICATES FOR NEW AIRCRAFT MANUFACTURED OUTSIDE THE UNITED STATES

1. PURPOSE. This appendix describes the procedures for issuance of Form 8100-2, for new aircraft manufactured in other countries that are to be placed on the United States Civil Aircraft Registry. This procedure is intended primarily for guidance to the U.S. aircraft owner, the CAA, the manufacturer, and the FAA Aircraft Registration Branch, AFS-750, in Oklahoma City, Oklahoma. For the purpose of this procedure, a U.S. aircraft owner may be represented by an agent as indicated § 21.173.

NOTE: This procedure does not relieve persons involved in the standard airworthiness certification process from any responsibilities or legal requirements of part 21.

2. APPLICABILITY.

- **a.** The FAA will at times seek assistance from BAA and BASA partners in the final processing, dating, and delivery of Form 8100-2 for newly manufactured aircraft destined for export to the United States. The FAA issues the form and the CAA provides assistance with specific process steps. The certificate issuing office may only apply the procedure identified in this appendix when approved by AIR-200, and the directorate with responsibility for importing the aircraft. Furthermore, the use of this procedure is only allowed if no conflict exists with the BAA/BASA of the country or jurisdiction of manufacture.
- **b.** Upon request from the U.S. aircraft owner, the CAA, or jurisdiction of manufacture, the FAA may at its discretion, authorize the CAA to act on its behalf. If authorized, this activity will be performed in accordance with the detailed procedures identified in this appendix, and only for aircraft that are:
 - (1) Newly manufactured in that country or jurisdiction.
 - (2) Properly placed on the U.S. Civil Aircraft Registry.
 - (3) Fully compliant with the requirements of the applicable FAA type certificate.
 - (4) Presently in a condition for safe operation.
 - (5) Accompanied by a Certificate of Airworthiness for Export from the exporting CAA.

3. PROCEDURE.

a. The aircraft manufacturer notifies the CAA of the country or jurisdiction of manufacture that an aircraft, identified in paragraph 3b below, has been sold to a named U.S. owner and is to be placed on the U.S. Civil Aircraft Registry. As a result, the U.S. aircraft owner will be requesting issuance of Form 8100-2 at the point of manufacture.

Par 1 Page 1

b. The U.S. owner submits to AFS-750, a request for assignment of a U.S. identification number for the particular aircraft. This request will include the following information:

- (1) U.S. owner's name.
- (2) Manufacturer's name.
- (3) Aircraft type.
- (4) Aircraft model number.
- (5) Aircraft serial number.
- **c.** The U.S. owner, upon receipt of the identification number, supplies it to the aircraft manufacturer for permanent marking of the aircraft (reference part 45). The U.S. owner also provides this information to the CAA for its use. This identification number will become the final registration number.
- **d.** The U.S. owner notifies the manager of the FAA office that issues Standard Airworthiness Certificates for import aircraft of the desire to have Form 8100-2 issued at the point of manufacture. The U.S. owner also provides the FAA office with Form 8130-6, sections I, II, and III completed as applicable. All entries should be typed or printed legibly. Certain items in section III, Owner's Certification, are to be left blank until the final application is completed, since the information for these items is not known until the aircraft's final delivery. Form 8130-6 is considered to be "initial" until the items are completed. The items to be left blank are:
- (1) The status of compliance up to the most current and applicable airworthiness directives as indicated in the Airworthiness Directives block of subsection B, Aircraft Certification Basis.
- (2) The recording of total airframe hours (including production flight test time) in the applicable block of subsection C, Total Airframe Hours.
 - (3) The date of the application as indicated in subsection D, Certification.

NOTE: The "initial" Form 8130-6 should be filled out in accordance with AC 21-12, Application for U.S. Airworthiness Certificate, Form 8130-6, or Order 8130.2.

- **e.** The CAA notifies the manager of the FAA certificate issuing office of its desire to act on behalf of the FAA in the delivery of Form 8100-2 for the particular aircraft. The following information is to be supplied by the CAA:
 - (1) Identification number of the aircraft.
 - (2) Name of the U.S. aircraft owner.

Page 2 Par 3

12/18/00 8130.2D CHG 2 Appendix 1

(3) Scheduled aircraft delivery date.

NOTE: A letter of ongoing support from an individual CAA can be the method of FAA notification upon acceptance by the FAA certificate issuing office.

- **f.** The FAA certificate issuing office prepares Form 8100-2, including two carbon copies.
- (1) List in block 5 any existing exemptions granted by the FAA which are applicable to the aircraft, as cited on the Type Certificate Data Sheet (TCDS) or other official correspondence.
 - (2) Leave the date of issuance block blank.
- (3) Sign the original and two copies in blue ink and forward them to the designated CAA point of contact. Blue ink is used so that the original signature can be easily identified.
- (4) The following sentence is to be included in the transmittal letter from the FAA certificate issuing office: "Do not deliver this Standard Airworthiness Certificate, issued for the subject aircraft above, until AFS-750 or this office has notified you that the aircraft has been properly registered."

NOTE: If AFS-750 notifies the CAA directly, they are to also notify the FAA certificate issuing office that the aircraft is registered and that the CAA has been notified.

g. The aircraft manufacturer installs an identification plate on the aircraft that meets the requirements of § 45.11 upon completion of all necessary flight tests and inspections. The aircraft manufacturer also applies the nationality and registration marks to the aircraft in accordance with § 45.21.

NOTE: The FAA has, in some cases, granted regulatory exemptions permitting alternate mounting locations of aircraft identification plates for certain aircraft of qualifying air carriers. Any aircraft whose identification plate is mounted in a location other than that which is required in § 45.11 must be covered by the provisions of a current regulatory exemption for alternate identification plate location.

h. The CAA issues a Certificate of Airworthiness for Export for the aircraft after completing all tasks and inspections necessary to determine the aircraft conforms to the FAA-approved type design and is in condition for safe operation. This certificate must contain the certification statement prescribed in the applicable FAA TCDS under the heading "Import Requirements."

NOTE: If any nonconformities, deviations, or exceptions exist, the CAA must obtain written concurrence and acceptance of these conditions from the FAA certificate issuing office prior to delivering Form 8100-2 for the subject aircraft. Conditions of this nature may disqualify the aircraft from receiving the intended Form 8100-2 due to its inability to fully meet the requirements of the U.S. type certificate.

Page 3

- i. Additional work performed after issuance of CAA Export Certificate of Airworthiness.
- (1) If any additional work (e.g., modifications, alteration, repairs, etc.) is performed on the aircraft by the manufacturer after issuance of the CAA's Export Certificate of Airworthiness, and prior to receipt of the U.S. Standard Airworthiness Certificate, the following must be accomplished:
- (a) The work must be controlled, documented, and completed by the manufacturer under its CAA-approved production quality control system and associated procedures.
- (b) The exporting CAA will review the manufacturer's additional completed work to ensure that the aircraft continues to remain in full compliance to its FAA-approved type design and is in condition for safe operation. If the CAA is satisfied that these requirements are fully met, the U.S. Standard Airworthiness Certificate may be released to the registered owner/operator as per paragraph 3h of this procedure.
- (2) If any additional work (e.g., modifications, alterations, repairs, etc.) is performed on the aircraft by someone other than the manufacturer (which may also include any other persons or organizations under the direct control of the manufacturer), after issuance of the CAA's Export Certificate of Airworthiness, the aircraft may possibly be disqualified from receipt of the U.S. Standard Airworthiness Certificate issued under this special procedure.

NOTE: The CAA is not responsible for the review and acceptance of any additional work performed outside of its direct control and oversight. This includes any additional work (as described above) performed on the aircraft directly by the new U.S.-owner prior to receiving the U.S. Standard Airworthiness Certificate. The FAA issuing office could not, therefore, be assured of the continued validity of the CAA's Export Certificate of Airworthiness upon which this special procedure and the issuance of the U.S. Standard Airworthiness Certificate are based.

- (3) The new U.S.-owner/operator (or his authorized agent) may at times perform the various functions and activities which may be necessary to prepare the newly acquired aircraft for their departure flight from the manufacturer and placement into operation.
- (a) These functions and activities (e.g., pre-operational servicing/maintenance, pre-flight inspections, aircraft systems functional checks, navigation/communication equipment, operational software installation, etc.) must be properly documented when necessary and may be undertaken after issuance of the CAA's Export Certificate of Airworthiness and prior to receipt of the U.S. Standard Airworthiness Certificate.
- (b) After the completion of these tasks, the new U.S.-owner/operator must ensure that the aircraft has remained in full compliance to the FAA-approved type design and continued condition for safe operation. The CAA may, at its discretion, monitor these functions and activities in advance of the release of the U.S. Standard Airworthiness Certificate.

Page 4 Par 3

12/18/00 8130.2D CHG 2 Appendix 1

(4) The FAA certificate issuing office should be contacted by the CAA when any problems arise pertaining to these requirements which would preclude the release and delivery of the U.S. Standard Airworthiness Certificate to the new U.S.-owner/operator.

- **j.** The aircraft manufacturer and the U.S.-owner will request the CAA to supply the U.S.-owner with a statement concerning the aircraft's current registration status in its country or jurisdiction of manufacture. The statement concerning the aircraft's current registration must attest that the particular aircraft has not been previously registered or been removed from the foreign registry if previously registered. Reference §§ 47.15(a)(1) and 47.37(b).
 - NOTE: For aircraft manufactured in countries that require domestic registration as a condition for production flight checks, this step may entail some delay in final U.S. registration. Such delay may be minimized by faxing the current registration status statement directly from the CAA to AFS-750 upon completion of the production flight checks and removal of the aircraft from the domestic register. The faxed statement should identify the aircraft and name of the U.S. owner as described in paragraph b above.
- **k.** The U.S. owner submits to AFS-750 all information required to obtain aircraft registration. Permanent registration will be received via AC Form 8050-3, Certificate of Aircraft Registration. If the U.S. aircraft owner desires to receive a temporary registration prior to receiving the permanent one, a request should also be made at this time for Standard Form 14, Telegraphic Message. This form serves as a temporary Certificate of Aircraft Registration. The required information for aircraft registration consists of:
- (1) AC Form 8050-1, Application for Aircraft Registration, including the original AC Form 8050-2, Bill of Sale, or other evidence of ownership as indicated in § 47.11.
 - (2) The appropriate fee (reference §§ 47.17 and 47.31).
 - (3) The registration status statement received from the CAA in paragraph 3j above.
- **1.** The U.S. owner supplies the CAA with a complete Form 8130-6 after receipt of Form 8050-3 or Standard Form 14. Sections IV, V, and the entire back portion of Form 8130-6 are to be left blank. However, the items left blank from the initial form, and one additional item should now be completed as follows:
- (1) The status of compliance up to the most current and applicable airworthiness directives as indicated in the Airworthiness Directives block of subsection B, Aircraft Certification Basis.
- (2) The recording of total airframe hours (including production flight test time) in the applicable block of subsection C, Aircraft Operation and Maintenance Records.

Par 3 Page 5

- (3) The final date entered by the applicant must be the same as or later than the date of the Certificate of Airworthiness for Export issued by the CAA of the country or jurisdiction of manufacture.
 - (a) The date cannot be later than the date entered on Form 8100-2 for the aircraft.
- **(b)** The signature of the person in subsection D, Certification, must be that of the registered owner (or an authorized employee of the corporation or company signified as the registered owner) identified under subsection A of section III, Owner's Certification. If the signature is other than one of these persons, the application must be accompanied with a notarized letter or current power of attorney delegating the authority to act as an agent on the owner's behalf to apply for the airworthiness certificate.
- (4) The specific 14 CFR reference listed in section III, Owner's Certification, subsection C, Aircraft Operation and Maintenance Records, should be lined out and changed FROM 91.173 TO 91.417.
 - **m.** The CAA verifies the following prior to delivery of Form 8100-2:
- (1) The registered owner identified on Form 8130-6 is still the same person, company, or corporation confirmed as the final registered owner by AFS-750 on Form 8050-3 or Standard Form 14.
- (2) The aircraft's "N" numbers painted on the exterior of the fuselage are identical to those assigned to the aircraft by AFS-750 on Form 8050-3 or Standard Form 14. In addition, the aircraft markings must meet the requirements of part 45.
- (3) The aircraft's nationality and registration marks entered on Form 8100-2, block #1, are identical to those assigned to the aircraft by AFS-750 on Form 8050-3 or Standard Form 14.
- (4) The aircraft's identification plate has all the required data and proper information, and is mounted in the proper location on the aircraft.
 - **n.** The CAA finalizes and installs Form 8100-2 in the aircraft as follows:
- (1) The specific date on which the form was issued is entered in the Date of Issuance block on the original and on the two carbon copies. Date entries are to include the month identifier in either a three-letter format or completely spelled out, e.g., Mar or March. Date of Issuance entries must be made with a typewriter or other appropriate instrument, e.g., a mechanical date stamping device for the date entry. No handwritten entries are permitted.
- (2) The original Form 8100-2 is then installed in the aircraft and the following statement is entered into the aircraft logbook: "U.S. Standard Airworthiness Certificate, issued (date), has been installed in the aircraft on behalf of (FAA certificate issuing office) on (date)."

Page 6 Par 3

12/18/00 8130.2D CHG 2 Appendix 1

NOTE: The person from the CAA performing the final issuance and installation of Form 8100-2 in the aircraft must sign the aircraft logbook and include a functional title or other evidence of authorization to act on behalf of the CAA.

- **o.** The CAA faxes the documents listed below to the FAA certificate issuing office prior to the first flight of the aircraft under Form 8100-2. This action is necessary because the FAA certificate issuing office must be in possession of legal documentation in the form of on-hand file records of proper airworthiness certification prior to the aircraft's first flight.
 - (1) A copy of the Certificate of Airworthiness for Export.
 - (2) A copy of Form 8050-3 or Standard Form 14.
 - (3) A copy of the completed and dated Form 8100-2.
- **p.** The CAA retains one carbon copy of Form 8100-2 and forwards the following documents to the manager of the FAA certificate issuing office.
 - (1) The remaining carbon copy of the dated Form 8100-2.
 - (2) The original and one copy of the completed Form 8130-6.
- (3) The original and one copy of the Certificate of Airworthiness for Export issued by the CAA of the country or jurisdiction of manufacture.
 - (4) A copy of Form 8050-3 or Standard Form 14.
- **q.** The U.S. owner takes delivery of the aircraft and installs either Form 8050-3 or Standard Form 14 (pending receipt of Form 8050-3) in the aircraft. The aircraft may then be flown or otherwise delivered to the United States.
- **r.** The FAA certificate issuing office endorses Form 8130-6 by entering a statement on the form in a location that can be clearly read. This statement is required to contain the following information at a minimum:
- (1) A statement indicating that the Standard Airworthiness Certificate was issued on the basis of the Certificate of Airworthiness for Export No. (number).
 - (2) The issuing CAA's name and the Certificate of Airworthiness for Export's date of issuance.
- (3) The FAA certificate issuing office then forwards the application, along with the copy of Form 8100-2 and the original Certificate of Airworthiness for Export to AFS-750 for permanent filing.
 - s. The U.S. owner receives Form 8050-3 from AFS-750 if one has not already been obtained.

Par 3 Page 7

4. ADMINISTRATIVE REQUIREMENTS.

- **a.** The FAA requests that the "initial" Form 8130-6 be received at least 20 days prior to the expected delivery date of the aircraft to allow ample time for authority coordination, certificate preparation, and final dispatch and delivery. An application received with less than the 20-day processing requirement will be handled on a case by case basis as available FAA resources allow.
- **b.** The FAA normally will not dispatch a Form 8100-2 more than 45 days in advance of the expected delivery date unless specific circumstances warrant an earlier dispatch. Certificates will not be dispatched more than 45 days in advance for future production runs, anticipated long-range customer deliveries, etc.
- **c.** In the event that Form 8100-2 is suspected of being lost in the mail, the FAA will prepare a duplicate/replacement form only after a 10-day period from the date of the mailing of the original form has elapsed. All other reasons necessitating the issuance of a duplicate/replacement form will be handled on a case by case basis as available FAA resources allow.
- **d.** Any costs of overnight courier services for the dispatch and delivery of forms needing expedited delivery to the CAA point of contact will be paid for by the applicant and/or the manufacturer.
- **e.** The AIR-200 approved certificate issuing office may delegate these functions to Flight Standards ASI's as necessary.

Page 8 Par 4



Federal Aviation Administration

FAA Form 1320-19 (8-89)

Directive Feedback Information

Please submit any written comments or recommendations for improving this directive, or suggest new items or subjects to be added to it. Also, if you find an error, please tell us about it.

Su	bject: Order <u>8130.2D</u>				
To	: Directive Management Officer, AIR-520				
(PI	ease check all appropriate line items)				
ÿ	An error (procedural or typographical has been noted in paragraph on page				
ÿ	Recommend paragraph on page be changed as follows: (attach separate sheet if necessary)				
ÿ	In a future change to this directive, please include coverage on the following subject (briefly describe what you want added):				
ÿ	Other comments:				
ÿ	I would like to discuss the above. Please contact me.				
Sul	bmitted by: Date:				
FTS Telephone Number: Routing Symbol:					